

TEST REPORT

Product Name	:	Zophia Wire. less Earphone
Brand Mark	:	Zorloo
Model No.	:	EZ27
FCC ID	:	2A37ZEZ27ZPA
Report Number	:	BLA-EMC-202112-A10503
Date of Sample Receipt	:	2021/12/24
Date of Test	:	2021/12/28 to 2022/1/6
Date of Issue	:	2022/1/6
Test Standard	:	47 CFR Part 1.1307, Part 2.1093, KDB 447498
Test Result	:	Pass

Prepared for:

Zorloo (HK) Limited

**Rm 1209, 12/F, OfficePlus@Prince Edward, 794-802 Nathan Road,
Mongkok, Kowloon, Hong Kong**

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

**Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**

TEL: +86-755-23059481

Compiled by:

Jozu

Approved by:

Blue.Zhong

Review by:

Sweell

Date:

2022/1/6



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/1/6	Original
01	2022/1/11	Product name changed from True Wireless Earphones to Zophia Wire.less Earphone

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY.....	4
2	GENERAL INFORMATION.....	5
3	GENERAL DESCRIPTION OF E.U.T.....	5
4	LABORATORY LOCATION.....	6
5	RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.1	STANDARD REQUIREMENT.....	7
5.2	LIMITS.....	7
5.3	EUT RF EXPOSURE.....	7

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	pass

BlueAsia

2 GENERAL INFORMATION

Applicant	Zorloo (HK) Limited
Address	Rm 1209, 12/F, OfficePlus@Prince Edward, 794-802 Nathan Road, Mongkok, Kowloon, Hong Kong
Manufacturer	Concept Audio Co., Ltd.
Address	5F, NO.7, PingXi Three Road, Nanping Industrial Zone, Zhuhai City, Guangdong 519060, China
Factory	Concept Audio Co., Ltd.
Address	5F, NO.7, PingXi Three Road, Nanping Industrial Zone, Zhuhai City, Guangdong 519060, China
Product Name	Zophia Wire.less Earphone
Test Model No.	EZ27

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	1940-QCC3040-V1.2
Software Version	YS2052_20210721_V0.1.4
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	1.9dBi(Provided by the applicant)

4 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

BlueAsia

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.3 EUT RF EXPOSURE

Operational Mode: GFSK		Maximum tune-up Power				Calculated value	Exclusion threshold
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	(dBm)	(mW)			
2402 MHz	-1.878	± 1	-0.878	0.82	0.25	3.0	3.0
2441 MHz	-1.79	± 1	-0.79	0.83	0.26		
2480 MHz	-2.211	± 1	-1.211	0.76	0.24		

Conclusion: the calculated value ≤ 3.0 , SAR is exempted.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.