

YET2128C Remote control manual

1. Wireless transmitting power: <0dbm;
2. Rf open band, no need to apply frequency point, carrier frequency 433.92MHz;
3. Modulation method: ASK/OOK
4. In case of line-of-sight, reliable transmission distance: >50 meters;
5. Low power consumption, 3.0V @ 433.92MHz, <18mA.

Name	parameter			Unit
	Minimum	Type	Maximum	
Electrical properties(25°C)				
Supply voltage		6		V
Emission current		18		mA
Static current		0		uA
RF performance (25°C)				
Working frequency		433.92		MHz
Transmission power		0		dBm
Baud rate		1.4		kHZ
General performance				
Working temperature	-20		60	°C

6. Function:

This product code format is HCS300 roll code, there are four keys, operation of each key issued by a different key value.

FCC warning statements:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The device has been evaluated to meet general RF exposure requirement.