

TEST REPORT

Applicant:	Huizhou Jinghao Medical Technology Co., Ltd
Address of Applicant:	Floor 6, Huicheng Industry Building, No.9 Huifeng Dong'er Road, ZhongKai High tech Zone, Huizhou City, Guangdong Province, 516000, P.R.China
Manufacturer:	Huizhou Jinghao Medical Technology Co., Ltd
Address of Manufacturer:	Floor 6, Huicheng Industry Building, No.9 Huifeng Dong'er Road, ZhongKai High tech Zone, Huizhou City, Guangdong Province, 516000, P.R.China
Product name:	HEARING AIDS/ hearing amplifier
Model:	JH-A61HT, JH-DW2AT, JH-AW2B, JH-AW2BT, JH-D59FT, JH-DW1A, JH-DW3A, JH-DW3E, JH-DW3F, JH-DW3FT, JH-DW4AT, JH-DW5A, JH-TW4AT, JH-TW4A, JH-D59ET, JH-DW1AT, JH-A32D, JH-A32E, JH-A32F, JH-A32G, HNB-4/0143
Rating(s):	Input: DC 5V, 1A Output: DC 4.2V 0.05A
Trademark:	JINGHAO
Standards:	47 CFR PART 15 Subpart C section 15.247
FCC ID:	2A39M-JH22A61H
Date of Receipt:	2022-10-26
Date of Test:	2022-10-26~2022-11-17
Date of Issue:	2022-11-17
Test Result	Pass*


* In the configuration tested, the test item complied with the standards specified above.

Authorized for issue by:**Test by:**

Nov.17, 2022 Chivas Tsang
Project Engineer




Victor Meng
Project Manager



Date Name/Position Signature Date Name/Position Signature

Possible test case verdicts:

test case does not apply to the test object...: N/A

test object does meet the requirement.....: P (Pass)

test object does not meet the requirement...: F (Fail)

Testing Laboratory information:

Testing Laboratory Name: ITL Co., Ltd

Address.....: No. 8 Jinqianling Street 5, Huangjiang Town, Dongguan, Guangdong, 523757 P.R.C.

Testing location : Same as above

Tel : 0086-769-39001678

Fax : 0086-20-62824387

E-mail : itl@i-testlab.com

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report would be invalid test report without all the signatures of testing technician and approver.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

General product information:

The left and right ears are symmetrical in structure, basically the same in design, slightly different in layout and wiring, and will not affect the RF performance.

All models are identical to each other except the model name.

All tests were performed on the model JH-A61HT as representative.

1 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
Occupied Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10:2013	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	ANSI C63.10:2013	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10:2013	PASS
Conducted Spurious Emission (30 MHz to 25 GHz)	FCC PART 15 C section 15.209 & 15.247(d)	ANSI C63.10:2013	PASS
Radiated Spurious Emission (30 MHz to 25 GHz)	FCC PART 15 C section 15.209 & 15.247(d)	ANSI C63.10:2013	PASS
Band Edges Measurement	FCC PART 15 C section 15.209 & 15.247 (d)	ANSI C63.10:2013	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10:2013	PASS
Radiated Emissions which fall in the restricted bands	FCC PART 15 C section 15.209	ANSI C63.10:2013	PASS
Remark:			
N/A: not applicable. Refer to the relative section for the details.			
EUT: In this whole report EUT means Equipment Under Test.			
Tx: In this whole report Tx (or tx) means Transmitter.			
Rx: In this whole report Rx (or rx) means Receiver.			
RF: In this whole report RF means Radio Frequency.			
ANSI C63.10:2013 the detail version is ANSI C63.10:2013 in the whole report.			

2 Contents

	Page
TEST REPORT	1
1 TEST SUMMARY	3
2 CONTENTS	4
3 GENERAL INFORMATION	5
3.1 CLIENT INFORMATION	5
3.2 GENERAL DESCRIPTION OF E.U.T.	5
3.3 DETAILS OF E.U.T.	5
3.4 DESCRIPTION OF SUPPORT UNITS	5
3.5 TEST LOCATION	5
3.6 DEVIATION FROM STANDARDS	6
3.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
3.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
3.9 TEST FACILITY	6
3.10 MEASUREMENT UNCERTAINTY	6
4 INSTRUMENTS USED DURING TEST	7
5 TEST RESULTS	8
5.1 E.U.T. TEST CONDITIONS	8
5.2 ANTENNA REQUIREMENT	10
5.3 OCCUPIED BANDWIDTH	11
5.4 MAXIMUM PEAK OUTPUT POWER	16
5.5 PEAK POWER SPECTRAL DENSITY	21
5.6 CONDUCTED SPURIOUS EMISSIONS	26
5.7 RADIATED SPURIOUS EMISSIONS	30
5.7.1 Harmonic and other spurious emissions	33
5.8 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	42
5.9 BAND EDGES REQUIREMENT	45

No tests were sub-contracted.

3.6 Deviation from Standards

None.

3.7 Abnormalities from Standard Conditions

None.

3.8 Other Information Requested by the Customer

None.

3.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS Lab code:L9342**
- **FCC Designation No.:CN5035**
- **IC Registration NO.: 12593A**
- **NVLAP LAB CODE: 600199-0**

3.10 Measurement Uncertainty

The below measurement uncertainties given below are based on a 95% confidence level (base on a coverage factor (k=2).)

Parameter	Uncertainty
Radio frequency	2.25%
total RF power, conducted	±1.34 dB
RF power density , conducted	±1.49 dB
All emissions, radiated	±2.72 dB
Temperature	±5.02 dB
Humidity	±0.8°C
DC and low frequency voltages	±1.5 %

4 Instruments Used during Test

No.	Test Equipment	Manufacturer	Model	Serial No.	Last Cal.	Cal. Due
ITL-114	Spectrum Analyzer	Agilent	N9010A	MY51250936	2022/01/14	2023/01/13
ITL-154	EMI test receiver 9kHz to 26.5GHz	R&S	ESR26	101257	2022/01/14	2023/01/13
ITL-116	Pre Amplifier	HP	8447F	3113A05905	2022/01/14	2023/01/13
ITL-117	Wideband Amplifier Super Ultra	Mini-circuits	ZVA-183-S+	469101134	2022/01/14	2023/01/13
ITL-180	Trilog-Broadband Antenna	Schwarzbeck	VULB 9164	005	2021/01/31	2023/01/30
ITL-110	Horn Antenna	A-INFOMW	JXTXLB-10180-N	J2031090612 133	2022/01/14	2023/01/13
ITL-103	Two-line v-network	R&S	ENV216	100120	2022/06/17	2024/06/16
ITL-115	50Ω Coaxial Cable	Mini-circuits	CBL	C001	2022/06/15	2024/06/14
ITL-100	Semi-Anechoic chamber	ETS•Lindgren	FACT3 2.0	CT09015	2022/10/14	2025/10/13
ITL-145	Loop Antenna	ZHINAN	Z30900A	002489	2022/01/16	2024/01/15
ITL-101	Shielded Room	ETS•Lindgren	8*4*3	CT09010	2021/01/22	2024/01/21
ITL-165	Power Meter	R&S	NRVS	838246/026	2022/10/16	2023/10/15
ITL-166	Power Sensor	Agilent	U2021XA	MY5365004	2022/01/20	2023/01/19

5 Test Results

5.1 E.U.T. test conditions

Test Voltage:	300mAh battery
Temperature:	20.0 -25.0 °C
Humidity:	38-50 % RH
Atmospheric Pressure:	1000 -1010 mbar
Requirements:	<p>15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.</p> <p>15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.</p>
Test frequencies and frequency range:	According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:
	According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz,
At or above 10 GHz to below	5th harmonic of highest fundamental frequency or to 100 GHz,
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz,

EUT channels and frequencies list:

channel	Frequency	channel	Frequency	channel	Frequency	channel	Frequency
1	2402	11	2422	21	2442	31	2462
2	2404	12	2424	22	2444	32	2464
3	2406	13	2426	23	2446	33	2466
4	2408	14	2428	24	2448	34	2468
5	2410	15	2430	25	2450	35	2470
6	2412	16	2432	26	2452	36	2472
7	2414	17	2434	27	2454	37	2474
8	2416	18	2436	28	2456	38	2476
9	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

Test frequencies are the lowest channel: 1 channel (2402MHz), middle channel: 21 channel (2442 MHz) and highest channel: 40 channel (2480 MHz)

Test the EUT in continuous transmission mode, duty cycle > 98%.

5.2 Antenna requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is an Internal Antenna and no consideration of replacement. The best case gain of the antenna is 0.5dBi.

Test result: The unit does meet the FCC requirements.

5.3 Occupied Bandwidth


Test Requirement: FCC Part 15 C section 15.247

(a)(2)Systems using digital modulation techniques may operate in the 902-928 MHz, 2400 -2483.5MHz, and 5725 -5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:






Test Procedure:



1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =0.5dB) from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW=100kHz, VBW = 300kHz, Sweep = auto; Detector Function = Peak. Trace = Max Hold, Set span to encompass the entire emission bandwidth of the signal.
3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
4. Repeat until all the test status is investigated.
5. Report the worst case.


Test result (6 dB bandwidth)

Channel No.	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
1	BLE 1M	2402	Ant1	0.656	0.5	Pass
21	BLE 1M	2442	Ant1	0.643	0.5	Pass
40	BLE 1M	2480	Ant1	0.703	0.5	Pass
1	BLE 2M	2402	Ant1	1.139	0.5	Pass
21	BLE 2M	2442	Ant1	1.169	0.5	Pass
40	BLE 2M	2480	Ant1	1.266	0.5	Pass









5.4 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247

(b)(3) For systems using digital modulation in the 902-928 MHz,


2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:




Test Procedure:


1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss = 2.01 dB) from the antenna port to the spectrum .
2. Set the RBW \geq DTS bandwidth
3. Set VBW $\geq 3 \times$ RBW
4. Set span $\geq 3 \times$ RBW.
5. Sweep time = auto.
6. Detector = peak.
7. Trace mode = max hold.
8. Allow trace to fully stabilize
9. Use peak marker function to determine the peak amplitude level

Test Data:


Channel No.	Mode	Frequency (MHz)	Measured Power (dBm)	Limit (dBm)	Result
1	BLE 1M	2402	-9.077	30	Pass
21	BLE 1M	2442	-10.628	30	Pass
40	BLE 1M	2480	-10.965	30	Pass
1	BLE 2M	2402	-11.917	30	Pass
21	BLE 2M	2442	-14.552	30	Pass
40	BLE 2M	2480	-12.280	30	Pass

The unit does meet the FCC requirements


Power NVNT BLE 1M 2442MHz Ant1




Power NVNT BLE 1M 2480MHz Ant1




Power NVNT BLE 2M 2402MHz Ant1



Power NVNT BLE 2M 2442MHz Ant1





5.5 Peak Power Spectral Density


Test Requirement: FCC Part15 C section 15.247

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channel and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =2.01 dB) from the antenna port to the spectrum analyzer or power meter.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.

- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Measure the Power Spectral Density of the test frequency with special test status.

Repeat until all the test status is investigated.

Report the worst case.


Test result:

Channel No.	Mode	Frequency (MHz)	Max PSD (dBm)	Limit (dBm)	Verdict
1	BLE 1M	2402	-16.189	8	Pass
21	BLE 1M	2442	-17.226	8	Pass
40	BLE 1M	2480	-17.927	8	Pass
1	BLE 2M	2402	-20.912	8	Pass
21	BLE 2M	2442	-21.587	8	Pass
40	BLE 2M	2480	-23.001	8	Pass


Remark : 1) Output Peak Power = Reading Peak Power + Cable loss

2) Cable loss = 2.01db

The unit does meet the FCC requirements.



PSD NVNT BLE 1M 2442MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2402MHz Ant1



PSD NVNT BLE 2M 2442MHz Ant1



PSD NVNT BLE 2M 2480MHz Ant1



5.6 Conducted Spurious Emissions


Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channel and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.



Test Configuration:





Test Procedure:


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worst case.

Result plot as follows:






Tx. Spurious NVNT BLE 2M 2442MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission



The unit does meet the FCC requirements.

5.7 Radiated Spurious Emissions

Test Requirement: FCC Part15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Detector: For PK value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz, 9kHz for <30MHz

VBW \geq RBW Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz, 9kHz for <30MHz

VBW = 10 Hz

Sweep = auto

Detector function = peak

Trace = max hold

15.209 Limit:

40.0 dB μ V/m between 30MHz & 88MHz


43.5 dB μ V/m between 88MHz & 216MHz

46.0 dB μ V/m between 216MHz & 960MHz


54.0 dB μ V/m above 960MHz

Test Configuration:


- 1) 9kHz to 30MHz emissions:



- 2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 40 GHz emissions:

**Test Procedure:**

(1) The receiver was scanned from 9kHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. After pre-test, it was found that the worse radiation emission was get at the X position. So the data shown was the X position only. The worst case emissions were reported.

(2) Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

(3) Pre-test under all modes below 1GHz, choose the worst case mode record On the report.

5.7.1 Harmonic and other spurious emissions

Test at low Channel in transmitting status

9kHz~30MHz Test result


The Low frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not report

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dB μ V/m)



Quasi-peak measurement


No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	30.000	24.98	22.90	0.63	28.50	20.01	40.00	-19.99	HORIZONTAL	QP
2	291.900	24.64	13.27	2.09	27.52	12.48	46.00	-33.52	HORIZONTAL	QP
3	373.380	26.03	14.99	2.35	28.33	15.04	46.00	-30.96	HORIZONTAL	QP
4	475.230	26.79	16.65	2.70	28.40	17.74	46.00	-28.26	HORIZONTAL	QP
5	749.740	28.30	20.35	3.44	27.50	24.59	46.00	-21.41	HORIZONTAL	QP
6	797.270	27.53	20.78	3.56	27.67	24.20	46.00	-21.80	HORIZONTAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)


Quasi-peak measurement

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/Phase	Remark
1	30.970	28.26	22.21	0.64	28.52	22.59	40.00	-17.41	VERTICAL	QP
2	138.640	30.31	8.18	1.40	28.23	11.66	43.50	-31.84	VERTICAL	QP
3	179.380	30.13	9.55	1.61	27.84	13.45	43.50	-30.05	VERTICAL	QP
4	251.160	29.15	13.10	1.93	27.34	16.84	46.00	-29.16	VERTICAL	QP
5	368.530	28.92	14.88	2.34	28.12	18.02	46.00	-27.98	VERTICAL	QP
6	406.360	30.61	15.69	2.47	28.17	20.60	46.00	-25.40	VERTICAL	QP

Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor

Spurious emissions above 1GHz**Horizontal:**

Peak scan


Level (dB μ V/m)

No.	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Pol/ Phase	Remark
	11867.000	37.62	27.14	27.64	37.12	74.00	-36.88	HORIZONTAL	Peak
	21867.000	31.38	27.14	27.64	30.88	54.00	-23.12	HORIZONTAL	Average
	33312.000	35.75	30.76	27.83	38.68	74.00	-35.32	HORIZONTAL	Peak
	43312.000	28.25	30.76	27.83	31.18	54.00	-22.82	HORIZONTAL	Average
	56559.000	36.03	35.61	27.37	44.27	74.00	-29.73	HORIZONTAL	Peak
	66559.000	29.94	35.61	27.37	38.18	54.00	-15.82	HORIZONTAL	Average

Note: The emission above limit is fundamental emission, which is not subject to the limit.

Vertical:

Peak scan


Level (dB μ V/m)

Freq MHz	Read Level dB μ V	Antenna Factor dB	Preamp Factor dB	Level dB μ V/m	Limit Line dB μ V/m	Over Limit dB	Pol/ Phase	Remark
6134.000	34.45	35.87	27.41	42.91	74.00	-31.09	VERTICAL	Peak
6134.000	29.17	35.87	27.41	37.63	54.00	-16.37	VERTICAL	Average
9279.000	32.97	38.80	27.18	44.59	74.00	-29.41	VERTICAL	Peak
9279.000	27.98	38.80	27.18	39.60	54.00	-14.40	VERTICAL	Average
13852.000	34.11	39.44	26.25	47.30	74.00	-26.70	VERTICAL	Peak
13852.000	29.25	39.44	26.25	42.44	54.00	-11.56	VERTICAL	Average

Note: The emission above limit is fundamental emission, which is not subject to the limit.

Test at Middle Channel in transmitting status**Spurious emissions above 1GHz****Horizontal:**

Peak scan


Level (dB μ V/m)

Freq MHz	Read Level dB μ V	Antenna Factor	Preamp Factor	Level dB μ V/m	Limit Line dB μ V/m	Over Limit dB	Pol/ Phase	Remark
6559.000	35.03	35.61	27.37	43.27	74.00	-30.73	HORIZONTAL	Peak
6559.000	30.15	35.61	27.37	38.39	54.00	-15.61	HORIZONTAL	Average
9279.000	32.57	38.80	27.18	44.19	74.00	-29.81	HORIZONTAL	Peak
9279.000	27.85	38.80	27.18	39.47	54.00	-14.53	HORIZONTAL	Average
13597.000	33.45	39.84	26.30	46.99	74.00	-27.01	HORIZONTAL	Peak
13597.000	28.36	39.84	26.30	41.90	54.00	-12.10	HORIZONTAL	Average

Note: The emission above limit is fundamental emission, which is not subject to the limit.

Vertical:

Peak scan


Level (dB μ V/m)

Freq MHz	Read Level dB μ V	Antenna Factor dB	Preamp Factor dB	Level dB μ V/m	Limit Line dB μ V/m	Over Limit dB	Pol/ Phase	Remark
6049.000	34.76	35.95	27.42	43.29	74.00	-30.71	VERTICAL	Peak
6049.000	30.37	35.95	27.42	38.90	54.00	-15.10	VERTICAL	Average
9330.000	33.22	38.80	27.17	44.85	74.00	-29.15	VERTICAL	Peak
9330.000	27.58	38.80	27.17	39.21	54.00	-14.79	VERTICAL	Average
13597.000	33.87	39.84	26.30	47.41	74.00	-26.59	VERTICAL	Peak
13597.000	27.82	39.84	26.30	41.36	54.00	-12.64	VERTICAL	Average

Note: The emission above limit is fundamental emission, which is not subject to the limit.

Test at high Channel in transmitting status**Spurious emissions above 1GHz****Horizontal:**

Peak scan


Level (dB μ V/m)

Freq MHz	Read Level dB μ V	Antenna Factor dB	Preamp Factor dB	Level dB μ V/m	Limit Line dB μ V/m	Over Limit dB	Pol/ Phase	Remark
7018.000	35.03	36.43	27.34	44.12	74.00	-29.88	HORIZONTAL	Peak
7018.000	29.66	36.43	27.34	38.75	54.00	-15.25	HORIZONTAL	Average
9806.000	33.71	38.92	27.12	45.51	74.00	-28.49	HORIZONTAL	Peak
9806.000	27.62	38.92	27.12	39.42	54.00	-14.58	HORIZONTAL	Average
13053.000	33.30	40.63	26.46	47.47	74.00	-26.53	HORIZONTAL	Peak
13053.000	28.57	40.63	26.46	42.74	54.00	-11.26	HORIZONTAL	Average

Note: The emission above limit is fundamental emission, which is not subject to the limit.

Vertical:

Peak scan

Level (dB μ V/m)

Freq MHz	Read Level dB μ V	Antenna Factor dB	Preamp Factor dB	Level dB μ V/m	Limit Line dB μ V/m	Over Limit dB	Pol/ Phase	Remark
1731.000	45.02	26.16	27.57	43.61	74.00	-30.39	VERTICAL	Peak
1731.000	31.64	26.16	27.57	30.23	54.00	-23.77	VERTICAL	Average
6372.000	34.57	35.63	27.38	42.82	74.00	-31.18	VERTICAL	Peak
6372.000	28.87	35.63	27.38	37.12	54.00	-16.88	VERTICAL	Average
9262.000	34.55	38.80	27.18	46.17	74.00	-27.83	VERTICAL	Peak
9262.000	28.33	38.80	27.18	39.95	54.00	-14.05	VERTICAL	Average

Note: The emission above limit is fundamental emission, which is not subject to the limit.

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), the amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

Remark:

- 1) For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonics of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 3rd harmonic.
- 2) As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3) The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.

5.8 Radiated Emissions which fall in the restricted bands

Test Requirement: FCC Part15 C Section 15.247

(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit: 40.0 dB μ V/m between 30MHz & 88MHz;

43.5 dB μ V/m between 88MHz & 216MHz;

46.0 dB μ V/m between 216MHz & 960MHz;

54.0 dB μ V/m above 960MHz.

Detector: For PK value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW = 10 Hz

Sweep = auto

Detector function = peak

Trace = max hold

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. Only spurious emissions are permitted in any ~~the~~ frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

Test Result:

Test at Channel 1 (2.402 GHz) in transmitting status

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Preamp factor(dB)	Peak Reading Level (dB μ V)	Average Reading Level (dB μ V)	Peak Emission Level (dB μ V/m)	Average Emission Level (dB μ V/m)
2310.000	26.65	6.45	27.78	34.22	23.35	39.54	28.67
2390.000	26.56	6.46	27.79	35.75	24.86	40.98	30.09
2500.000	25.70	6.62	27.80	34.36	23.42	38.88	27.94
2483.500	25.79	6.61	27.80	35.16	23.98	39.76	28.58

Antenna polarization: Horizontal

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Preamp factor(dB)	Peak Reading Level (dB μ V)	Average Reading Level (dB μ V)	Peak Emission Level (dB μ V/m)	Average Emission Level (dB μ V/m)
2310.000	26.65	6.45	27.78	34.24	22.55	39.56	27.87
2390.000	26.56	6.46	27.79	34.36	23.84	39.59	29.07
2500.000	25.70	6.62	27.80	35.74	22.47	40.26	26.99
2483.500	25.79	6.61	27.80	35.71	23.32	40.31	27.92

Test at Channel 40 (2.480 GHz) in transmitting status

Antenna polarization: Vertical

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Preamp factor(dB)	Peak Reading Level (dB μ V)	Average Reading Level (dB μ V)	Peak Emission Level (dB μ V/m)	Average Emission Level (dB μ V/m)
2310.000	26.65	6.45	27.78	34.32	23.35	39.64	28.67
2390.000	26.56	6.46	27.79	35.85	22.75	41.08	27.98
2500.000	25.70	6.62	27.80	35.42	23.27	39.94	27.79
2483.500	25.79	6.61	27.80	35.06	23.16	39.66	27.76

Antenna polarization: Horizontal

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Preamp factor(dB)	Peak Reading Level (dB μ V)	Average Reading Level (dB μ V)	Peak Emission Level (dB μ V/m)	Average Emission Level (dB μ V/m)
2310.000	26.65	6.45	27.78	35.74	23.43	41.06	28.75
2390.000	26.56	6.46	27.79	33.32	22.21	38.55	27.44
2500.000	25.70	6.62	27.80	34.77	24.62	39.29	29.14
2483.500	25.79	6.61	27.80	35.26	23.47	39.86	28.07

Test result: The unit does meet the FCC requirements.

5.9 Band Edges Requirement

Test Requirement: FCC Part15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: ANSI C63.10:2013 Clause 6.9

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set RBW=100 kHz, VBW=300 KHz, suitable frequency span including 1000 kHz bandwidth from band edge.
3. Measure the Conducted Spurious Emissions and Radiated Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse.



Test result with plots as follows:



The band edges was measured and recorded Result:

The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.

Result plot as follows:





Test result: The unit does meet the FCC requirements.

5.10 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz

Test Requirement: FCC Part 15 C section 15.207

Test Method: ANSI C63.10:2013 Clause 6.2

Test Voltage: 120Vac 60Hz

Frequency Range: 150 kHz to 30 MHz

Detector: Peak for pre-scan (9 kHz Resolution Bandwidth)


Test Limit

Limits for conducted disturbance at the mains ports of class B

Frequency Range	Class B Limit dB(µV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.
Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Test Configuration:**Test procedure:**

1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1(Line Impedance Stabilization Network) which provides a 500/50uh 5Q linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0. 8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0. 4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0. 8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNS mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0, 8 m from the LISN 2.

5.10.1 Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.


Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

The following Quasi-Peak and Average measurements were performed on the EUT

Live line

Peak Scan:

Level (dB μ V)




Quasi-peak and Average measurement

NO.	Freq MHz	Level dB μ V	Remark	LISN Factor dB	Cable Loss dB	Limit Line dB μ V	Over Limit dB
1	0.169	51.57	QP	9.69	0.21	64.99	-13.42
2	0.169	26.02	Average	9.69	0.21	54.99	-28.97
3	0.480	45.77	QP	9.65	0.27	56.33	-10.56
4	0.480	31.76	Average	9.65	0.27	46.33	-14.57
5	0.847	40.33	QP	9.69	0.30	56.00	-15.67
6	0.847	25.69	Average	9.69	0.30	46.00	-20.31
7	2.293	39.70	QP	9.64	0.35	56.00	-16.30
8	2.293	24.28	Average	9.64	0.35	46.00	-21.72
9	5.022	34.55	QP	9.60	0.40	60.00	-25.45
10	5.022	21.58	Average	9.60	0.40	50.00	-28.42
11	23.326	25.67	QP	9.67	0.49	60.00	-34.33
12	23.326	16.76	Average	9.67	0.49	50.00	-33.24

Neutral Line

Peak Scan:

Level (dB μ V)

Quasi-peak and Average measurement

NO.	Freq MHz	Level dB μ V	Remark	LISN Factor dB	Cable Loss dB	Limit Line dB μ V	Over Limit dB
1	0.215	50.12	QP	9.63	0.22	63.01	-12.89
2	0.215	27.51	Average	9.63	0.22	53.01	-25.50
3	0.483	44.98	QP	9.67	0.27	56.29	-11.31
4	0.483	35.71	Average	9.67	0.27	46.29	-10.58
5	1.008	38.21	QP	9.63	0.31	56.00	-17.79
6	1.008	28.83	Average	9.63	0.31	46.00	-17.17
7	3.035	37.53	QP	9.62	0.37	56.00	-18.47
8	3.035	28.00	Average	9.62	0.37	46.00	-18.00
9	5.072	33.20	QP	9.62	0.40	60.00	-26.80
10	5.072	24.47	Average	9.62	0.40	50.00	-25.53
11	23.456	25.15	QP	9.63	0.49	60.00	-34.85
12	23.456	15.62	Average	9.63	0.49	50.00	-34.38

--End of Report--