

Maximum Permissible Exposure Evaluation

FCC ID: 2A3AA-GD850

1. Client Information

Applicant	:	Shenzhen Hengyifa Trading Co.,Ltd.
Address	:	No.301, Factory 1, Dongfang Wugang Industrial Zone, Song Yu Road, Dongfang Community, Songgang Street, Baoan District, Shenzhen, China
Manufacturer	:	Shenzhen Hengyifa Trading Co.,Ltd.
Address	:	No.301, Factory 1, Dongfang Wugang Industrial Zone, Song Yu Road, Dongfang Community, Songgang Street, Baoan District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Dash Camera	
Models No.	:	GD850, GD100, GD200, GD300, GD400, GD500, GD600, GD700, GD800, GD900, GD150, GD250, GD350, GD450, GD550, GD650, GD750, GD950, GD120, GD520	
Model Different	:	All these models are the same in the same PCB, layout and circuit, the only difference is the color and model name.	
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz	
	Number of Channel:	802.11b/g/n(HT20):11 channels	
	RF Output Power:	802.11b: 11.43dBm (MAX)	
	Antenna Gain:	2.4dBi FPC Antenna	
Power Rating	:	Input: DC 5V1.5A Output: DC 3.7V by 240 mAh Rechargeable Li-ion battery	
Software Version	:	N/A	
Hardware Version	:	V0.3	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Remark	:	the evaluation report used the EUT (20210817-21-02).	

MPE Calculations for WIFI

1. Antenna Gain:

FPC Antenna: 2.4dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

2.4G WiFi

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]	Limit of Power Density (mW/ cm ²) (S)
802.11B	11.43	11±1	12	2.4	20	0.00548	1
802.11G	10.38	10±1	11	2.4	20	0.00435	1
802.11N(HT20)	11.10	11±1	12	2.4	20	0.00548	1

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 2.4WIFI: 2412~2462 MHz
MPE limit S: 1mW/ cm²

The MPE is calculated as **0.00548 mW / cm² < limit 1mW / cm²**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

6. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF REPORT-----