

Wireless remote control manual

Wireless remote control manual

No	Notes	Technical specifications
1	ambient temperature	0-60°C
2	relative humidity	< 90%
3	Storage temperature	-20-60°C
4	atmospheric pressure	86-106Kpa
5	supply voltage	DC3.0V
6	Ambient brightness	No requirement
7	Silicone material	silica gel
8	Radio frequency	433.92M
9	Quiescent current	≤5uA
10	Working current	≤20mA
11	Operating voltage range	2.4V-3.4V
12	Transmit power	+4DB
13	Directivity	No
14	Action distance	≥20m
15	Operating distance under voltage (2.5V)	≥10m
16	Key force	90-180g
17	Free drop test	76cm6 times
18	Electrostatic environment test	15KV
19	High temperature storage test	50°C
20	Low temperature storage test	-20°C
21	Constant temperature damp heat test	40 °C relative humidity 90
22	PCB board material	1.0mm carbon oil filler plate
23	Appearance color	(customer requirements)
24	Plastic material	ABS
25	Thickness of plastic material	≥2.0mm
26	Use battery	2 AAA batteries (2.5-3.4v)
27	Working power supply	2.5-3.4V
28	Power consumption	8-10mW
29	Patch 1206 red light	1PCS
30		
31		
32		
33		
34		
35		
36		
附注： .		

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that

interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Warning: changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment

The device has been evaluated to meet general RF exposure requirement, the device can be used in portable exposure condition without restriction