

## FCC RF Exposure

EUT Description: Scout

Model No.: SC3100, 3100002

FCC ID: 2A3AR-SC3100

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F = frequency in MHz

Formula:  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where :

Pd = power density in mW/cm<sup>2</sup>,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi = 3.14$ ;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3. Test Result of RF Exposure Evaluation

Note: 2.4G wifi and 5G wifi cannot transmit at the same time

### 2.4G WIFI

	Output power (dBm/ mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11b	9.65/9.226	1.0	0.00231	1.0	Pass
802.11g	9.11/8.147	1.0	0.00204	1.0	Pass
802.11n(20MHz)	7.65/5.821	1.0	0.00146	1.0	Pass

### 5G WIFI

	Output power (dBm/ mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
U-NII-1a	18.51/70.958	1.0	0.01776	1.0	Pass
U-NII-1n(HT20)	16.99/50.003	1.0	0.01252	1.0	Pass
U-NII-3a	15.94/39.264	1.0	0.00983	1.0	Pass
U-NII-3n(HT20)	13.57/22.751	1.0	0.00569	1.0	Pass

### Turn-up power

Mode	Peak power range(dBm)
2.4G WIFI	7.00-9.65
5G WIFI	13.50-18.51

WIFI	Output power (dBm/ mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
2.4G WIFI	9.65/9.226	1.0	0.00231	1.0	Pass
5.8GWIFI	18.51/70.958	1.0	0.01776	1.0	Pass

Conclusion: No SAR is required