

TEST REPORT

Applicant: Beijing Orion Star Technology Co., Ltd.

Address: Room A-2570, 2nd Floor No. 30 Shixing Street, Shijingshan District, Beijing China.

Product Name: Dispatch Center

FCC ID: 2A3BD-OSADF02R

Standard(s): 47 CFR Part 15, Subpart E(15.407)
ANSI C63.10-2013
KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

Report Number: 2402W68103E-RF-00D

Report Date: 2024/10/9

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Reviewed By: Pedro Yun
Title: Project Engineer

Approved By: Ivan Cao
Title: EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	5
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	9
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	10
3.4 SUPPORT CABLE LIST AND DETAILS	10
3.5 BLOCK DIAGRAM OF TEST SETUP	11
3.6 TEST FACILITY	13
3.7 MEASUREMENT UNCERTAINTY	13
4. REQUIREMENTS AND TEST PROCEDURES	14
4.1 AC LINE CONDUCTED EMISSIONS	14
4.1.1 Applicable Standard	14
4.1.2 EUT Setup	15
4.1.3 EMI Test Receiver Setup	15
4.1.4 Test Procedure	16
4.1.5 Corrected Amplitude & Margin Calculation	16
4.1.6 Test Result	16
4.2 RADIATION SPURIOUS EMISSIONS	17
4.2.1 Applicable Standard	17
4.2.2 EUT Setup	18
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	19
4.2.4 Test Procedure	20
4.2.5 Corrected Result & Margin Calculation	20
4.2.6 Test Result	20
4.3 EMISSION BANDWIDTH	21
4.3.1 Applicable Standard	21
4.3.2 EUT Setup	21
4.3.3 Test Procedure	21
4.3.4 Test Result	22
4.4 MAXIMUM CONDUCTED OUTPUT POWER	23
4.4.1 Applicable Standard	23
4.4.2 EUT Setup	23
4.4.3 Test Procedure	23
4.4.4 Test Result	23
4.5 MAXIMUM POWER SPECTRAL DENSITY	24
4.5.1 Applicable Standard	24

4.5.2 EUT Setup	24
4.5.3 Test Procedure	24
4.5.4 Test Result	25
4.6 DUTY CYCLE	26
4.6.1 EUT Setup	26
4.6.2 Test Procedure	26
4.6.3 Judgment	26
4.7 ANTENNA REQUIREMENT	27
4.7.1 Applicable Standard	27
4.7.2 Judgment	27
5. Test DATA AND RESULTS	28
5.1 AC LINE CONDUCTED EMISSIONS	28
5.2 RADIATION SPURIOUS EMISSIONS	31
5.3 EMISSION BANDWIDTH	82
5.4 99% OCCUPIED BANDWIDTH	90
5.5 MAXIMUM CONDUCTED OUTPUT POWER	98
5.6 POWER SPECTRAL DENSITY	100
5.7 DUTY CYCLE	108
EXHIBIT A - EUT PHOTOGRAPHS	110
EXHIBIT B - TEST SETUP PHOTOGRAPHS	111

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402W68103E-RF-00D	Original Report	2024/10/9

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Dispatch Center
EUT Model:	OS-A-DF02R
Operation Frequency:	5150-5250MHz: 5180-5240 MHz(802.11a/n ht20) 5190-5230 MHz(802.11n ht40) 5250-5350MHz: 5260-5320 MHz (802.11a/n ht20) 5270-5310 MHz(802.11n ht40) 5470-5725MHz: 5500-5720 MHz (802.11a/n ht20) 5510-5710 MHz(802.11n ht40) 5725-5850MHz: 5745-5825 MHz (802.11a/n ht20) 5755-5795 MHz(802.11n ht40)
Maximum Average Conducted Output Power:	5150-5250MHz:11.85dBm
	5250-5350MHz:11.68dBm
	5350-5470MHz:12.22dBm
	5725-5850MHz:12.84dBm
Modulation Type:	802.11a/n: OFDM-BPSK, QPSK, 16QAM, 64QAM,256QAM
Rated Input Voltage:	DC 12V from Adapter
Serial Number:	2QWQ-1 (For RF Conducted Test) 2QWQ-3 (For AC Line Conducted Emissions and Radiated Spurious Emission Test)
EUT Received Date:	2024/8/30
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter	Shenzhen Keyu Power Supply Technology Co.,Ltd	KA24D-1202000US	Input:100-240Vac~50/60Hz 0.65A Max Output: 12Vdc,2000mA

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Huizhou Speed Wireless technology Co.,Ltd.	Dipole antenna	50	5.15~5.25GHz	4.16dBi
			5.25~5.35 GHz	4.16dBi
			5.47~5.725 GHz	4.32dBi
			5.725~5.85 GHz	4.23dBi
The design of compliance with §15.203: ☐ Unit uses a permanently attached antenna. ☐ Unit uses a unique coupling to the intentional radiator. ☒ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
FCC§15.407(a) (e)	Emission Bandwidth	Compliant
FCC§15.407 (a)	Maximum Conducted Output Power	Compliant
FCC§15.407 (a)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
Note 1: For AC line conducted emissions, the maximum output power channel was tested. Note 2: For Radiated Spurious Emissions 9kHz~ 1GHz and 18-40GHz, the maximum output power channel was tested.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11a/n ht20:

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	56	5280	104	5520	153	5765
44	5220	60	5300	108	5540	157	5785
48	5240	64	5320	112	5560	161	5805
/	/	/	/	116	5580	165	5825
/	/	/	/	120	5600	/	/
/	/	/	/	124	5620	/	/
/	/	/	/	128	5640	/	/
/	/	/	/	132	5660	/	/
/	/	/	/	136	5680	/	/
/	/	/	/	140	5700	/	/
/	/	/	/	144	5720	/	/

For 802.11n ht40:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
/	/	/	/	118	5590	/	/
/	/	/	/	126	5630	/	/
/	/	/	/	134	5670	/	/
/	/	/	/	142	5710	/	/

Note: Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

3.2 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

The EUT configuration is below:

EUT Exercise Software: CMD.exe				
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
5150-5250 MHz Band:				
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting
802.11a	Lowest	5180	6Mbps	15.5
	Middle	5200	6Mbps	15.5
	Highest	5240	6Mbps	15.5
802.11n ht20	Lowest	5180	MCS0	14.5
	Middle	5200	MCS0	14.5
	Highest	5240	MCS0	14.5
802.11n ht40	Lowest	5190	MCS0	13.5
	Highest	5230	MCS0	13.5
5250-5350 MHz Band:				
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting
802.11a	Lowest	5260	6Mbps	15.5
	Middle	5280	6Mbps	15.5
	Highest	5320	6Mbps	15.5
802.11n ht20	Lowest	5260	MCS0	14.5
	Middle	5280	MCS0	14.5
	Highest	5320	MCS0	14.5
802.11n ht40	Lowest	5270	MCS0	13.5
	Highest	5310	MCS0	13.5
5470-5725 MHz Band:				
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting
802.11a	Lowest	5500	6Mbps	20
	Middle	5580	6Mbps	20
	Highest	5700	6Mbps	20
	Cross	5720	6Mbps	20
802.11n ht20	Lowest	5500	MCS0	20
	Middle	5580	MCS0	20
	Highest	5700	MCS0	20
	Cross	5720	MCS0	20
802.11n ht40	Lowest	5510	MCS0	18
	Middle	5550	MCS0	18
	Highest	5670	MCS0	18
	Cross	5710	MCS0	18

5725-5850 MHz Band:				
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting
802.11a	Lowest	5745	6Mbps	22
	Middle	5785	6Mbps	22
	Highest	5825	6Mbps	22
802.11n ht20	Lowest	5745	MCS0	22
	Middle	5785	MCS0	22
	Highest	5825	MCS0	22
802.11n ht40	Lowest	5755	MCS0	21
	Highest	5795	MCS0	21

Note:
1. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
PHILIPS	Mouse	SPK7214	M214BQ210411117
PHILIPS	Keyboard	SPK6234	K234210510744
CLC	Earphone	Blackview5.0	EMZBEP21103001W
Lenovo	Laptop	E450	PF-OMR8KV
DELL	Monitor	P2721Q	CN-0XJ46C-FCC00-135-A97L-A03

3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	1	Adapter	EUT
RJ45 Cable	No	No	10	Laptop	EUT
HDMI Cable	Yes	Yes	1.2	Monitor	EUT
Mouse Cable	No	No	1.5	Mouse	EUT
Keyboard Cable	No	No	1.5	Keyboard	EUT
Earphone Cable	No	No	1.5	Earphone	EUT


3.5 Block Diagram of Test Setup

AC line conducted emissions:




Spurious Emissions:

Below 1GHz:



Above 1GHz:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard


FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.
- (10) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.
- (c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.


4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:

The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2013. The specification used was FCC 15.209, FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz
30 MHz – 1000 MHz	PK	100 kHz	300 kHz	/
	QP	/	/	120 kHz

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value is under the QP limit by more than 6dB, then it is unnecessary to perform an QP measurement.

If the maximized peak measured value is under the average limit, then it is unnecessary to perform an QP measurement.

4.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

For Radiated Bandedge test, which was performed at 1.5 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$ dB = 6.0dB

4.2.5 Corrected Result & Margin Calculation

The basic equation except radiated bandedge test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

Result = Reading + Factor

For Radiated Bandedge test:

Factor = Antenna Factor + Cable Loss-Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.

4.3 Emission Bandwidth

4.3.1 Applicable Standard


FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.3.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2013 Section 12.4.1

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) ≥ 3 RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3.4 Test Result

Please refer to section 5.3 and section 5.4.

4.4 Maximum Conducted Output Power

4.4.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer ▲.

4.4.3 Test Procedure

According to ANSI C63.10-2013 Section 12.3.3.1

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.4.4 Test Result

Please refer to section 5.5.

4.5 Maximum Power Spectral Density

4.5.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer ▲.

4.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle <98%, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle <98%, duty cycle variations exceed $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

4.5.4 Test Result

Please refer to section 5.6.

4.6 Duty Cycle

4.6.1 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.6.2 Test Procedure

According to ANSI C63.10-2013 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.6.3 Judgment

Report Only. Please refer to section 5.7.

4.7 Antenna Requirement

4.7.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.7.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2QWQ-3	Test Date:	2024/9/8
Test Site:	CE	Test Mode:	Transmitting
Tester:	Lane Sun	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	63	ATM Pressure: (kPa)	100.3
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2023/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2024/9/5	2025/9/4
R&S	EMI Test Receiver	ESCI	100035	2024/8/18	2025/8/17
Audix	Test Software	E3	191218 V9	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Project No.: 2402W68103E-RF
Port: Line
Test Mode: Transmitting
Note: 5G Wifi 802.11n20 5825MHz

Serial No.: 20WQ-3
Tester: Lane Sun

Date: 2024-09-08




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.159	41.24	10.77	52.01	65.52	13.51	QP
2	0.159	23.59	10.77	34.36	55.52	21.16	Average
3	0.479	27.75	10.84	38.59	56.36	17.77	QP
4	0.479	24.18	10.84	35.02	46.36	11.34	Average
5	0.638	18.65	10.84	29.49	56.00	26.51	QP
6	0.638	10.87	10.84	21.71	46.00	24.29	Average
7	0.937	16.70	10.86	27.56	56.00	28.44	QP
8	0.937	11.69	10.86	22.55	46.00	23.45	Average
9	12.746	25.82	10.81	36.63	60.00	23.37	QP
10	12.746	17.87	10.81	28.68	50.00	21.32	Average
11	29.908	30.90	10.87	41.77	60.00	18.23	QP
12	29.908	24.14	10.87	35.01	50.00	14.99	Average

Project No.: 2402W68103E-RF
Port: neutral
Test Mode: Transmitting
Note: 5G Wifi 802.11n20 5825MHz

Serial No.: 20WQ-3
Tester: Lane Sun

Date: 2024-09-08



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.156	40.25	10.85	51.10	65.70	14.60	QP
2	0.156	20.71	10.85	31.56	55.70	24.14	Average
3	0.183	38.94	10.85	49.79	64.33	14.54	QP
4	0.183	21.91	10.85	32.76	54.33	21.57	Average
5	0.478	27.70	10.75	38.45	56.37	17.92	QP
6	0.478	24.10	10.75	34.85	46.37	11.52	Average
7	0.721	18.86	10.77	29.63	56.00	26.37	QP
8	0.721	13.82	10.77	24.59	46.00	21.41	Average
9	12.449	25.24	10.85	36.09	60.00	23.91	QP
10	12.449	17.83	10.85	28.68	50.00	21.32	Average
11	29.599	30.40	10.97	41.37	60.00	18.63	QP
12	29.599	23.84	10.97	34.81	50.00	15.19	Average

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	2QWQ-3	Test Date:	2024/9/26
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Alan Xie	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.7	Relative Humidity: (%)	44	ATM Pressure: (kPa)	100.6
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-3	2024/1/12	2027/1/11
Wilson	Coaxial Attenuator	859936	F-08-EM014	2024/1/12	2027/1/11
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	372193	2024/8/16	2025/8/15
R&S	EMI Test Receiver	ESR3	102453	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to table and plots.

9kHz~30MHz


The 802.11 n20 5825MHz was tested. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30MHz-1GHz

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_5825MHz

Serial No.: 20WQ-3
Tester: Alan Xie


Date: 2024-09-26



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	32.91	42.41	-5.43	36.98	40.00	3.02	QP
2	47.46	51.60	-14.84	36.76	40.00	3.24	QP
3	93.05	55.31	-15.59	39.72	43.50	3.78	QP
4	144.46	49.70	-10.93	38.77	43.50	4.73	QP
5	245.34	50.58	-11.23	39.35	46.00	6.65	Peak
6	485.90	43.96	-4.47	39.49	46.00	6.51	Peak

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_5825MHz

Serial No.: 20WQ-3
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	35.82	43.99	-7.35	36.64	40.00	3.36	QP
2	47.46	52.80	-14.84	37.96	40.00	2.04	QP
3	59.10	52.39	-17.00	35.39	40.00	4.61	QP
4	98.87	53.70	-13.71	39.99	43.50	3.51	QP
5	104.69	52.80	-12.31	40.49	43.50	3.01	QP
6	140.58	49.31	-10.58	38.73	43.50	4.77	QP

2) 1-40GHz:

Serial Number:	2QWQ-3	Test Date:	2024/9/5-2024/9/6
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Nat Zhou, Colin Yang	Test Result:	Pass





Environmental Conditions:

Temperature: (°C)	25.2-26.2	Relative Humidity: %	34-40	ATM Pressure: (kPa)	99.4-99.5
----------------------	-----------	-------------------------	-------	------------------------	-----------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2023/11/17	2024/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2023/12/11	2024/12/10
AH	Preamplifier	PAM-0118P	469	2024/4/15	2025/4/15
AH	Preamplifier	PAM-1840VH	191	2023/9/7	2024/9/6
R&S	Spectrum Analyzer	FSV40	101944	2023/10/18	2024/10/17
Audix	Test Software	E3	191218 (V9)	N/A	N/A
Sinoscite	Band Rejection Filter	BSF5150-5850MN	0899003	2024/2/21	2025/2/20
Mini-Circuits	High Pass Filter	VHF-6010+	31118	2023/12/1	2024/11/30




* Statement of Traceability: Bay Area Compliance Laboratories Corp.(Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Worst Channel Test plots:
5150-5250MHz:****802.11a mode, Low Channel, Horizontal****802.11a mode, Low Channel, Vertical**


802.11a mode, Middle Channel, Horizontal






802.11a mode, Middle Channel, Vertical




802.11a mode, High Channel, Horizontal






802.11a mode, High Channel, Vertical



802.11n ht20 mode, Low Channel, Horizontal



802.11n ht20 mode, Low Channel, Vertical




802.11n ht20 mode, Middle Channel,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-1 middle channel 5200MHz

Serial No.: 20M0-3
Tester: Nat Zhou

Date: 2024-09-06




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4657.00	50.92	-10.11	40.81	74.00	33.19	Peak
2	4657.00	38.68	-10.11	28.57	54.00	25.43	Average

802.11n ht20 mode, Middle Channel, Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-1 middle channel 5200MHz

Serial No.: 20M0-3
Tester: Nat Zhou

Date: 2024-09-06




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4835.00	51.25	-10.07	41.18	74.00	32.82	Peak
2	4835.00	39.18	-10.07	29.11	54.00	24.89	Average

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-1 middle channel 5200MHz

Serial No.: 20M0-3
Tester: Nat Zhou

Date: 2024-09-06




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18400.00	49.59	0.40	49.99	68.20	18.21	Peak
2	15600.00	47.61	0.58	48.19	74.00	25.81	Peak
3	15600.00	37.40	0.58	37.98	54.00	16.02	Average
4	17988.00	45.98	8.05	54.03	74.00	19.97	Peak
5	17988.00	39.53	8.05	47.58	54.00	6.42	Average

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-1 middle channel 5200MHz


Serial No.: 20M0-3
Tester: Nat Zhou

Date: 2024-09-06






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18400.00	50.34	0.40	50.74	68.20	17.46	Peak
2	15600.00	48.60	0.58	49.18	74.00	24.82	Peak
3	15600.00	38.18	0.58	38.76	54.00	15.24	Average
4	17997.60	46.46	8.12	54.58	74.00	19.42	Peak
5	17997.60	39.65	8.12	47.77	54.00	6.23	Average


802.11n ht20 mode, High Channel, Horizontal






802.11n ht20 mode, High Channel, Vertical




802.11n ht40 mode, Low Channel, Horizontal






802.11n ht40 mode, Low Channel, Vertical



802.11n ht40 mode, High Channel, Horizontal




802.11n ht40 mode, High Channel, Vertical






5250-5350MHz:


802.11a mode, Low Channel, Horizontal






802.11a mode, Low Channel, Vertical




802.11a mode, Middle Channel, Horizontal






802.11a mode, Middle Channel, Vertical




802.11a mode, High Channel, Horizontal






802.11a mode, High Channel, Vertical




802.11n20 mode, Low Channel, Horizontal






802.11n20 mode, Low Channel, Vertical




802.11n20 mode, Middle Channel, Horizontal






802.11n20 mode, Middle Channel, Vertical




802.11n20 mode, High Channel, Horizontal






802.11n20 mode, High Channel, Vertical




802.11n40 mode, Low Channel, Horizontal






802.11n40 mode, Low Channel, Vertical



802.11n40 mode, High Channel, Horizontal




802.11n40 mode, High Channel, Vertical






5470-5725MHz:


802.11a mode, Low Channel, Horizontal






802.11a mode, Low Channel, Vertical




802.11a mode, Middle Channel, Horizontal






802.11a mode, Middle Channel, Vertical




802.11a mode, High Channel, Horizontal






802.11a mode, High Channel, Vertical




802.11n20 mode, Low Channel, Horizontal






802.11n20 mode, Low Channel, Vertical




802.11n20 mode, Middle Channel, Horizontal






802.11n20 mode, Middle Channel, Vertical




802.11n20 mode, High Channel, Horizontal






802.11n20 mode, High Channel, Vertical




802.11n40 mode, Low Channel, Horizontal






802.11n40 mode, Low Channel, Vertical




802.11n40 mode, Middle Channel, Horizontal






802.11n40 mode, Middle Channel, Vertical



802.11n40 mode, High Channel, Horizontal




802.11n40 mode, High Channel, Vertical






5725-5850MHz:


802.11a mode, Low Channel, Horizontal






802.11a mode, Low Channel, Vertical




802.11a mode, Middle Channel, Horizontal






802.11a mode, Middle Channel, Vertical




802.11a mode, High Channel, Horizontal






802.11a mode, High Channel, Vertical




802.11n20 mode, Low Channel, Horizontal






802.11n20 mode, Low Channel, Vertical




802.11n20 mode, Middle Channel, Horizontal






802.11n20 mode, Middle Channel, Vertical




802.11n20 mode, High Channel, Horizontal






802.11n20 mode, High Channel, Vertical




802.11n40 mode, Low Channel, Horizontal






802.11n40 mode, Low Channel, Vertical



802.11n40 mode, High Channel, Horizontal




802.11n40 mode, High Channel, Vertical



Bandedge:**802.11a mode, Low Channel, 5180MHz,
Horizontal**

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 low channel 5180MHz

Serial No.: 20M0-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	31.90	28.76	60.66	74.00	13.34	Peak
2	5150.00	18.34	28.76	47.10	54.00	6.90	Average

**802.11a mode, Low Channel,
5180MHz,Vertical**

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 low channel 5180MHz

Serial No.: 20M0-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	34.80	28.76	63.56	74.00	10.44	Peak
2	5150.00	22.79	28.76	51.55	54.00	2.45	Average

**802.11a mode, High Channel, 5240MHz,
Horizontal**

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz

Serial No.: 20M0-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	29.85	29.15	59.00	74.00	15.00	Peak
2	5350.00	18.35	29.15	47.50	54.00	6.50	Average

**802.11a mode, High Channel,
5240MHz,Vertical**

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz


Serial No.: 20M0-3
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	29.46	29.15	58.61	74.00	15.39	Peak
2	5350.00	18.02	29.15	47.17	54.00	6.83	Average

802.11n20 mode, Low Channel, 5180MHz,
Horizontal


Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-1 low channel 5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	30.88	28.76	59.64	74.00	14.36	Peak
2	5150.00	18.16	28.76	46.92	54.00	7.08	Average

802.11n20 mode, Low Channel,
5180MHz,Vertical


Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-1 low channel 5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	35.51	28.76	64.27	74.00	9.73	Peak
2	5150.00	22.30	28.76	51.06	54.00	2.94	Average

802.11n20 mode, High Channel, 5240MHz,
Horizontal


Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-1 high channel 5240MHz







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	29.45	29.15	58.60	74.00	15.40	Peak
2	5350.00	18.05	29.15	47.20	54.00	6.80	Average

802.11n20 mode, High Channel,
5240MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-1 high channel 5240MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	29.40	29.15	58.55	74.00	15.45	Peak
2	5350.00	18.32	29.15	47.47	54.00	6.53	Average

802.11n40 mode, Low Channel, 5190MHz,
Horizontal802.11n40 mode, Low Channel,
5190MHz,Vertical802.11n40 mode, High Channel, 5230MHz,
Horizontal802.11n40 mode, High Channel,
5230MHz,Vertical

802.11a mode, Low Channel, 5260MHz,
Horizontal


Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11a_U-NII-2A low channel 5260MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	30.33	28.76	59.09	74.00	14.91	Peak
2	5150.00	18.32	28.76	47.08	54.00	6.92	Average

802.11a mode, Low Channel, 5260MHz,Vertical


Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11a_U-NII-2A low channel 5260MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	30.50	28.76	59.26	74.00	14.74	Peak
2	5150.00	18.41	28.76	47.17	54.00	6.83	Average

802.11a mode, High Channel, 5320MHz,
Horizontal


Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11a_U-NII-2A high channel 5320MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	32.25	29.15	61.40	74.00	12.60	Peak
2	5350.00	19.37	29.15	48.52	54.00	5.48	Average

802.11a mode, High Channel, 5320MHz,Vertical


Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11a_U-NII-2A high channel 5320MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	34.04	29.15	63.19	74.00	10.81	Peak
2	5350.00	22.49	29.15	51.64	54.00	2.36	Average

802.11n20 mode, Low Channel, 5260MHz,
Horizontal


Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-2A low channel 5260MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	29.13	28.76	57.89	74.00	16.11	Peak
2	5150.00	17.89	28.76	46.65	54.00	7.35	Average

802.11n20 mode, Low Channel,
5260MHz,Vertical


Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-2A low channel 5260MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	30.55	28.76	59.31	74.00	14.69	Peak
2	5150.00	18.32	28.76	47.08	54.00	6.92	Average

802.11n20 mode, High Channel, 5320MHz,
Horizontal


Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-2A high channel 5320MHz







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	32.70	29.15	61.85	74.00	12.15	Peak
2	5350.00	20.23	29.15	49.38	54.00	4.62	Average

802.11n20 mode, High
Channel,5320MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 20MQ-3
Tester: Colin Yang
Note: 802.11n20_U-NII-2A high channel 5320MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.00	36.34	29.15	65.49	74.00	8.51	Peak
2	5350.00	23.12	29.15	52.27	54.00	1.73	Average

802.11n40 mode, Low Channel, 5270MHz,
Horizontal802.11n40 mode, Low Channel,
5270MHz,Vertical802.11n40 mode, High Channel, 5310MHz,
Horizontal802.11n40 mode, High Channel,
5310MHz,Vertical

802.11a mode, Low Channel, 5500MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C low channel 5500MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5460.00	31.61	29.34	60.95	74.00	13.05	Peak
2	5460.00	18.43	29.34	47.77	54.00	6.23	Average
3	5470.00	34.14	29.36	63.50	68.20	4.70	Peak

802.11a mode, Low Channel,
5500MHz, Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C low channel 5500MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5460.00	32.80	29.34	62.14	74.00	11.86	Peak
2	5460.00	20.11	29.34	49.45	54.00	4.55	Average
3	5470.00	36.83	29.36	66.19	68.20	2.01	Peak

802.11a mode, High Channel, 5700MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C high channel 5700MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5725.00	34.05	29.81	63.86	68.20	4.34	Peak

802.11a mode, High Channel,
5700MHz, Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C high channel 5700MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5725.00	35.30	29.81	65.11	68.20	3.09	Peak

802.11n20 mode, Low Channel, 5500MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C low channel 5500MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5460.00	30.89	29.34	60.23	74.00	13.77	Peak
2	5460.00	21.13	29.34	50.47	54.00	3.53	Average
3	5470.01	34.57	29.36	63.93	68.20	4.27	Peak

802.11n20 mode, Low Channel,
5500MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C low channel 5500MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5460.00	32.11	29.34	61.45	74.00	12.55	Peak
2	5460.00	22.38	29.34	51.72	54.00	2.28	Average
3	5470.01	37.32	29.36	66.68	68.20	1.52	Peak

802.11n20 mode, High Channel, 5700MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C high channel 5700MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	35.26	29.81	65.07	68.20	3.13	Peak

802.11n20 mode, High Channel,
5700MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C high channel 5700MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	37.21	29.81	67.02	68.20	1.18	Peak

802.11n40 mode, Low Channel, 5510MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40_U-NII-2C low channel 5510MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5460.00	30.99	29.34	60.33	74.00	13.67	Peak
2	5460.00	20.66	29.34	50.00	54.00	4.00	Average
3	5470.00	35.57	29.36	64.93	68.20	3.27	Peak

802.11n40 mode, Low Channel, 5510MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40_U-NII-2C low channel 5510MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5460.00	33.12	29.34	62.46	74.00	11.54	Peak
2	5460.00	21.82	29.34	51.16	54.00	2.84	Average
3	5470.00	37.83	29.36	67.19	68.20	1.01	Peak

802.11n40 mode, High Channel, 5670MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40_U-NII-2C high channel 5670MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	32.04	29.81	61.85	68.20	6.35	Peak

802.11n40 mode, High Channel, 5670MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40_U-NII-2C high channel 5670MHz

Serial No.: 20M0-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	35.48	29.81	65.29	68.20	2.91	Peak

802.11a mode, Low Channel, 5745MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-3 low channel 5745MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	30.64	29.69	60.33	68.20	7.87	Peak
2	5700.00	31.63	29.77	61.40	105.20	43.80	Peak
3	5720.00	45.00	29.80	74.80	110.80	36.00	Peak
4	5725.00	47.94	29.81	77.75	122.20	44.45	Peak

802.11a mode, Low Channel, 5745MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-3 low channel 5745MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	31.48	29.69	61.17	68.20	7.03	Peak
2	5700.00	34.44	29.77	64.21	105.20	40.99	Peak
3	5720.00	47.81	29.80	77.61	110.80	33.19	Peak
4	5725.00	50.73	29.81	80.54	122.20	41.66	Peak

802.11a mode, High Channel, 5825MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	34.57	30.00	64.57	122.20	57.63	Peak
2	5855.00	32.46	30.01	62.47	110.80	48.33	Peak
3	5875.00	32.26	30.04	62.30	105.20	42.90	Peak
4	5925.00	32.25	30.12	62.37	68.20	5.83	Peak





802.11a mode, High Channel, 5825MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz

Serial No.: 20MQ-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	36.53	30.00	66.53	122.20	55.67	Peak
2	5855.00	35.10	30.01	65.11	110.80	45.69	Peak
3	5875.00	31.20	30.04	61.24	105.20	43.96	Peak
4	5925.00	31.89	30.12	62.01	68.20	6.19	Peak

802.11n20 mode, Low Channel, 5745MHz,
Horizontal802.11n20 mode, Low Channel,
5745MHz,Vertical802.11n20 mode, High Channel, 5825MHz,
Horizontal802.11n20 mode, High Channel,
5825MHz,Vertical

802.11n40 mode, Low Channel, 5755MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40_U-NII-3 low channel 5755MHz

Serial No.: 20M0-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	31.00	29.69	60.69	68.20	7.51	Peak
2	5700.00	36.14	29.77	65.91	105.20	39.29	Peak
3	5720.00	44.52	29.80	74.32	110.80	36.48	Peak
4	5725.00	47.12	29.81	76.93	122.19	45.26	Peak

802.11n40 mode, Low Channel, 5755MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40_U-NII-3 low channel 5755MHz

Serial No.: 20M0-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	32.18	29.69	61.87	68.20	6.33	Peak
2	5700.00	40.30	29.77	70.07	105.20	35.13	Peak
3	5720.00	50.37	29.80	80.17	110.80	30.63	Peak
4	5725.00	51.09	29.81	80.90	122.19	41.29	Peak

802.11n40 mode, High Channel, 5795MHz,
Horizontal

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40_U-NII-3 high channel 5795MHz

Serial No.: 20M0-3
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	33.50	30.00	63.50	122.20	58.70	Peak
2	5855.00	31.68	30.01	61.69	110.80	49.11	Peak
3	5875.00	32.03	30.04	62.07	105.20	43.13	Peak
4	5925.00	31.50	30.12	61.62	68.20	6.58	Peak

802.11n40 mode, High Channel, 5795MHz,Vertical

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40_U-NII-3 high channel 5795MHz

Serial No.: 20M0-3
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	31.75	30.00	61.75	122.20	60.45	Peak
2	5855.00	32.14	30.01	62.15	110.80	48.65	Peak
3	5875.00	31.63	30.04	61.67	105.20	43.53	Peak
4	5925.00	32.26	30.12	62.38	68.20	5.82	Peak

18-40GHz:


No Emission was detected in the range 18-40GHz, test was performed on the mode and channel which with the maximum power.

**802.11n20 mode, Low Channel,
Horizontal ,5825MHz**

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-3 high channel 5825MHz

Serial No.: 20MQ-3
Tester: Nat Zhou

Date: 2024-09-06




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	22530.50	45.61	7.91	53.52	74.00	20.48	Peak
2	22530.50	39.64	7.91	47.55	54.00	6.45	Average

**802.11n20 mode, Low Channel,
Vertical,5825MHz**

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-3 high channel 5825MHz

Serial No.: 20MQ-3
Tester: Nat Zhou

Date: 2024-09-06




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	22187.10	45.34	7.71	53.05	74.00	20.95	Peak
2	22187.10	39.67	7.71	47.38	54.00	6.62	Average

Project No.: 2402W68103E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-3 high channel 5825MHz

Serial No.: 20MQ-3
Tester: Nat Zhou

Date: 2024-09-06




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38650.00	45.59	17.06	62.65	74.00	11.35	Peak
2	38650.00	30.62	17.06	47.68	54.00	6.32	Average

Project No.: 2402W68103E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-3 high channel 5825MHz

Serial No.: 20MQ-3
Tester: Nat Zhou

Date: 2024-09-06



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38938.90	45.42	16.79	62.21	74.00	11.79	Peak
2	38938.90	30.57	16.79	47.36	54.00	6.64	Average

5.3 Emission Bandwidth

Serial No.:	2QWQ-1	Test Date:	2024/09/11~2024/09/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.9~26.4	Relative Humidity: (%)	39~44	ATM Pressure: (kPa)	100.2~100.9
-----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G- 10dB	F-08-EM502	2024/06/07	2025/06/06

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:
26dB Emission Bandwidth:
5150-5250MHz

Mode	Value (MHz)
a_5180MHz	19.820
a_5200MHz	20.796
a_5240MHz	22.607
n20_5180MHz	24.009
n20_5200MHz	24.009
n20_5240MHz	24.187
n40_5190MHz	46.146
n40_5230MHz	47.748

5250-5350MHz

Mode	Value (MHz)
a_5260MHz	27.144
a_5280MHz	26.666
a_5320MHz	31.481
n20_5260MHz	27.455
n20_5280MHz	29.719
n20_5320MHz	29.842
n40_5270MHz	57.014
n40_5310MHz	63.547

5470-5725MHz


Mode	Value (MHz)
a_5500MHz	21.051
a_5580MHz	22.138
a_5700MHz	32.714
a_5720MHz	33.550
n20_5500MHz	29.898
n20_5580MHz	33.267
n20_5700MHz	37.591
n20_5720MHz	37.515
n40_5510MHz	66.427
n40_5550MHz	66.414
n40_5670MHz	72.827
n40_5710MHz	75.294

**6dB Emission Bandwidth:
5725-5850MHz**

Mode	Value (MHz)	Limit (MHz)	Result
a_5745MHz	15.816	0.5	Pass
a_5785MHz	15.766	0.5	Pass
a_5825MHz	15.816	0.5	Pass
n20_5745MHz	17.317	0.5	Pass
n20_5785MHz	17.317	0.5	Pass
n20_5825MHz	17.317	0.5	Pass
n40_5755MHz	35.235	0.5	Pass
n40_5795MHz	35.335	0.5	Pass


5150-5250MHz

a_5180MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 20:57:24

a_5200MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 20:59:33

a_5240MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:01:20

n20_5180MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:32:30

n20_5200MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:37:00

n20_5240MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:40:02

n40_5190MHz




n40_5230MHz




5250-5350MHz


a_5260MHz




a_5280MHz




a_5320MHz



n20_5260MHz




n20_5280MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:46:47

n20_5320MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:49:42

n40_5270MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:46:49


n40_5310MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:49:01


5470-5725MHz

a_5500MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:34:27

a_5580MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:37:21

a_5700MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:43:15

a_5720MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:45:32

n20_5500MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:53:06

n20_5580MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:55:59

n20_5700MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:58:46

n20_5720MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:01:04

n40_5510MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:51:33

n40_5550MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:53:53

n40_5670MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:01:31


n40_5710MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:04:09


5725-5850MHz

a_5745MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:47:24

a_5785MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:49:55

a_5825MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:54:27

n20_5745MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:04:06

n20_5785MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:09:46

n20_5825MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:13:01

n40_5755MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:05:33

n40_5795MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:07:04

5.4 99% Occupied Bandwidth

Serial No.:	2QWQ-1	Test Date:	2024/09/11~2024/09/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	/

Environmental Conditions:

Temperature: (°C):	25.9~26.4	Relative Humidity: (%)	39~44	ATM Pressure: (kPa)	100.2~100.9
-------------------------------	-----------	---------------------------------------	-------	--------------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2024/06/07	2025/06/06

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:
5150-5250MHz**

Mode	99% OBW (MHz)
a_5180MHz	16.450
a_5200MHz	16.450
a_5240MHz	16.450
n20_5180MHz	17.700
n20_5200MHz	17.700
n20_5240MHz	17.700
n40_5190MHz	36
n40_5230MHz	36

Note:

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

5250-5350MHz

Mode	99% OBW (MHz)
a_5260MHz	16.550
a_5280MHz	16.550
a_5320MHz	16.550
n20_5260MHz	17.750
n20_5280MHz	17.750
n20_5320MHz	17.750
n40_5270MHz	36.100
n40_5310MHz	36.100

5470-5725MHz

Mode	99% OBW (MHz)
a_5500MHz	16.450
a_5580MHz	16.500
a_5700MHz	16.700
a_5720MHz	16.750
n20_5500MHz	17.750
n20_5580MHz	17.850
n20_5700MHz	18.650
n20_5720MHz	18.400
n40_5510MHz	36.400
n40_5550MHz	36.400
n40_5670MHz	38.500
n40_5710MHz	40

5725-5850MHz


Mode	99% OBW (MHz)
a_5745MHz	16.550
a_5785MHz	16.450
a_5825MHz	16.450
n20_5745MHz	17.900
n20_5785MHz	17.750
n20_5825MHz	17.750
n40_5755MHz	36.800
n40_5795MHz	36.200

Note:


The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.

5150-5250MHz


a_5180MHz




a_5200MHz




a_5240MHz




n20_5180MHz




n20_5200MHz




n20_5240MHz



n40_5190MHz




n40_5230MHz




5250-5350MHz


a_5260MHz




a_5280MHz




a_5320MHz




n20_5260MHz




n20_5280MHz




n20_5320MHz



n40_5270MHz




n40_5310MHz




5470-5725MHz


a_5500MHz



a_5580MHz




a_5700MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:43:43

a_5720MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:45:56

n20_5500MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:53:36

n20_5580MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:56:26

n20_5700MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 22:59:18

n20_5720MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:01:31

n40_5510MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:51:54

n40_5550MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:54:14

n40_5670MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:01:42


n40_5710MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:04:22


5725-5850MHz

a_5745MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:47:52

a_5785MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:50:27

a_5825MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 21:54:49

n20_5745MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:04:37

n20_5785MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:10:20

n20_5825MHz




ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 11.SEP.2024 23:13:26

n40_5755MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:05:46

n40_5795MHz



ProjectNo.:2402W68103E-RF Tester:Roy Xiao
Date: 12.SEP.2024 00:07:16

5.5 Maximum Conducted Output Power

Serial No.:	2QWQ-1	Test Date:	2024/09/11~2024/09/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.9~26.4	Relative Humidity: (%)	39~44	ATM Pressure: (kPa)	100.2~100.9
-------------------------------	-----------	---------------------------------------	-------	--------------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2024/06/07	2025/06/06
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2024/09/04	2025/09/03

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:
5150-5250MHz**

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5180MHz	11.77	24	Pass
a_5200MHz	11.65	24	Pass
a_5240MHz	11.85	24	Pass
n20_5180MHz	10.69	24	Pass
n20_5200MHz	10.7	24	Pass
n20_5240MHz	10.7	24	Pass
n40_5190MHz	9.75	24	Pass
n40_5230MHz	9.88	24	Pass
Note: The device is a Client device.			

5250-5350MHz

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5260MHz	11.68	24	Pass
a_5280MHz	11.29	24	Pass
a_5320MHz	10.08	24	Pass
n20_5260MHz	10.61	24	Pass
n20_5280MHz	10.2	24	Pass
n20_5320MHz	8.99	24	Pass
n40_5270MHz	9.39	24	Pass
n40_5310MHz	8.36	24	Pass

5470-5725MHz

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5500MHz	6.26	24	Pass
a_5580MHz	6.92	24	Pass
a_5700MHz	11.05	24	Pass
a_5720MHz	11.69	24	Pass
n20_5500MHz	6.66	24	Pass
n20_5580MHz	7.49	24	Pass
n20_5700MHz	11.56	24	Pass
n20_5720MHz	12.22	24	Pass
n40_5510MHz	6.64	24	Pass
n40_5550MHz	6.72	24	Pass
n40_5670MHz	9.38	24	Pass
n40_5710MHz	11.71	24	Pass

5725-5850MHz

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5745MHz	11.61	30	Pass
a_5785MHz	11.47	30	Pass
a_5825MHz	12.35	30	Pass
n20_5745MHz	12.1	30	Pass
n20_5785MHz	11.99	30	Pass
n20_5825MHz	12.84	30	Pass
n40_5755MHz	12.04	30	Pass
n40_5795MHz	12.2	30	Pass

5.6 Power Spectral Density

Serial No.:	2QWQ-1	Test Date:	2024/09/11~2024/09/12
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	25.9~26.4	Relative Humidity: (%)	39~44	ATM Pressure: (kPa)	100.2~100.9
-----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2024/06/07	2025/06/06

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

5150-5250MHz

Mode	Value (dBm/MHz)	Duty Cycle Factor(dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5180MHz	0.24	1.15	1.39	11	Pass
a_5200MHz	-0.07	1.15	1.08	11	Pass
a_5240MHz	0.01	1.15	1.16	11	Pass
n20_5180MHz	-1.29	1.22	-0.07	11	Pass
n20_5200MHz	-1.03	1.22	0.19	11	Pass
n20_5240MHz	-1.20	1.22	0.02	11	Pass
n40_5190MHz	-5.37	1.93	-3.44	11	Pass
n40_5230MHz	-5.81	1.93	-3.88	11	Pass

Note: The device is a Client device.

5250-5350MHz

Mode	Value (dBm/MHz)	Duty Cycle Factor(dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5260MHz	-0.30	1.15	0.85	11	Pass
a_5280MHz	-0.11	1.15	1.04	11	Pass
a_5320MHz	-1.35	1.15	-0.20	11	Pass
n20_5260MHz	-1.40	1.22	-0.18	11	Pass
n20_5280MHz	-1.78	1.22	-0.56	11	Pass
n20_5320MHz	-2.95	1.22	-1.73	11	Pass
n40_5270MHz	-5.76	1.93	-3.83	11	Pass
n40_5310MHz	-7.02	1.93	-5.09	11	Pass

5470-5725MHz


Mode	Value (dBm/MHz)	Duty Cycle Factor(dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5500MHz	-5.14	1.15	-3.99	11	Pass
a_5580MHz	-4.86	1.15	-3.71	11	Pass
a_5700MHz	-0.51	1.15	0.64	11	Pass
a_5720MHz	0.30	1.15	1.45	11	Pass
n20_5500MHz	-5.00	1.22	-3.78	11	Pass
n20_5580MHz	-4.33	1.22	-3.11	11	Pass
n20_5700MHz	-0.56	1.22	0.66	11	Pass
n20_5720MHz	0.41	1.22	1.63	11	Pass
n40_5510MHz	-8.72	1.93	-6.79	11	Pass
n40_5550MHz	-8.25	1.93	-6.32	11	Pass
n40_5670MHz	-5.99	1.93	-4.06	11	Pass
n40_5710MHz	-2.78	1.93	-0.85	11	Pass

5725-5850MHz


Mode	Value (dBm/500kHz)	Duty Cycle Factor(dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
a_5745MHz	-2.63	1.15	-1.48	30	Pass
a_5785MHz	-3.09	1.15	-1.94	30	Pass
a_5825MHz	-1.49	1.15	-0.34	30	Pass
n20_5745MHz	-2.59	1.22	-1.37	30	Pass
n20_5785MHz	-2.19	1.22	-0.97	30	Pass
n20_5825MHz	-1.87	1.22	-0.65	30	Pass
n40_5755MHz	-5.42	1.93	-3.49	30	Pass
n40_5795MHz	-4.75	1.93	-2.82	30	Pass

5150-5250MHz


a_5180MHz




a_5200MHz




a_5240MHz



n20_5180MHz



n20_5200MHz



n20_5240MHz

