

RF EXPOSURE REPORT

Report No.: DDT-B23102009-2E06

Applicant	:	Beijing Orion Star Technology Co., Ltd.
Applicant Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China.
Equipment Under Test	:	AI Delivery Robot
Model No.	:	OS-R-DR02-A
Trade Mark	:	ORIONSTAR
FCC ID	:	2A3BD-OSRDR02
Manufacturer	:	Beijing Orion Star Technology Co., Ltd.
Manufacturer Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China.

Issued By: Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weishi Road, Microelectronics Industrial Park, Development Area, Tianjin, China.

Tel: +86-22-58038033, **E-mail:** ddt@dddt.com, **http://www.ddttest.com**



REPORT

Table of Contents

1.	General information.....	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory.....	7
2.	RF Exposure Evaluation	8
2.1.	Requirement.....	8
2.2.	Calculation method	9
2.3.	Estimation result.....	9

Test Report Declare

Applicant	:	Beijing Orion Star Technology Co., Ltd.
Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China.
Equipment under Test	:	AI Delivery Robot
Model No.	:	OS-R-DR02-A
Trade Mark	:	ORIONSTAR
FCC ID	:	2A3BD-OSRSD03
Manufacturer	:	Beijing Orion Star Technology Co., Ltd.
Address	:	Room A-2570, 2nd Floor, No. 30, Shixing Street, Shijingshan District, Beijing China.

Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Tianjin Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Tianjin Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-B23102009-2E06		
Date of Receipt:	Nov. 13, 2023	Date of Test:	Nov. 13, 2023 ~ Nov. 29, 2023

Prepared By:

Novak Wei

Novak Wei/Engineer**Approved By:**

Aaron Zhang

Aaron Zhang/Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Tianjin Dongdian Testing Service Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Nov. 29, 2023	

1. General information

1.1. Description of Equipment

EUT Description	AI Delivery Robot									
Model Number	OS-R-DR02-A									
Models Difference	OS-R-DR02-A compare with original model OS-R-DR02: 1.Added four auto door in term of appearance. 2.Added ushhub motherboard, control motor to open or close the door the ushhub motherboard has no RF circuit, No impact on RF test results. Others hardware and software exactly same, such as modules, PCBA, antenna, crystal oscillator and so on. So the Report data based on original model OS-R-DR02, Only the Radiated Spurious Emissions data is updated, The original model report number is DDT-B23020802-2E06.									
Trade Mark	ORIONSTAR									
IMEI	865326069103370									
Serial Number	N/A									
Hardware Version	N/A									
Software Version	N/A									
Sample Type	mobile Device									
Frequency band	E-UTRA	Duplex Mode	Tx (MHz)	Rx (MHz)	Supported Channel Bandwidth					
					1.4	3	5	10	15	20
	Band 2	FDD	1850-1910	1930-1990	☑	☑	☑	☑	☑	☑
	Band 4	FDD	1710-1755	2110-2155	☑	☑	☑	☑	☑	☑
	Band 5	FDD	824-849	869-894	☑	☑	☑	☑	---	---
	Band 7	FDD	2500-2570	2620-2690	---	---	☑	☑	☑	☑
	Band 12	FDD	699-716	729-746	☑	☑	☑	☑	---	---
	Band 13	FDD	777-787	746-756	---	---	☑	☑	---	---
	Band 25	FDD	1850-1915	1930-1995	☑	☑	☑	☑	☑	☑
	Band 26	FDD	814-824	859-869	☑	☑	☑	☑	---	---
	Band 26	FDD	824-849	869-894	☑	☑	☑	☑	☑	---
	Band 38	TDD	2570-2620	2570-2620	---	---	☑	☑	☑	☑
	Band 41	TDD	2496-2690	2496-2690	---	---	☑	☑	☑	☑
	WLAN_1 2.4G	Frequency (MHz)			Supported Channel Bandwidth					
	IEEE 802.11b	2412-2462			20MHz					
	IEEE 802.11g	2412-2462			20MHz					
	IEEE 802.11n-HT20	2412-2462			20MHz					
	IEEE 802.11n-HT40	2422-2452			40MHz					
	WLAN_1 5G	Frequency (MHz)			Supported Channel Bandwidth					
	IEEE 802.11a	5180-5240 5260-5320 5500-5700 5745-5825			20MHz					
	IEEE 802.11n-HT20	5180-5240 5260-5320 5500-5700 5745-5825			20MHz					

	:	IEEE 802.11n-HT40	5190-5230 5270-5310 5510-5670 5755-5795	40MHz	
	:	IEEE 802.11ac-VHT20	5180-5240 5260-5320 5500-5700 5745-5825	20MHz	
	:	IEEE 802.11ac-VHT40	5190-5230 5270-5310 5510-5670 5755-5795	40MHz	
	:	IEEE 802.11ac-VHT80	5210 5290 5530 5775	80MHz	
	:	WLAN_2 2.4G	Frequency (MHz)	Supported Channel Bandwidth	
	:	IEEE 802.11b	2412-2462	20MHz	
	:	IEEE 802.11g	2412-2462	20MHz	
	:	IEEE 802.11n-HT20	2412-2462	20MHz	
	:	IEEE 802.11n-HT40	2422-2452	40MHz	
	Type of modulation	:	E-UTRA	UL: QPSK&16QAM DL: QPSK&16QAM	
:		IEEE 802.11b	DSSS (CCK, DQPSK, DBPSK)		
:		IEEE 802.11g	OFDM (64QAM, 16QAM, QPSK, BPSK)		
:		IEEE 802.11n HT20, HT40	OFDM (64QAM, 16QAM, QPSK, BPSK)		
:		IEEE 802.11a	OFDM (64QAM, 16QAM, QPSK, BPSK)		
:		IEEE 802.11ac VHT20, VHT40, VHT80	OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)		
Smart Condition	:	E-UTRA	☒ SISO ☐ MIMO ☒ Diversity		
	:	WLAN_1 2.4G	☒ SISO (802.11b/g/n) ☒ MIMO (802.11n) ☐ Diversity (802.11b/g/n)		
	:	WLAN_1 5G	☒ SISO (802.11a/n/ac) ☒ MIMO (802.11n/ac) ☐ Diversity(802.11a/n/ac)		
	:	WLAN_2 2.4G	☒ SISO (802.11b/g/n) ☐ MIMO (802.11n) ☐ Diversity (802.11b/g/n)		
Antenna Type	:	E-UTRA & WLAN_1: Fixed Internal Dedicated FPCB Antenna WLAN_2: Fixed Internal ROD Antenna			
Antenna Information	:	Mode	Band	Antenna1	Antenna2
	:	E-UTRA	LTE Band2	2.54dBi	N/A
			LTE Band 4	2.25dBi	N/A
			LTE Band 5	-0.23dBi	N/A
			LTE Band 7	3.20dBi	N/A
			LTE Band 12	-2.46dBi	N/A
			LTE Band 13	-2.77dBi	N/A
			LTE Band 25	2.51dBi	N/A
			LTE Band 26	0.34dBi	N/A

		LTE Band 38	3.20dBi	N/A
		LTE Band 41	3.43dBi	N/A
	WLAN_1 2.4G	IEEE 802.11b	3.77dBi	3.68dBi
		IEEE 802.11g	3.77dBi	3.68dBi
		IEEE 802.11n HT20, HT40	3.77dBi	3.68dBi
		IEEE 802.11a	6.22dBi	4.44dBi
	WLAN_1 5G	IEEE 802.11n HT20, HT40	6.22dBi	4.44dBi
		IEEE 802.11ac HT20, HT40, HT80	6.22dBi	4.44dBi
	WLAN_2 2.4G	IEEE 802.11b	2.00dBi	N/A
		IEEE 802.11g	2.00dBi	N/A
		IEEE 802.11n HT20, HT40	2.00dBi	N/A
Power Supply	Internal battery			

1.2. Assess laboratory

Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China., 300385

Tel: +86-22-58038033, <http://www.ddttest.com>, Email: ddt@dgddt.com

NVLAP (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

CNAS (China National Accreditation Service for Conformity Assessment) CODE: L13402

FCC Designation Number: CN5004; FCC Test Firm Registration Number: 368676

ISED (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

VCCI Facility Registration Number: C-20089, T-20093, R-20125, G-20122

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Note1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

2.2. Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2$ m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Mode	Band	Output power Tune up (dBm)	Output power Tune up (mW)	Antenna Gain (dBi)	Antenna Gain (mW)	MPE Value (mW/cm ²)	MPE ratio	MPE Limit (mW/cm ²)
E-UTRA	LTE Band2	25	316.23	2.54	1.79	0.112907	0.112907	1.00
	LTE Band 4	25	316.23	2.25	1.68	0.105614	0.105614	1.00
	LTE Band 5	25	316.23	-0.23	0.95	0.059665	0.108614	0.55
	LTE Band 7	25	316.23	3.20	2.09	0.131438	0.131438	1.00
	LTE Band 12	25	316.23	-2.46	0.57	0.035704	0.076619	0.47
	LTE Band 13	25	316.23	-2.77	0.53	0.033245	0.064179	0.52
	LTE Band 25	25	316.23	2.51	1.78	0.112130	0.112130	1.00
	LTE Band 26	25	316.23	0.34	1.08	0.068033	0.125368	0.54
	LTE Band 38	25	316.23	3.20	2.09	0.131438	0.131438	1.00
	LTE Band 41	25	316.23	3.43	2.20	0.138586	0.138586	1.00
WLAN1_2.4G	IEEE 802.11b	18	63.10	3.77	2.38	0.029903	0.029903	1.00
	IEEE 802.11g	24	251.19	3.77	2.38	0.119047	0.119047	1.00
	IEEE 802.11n	25	316.23	3.77	2.38	0.149872	0.149872	1.00
WLAN1_5G	IEEE 802.11a	13	19.95	6.22	4.19	0.016623	0.016623	1.00
	IEEE 802.11n	14	25.12	6.22	4.19	0.020928	0.020928	1.00
	IEEE 802.11ac	14	25.12	6.22	4.19	0.020928	0.020928	1.00

WLAN2_2.4G	IEEE 802.11b	22	158.49	2.00	1.58	0.049971	0.049971	1.00
	IEEE 802.11g	22	158.49	2.00	1.58	0.049971	0.049971	1.00
	IEEE 802.11n	22	158.49	2.00	1.58	0.049971	0.049971	1.00

Maximum Simultaneous transmission MPE Ratio for E-UTRA and WLAN2:

Maximum MPE ratio E-UTRA	Maximum MPE ratio WLAN2_2.4G	Σ MPE ratios	Limit	Results
0.138586	0.049971	0.188557	1.000	Pass

Maximum Simultaneous transmission MPE Ratio for WLAN1_2.4G and WLAN2:

Maximum MPE ratio WLAN1_2.4G	Maximum MPE ratio WLAN2_2.4G	Σ MPE ratios	Limit	Results
0.149872	0.049971	0.199843	1.000	Pass

Maximum Simultaneous transmission MPE Ratio for WLAN1_5G and WLAN2:

Maximum MPE ratio WLAN1_5G	Maximum MPE ratio WLAN2_2.4G	Σ MPE ratios	Limit	Results
0.020928	0.049971	0.070899	1.000	Pass

Note: The estimation distance is 20 cm.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.

END OF REPORT