



RF Exposure Evaluation Report

APPLICANT : GigaDevice Semiconductor Inc.
EQUIPMENT : 2.4 GHz Wi-Fi 6 (802.11 ax) and Bluetooth5 (LE) module
BRAND NAME : GigaDevice
MODEL NAME : GD32VW553-MINI-EMK6
FCC ID : 2A3BS-GDVW553MINI-E
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Jun. 30, 2025 and completed on Jun. 30, 2025. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sportun International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	5
4. RF EXPOSURE LIMIT INTRODUCTION	6
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	7
5.1. Standalone Power Density Calculation	7



Revision History



1. Administration Data

1.1. Testing Laboratory

Sportun International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sportun International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sportun Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	GigaDevice Semiconductor Inc.
Address	Building No. 8, IC Park, No. 9 Fenghao East Road, Haidian District, Beijing 100094, China

Manufacturer	
Company Name	Jiangsu Fulian Communication Technology Co.
Address	South of Lanling Road, Yong'an Community, Development Zone, Danyang City, Jiangsu Province, China



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	2.4 GHz Wi-Fi 6 (802.11 ax) and Bluetooth5 (LE) module
Brand Name	GigaDevice
Model Name	GD32VW553-MINI-EMK6
FCC ID	2A3BS-GDVW553MINI-E
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz 802.11b/g/n HT20 WLAN 2.4GHz 802.11ax HE20 Bluetooth LE
Antenna Gain	Bluetooth: 2.1 dBi WLAN 2.4GHz: 2.1 dBi
Antenna Type	WLAN/Bluetooth: Dipole Antenna
HW Version	GD32VW553-MINI-EMK6-A
SW Version	image-all-mp-1.0.2_01-20241024.bin
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

3. Maximum RF average output tune up power among production units

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	19.00
	802.11g	17.00
	802.11n-HT20	17.00
	802.11ax HE20	17.00

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	LE	15.0



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm^2)	Limit (mW/cm^2)
Bluetooth	2402.0	2.10	15.00	17.100	51.286	0.010	1.000
2.4GHz WLAN	2412.0	2.10	19.00	21.100	128.825	0.026	1.000

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, WLAN (2.4GHz) and Bluetooth cannot transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----