

Test Report

Part 15 Subpart C 15.247

Equipment under test InBirdie TEMPO Plus
Model name InBirdie TEMPO Plus
FCC ID 2A3CB-INBIRDIETP3
Applicant DMBH Co., Ltd.
Manufacturer DMBH Co., Ltd.
Date of test(s) 2022.11.02 ~ 2022.12.02
Date of issue 2022.12.07

Issued to
DMBH Co., Ltd.
#401-603, Bucheon Techno-park, 655, Pyeongcheon-ro, Wonmi-gu, Bucheon-si,
Gyeonggi-do, Korea
Tel: +82-32-203-8889 / Fax: +82-32-712-4907

Issued by
KES Co., Ltd.
3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
	
Gu-Bong, Kang Test engineer	Yeong-Jun, Cho Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.



Revision history

Revision	Date of issue	Test report No.	Description
-	2022.11.04	KES-RF1-22T0161	Initial
R1	2022.12.07	KES-RF1-22T0161-R1	Change FCC ID and Re-test the Radiated restricted band and emissions (Above 1 000 MHz)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.



TABLE OF CONTENTS

1.	General information	4
1.1.	EUT description	4
1.2.	Test configuration.....	4
1.3.	Device modifications.....	5
1.4.	Accessory information.....	5
1.5.	Sample calculation	5
1.6.	Measurement Uncertainty	5
1.7.	Frequency/channel operations	5
2.	Summary of tests	6
3.	Test results.....	7
3.1.	6 dB bandwidth	7
3.2.	Output power.....	10
3.3.	Power spectral density.....	12
3.4.	Radiated restricted band and emissions.....	15
3.5.	Conducted spurious emissions & band edge	35
3.6.	AC conducted emissions	40
Appendix A.	Measurement equipment	42
Appendix B.	Test setup photos	43

1. General information

Applicant: DMBH Co., Ltd.
Applicant address: #401-603, Bucheon Techno-park, 655, Pyeongcheon-ro, Wonmi-gu, Bucheon-si
Gyeonggi-do, Korea
Test site: KES Co., Ltd.
Test site address: ☐ 3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
☒ 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea
Test Facility: FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s): 15.247
FCC ID: 2A3CB-INBIRDIETP3
Test device serial No.: ☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test: InBirdie TEMPO Plus
Frequency range: 2 402 MHz ~ 2 480 MHz (LE 1,2 Mbps)
Model: InBirdie TEMPO Plus
Modulation technique: GFSK
Number of channels: 2 402 MHz ~ 2 480 MHz (LE 1,2 Mbps) : 40 ch
Antenna specification: Antenna type : Chip Antenna // Peak gain: 1.9 dBi
Power source: DC 5.0 V (USB)
H/W version: V 1.0
S/W version: V 1.0

1.2. Test configuration

The **DMBH Co., Ltd. // Inbirdie TEMPO Plus // Inbirdie TEMPO Plus // FCC ID: 2A3CB-INBIRDIETP3** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
KDB 558074 D01 v05 r02
ANSI C63.10-2013

1.3. Device modifications

N/A

1.4. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

1.5. Sample calculation

Where relevant, the following sample calculation is provided

For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.47 + 10 = 10.47 \text{ (dB)}\end{aligned}$$

For Radiation test :

Field strength level ($\text{dB}\mu\text{V/m}$) = Measured level ($\text{dB}\mu\text{V}$) + Antenna factor (dB) + Cable loss (dB) – Amplifier gain (dB)

1.6. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.38 dB
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1GHz	4.50 dB
	Above 1GHz	4.90 dB
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

1.7. Frequency/channel operations

Ch.	Frequency (MHz)	Rate(Mbps)
00	2 402	LE 1,2 Mbps
.	.	.
20	2 442	LE 1,2 Mbps
.	.	.
39	2 480	LE 1,2 Mbps



2. Summary of tests

Section in FCC Part 15	Test description	Test results
15.247(a)(2)	6 dB bandwidth	Pass
15.247(b)(3)	Output power	Pass
15.247(e)	Power spectral density	Pass
15.205, 15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted spurious emission and band edge	Pass
15.207(a)	AC Conducted emissions	Pass

Note

1. This product is floor-standing equipment.

3. Test results

3.1. 6 dB bandwidth

Test procedure

ANSI C63.10-2013 - Section 11.8.2

Test setup



ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., $RBW = 100 \text{ kHz}$, $VBW \geq 3 \times RBW$, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6 \text{ dB}$.

Limit


According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.



Test results

Mode: LE 1 Mbps

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 402	0.689	≥ 0.500
2 442	0.693	
2 480	0.687	




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.



Mode: LE 2 Mbps

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 402	1.150	≥ 0.500
2 442	1.140	
2 480	1.140	




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.

3.2. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.



Test results

Mode: LE 1 Mbps

Mode	2 402 MHz		2 442 MHz		2 480 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 1 Mbps	0.60	0.88	0.34	0.62	0.09	0.39

Mode: LE 2 Mbps

Mode	2 402 MHz		2 442 MHz		2 480 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 2 Mbps	0.59	0.89	0.35	0.62	0.10	0.37

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.

3.3. Power spectral density

Test procedure

ANSI C63.10-2013 - Section 11.10.2

Test setup



Section 10.2 & ANSI C63.10-2013 - Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Limit


According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.



Results

Mde: LE 1 Mbps

Frequency(MHz)	PSD (dBm)	Limit(dBm)
2 402	-16.04	8
2 442	-16.92	
2 480	-17.13	




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.



Mode: LE 2 Mbps

Frequency(MHz)	PSD (dBm)	Limit(dBm)
2 402	-18.29	8
2 442	-18.67	
2 480	-19.27	

LE 2 Mbps




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.


3.4. Radiated restricted band and emissions

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that **parallel** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **parallel**.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 MHz

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
5. Spectrum analyzer settings for $f < 1 \text{ GHz}$:

- ① Span = wide enough to fully capture the emission being measured
 - ② RBW = 100 kHz
 - ③ VBW $\geq$ RBW
 - ④ Detector = quasi peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
6. Spectrum analyzer settings for $f \geq 1$ GHz: Peak
- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
 - ② RBW = 1 MHz
 - ③ VBW $\geq$ 3 MHz
 - ④ Detector = peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
 - ⑦ Trace was allowed to stabilize
7. Spectrum analyzer settings for $f \geq 1$ GHz: Average
- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
 - ② RBW = 1 MHz
 - ③ VBW $\geq 3 \times$ RBW
 - ④ Detector = RMS, if span/(# of points in sweep) $\leq$ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
 - ⑤ Averaging type = power(i.e., RMS)
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
 - ⑥ Sweep = auto
 - ⑦ Trace = max hold
 - ⑧ Perform a trace average of at least 100 traces.
 - ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

Note.

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40\log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20\log(D_m/D_s)$
 Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
2. Field strength(dB μ V/m) = Level(dB μ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (μ V/m)
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Duty cycle


Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode	T _{on} time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (dB)
LE 1Mbps	2.141	2.500	0.856	85.64	0.67
LE 2Mbps	1.084	1.876	0.578	57.78	2.38

Duty cycle (Linear) = T_{on} time/Period


DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)






Test results (Below 30 MHz)

Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 0 (Worst case)






Mode: LE 2 Mbps
Distance of measurement: 3 meter
Channel: 0 (Worst case)



Test results (Below 1 000 MHz)

Mode: LE 1 Mbps
 Distance of measurement: 3 meter
 Channel: 0 (Worst case)

Horizontal // Vertical



Final Result


No.	Frequency	Pol	Reading	c.f	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		QP		QP	QP	QP			
			[dB(μV)]	[dB(1/m)]	[dB(μV/m)]	[dB(μV/m)]	[dB]	[cm]	[deg]	
1	31.576	V	42.8	-14.6	28.2	40.0	11.8	100.0	76.2	
2	37.760	V	42.9	-13.1	29.8	40.0	10.2	101.0	249.7	
3	46.126	H	35.2	-11.6	23.6	40.0	16.4	204.0	0.1	
4	50.006	H	36.7	-11.0	25.7	40.0	14.3	372.0	44.0	
5	52.795	V	42.0	-11.3	30.7	40.0	9.3	100.0	270.8	
6	56.675	V	43.1	-11.7	31.4	40.0	8.6	100.0	76.2	
7	56.918	H	32.2	-11.7	20.5	40.0	19.5	269.0	53.1	
8	121.301	H	37.0	-14.5	22.5	43.5	21.0	338.0	22.7	
9	208.601	V	39.8	-11.6	28.2	43.5	15.3	100.0	293.5	
10	229.456	H	39.5	-10.9	28.6	46.0	17.4	379.0	22.7	
11	360.043	V	37.4	-7.0	30.4	46.0	15.6	100.0	270.8	
12	360.043	H	45.7	-7.0	38.7	46.0	7.3	202.0	207.3	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr.



Mode: LE 2 Mbps
Distance of measurement: 3 meter
Channel: 0 (Worst case)

Horizontal // Vertical



Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB (μV)]	c.f [dB (1/m)]	Result QP [dB (μV/m)]	Limit QP [dB (μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	31.940	V	45.1	-14.5	30.6	40.0	9.4	100.0	90.2	
2	37.639	V	42.0	-13.1	28.9	40.0	11.1	1010.0	178.9	
3	46.490	H	32.9	-11.5	21.4	40.0	18.6	388.0	293.0	
4	49.885	H	36.9	-11.0	25.9	40.0	14.1	17936.9	68.4	
5	51.098	V	43.1	-11.1	32.0	40.0	8.0	375.0	22.8	
6	56.675	V	43.9	-11.7	32.2	40.0	7.8	104.0	69.1	
7	121.301	H	37.1	-14.5	22.6	43.5	20.9	206.0	199.6	
8	170.044	H	36.9	-14.0	22.9	43.5	20.6	210.0	354.9	
9	211.511	V	40.1	-11.5	28.6	43.5	14.9	100.0	290.0	
10	230.548	H	40.2	-10.8	29.4	46.0	16.6	391.0	28.5	
11	360.043	V	36.1	-7.0	29.1	46.0	16.9	10.0	290.0	
12	360.043	H	37.0	-7.0	30.0	46.0	16.0	210.0	177.9	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.



Test results (Above 1 000 MHz)

Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 00

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 043.70	45.25	Peak	V	-10.15	-	35.10	74.00	38.90
1 330.07	44.33	Peak	H	-8.40	-	35.93	74.00	38.07
4 803.60	42.27	Peak	V	4.70	-	46.97	74.00	27.03
4 805.10	42.76	Peak	H	4.71	-	47.47	74.00	26.53

- Band edge


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 317.64	41.79	Peak	V	-1.78	-	40.01	74.00	33.99
2 330.92	41.35	Peak	H	-1.77	-	39.58	74.00	34.42




Restricted band // Horizontal // Peak




Restricted band // Vertical // Peak




Horizontal // Peak for 1 GHz to 3 GHz




Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.


1. Average test would be performed if the peak result were greater than the average limit.



Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 20

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 115.09	43.84	Peak	H	-9.72	-	34.12	74.00	39.88
1 696.23	44.14	Peak	V	-5.31	-	38.83	74.00	35.17
4 884.60	43.72	Peak	H	5.32	-	49.04	74.00	24.96
4 884.60	42.36	Peak	V	5.32	-	47.68	74.00	26.32



Note.

1. Average test would be performed if the peak result were greater than the average limit.



Mode: LE 1 Mbps
Distance of measurement: 3 meter
Channel: 39


- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 098.29	43.91	Peak	V	-9.82	-	34.09	74.00	39.91
1 664.43	45.20	Peak	H	-5.67	-	39.53	74.00	34.47
4 959.60	42.92	Peak	V	5.89	-	48.81	74.00	25.19
4 961.10	42.23	Peak	H	5.91	-	48.14	74.00	25.86


- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 486.41	42.37	Peak	V	-1.67	-	40.70	74.00	33.30
2 497.97	42.79	Peak	H	-1.66	-	41.80	74.00	32.20


Restricted band // Horizontal // Peak




Restricted band // Vertical // Peak




Horizontal // Peak for 1 GHz to 3 GHz




Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.

1. Average test would be performed if the peak result were greater than the average limit.



Test results (Above 1 000 MHz)

Mode: LE 2 Mbps
Distance of measurement: 3 meter
Channel: 00


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 230.28	44.70	Peak	H	-9.01	-	35.69	74.00	38.31
1 334.87	44.42	Peak	V	-8.37	-	36.05	74.00	37.95
4 803.60	42.86	Peak	V	4.70	-	47.56	74.00	26.44
4 805.10	42.51	Peak	H	4.71	-	47.22	74.00	26.78


- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 358.96	42.20	Peak	V	-1.73	-	40.47	74.00	33.53
2 360.66	42.26	Peak	H	-1.73	-	40.53	74.00	33.47


Restricted band // Horizontal // Peak




Restricted band // Vertical // Peak




Horizontal // Peak for 1 GHz to 3 GHz




Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz




Note.

1. Average test would be performed if the peak result were greater than the average limit.

Mode: LE 2 Mbps
 Distance of measurement: 3 meter
 Channel: 20

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 329.67	46.32	Peak	V	-8.40	-	37.92	74.00	36.08
1 330.87	44.75	Peak	H	-8.39	-	36.36	74.00	37.64
4 883.10	42.16	Peak	H	5.31	-	47.47	74.00	26.53
4 884.60	41.61	Peak	V	5.32	-	46.93	74.00	27.07



Note.

1. Average test would be performed if the peak result were greater than the average limit.



Mode: LE 2 Mbps
Distance of measurement: 3 meter
Channel: 39


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 139.69	45.03	Peak	H	-9.57	-	35.46	74.00	38.54
1 331.67	44.86	Peak	V	-8.39	-	36.47	74.00	37.53
4 959.60	43.00	Peak	V	5.89	-	48.89	74.00	25.11
4 961.10	42.59	Peak	H	5.91	-	48.50	74.00	25.50


- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 486.92	42.07	Peak	H	-1.67	-	40.40	74.00	33.60
2 498.87	42.43	Peak	V	-1.66	-	40.77	74.00	33.23


Restricted band // Horizontal // Peak




Restricted band // Vertical // Peak




Horizontal // Peak for 1 GHz to 3 GHz




Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.

1. Average test would be performed if the peak result were greater than the average limit.


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr.

Test results (18 GHz to 30 GHz) – Worst case

Mode: LE 2 Mbps (Worst case)

Distance of measurement: 3 meter

Channel: 0 (Worst case)




Note.

No spurious emission were detected above 18 GHz.

3.5. Conducted spurious emissions & band edge

Test setup



Test procedure

Band edge

ANSI C63.10-2013 - Section 11.11

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Set the RBW = 100 kHz
4. Set the VBW = $[3 \times \text{RBW}]$.
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow trace to fully stabilize.

Out of band emissions


ANSI C63.10-2013 - Section 11.11

1. Start frequency was set to 30 MHz and stop frequency was set to 25 GHz for 2.4 GHz frequencies and 40 GHz for 5 GHz frequencies
2. Set the RBW = 100 kHz
3. Set the VBW = $[3 \times \text{RBW}]$.
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow trace to fully stabilize.




Limit


According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

Test results






This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr.

LE 1 Mbps																																											
2 480 MHz	-																																										
	BLANK																																										
	BLANK																																										
 <table><thead><tr><th>Type</th><th>Ref</th><th>Freq</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td>2.4795 GHz</td><td>-0.90 dBm</td><td></td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td>4.9608 GHz</td><td>-54.89 dBm</td><td></td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td>2.3523 GHz</td><td>-58.53 dBm</td><td></td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td>7.4398 GHz</td><td>-59.51 dBm</td><td></td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td>2.609 GHz</td><td>-58.99 dBm</td><td></td><td></td><td></td></tr></tbody></table>	Type	Ref	Freq	X-Value	Y-Value	Function	Function Result	M1	1	2.4795 GHz	-0.90 dBm				M2	1	4.9608 GHz	-54.89 dBm				M3	1	2.3523 GHz	-58.53 dBm				M4	1	7.4398 GHz	-59.51 dBm				M5	1	2.609 GHz	-58.99 dBm				BLANK
Type	Ref	Freq	X-Value	Y-Value	Function	Function Result																																					
M1	1	2.4795 GHz	-0.90 dBm																																								
M2	1	4.9608 GHz	-54.89 dBm																																								
M3	1	2.3523 GHz	-58.53 dBm																																								
M4	1	7.4398 GHz	-59.51 dBm																																								
M5	1	2.609 GHz	-58.99 dBm																																								



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr.




LE 2 Mbps	
2 480 MHz	-
	BLANK
	BLANK
	BLANK

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.

3.6. AC conducted emissions

Test setup



Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dBμV/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50




Test results – Worst case

Mode: LE
Transfer rate: 2 Mbps
Channel: 00 (Worst case)

LE 2 Mbps


Hot Line



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.538000	37.64	---	56.00	18.36	1000.0	9.000	L1	19.9
0.538000	---	23.53	46.00	22.47	1000.0	9.000	L1	19.9
0.714000	---	27.73	46.00	18.27	1000.0	9.000	L1	20.1
0.714000	42.19	---	56.00	13.81	1000.0	9.000	L1	20.1
1.354000	---	21.93	46.00	24.07	1000.0	9.000	L1	20.3
1.354000	36.07	---	56.00	19.93	1000.0	9.000	L1	20.3
1.362000	37.32	---	56.00	18.68	1000.0	9.000	L1	20.3
1.362000	---	23.48	46.00	22.52	1000.0	9.000	L1	20.3
2.154000	35.73	---	56.00	20.27	1000.0	9.000	L1	20.5
2.154000	---	21.15	46.00	24.85	1000.0	9.000	L1	20.5
12.242000	37.45	---	60.00	22.55	1000.0	9.000	L1	20.5
12.242000	---	23.98	50.00	26.02	1000.0	9.000	L1	20.5

Neutral Line



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.702000	---	14.56	46.00	31.44	1000.0	9.000	N	20.0
0.702000	31.84	---	56.00	24.16	1000.0	9.000	N	20.0
0.710000	---	14.77	46.00	31.23	1000.0	9.000	N	20.0
0.710000	32.08	---	56.00	23.92	1000.0	9.000	N	20.0
1.410000	---	11.67	46.00	34.33	1000.0	9.000	N	20.3
1.410000	27.98	---	56.00	28.02	1000.0	9.000	N	20.3
2.222000	---	10.71	46.00	35.29	1000.0	9.000	N	20.4
2.222000	26.75	---	56.00	29.25	1000.0	9.000	N	20.4
11.862000	---	14.78	50.00	35.22	1000.0	9.000	N	20.4
11.862000	35.98	---	60.00	24.02	1000.0	9.000	N	20.4
12.282000	---	15.95	50.00	34.05	1000.0	9.000	N	20.5
12.282000	36.46	---	60.00	23.54	1000.0	9.000	N	20.5



Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum Analyzer	R&S	FSV40-N	101725	1 year	2023.08.11
Spectrum Analyzer	R&S	FSV3044	101272	1 year	2023.03.14
SIGNAL GENERATOR	KEYSIGHT	N5182B	MY59100115	1 year	2023.04.27
Power Meter	Anritsu	ML2495A	2010001	1 year	2023.04.27
Pulse Power Sensor	Anritsu	MA2411B	1911111	1 year	2023.04.27
Attenuator	Mini-Circuits	BW-S10-2W263+	3	1 year	2023.01.17
Attenuator	6806.17.A	HUBER+SUHNER	-	1 year	2023.04.01
Loop Antenna	Schwarzbeck	FMZB1513	225	2 years	2023.01.18
TRILOG-BROADBAND ANTENNA	Schwarzbeck	VULB 9163	714	2 years	2024.04.19
Horn Antenna	A.H	SAS-571	414	1 year	2023.01.18
Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170550	1 year	2023.01.20
Amplifier	SONOMA INSTRUMENT	310N	186549	1 year	2023.04.21
PREAMPLIFIER	8449B	8449B	3008A00538	1 year	2023.06.02
EMI Test Receiver	R&S	ESU26	100517	1 year	2023.08.01
DC Power supply	Agilent	6632B	MY43004090	1 year	2023.06.21
BROADBAND AMPLIFIER	SCHWARZBECK	BBV9721	PS9721-003	1 year	2023.01.17
LISN	ENV216	R & S	101787	1 year	2022.12.27
EMI TEST RECEIVER	ESR3	R & S	101783	1 year	2022.12.28
PULSE LIMITER	ESH3-Z2	R & S	101915	1 year	2022.12.27

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
NoteBook	LG Electronics.	LG15N54	411NZJV044052
NoteBook DC Power Unit	LITE-ON TECHNOLOGY (CHANGZHOU)CO., LTD	PA-1900-14	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr.