

# Radiofrequency radiation exposure evaluation: mobile devices

RESULT: Pass

### **Test Specification**

Test item : Scout Smart Camera Identification / Type No. : PLPC001, PLPC0001 FCC ID : 2A3DE-PLPC001

Test standard : CFR47 FCC Part 2: Section 2.1091

CFR47 FCC Part 1: Section 1.1310 FCC KDB Publication 447498 D04

#### > FCC requirements

**FCC requirement:** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

#### MPE Calculation Method according to KDB 447498 D04

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
f <sub>L</sub> MHz		<i>f</i> н МНz	$\lambda_L / 2\pi$		$\lambda_{\rm H}$ / $2\pi$	W
0.3	-	1.34	159 m	_	35.6 m	1,920 R <sup>2</sup>
1.34	1	30	35.6 m	_	1.6 m	3,450 R <sup>2</sup> /f <sup>2</sup>
30	-	300	1.6 m	_	159 mm	3.83 R <sup>2</sup>
300	1	1,500	159 mm	_	31.8 mm	0.0128 R <sup>2</sup> f
1,500	1	100,00	31.8 mm	1	0.5 mm	19.2R <sup>2</sup>

Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

$$P_{\text{th }}(\text{mW}) = ERP_{20 \text{ cm}}(\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B. 1)

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$
(B. 2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\,\mathrm{cm}}\sqrt{f}}\right)$$



## a) EUT RF Exposure Evaluation operations, Worst Case mode

Test Mode	Measured Power (dBm)	ERP (dBm)	ERP (m₩)	Minimum Separation Distances (cm)	Limit (mW)
BLE	7.08	8.08	6.426		
BR+EDR	6.84	7.84	6.081	20	3060
2.4GHz band Wi-Fi	14.99	15.99	39.719		

Test Mode	Measured Power (dBm)	Measured Power (ℼ₩)	Minimum Separation Distances (cm)	Limit (mW)
5GHz band Wi-Fi	17.57	57.147	20	3060

Bluetooth + WLAN 2.4GHz + WLAN 5GHz =6.426/3060 + 39.719/3060 + 57.147/3060=0.0337

Therefore, the maximum calculations of above situations are less than the "1" limit.