

Remote Control Manual

360 Photobooth

1. Basic parameters

Size: 41*96*12MM

Power: +3V button battery

Connection method: connected by radio frequency

2. Electrical parameters

Working voltage: 3V(2025 battery)

Working frequency: 315MHz (can customized other frequency)

Stand-by current: 0mA

Working current: 35mA

Coding method: fixed code

Transmission distance: >100m (the sensitivity of the receiving board in an open area is above -103dBm)

Modulation: OOK

Working temperature: -10°C~+70°C

3. Precautions for use

1.) Our company's remote control only adapts to our company's receiver products, and cannot be used with remote controls produced by other companies

2.)When the button is pressed down, the LED does not light up, please replace the battery

3.)When not in use for a long time, remove the battery

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device and its antenna(s) must not be co-located or operation in conjunction with any other antenna or transmitter.

Radiation Exposure Statement

The device has been evaluated to meet general RF exposure requirement in portable exposure condition without restriction.