



■ Report No.: DDT-R21082305-1E02

■ Issued Date: Sep. 03, 2021

RF EXPOSURE REPORT

FOR

Applicant	:	Dongguan ITC Lighting Manufacturing Co.
Address	:	No 245 ShiHeng Avenue XiaSha Village, Shipai Town DongGuan City GuangDong Province
Equipment under Test	:	Bluetooth module
Model No.	:	220-00810-r1
Trade Mark	:	N/A
FCC ID	:	2A3DLA00810
Manufacturer	:	Dongguan ITC Lighting Manufacturing Co.
Address	:	No 245 ShiHeng Avenue XiaSha Village, Shipai Town DongGuan City GuangDong Province

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-Mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

Test report declares.....	3
1. General information	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation.....	5
2.1. Requirement.....	5
2.2. Calculation Method	6
2.3. Estimation Result.....	6

TEST REPORT DECLARE

Applicant	:	Dongguan ITC Lighting Manufacturing Co.
Address	:	No 245 ShiHeng Avenue XiaSha Village, Shipai Town DongGuan City GuangDong Province
Equipment under Test	:	Bluetooth module
Model No.	:	220-00810-r1
Trade mark	:	N/A
Manufacturer	:	Dongguan ITC Lighting Manufacturing Co.
Address	:	No 245 ShiHeng Avenue XiaSha Village, Shipai Town DongGuan City GuangDong Province

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-R21082305-1E02	
Date of Receipt:	Jun. 07, 2021	Date of Test: Jun. 07, 2021 ~ Sep. 02, 2021

Prepared By:



Ben Jin/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 03, 2021	

1. General information

1.1. Description of Equipment

EUT* Name	:	Bluetooth module
Model Number	:	220-00810-r1
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 3.3V
Radio Specification	:	Bluetooth V5.2
Operation Frequency	:	2402 MHz - 2480 MHz
Modulation	:	GFSK
Data Rate	:	1 Mbps, 2 Mbps
Antenna Gain	:	Maximum PK gain: 3 dBi
Sample Type	:	Series production
Serial Number	:	N/A

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \text{ or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation Result

Manufacturing Tolerance

GFSK 1MHz (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-3	-3	-3
Tolerance \pm (dB)	1	1	1
GFSK 2MHz (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-2	1	0
Tolerance \pm (dB)	1	1	1

Estimation Result

Mode	F (GHz)	Distance (mm)	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW /cm ²)	MPE Test Exclusion Threshold (mW/cm ²)	MPE Test Exclusion
			dBm	mW					
GFSK 1MHz	2.450	20	-2	0.63	3	2	0.00025	1	Yes
GFSK 2MHz	2.450	20	2	1.58	3	2	0.00063	1	Yes

Note: The estimation distance is 20cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

END OF REPORT