



# FCC RADIO TEST REPORT

**FCC ID** : 2A3DW-MZ1000  
**Equipment** : Head-mounted tablet  
**Brand Name** : Moziware  
**Model Name** : MZ1000  
**Marketing Name** : cimo  
**Applicant** : RealWear (Shanghai) Intelligent Technology Co., Ltd.  
2F,Block21, No.55 Chuanhe Road,  
Pudong New District, Shanghai, China  
**Manufacturer** : RealWear (Shanghai) Intelligent Technology Co., Ltd.  
2F,Block21, No.55 Chuanhe Road,  
Pudong New District, Shanghai, China  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Oct. 01, 2021 and testing was started from Oct. 14, 2021 and completed on Oct. 27, 2021. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Reviewed by: Louis Wu

**Sportun International Inc. Wensan Laboratory**

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Location .....	5
1.4 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test.....</b>	<b>7</b>
2.1 Carrier Frequency Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	9
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 Test Result.....</b>	<b>11</b>
3.1 Number of Channel Measurement .....	11
3.2 Hopping Channel Separation Measurement .....	13
3.3 Dwell Time Measurement .....	17
3.4 20dB and 99% Bandwidth Measurement .....	19
3.5 Output Power Measurement.....	26
3.6 Conducted Band Edges Measurement.....	27
3.7 Conducted Spurious Emission Measurement .....	32
3.8 Radiated Band Edges and Spurious Emission Measurement .....	39
3.9 AC Conducted Emission Measurement.....	43
3.10 Antenna Requirements .....	45
<b>4 List of Measuring Equipment .....</b>	<b>46</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>48</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	
<b>Appendix F. Setup Photographs</b>	



## History of this test report



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 5.68 dB at 14445.000 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 13.45 dB at 0.908 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Sheng Kuo****Report Producer: Emma Lo**



## 1 General Description

### 1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, and Wi-Fi 5GHz 802.11a/n/ac.

Product Specification subjective to this standard		
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna	
Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	0.11

**Remark:** The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

### 1.2 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.3 Testing Location

Test Site	Sportun International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	<b>Sportun Site No.</b> CO05-HY (TAF Code: 1190)
Remark	The Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

**Note:** The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sportun International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	<b>Sportun Site No.</b> TH05-HY, 03CH11-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786



## 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-




## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Z Plane as worst plane, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
Conducted Test Cases	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
AC Conducted Emission	Mode 3: CH78_2480 MHz		
	Mode 6: CH78_2480 MHz		
Remark:	Mode 9: CH78_2480 MHz		
	For Radiated Test Cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.		

## 2.3 Connection Diagram of Test System



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	Earphone	Sony	AG-1100	NA	Unshielded, 1.5m	N/A
3.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
4.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
5.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Adapter	DVE	DSA-5PFM-05 FUS 050100	FCC DoC	N/A	N/A
7.	Adapter	Sony	CAA-002016-TW	NA	N/A	N/A



## 2.5 EUT Operation Test Setup

The RF test items, utility “QRCT Ver.4.0.00175.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

*Offset(dB) = RF cable loss(dB) + attenuator factor(dB).*

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$



### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300 kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.


##### 3.1.4 Test Setup





### 3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.



## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300 kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.




&lt;1Mbps&gt;






&lt;2Mbps&gt;





&lt;3Mbps&gt;



### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

**Remark:**

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

## 3.4 20dB and 99% Bandwidth Measurement

### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Use the following spectrum analyzer settings for 20 dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
RBW  $\geq$  1-5% of the 99% bandwidth; VBW  $\geq$  3 \* RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

### 3.4.4 Test Setup




### 3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.




&lt;1Mbps&gt;






&lt;2Mbps&gt;





&lt;3Mbps&gt;






### 3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




&lt;2Mbps&gt;



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



&lt;3Mbps&gt;



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band:

1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


### 3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.



## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set the maximum power setting and enable the EUT to transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2 and 3.
5. Measure and record the results in the test report.


### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges

<1Mbps>




<2Mbps>






&lt;3Mbps&gt;




### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

<1Mbps>




<2Mbps>





&lt;3Mbps&gt;





## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurious must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.7.4 Test Setup






### 3.7.5 Test Result of Conducted Spurious Emission


<1Mbps>









&lt;2Mbps&gt;








&lt;3Mbps&gt;







## 3.8 Radiated Band Edges and Spurious Emission Measurement

### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics / spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.8.2 Measuring Instruments

See list of measuring equipment of this test report.




### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW = 100 kHz for  $f < 1$  GHz, RBW = 1 MHz for  $f > 1$  GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 \cdot \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. Radiated testing below 1GHz was performed by adjusting the antenna tower from 1m to 4m and by rotating the turn table from 0degree to 360 degree to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6dB margin against QP limit line, the position is marked as “-“.
8. Radiated testing above 1GHz was performed by adjusting the antenna tower from 1m to 4m and by rotating the turn table from 0degree to 360 degree to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6dB margin against average limit line, the position is marked as “-“.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.8.7 Duty Cycle

Please refer to Appendix E.

### 3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix C and D.



## 3.9 AC Conducted Emission Measurement

### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## 3.10 Antenna Requirements

### 3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### 3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

### 3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~50 MHz	Sep. 07, 2021	Oct. 20, 2021~Oct. 26, 2021	Sep. 06, 2022	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	40103 & 07	30MHz~1GHz	Apr. 28, 2021	Oct. 20, 2021~Oct. 26, 2021	Apr. 27, 2022	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-02114	1GHz ~ 18GHz	Aug. 04, 2021	Oct. 20, 2021~Oct. 26, 2021	Aug. 03, 2022	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00993	18GHz~40GHz	Nov. 19, 2020	Oct. 20, 2021~Oct. 26, 2021	Nov. 18, 2021	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 02, 2020	Oct. 20, 2021~Oct. 26, 2021	Dec. 01, 2021	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 12, 2020	Oct. 20, 2021~Oct. 26, 2021	Nov. 11, 2021	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055007	1GHz~18GHz	Jun. 16, 2021	Oct. 20, 2021~Oct. 26, 2021	Jun. 15, 2022	Radiation (03CH11-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 22, 2021	Oct. 20, 2021~Oct. 26, 2021	Jun. 21, 2022	Radiation (03CH11-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	NA	Dec. 02, 2020	Oct. 20, 2021~Oct. 26, 2021	Dec. 01, 2021	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY55420170	20MHz~8.4GHz	Jul. 15, 2021	Oct. 20, 2021~Oct. 26, 2021	Jul. 14, 2022	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Oct. 20, 2021~Oct. 26, 2021	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Oct. 20, 2021~Oct. 26, 2021	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Oct. 20, 2021~Oct. 26, 2021	N/A	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Oct. 20, 2021~Oct. 26, 2021	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 11, 2021	Oct. 20, 2021~Oct. 26, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 11, 2021	Oct. 20, 2021~Oct. 26, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 11, 2021	Oct. 20, 2021~Oct. 26, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11681/4PE	30MHz-18GHz	Mar. 11, 2021	Oct. 20, 2021~Oct. 26, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1.53G Low Pass	Sep. 13, 2021	Oct. 20, 2021~Oct. 26, 2021	Sep. 12, 2022	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	3GHz High Pass Filter	Sep. 13, 2021	Oct. 20, 2021~Oct. 26, 2021	Sep. 12, 2022	Radiation (03CH11-HY)
Hygrometer	TECPTEL	DTM-303B	TP140325	N/A	Nov. 18, 2020	Oct. 20, 2021~Oct. 26, 2021	Nov. 17, 2021	Radiation (03CH11-HY)

**FCC RADIO TEST REPORT**

Report No. : FR193007A

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 27, 2021	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 30, 2020	Oct. 27, 2021	Nov. 29, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 18, 2020	Oct. 27, 2021	Nov. 17, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 01, 2020	Oct. 27, 2021	Nov. 30, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 16, 2020	Oct. 27, 2021	Nov. 15, 2021	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Oct. 27, 2021	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 28, 2021	Oct. 27, 2021	Jul. 27, 2022	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 31, 2020	Oct. 27, 2021	Dec. 30, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 01, 2021	Oct. 14, 2021~Oct. 20, 2021	Feb. 28, 2022	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SNO12	10MHz~6GHz	Dec. 16, 2020	Oct. 14, 2021~Oct. 20, 2021	Dec. 15, 2021	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101565	10Hz ~ 40GHz	Nov. 13, 2020	Oct. 14, 2021~Oct. 20, 2021	Nov. 12, 2021	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2021	Oct. 14, 2021~Oct. 20, 2021	Mar. 16, 2022	Conducted (TH05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	3.1 dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	5.8 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	5.4 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	5.9 dB
---	--------

## Appendix A. Test Result of Conducted Test Items

Test Engineer:	Jacob Yu	Temperature:	22.8~24.5	°C
Test Date:	2021/10/14~2021/10/20	Relative Humidity:	52.8~54.7	%

TEST RESULTS DATA									
20dB and 99% Occupied Bandwidth and Hopping Channel Separation									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.871	0.822	0.999	0.5808	Pass
DH	1Mbps	1	39	2441	0.871	0.825	1.003	0.5808	Pass
DH	1Mbps	1	78	2480	0.871	0.825	1.003	0.5808	Pass
2DH	2Mbps	1	0	2402	1.255	1.164	1.007	0.8365	Pass
2DH	2Mbps	1	39	2441	1.255	1.164	0.999	0.8365	Pass
2DH	2Mbps	1	78	2480	1.255	1.166	1.003	0.8365	Pass
3DH	3Mbps	1	0	2402	1.242	1.149	1.003	0.8278	Pass
3DH	3Mbps	1	39	2441	1.242	1.149	1.003	0.8278	Pass
3DH	3Mbps	1	78	2480	1.237	1.149	0.999	0.8249	Pass

TEST RESULTS DATA						
Dwell Time						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time (hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH5	79	106.670	2.90	0.31	0.4	Pass
DH5 (AFH)	20	53.330	2.90	0.15	0.4	Pass

TEST RESULTS DATA					
Peak Power Table					
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	6.05	20.97	Pass
	39	1	6.22	20.97	Pass
	78	1	8.08	20.97	Pass
2DH1	0	1	4.98	20.97	Pass
	39	1	5.15	20.97	Pass
	78	1	7.02	20.97	Pass
3DH1	0	1	5.17	20.97	Pass
	39	1	5.41	20.97	Pass
	78	1	7.33	20.97	Pass

TEST RESULTS DATA				
Average Power Table				
(Reporting Only)				
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	5.26	5.17
	39	1	5.31	5.17
	78	1	7.47	5.17
2DH1	0	1	1.80	5.08
	39	1	2.06	5.08
	78	1	4.52	5.08
3DH1	0	1	1.97	5.12
	39	1	2.16	5.12
	78	1	4.64	5.12

TEST RESULTS DATA			
Number of Hopping Frequency			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




## **Appendix B. AC Conducted Emission Test Results**

<b>Test Engineer :</b>	Calvin Wang	<b>Temperature :</b>	23~26°C
		<b>Relative Humidity :</b>	45~55%

## EUT Information

Report NO : 193007  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum



## Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	32.26	55.88	23.62	L1	OFF	19.7
0.152250	42.90	---	65.88	22.98	L1	OFF	19.7
0.483000	---	30.81	46.29	15.48	L1	OFF	19.8
0.483000	37.94	---	56.29	18.35	L1	OFF	19.8
0.537000	---	29.94	46.00	16.06	L1	OFF	19.9
0.537000	37.59	---	56.00	18.41	L1	OFF	19.9
0.588750	---	29.94	46.00	16.06	L1	OFF	19.9
0.588750	38.57	---	56.00	17.43	L1	OFF	19.9
0.640500	---	29.83	46.00	16.17	L1	OFF	19.9
0.640500	37.84	---	56.00	18.16	L1	OFF	19.9
0.696750	---	30.43	46.00	15.57	L1	OFF	20.0
0.696750	38.65	---	56.00	17.35	L1	OFF	20.0
0.750750	---	31.05	46.00	14.95	L1	OFF	20.0
0.750750	39.40	---	56.00	16.60	L1	OFF	20.0
0.804750	---	31.79	46.00	14.21	L1	OFF	20.1
0.804750	40.00	---	56.00	16.00	L1	OFF	20.1
0.856500	---	31.81	46.00	14.19	L1	OFF	20.1
0.856500	40.04	---	56.00	15.96	L1	OFF	20.1
0.908250	---	32.55	46.00	13.45	L1	OFF	20.1
0.908250	41.11	---	56.00	14.89	L1	OFF	20.1
0.962250	---	32.41	46.00	13.59	L1	OFF	20.2

<b>0.962250</b>	<b>40.86</b>	---	<b>56.00</b>	<b>15.14</b>	L1	OFF	<b>20.2</b>
<b>1.014000</b>	---	<b>31.64</b>	<b>46.00</b>	<b>14.36</b>	L1	OFF	<b>20.2</b>
<b>1.014000</b>	<b>39.82</b>	---	<b>56.00</b>	<b>16.18</b>	L1	OFF	<b>20.2</b>
<b>1.065750</b>	---	<b>32.29</b>	<b>46.00</b>	<b>13.71</b>	L1	OFF	<b>20.2</b>
<b>1.065750</b>	<b>40.36</b>	---	<b>56.00</b>	<b>15.64</b>	L1	OFF	<b>20.2</b>
<b>1.115250</b>	---	<b>29.46</b>	<b>46.00</b>	<b>16.54</b>	L1	OFF	<b>20.2</b>
<b>1.115250</b>	<b>36.99</b>	---	<b>56.00</b>	<b>19.01</b>	L1	OFF	<b>20.2</b>
<b>1.180500</b>	---	<b>29.06</b>	<b>46.00</b>	<b>16.94</b>	L1	OFF	<b>20.2</b>
<b>1.180500</b>	<b>36.36</b>	---	<b>56.00</b>	<b>19.64</b>	L1	OFF	<b>20.2</b>
<b>1.596750</b>	---	<b>26.24</b>	<b>46.00</b>	<b>19.76</b>	L1	OFF	<b>20.2</b>
<b>1.596750</b>	<b>31.10</b>	---	<b>56.00</b>	<b>24.90</b>	L1	OFF	<b>20.2</b>
<b>6.006750</b>	---	<b>27.32</b>	<b>50.00</b>	<b>22.68</b>	L1	OFF	<b>20.0</b>
<b>6.006750</b>	<b>30.46</b>	---	<b>60.00</b>	<b>29.54</b>	L1	OFF	<b>20.0</b>

## EUT Information

Report NO : 193007  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.17	55.88	26.71	N	OFF	19.7
0.152250	44.33	---	65.88	21.55	N	OFF	19.7
0.429000	---	28.51	47.27	18.76	N	OFF	19.7
0.429000	36.47	---	57.27	20.80	N	OFF	19.7
0.539250	---	25.41	46.00	20.59	N	OFF	19.9
0.539250	32.32	---	56.00	23.68	N	OFF	19.9
0.919500	---	26.41	46.00	19.59	N	OFF	20.2
0.919500	32.07	---	56.00	23.93	N	OFF	20.2
1.027500	---	25.41	46.00	20.59	N	OFF	20.2
1.027500	30.18	---	56.00	25.82	N	OFF	20.2
6.504000	---	25.97	50.00	24.03	N	OFF	20.1
6.504000	27.51	---	60.00	32.49	N	OFF	20.1



## Appendix C. Radiated Spurious Emission

Test Engineer :	Harvey Guo and Fu Chen	Temperature :		23.1 ~ 24.6°C	
		Relative Humidity :		64.3 ~ 68.5%	

### 2.4GHz 2400~2483.5MHz

#### BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH00 2402MHz		2370.375	42.98	-31.02	74	42.05	27.28	7.11	33.46	117	111	P	H
		2370.375	18.22	-35.78	54	-	-	-	-	-	-	A	H
	*	2402	103.85	-	-	102.75	27.41	7.14	33.45	117	111	P	H
		2402	79.09	25.09	54	-	-	-	-	-	-	A	H
													H
													H
		2388.12	43.34	-30.66	74	42.32	27.35	7.13	33.46	120	322	P	V
		2388.12	18.58	-35.42	54	-	-	-	-	-	-	A	V
	*	2402	99.43	-	-	98.33	27.41	7.14	33.45	120	322	P	V
		2402	74.67	20.67	54	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2380.7	43.23	-30.77	74	42.25	27.32	7.12	33.46	120	246	P	H
		2380.7	18.47	-35.53	54	-	-	-	-	-	-	A	H
	*	2441	102.33	-	-	101	27.56	7.2	33.43	120	246	P	H
		2441	77.57	23.57	54	-	-	-	-	-	-	A	H
		2490.76	43.73	-30.27	74	42.01	27.84	7.28	33.4	120	246	P	H
		2490.76	18.97	-35.03	54	-	-	-	-	-	-	A	H
		2363.06	43.23	-30.77	74	42.34	27.25	7.11	33.47	109	300	P	V
		2363.06	18.47	-35.53	54	-	-	-	-	-	-	A	V
	*	2441	100.02	-	-	98.69	27.56	7.2	33.43	109	300	P	V
		2441	75.26	21.26	54	-	-	-	-	-	-	A	V
		2486.35	44.3	-29.7	74	42.62	27.82	7.27	33.41	109	300	P	V
		2486.35	19.54	-34.46	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	105.01	-	-	103.38	27.78	7.26	33.41	111	121	P	H	
		2480	80.25	26.25	54	-	-	-	-	-	-	A	H	
		2483.52	52.18	-21.82	74	50.52	27.8	7.27	33.41	111	121	P	H	
		2483.52	27.42	-26.58	54	-	-	-	-	-	-	A	H	
													H	
													H	
	*	2480	100.7	-	-	99.07	27.78	7.26	33.41	100	288	P	V	
		2480	75.94	21.94	54	-	-	-	-	-	-	A	V	
		2483.64	48.5	-25.5	74	46.84	27.8	7.27	33.41	100	288	P	V	
		2483.64	23.74	-30.26	54	-	-	-	-	-	-	A	V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



## 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	38.93	-35.07	74	53.91	32.41	11.07	58.46	-	-	P	H
		4804	14.17	-39.83	54	-	-	-	-	-	-	A	H
		11340	47.24	-26.76	74	52.22	39.2	17.73	61.91	-	-	P	H
		11340	22.48	-31.52	54	-	-	-	-	-	-	A	H
		14460	48.03	-25.97	74	49.46	40.4	21.23	63.06			P	H
		14460	23.27	-30.73	54	-	-	-	-	-	-	A	H
		17985	51.71	-22.29	74	41.47	42.88	24	56.64	-	-	P	H
		17985	26.95	-27.05	54	-	-	-	-	-	-	A	H
													H
													H
													H
													H
		4804	37.76	-36.24	74	52.74	32.41	11.07	58.46	-	-	P	V
		4804	13	-41	54	-	-	-	-	-	-	A	V
		11025	47.04	-26.96	74	52.25	38.9	17.42	61.53	-	-	P	V
		11025	22.28	-31.72	54	-	-	-	-	-	-	A	V
		14445	48.23	-25.77	74	49.71	40.4	21.2	63.08	-	-	P	V
		14445	23.47	-30.53	54	-	-	-	-	-	-	A	V
		17955	50.54	-23.46	74	40.64	42.64	23.97	56.71	-	-	P	V
		17955	25.78	-28.22	54	-	-	-	-	-	-	A	V
													V
													V
													V

**FCC RADIO TEST REPORT**

Report No. : FR193007A

BT	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BT CH 39 2441MHz		4882	40.24	-33.76	74	54.85	32.63	11.24	58.48	-	-	P	H
		4882	15.48	-38.52	54	-	-	-	-	-	-	A	H
		7323	42.58	-31.42	74	51.45	36.75	13.55	59.17	-	-	P	H
		7323	17.82	-36.18	54	-	-	-	-	-	-	A	H
		11595	47.38	-26.62	74	52.88	38.8	17.97	62.27	-	-	P	H
		11595	22.62	-31.38	54	-	-	-	-	-	-	A	H
		14535	49.68	-24.32	74	50.99	40.33	21.38	63.02	-	-	P	H
		14535	24.92	-29.08	54	-	-	-	-	-	-	A	H
		17970	51.3	-22.7	74	41.23	42.76	23.98	56.67	-	-	P	H
		17970	26.54	-27.46	54	-	-	-	-	-	-	A	H
													H
													H
		4882	38.39	-35.61	74	53	32.63	11.24	58.48	-	-	P	V
		4882	13.63	-40.37	54	-	-	-	-	-	-	A	V
		7323	41.97	-32.03	74	50.84	36.75	13.55	59.17	-	-	P	V
		7323	17.21	-36.79	54	-	-	-	-	-	-	A	V
		10755	47.86	-26.14	74	52.77	39.11	17.19	61.21	-	-	P	V
		10755	23.1	-30.9	54	-	-	-	-	-	-	A	V
		14565	48.68	-25.32	74	50.01	40.27	21.44	63.04	-	-	P	V
		14565	23.92	-30.08	54	-	-	-	-	-	-	A	V
		17985	51.15	-22.85	74	40.91	42.88	24	56.64	-	-	P	V
		17985	26.39	-27.61	54	-	-	-	-	-	-	A	V
													V
													V



BT	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BT CH 78 2480MHz		4960	39.34	-34.66	74	53.4	33.02	11.84	58.49	-	-	P	H
		4960	14.58	-39.42	54	-	-	-	-	-	-	A	H
		7440	41.18	-32.82	74	50.27	36.22	14.3	59.12	-	-	P	H
		7440	16.42	-37.58	54	-	-	-	-	-	-	A	H
		11385	46.83	-27.17	74	51.82	39.2	18.24	61.96	-	-	P	H
		11385	22.07	-31.93	54	-	-	-	-	-	-	A	H
		14535	48.97	-25.03	74	50.28	40.33	22.03	63.02	-	-	P	H
		14535	24.21	-29.79	54	-	-	-	-	-	-	A	H
		17985	50.66	-23.34	74	40.42	42.88	24.82	56.64	-	-	P	H
		17985	25.9	-28.1	54	-	-	-	-	-	-	A	H
													H
													H
		4960	39.6	-34.4	74	53.66	33.02	11.41	58.49	-	-	P	V
		4960	14.84	-39.16	54	-	-	-	-	-	-	A	V
		7440	41.37	-32.63	74	50.46	36.22	13.81	59.12	-	-	P	V
		7440	16.61	-37.39	54	-	-	-	-	-	-	A	V
		10830	47.03	-26.97	74	51.99	39.08	17.26	61.3	-	-	P	V
		10830	47.03	-6.97	54	-	-	-	-	-	-	A	V
		14445	48.32	-25.68	74	49.8	40.4	21.2	63.08	-	-	P	V
		14445	48.32	-5.68	54	-	-	-	-	-	-	A	V
		17985	50.57	-23.43	74	40.33	42.88	24	56.64	-	-	P	V
		17985	25.81	-28.19	54	-	-	-	-	-	-	A	V
													V
Remark	1.	No other spurious found.											
	2.	All results are PASS against Peak and Average limit line.											
	3.	The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.											
	4.	The emission level close to 18GHz is checked that the average emission level is noise floor only.											



## Emission above 18GHz

## 2.4GHz BT (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
2.4GHz BT SHF	23460	38.95	-29.25	68.2	95.98	0	-3.01	54.02	-	-	P	H		
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	



## Emission below 1GHz

## 2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
												Avg.	
												( P/A )	( H/V )
2.4GHz BT LF		30	20.37	-19.63	40	27.45	24.57	0.79	32.44	-	-	P	H
		260.86	25.47	-20.53	46	35.71	19.6	2.45	32.29	-	-	P	H
		325.85	25.91	-20.09	46	35.67	19.57	2.71	32.04	-	-	P	H
		628.49	26.04	-19.96	46	29.25	25.8	3.74	32.75	-	-	P	H
		872.93	30.41	-15.59	46	28.46	28.79	4.47	31.31	-	-	P	H
		948.59	30.45	-15.55	46	26.46	30.2	4.67	30.88	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													V
		30	20.13	-19.87	40	27.21	24.57	0.79	32.44	-	-	P	V
		196.84	17.12	-26.38	43.5	32.6	14.93	2.13	32.54	-	-	P	V
		260.86	20.58	-25.42	46	30.82	19.6	2.45	32.29	-	-	P	V
		717.73	26.62	-19.38	46	28.51	26.34	4.02	32.25	-	-	P	V
		863.23	30.88	-15.12	46	28.9	28.89	4.44	31.35	-	-	P	V
		958.29	31.56	-14.44	46	26.95	30.73	4.7	30.82	-	-	P	V
													V
													V
													V
													V
													V
													V
	1. No other spurious found. 2. All results are PASS against limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.												

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak or Average</b>
H/V	<b>Horizontal or Vertical</b>



**A calculation example for radiated spurious emission is shown as below:**

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos		Avg.	
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A ) ( H/V )	
<b>BT CH 00 2402MHz</b>		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB $\mu$ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

**For Peak Limit @ 2390MHz:**

1. Level(dB $\mu$ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB $\mu$ V) – 35.86 (dB)

= 55.45 (dB $\mu$ V/m)

2. Over Limit(dB)

= Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

= 55.45(dB $\mu$ V/m) – 74(dB $\mu$ V/m)

= -18.55(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**





## Appendix D. Radiated Spurious Emission Plots


Test Engineer :	Harvey Guo and Fu Chen	Temperature :	23.1 ~ 24.6°C
		Relative Humidity :	64.3 ~ 68.5%

### 2.4GHz 2400~2483.5MHz




#### BT (Band Edge @ 3m)











BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak	 <p>14_Level (dBuV/m) Date: 2021-10-21</p> <p>Site : 030-HV Condition : PEAK_BE_74 3m HORN 9120002114_0804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>14_Level (dBuV/m) Date: 2021-10-21</p> <p>Site : 030-HV Condition : PEAK_BE_74 3m HORN 9120002114_0804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>14_Level (dBuV/m) Date: 2021-10-21</p> <p>Site : 030-HV Condition : PEAK_BE_74 3m HORN 9120002114_0804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank










## 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)










## Emission above 18GHz


## 2.4GHz BT (SHF @ 1m)





## Emission below 1GHz

## 2.4GHz BT (LF)



## Appendix E. Duty Cycle Plots



### Note:

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.89 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

### Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.89 \text{ ms} \times 20 \text{ channels} = 57.8 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100 \text{ ms} / 57.8 \text{ ms}] = 2 \text{ hops}$   
Thus, the maximum possible ON time:

$$2.89 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.78 \text{ ms}/100 \text{ ms}) = -24.76 \text{ dB}$$