



求是 价值 双赢

深圳市千目通讯科技有限公司

Shenzhen Qianmu Communication Technology Co., Ltd.

4th Floor, Block A, Huafeng Zhigu Hangcheng
High tech Industrial Park, Hangcheng Street,
Sanwei Community, Bao'an District, Shenzhen,
China

6A061-470Pro-H3

2022.9.9

A1

LIU CHU SHENG





ant

求是 价值 双赢





	FPC		
	WIFI2400~2500Mz 802.11b 11MBps		
Channel	1	6	11
TRP	13.44	13.79	14.55
TIS	-79.15	-79.42	-80.54
	WIFI5000~5800Mz 802.11a 54MBps		
Channel	36	161	165
TRP	10.86	10.28	10.51
TIS	-67.22	-67.23	-68.33




Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Point Values											
Ant. Port Input Pwr. (dBm)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Tot. Rad. Pwr. (dBm)	-5.52	-5.56	-5.46	-5.24	-5.19	-4.89	-4.97	-5.19	-5.15	-4.94	-4.89
Peak EIRP (dBm)	-0.30	-0.45	-0.30	0.07	0.11	0.34	0.05	-0.28	-0.27	-0.21	-0.18
Directivity (dBi)	5.23	5.11	5.16	5.31	5.30	5.22	5.02	4.91	4.87	4.73	4.71
Efficiency (dB)	-5.52	-5.56	-5.46	-5.24	-5.19	-4.89	-4.97	-5.19	-5.15	-4.94	-4.89
Efficiency (%)	28.00	27.80	28.40	29.90	30.30	32.50	31.80	30.30	30.60	32.10	32.40
Gain (dBi)	1.30	1.45	2.30	2.07	2.11	2.19	2.05	1.28	1.27	1.21	1.18
NHPRP $\pm\pi/4$ (dBm)	-7.47	-7.55	-7.48	-7.28	-7.24	-6.95	-7.04	-7.27	-7.24	-7.04	-7.01
NHPRP $\pm\pi/6$ (dBm)	-9.30	-9.39	-9.32	-9.11	-9.08	-8.79	-8.90	-9.15	-9.13	-8.92	-8.88
NHPRP $\pm\pi/8$ (dBm)	-10.71	-10.80	-10.74	-10.54	-10.50	-10.20	-10.32	-10.57	-10.53	-10.29	-10.21
Upper Hem. PRP (dBm)	-8.22	-8.22	-8.13	-7.91	-7.83	-7.50	-7.57	-7.78	-7.74	-7.56	-7.51
Lower Hem. PRP (dBm)	-8.87	-8.94	-8.84	-8.62	-8.61	-8.33	-8.44	-8.66	-8.61	-8.38	-8.33
Upper Hem. PRP (%)	15.07	15.06	15.37	16.17	16.47	17.77	17.51	16.66	16.82	17.54	17.75
Lower Hem. PRP (%)	12.96	12.75	13.06	13.74	13.78	14.68	14.32	13.62	13.77	14.52	14.68



Frequency ID	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26
Frequency (MHz)	5150.0	5200.0	5250.0	5300.0	5350.0	5400.0	5450.0	5500.0	5550.0	5600.0	5650.0	5700.0	5750.0	5800.0	5850.0
Point Values															
Ant. Port Input Pwr. (dBm)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Tot. Rad. Pwr. (dBm)	-5.28	-4.82	-5.02	-5.52	-5.65	-4.85	-5.74	-6.78	-6.82	-5.63	-5.62	-6.44	-6.13	-5.78	-5.79
Peak EIRP (dBm)	1.64	1.63	1.28	0.60	0.31	0.48	0.39	-0.58	-1.27	0.02	0.21	-0.60	-0.42	-0.06	-0.28
Directivity (dBi)	6.92	6.45	6.31	6.12	5.96	5.32	6.13	6.20	5.54	5.66	5.82	5.85	5.71	5.72	5.51
Efficiency (dB)	-5.28	-4.82	-5.02	-5.52	-5.65	-4.85	-5.74	-6.78	-6.82	-5.63	-5.62	-6.44	-6.13	-5.78	-5.79
Efficiency (%)	29.70	32.90	31.40	28.00	27.20	32.80	26.60	21.00	20.80	27.30	27.40	22.70	24.40	26.40	26.40
Gain (dBi)	2.97	2.63	2.28	1.60	1.31	1.48	1.39	0.58	0.27	1.02	1.21	1.60	1.42	1.06	1.28
NHPRP $\pm\pi/4$ (dBm)	-6.54	-6.09	-6.32	-6.75	-6.92	-6.21	-7.00	-8.08	-8.15	-6.89	-6.92	-7.77	-7.39	-7.00	-7.03
NHPRP $\pm\pi/6$ (dBm)	-8.05	-7.62	-7.92	-8.27	-8.45	-7.76	-8.39	-9.46	-9.53	-8.22	-8.27	-9.10	-8.70	-8.35	-8.41
NHPRP $\pm\pi/8$ (dBm)	-9.25	-8.87	-9.24	-9.53	-9.74	-9.07	-9.55	-10.59	-10.63	-9.26	-9.31	-10.13	-9.71	-9.38	-9.44
Upper Hem. PRP (dBm)	-8.42	-7.91	-8.13	-8.72	-8.60	-7.76	-8.77	-9.67	-9.64	-8.56	-8.44	-9.32	-9.08	-8.63	-8.68
Lower Hem. PRP (dBm)	-8.17	-7.76	-7.94	-8.35	-8.72	-7.96	-8.74	-9.92	-10.02	-8.73	-8.82	-9.58	-9.21	-8.95	-8.92
Upper Hem. PRP (%)	14.40	16.18	15.37	13.41	13.80	16.75	13.27	10.79	10.86	13.94	14.31	11.69	12.37	13.70	13.54
Lower Hem. PRP (%)	15.25	16.75	16.08	14.63	13.44	16.00	13.38	10.17	9.95	13.38	13.13	11.01	11.99	12.75	12.83



2.4G





5.8G

