



TEST REPORT

Applicant Name : Shenzhen Junge Yunchuang Technology Co., Ltd.
Address : 1204, Unit 3, Building C, Fu Gui Yuan, Fu Gui Road, Fu Hua Community, Xixiang Street, Baoan District, Shenzhen, China
Report Number : SZNS220518-21374E-RF-00B
FCC ID: 2A3FP-PC007

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Tablet PC
Model No.: TB-JS101A
Multiple Model(s) No.: S31, S31T, JS31 (Please refer to DOS for Model difference)
Trade Mark: N/A
Date Received: 2022/05/18
Report Date: 2022/07/28

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Approved By:

Nick Fang
EMC Engineer

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	11
EXTERNAL I/O CABLE.....	11
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	13
TEST EQUIPMENT LIST	14
FCC§15.247 (I), §1.1307 (B) (3) & §2.1093 – RF EXPOSURE	16
APPLICABLE STANDARD	16
FCC §15.203 - ANTENNA REQUIREMENT.....	17
APPLICABLE STANDARD	17
ANTENNA CONNECTOR CONSTRUCTION	17
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
TRANSD FACTOR & MARGIN CALCULATION.....	19
TEST DATA	19
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	22
APPLICABLE STANDARD	22
EUT SETUP	22
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	23
TEST PROCEDURE	23
FACTOR & MARGIN CALCULATION	23
TEST DATA	23
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	54
APPLICABLE STANDARD	54
TEST PROCEDURE	54
TEST DATA	54

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	56
APPLICABLE STANDARD	56
TEST PROCEDURE	56
TEST DATA	56
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	63
APPLICABLE STANDARD	63
TEST PROCEDURE	63
TEST DATA	63

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2462MHz
Maximum Conducted Peak Output Power	BLE 1M: -3.08dBm; BLE 2M: -3.07dBm Wi-Fi: 19.55dBm(802.11b), 22.52dBm(802.11g), 22.52dBm(802.11n20), 21.86dBm(802.11n40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	0.5 dBi (provided by the applicant)
Voltage Range	DC 3.8V from battery or DC 5V from adapter
Sample serial number	SZNS220518-21374E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: FX2U-050200U Input: AC 100-240V, 50/60Hz, 0.4A max Output: DC 5.0V, 2.0A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Line Conducted emission		2.72dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz- 18GHz	4.98dB
	18GHz- 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

802.11n-HT40 mode was tested with Channel 3, 6 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

EUT was test in engineering mode.

The device was tested with the worst case was performed as below:


Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	19.5	19.5	19.5
802.11g	6Mbps	17.5	17.5	17.5
802.11n-HT20	MCS0	17.5	17.5	17.5
802.11n-HT40	MCS0	16.5	16.5	16.5
BLE 1M	1Mbps	Default	Default	Default
BLE 2M	2Mbps	Default	Default	Default

Note: the power level was provided by applicant.

Duty cycle

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	8.385	8.426	99.51
802.11g	1.391	1.438	96.73
802.11n-HT20	1.300	1.346	96.58
802.11n-HT40	0.649	0.694	93.52
BLE 1M	0.090	0.630	14.29
BLE 2M	0.055	0.630	8.73


BLE-1M




Date: 30.JUN.2022 16:33:26


:

BLE-2M



Date: 30.JUN.2022 16:44:44





Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Epik	Earphone	E250	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shield Detachable USB Cable	1.0	Adapter	EUT

Block Diagram of Test Setup

For conducted emission:



For radiated emission :



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (3) & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.18	N0850	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2021/12/13	2022/12/12
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200982	2021/07/06	2022/07/05
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200982	2022/07/06	2023/07/05
WEINSCHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (3) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance

1-mW Test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

For worst case:

For BLE:

Frequency (MHz)	Maximum Tune-up power		Exemption Limit (mW)	SAR Test Exclusion
	(dBm)	(mW)		
2402-2480	-3.0	0.50	1	Yes

Result: Compliant.

For Wi-Fi:

Test Result: Compliant, please refer to the SAR report: SZNS220518-21374E-SA

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached, and the maximum antenna gain is 0.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data


Environmental Conditions

Temperature:	24 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Jason on 2022-06-28.


EUT operation mode: Transmitting (Worst case is 802.11g, middle channel)

AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Mode : 2.4G WIFI
 Model : TB-JS101A
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.164	9.80	24.11	33.91	55.26	-21.35	Average
2	0.164	9.80	35.36	45.16	65.26	-20.10	QP
3	0.208	9.80	19.49	29.29	53.27	-23.98	Average
4	0.208	9.80	31.21	41.01	63.27	-22.26	QP
5	0.308	9.80	16.77	26.57	50.02	-23.45	Average
6	0.308	9.80	25.25	35.05	60.02	-24.97	QP
7	0.577	9.81	25.02	34.83	46.00	-11.17	Average
8	0.577	9.81	31.34	41.15	56.00	-14.85	QP
9	2.950	9.83	15.86	25.69	46.00	-20.31	Average
10	2.950	9.83	24.14	33.97	56.00	-22.03	QP
11	16.475	9.96	9.91	19.87	50.00	-30.13	Average
12	16.475	9.96	19.83	29.79	60.00	-30.21	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Mode : 2.4G WIFI
 Model : TB-JS101A
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.158	9.80	23.19	32.99	55.59	-22.60	Average
2	0.158	9.80	35.25	45.05	65.59	-20.54	QP
3	0.256	9.80	19.15	28.95	51.56	-22.61	Average
4	0.256	9.80	28.87	38.67	61.56	-22.89	QP
5	0.324	9.80	18.39	28.19	49.61	-21.42	Average
6	0.324	9.80	26.31	36.11	59.61	-23.50	QP
7	0.609	9.81	22.23	32.04	46.00	-13.96	Average
8	0.609	9.81	30.55	40.36	56.00	-15.64	QP
9	2.952	9.83	14.37	24.20	46.00	-21.80	Average
10	2.952	9.83	24.03	33.86	56.00	-22.14	QP
11	16.044	10.06	13.33	23.39	50.00	-26.61	Average
12	16.044	10.06	23.36	33.42	60.00	-26.58	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	25.6 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa


The testing was performed by Zeki Ma on 2022-06-04 for below 1GHz and for above 1GHz.

EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case X-axes orientation was recorded)

30MHz-1GHz: (Worst case is 802.11B mode, low Channel)

Note: When the test result of Peak was less than the limit of QP, just the peak value was recorded.

Horizontal:



Site : chamber


Condition: 3m HORIZONTAL

Job No. : SZNS220518-21374E-RF

Test Mode: 2.4G WIFI

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	55.027	-10.28	30.97	20.69	40.00	-19.31	Peak
2	82.323	-16.56	35.45	18.89	40.00	-21.11	Peak
3	167.457	-13.84	41.77	27.93	43.50	-15.57	Peak
4	265.559	-10.43	33.51	23.08	46.00	-22.92	Peak
5	362.031	-7.62	35.83	28.21	46.00	-17.79	Peak
6	796.532	-0.28	30.84	30.56	46.00	-15.44	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220518-21374E-RF
 Test Mode: 2.4G WIFI

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.563	-11.68	37.95	26.27	40.00	-13.73	Peak
2	51.571	-9.96	39.74	29.78	40.00	-10.22	Peak
3	61.832	-11.37	36.20	24.83	40.00	-15.17	Peak
4	82.143	-16.62	41.50	24.88	40.00	-15.12	Peak
5	171.017	-13.48	35.41	21.93	43.50	-21.57	Peak
6	362.031	-7.62	30.62	23.00	46.00	-23.00	Peak

1-25 GHz:**BLE 1M:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
Low Channel 2402 MHz									
2310	67.63	PK	31	1.4	H	-7.24	60.39	74	-13.61
2310	53.25	AV	31	1.4	H	-7.24	46.01	54	-7.99
2390	67.88	PK	59	2.2	H	-7.22	60.66	74	-13.34
2390	54.38	AV	59	2.2	H	-7.22	47.16	54	-6.84
2310	67.04	PK	324	2.4	V	-7.24	59.80	74	-14.2
2310	53.3	AV	324	2.4	V	-7.24	46.06	54	-7.94
2390	67.74	PK	214	2.3	V	-7.22	60.52	74	-13.48
2390	54.4	AV	214	2.3	V	-7.22	47.18	54	-6.82
4804	53.61	PK	222	1.2	H	-3.51	50.10	74	-23.90
4804	53.22	PK	68	1.2	V	-3.51	49.71	74	-24.29
Middle Channel 2440MHz									
4880	53.74	PK	253	1.4	H	-3.38	50.36	74	-23.64
4880	53.38	PK	14	1.8	V	-3.38	50.00	74	-24.00
High Channel 2480MHz									
2483.5	68.97	PK	323	1.9	H	-7.2	61.77	74	-12.23
2483.5	55.2	AV	323	1.9	H	-7.2	48.0	54	-6.00
2500	68.69	PK	265	1.1	H	-7.18	61.51	74	-12.49
2500	54.58	AV	265	1.1	H	-7.18	47.4	54	-6.60
2483.5	68.31	PK	342	2	V	-7.2	61.11	74	-12.89
2483.5	55.18	AV	342	2	V	-7.2	47.98	54	-6.02
2500	67.92	PK	102	2.3	V	-7.18	60.74	74	-13.26
2500	54.63	AV	102	2.3	V	-7.18	47.45	54	-6.55
4960	53.06	PK	312	1.2	H	-3.01	50.05	74	-23.95
4960	52.71	PK	339	1.9	V	-3.01	49.70	74	-24.30

BLE 2M:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
Low Channel 2402 MHz									
2310	67.02	PK	51	1.7	H	-7.24	59.78	74	-14.22
2310	53.65	AV	51	1.7	H	-7.24	46.41	54	-7.59
2390	68.23	PK	105	1.6	H	-7.22	61.01	74	-12.99
2390	54.64	AV	105	1.6	H	-7.22	47.42	54	-6.58
2310	67.31	PK	201	1.3	V	-7.24	60.07	74	-13.93
2310	53.75	AV	201	1.3	V	-7.24	46.51	54	-7.49
2390	68.23	PK	75	1.7	V	-7.22	61.01	74	-12.99
2390	54.7	AV	75	1.7	V	-7.22	47.48	54	-6.52
4804	53	PK	146	1.5	H	-3.51	49.49	74	-24.51
4804	53.45	PK	284	2.3	V	-3.51	49.94	74	-24.06
Middle Channel 2440MHz									
4880	53.87	PK	57	2.1	H	-3.38	50.49	74	-23.51
4880	53.2	PK	50	1.4	V	-3.38	49.82	74	-24.18
High Channel 2480MHz									
2483.5	68.7	PK	190	1.6	H	-7.2	61.5	74	-12.5
2483.5	55.52	AV	190	1.6	H	-7.2	48.32	54	-5.68
2500	69.09	PK	327	2	H	-7.18	61.91	74	-12.09
2500	54.98	AV	327	2	H	-7.18	47.8	54	-6.2
2483.5	69.04	PK	9	2.5	V	-7.2	61.84	74	-12.16
2483.5	55.59	AV	9	2.5	V	-7.2	48.39	54	-5.61
2500	68.25	PK	10	1.9	V	-7.18	61.07	74	-12.93
2500	54.92	AV	10	1.9	V	-7.18	47.74	54	-6.26
4960	52.68	PK	323	1.8	H	-3.01	49.67	74	-24.33
4960	52.34	PK	271	1.9	V	-3.01	49.33	74	-24.67

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak value were recorded.

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave		Heigh t (m)	Polar (H/V)				
802.11b, Low Channel									
2310	67.26	PK	209	1.2	H	-7.24	60.02	74	-13.98
2310	52.73	AV	209	1.2	H	-7.24	45.49	54	-8.51
2390	68.22	PK	5	1.5	H	-7.22	61	74	-13.00
2390	53.9	AV	5	1.5	H	-7.22	46.68	54	-7.32
2310	67.1	PK	294	2	V	-7.24	59.86	74	-14.14
2310	52.74	AV	294	2	V	-7.24	45.5	54	-8.50
2390	68.11	PK	101	2.2	V	-7.22	60.89	74	-13.11
2390	53.91	AV	101	2.2	V	-7.22	46.69	54	-7.31
4824	57.36	PK	7	1.6	H	-3.52	53.84	74	-20.16
4824	57.02	PK	295	2.5	V	-3.52	53.5	74	-20.50
802.11b, Middle Channel									
4874	57.29	PK	337	2.1	H	-3.42	53.87	74	-20.13
4874	56.96	PK	168	2.2	V	-3.42	53.54	74	-20.46
802.11b, High Channel									
2483.5	69.57	PK	271	1.5	H	-7.2	62.37	74	-11.63
2483.5	55.54	AV	271	1.5	H	-7.2	48.34	54	-5.66
2500	68.74	PK	80	1.9	H	-7.18	61.56	74	-12.44
2500	54	AV	80	1.9	H	-7.18	46.82	54	-7.18
2483.5	69.27	PK	160	2.1	V	-7.2	62.07	74	-11.93
2483.5	55.14	AV	160	2.1	V	-7.2	47.94	54	-6.06
2500	68.98	PK	343	1.6	V	-7.18	61.8	74	-12.20
2500	53.99	AV	343	1.6	V	-7.18	46.81	54	-7.19
4924	56.46	PK	136	1.1	H	-3.16	53.3	74	-20.70
4924	56.49	PK	108	1.3	V	-3.16	53.33	74	-20.67

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave		Heigh t (m)	Polar (H/V)				
802.11g, Low Channel									
2310	67.08	PK	74	2.2	H	-7.24	59.84	74	-14.16
2310	52.75	AV	74	2.2	H	-7.24	45.51	54	-8.49
2390	68.24	PK	103	1.6	H	-7.22	61.02	74	-12.98
2390	54.26	AV	103	1.6	H	-7.22	47.04	54	-6.96
2310	67.81	PK	155	1.7	V	-7.24	60.57	74	-13.43
2310	52.73	AV	155	1.7	V	-7.24	45.49	54	-8.51
2390	70.4	PK	103	2.3	V	-7.22	63.18	74	-10.82
2390	55.22	AV	103	2.3	V	-7.22	48	54	-6
4824	54.06	PK	328	1.8	H	-3.52	50.54	74	-23.46
4824	54.05	PK	6	1.8	V	-3.52	50.53	74	-23.47
802.11g, Middle Channel									
4874	53.73	PK	104	1.9	H	-3.42	50.31	74	-23.69
4874	53.32	PK	257	1	V	-3.42	49.9	74	-24.1
802.11g, High Channel									
2483.5	69.68	PK	75	2.4	H	-7.2	62.48	74	-11.52
2483.5	55.19	AV	75	2.4	H	-7.2	47.99	54	-6.01
2500	68.45	PK	237	1.3	H	-7.18	61.27	74	-12.73
2500	54	AV	237	1.3	H	-7.18	46.82	54	-7.18
2483.5	75.96	PK	281	1.5	V	-7.2	68.76	74	-5.24
2483.5	56.48	AV	281	1.5	V	-7.2	49.28	54	-4.72
2500	68.05	PK	260	1.8	V	-7.18	60.87	74	-13.13
2500	54.01	AV	260	1.8	V	-7.18	46.83	54	-7.17
4924	54.44	PK	107	2	H	-3.16	51.28	74	-22.72
4924	53.77	PK	181	1.2	V	-3.16	50.61	74	-23.39

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave		Height (m)	Polar (H/V)				
802.11n20, Low Channel									
2310	67.44	PK	72	2.1	H	-7.24	60.2	74	-13.8
2310	54.56	AV	72	2.1	H	-7.24	47.32	54	-6.68
2390	67.81	PK	245	1.2	H	-7.22	60.59	74	-13.41
2390	54.49	AV	245	1.2	H	-7.22	47.27	54	-6.73
2310	67	PK	296	2.2	V	-7.24	59.76	74	-14.24
2310	54.12	AV	296	2.2	V	-7.24	46.88	54	-7.12
2390	68.1	PK	134	1.8	V	-7.22	60.88	74	-13.12
2390	54.35	AV	134	1.8	V	-7.22	47.13	54	-6.87
4824	53.12	PK	5	2.2	H	-3.52	49.6	74	-24.4
4824	53.05	PK	175	2	V	-3.52	49.53	74	-24.47
802.11n20, Middle Channel									
4874	54.04	PK	59	1.7	H	-3.42	50.62	74	-23.38
4874	54.19	PK	239	2.3	V	-3.42	50.77	74	-23.23
802.11n20, High Channel									
2483.5	71.62	PK	36	1.8	H	-7.2	64.42	74	-9.58
2483.5	55.37	AV	36	1.8	H	-7.2	48.17	54	-5.83
2500	69.08	PK	47	2.4	H	-7.18	61.9	74	-12.1
2500	54.01	AV	47	2.4	H	-7.18	46.83	54	-7.17
2483.5	71.8	PK	41	1.8	V	-7.2	64.6	74	-9.4
2483.5	55.75	AV	41	1.8	V	-7.2	48.55	54	-5.45
2500	69.18	PK	199	2	V	-7.18	62	74	-12
2500	54.41	AV	199	2	V	-7.18	47.23	54	-6.77
4924	54.12	PK	72	1.9	H	-3.16	50.96	74	-23.04
4924	53.83	PK	167	2.3	V	-3.16	50.67	74	-23.33

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave		Heigh t (m)	Polar (H/V)				
802.11n40, Low Channel									
2310	67.03	PK	4	2	H	-7.24	59.79	74	-14.21
2310	52.74	AV	4	2	H	-7.24	45.5	54	-8.5
2390	74.31	PK	301	2.4	H	-7.22	67.09	74	-6.91
2390	56.82	AV	301	2.4	H	-7.22	49.6	54	-4.4
2310	66.9	PK	282	1.4	V	-7.24	59.66	74	-14.34
2310	52.74	AV	282	1.4	V	-7.24	45.5	54	-8.5
2390	74.18	PK	35	1.7	V	-7.22	66.96	74	-7.04
2390	56.79	AV	35	1.7	V	-7.22	49.57	54	-4.43
4844	53.58	PK	232	1	H	-3.54	50.04	74	-23.96
4844	52.97	PK	162	1	V	-3.54	49.43	74	-24.57
802.11n40, Middle Channel									
4874	53.7	PK	230	2.3	H	-3.42	50.28	74	-23.72
4874	53.86	PK	355	1.3	V	-3.42	50.44	74	-23.56
802.11n40, High Channel									
2483.5	78.41	PK	246	1.5	H	-7.2	71.21	74	-2.79
2483.5	57.56	AV	246	1.5	H	-7.2	50.36	54	-3.64
2500	68.42	PK	346	2	H	-7.18	61.24	74	-12.76
2500	54.01	AV	346	2	H	-7.18	46.83	54	-7.17
2483.5	78.66	PK	230	1.1	V	-7.2	71.46	74	-2.54
2483.5	58.05	AV	230	1.1	V	-7.2	50.85	54	-3.15
2500	68.56	PK	249	1.8	V	-7.18	61.38	74	-12.62
2500	53.48	AV	249	1.8	V	-7.18	46.3	54	-7.70
4904	53.62	PK	32	2.4	H	-3.26	50.36	74	-23.64
4904	54.14	PK	333	1	V	-3.26	50.88	74	-23.12

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level - Limit


The other spurious emission which is 20dB below to the limit was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.


1-18 GHz:

Pre-scan Plots:

802.11 b Middle Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan Plots:

802.11 b Middle Channel
Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa


The testing was performed by Cat Kang from 2022-06-30 to 2022-07-13.

EUT operation mode: Transmitting


Test Result: Compliant.

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode				
Low	2412	8.58	12.96	≥ 500
Middle	2437	8.56	12.80	≥ 500
High	2462	9.04	12.96	≥ 500
802.11g mode				
Low	2412	15.51	16.88	≥ 500
Middle	2437	15.78	16.88	≥ 500
High	2462	15.78	16.96	≥ 500
802.11n-HT20 mode				
Low	2412	15.99	17.84	≥ 500
Middle	2437	16.38	17.92	≥ 500
High	2462	16.38	17.92	≥ 500
802.11n-HT40 mode				
Low	2422	36.06	36.80	≥ 500
Middle	2437	32.69	36.08	≥ 500
High	2452	35.40	36.16	≥ 500


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Emission Bandwidth (MHz)	Limit (kHz)
BLE 1M				
Low	2402	0.51	1.04	≥ 500
Middle	2440	0.51	1.04	≥ 500
High	2480	0.51	1.04	≥ 500
BLE 2M				
Low	2402	0.88	2.08	≥ 500
Middle	2440	0.88	2.07	≥ 500
High	2480	0.87	2.08	≥ 500

802.11b mode:**6dB Bandwidth, Low Channel**


Date: 1.JUL.2022 10:39:37

6dB Bandwidth, Middle Channel


Date: 13.JUL.2022 17:02:53

6dB Bandwidth, High Channel


Date: 13.JUL.2022 17:08:51

99% Emission Bandwidth, Low Channel


Date: 1.JUL.2022 10:39:09

99% Emission Bandwidth, Middle Channel


Date: 12.JUL.2022 15:15:50

99% Emission Bandwidth, High Channel


Date: 12.JUL.2022 15:22:21

802.11g mode:**6dB Bandwidth, Low Channel**


Date: 1.JUL.2022 10:57:24

6dB Bandwidth, Middle Channel


Date: 12.JUL.2022 15:31:54

6dB Bandwidth, High Channel


Date: 12.JUL.2022 15:35:41

99% Emission Bandwidth, Low Channel

Date: 1.JUL.2022 10:56:56

99% Emission Bandwidth, Middle Channel


Date: 12.JUL.2022 15:31:26

99% Emission Bandwidth, High Channel

Date: 12.JUL.2022 15:35:13


802.11n20 mode:

6dB Bandwidth, Low Channel




Date: 1.JUL.2022 11:12:50


6dB Bandwidth, Middle Channel




Date: 12.JUL.2022 15:49:58

6dB Bandwidth, High Channel


Date: 12.JUL.2022 15:54:09

99% Emission Bandwidth, Low Channel


Date: 1.JUL.2022 11:12:22

99% Emission Bandwidth, Middle Channel


Date: 12.JUL.2022 15:49:29

99% Emission Bandwidth, High Channel


Date: 12.JUL.2022 15:53:41

802.11n40 mode:**6dB Bandwidth, Low Channel**


Date: 1.JUL.2022 11:31:32

6dB Bandwidth, Middle Channel


Date: 13.JUL.2022 17:15:37

6dB Bandwidth, High Channel


Date: 12.JUL.2022 16:55:18

99% Emission Bandwidth, Low Channel


Date: 1.JUL.2022 11:31:04

99% Emission Bandwidth, Middle Channel


Date: 12.JUL.2022 16:04:32

99% Emission Bandwidth, High Channel


Date: 12.JUL.2022 16:54:49

BLE 1M:**6dB Bandwidth, Low Channel**


Date: 30.JUN.2022 16:31:33

6dB Bandwidth, Middle Channel


Date: 30.JUN.2022 16:34:51

6dB Bandwidth, High Channel


Date: 30.JUN.2022 16:38:07

99% Emission Bandwidth, Low Channel


Date: 30.JUN.2022 16:31:05

99% Emission Bandwidth, Middle Channel


Date: 30.JUN.2022 16:34:23

99% Emission Bandwidth, High Channel


Date: 30.JUN.2022 16:37:39

BLE 2M:**6dB Bandwidth, Low Channel**


Date: 30.JUN.2022 16:43:03

6dB Bandwidth, Middle Channel


Date: 30.JUN.2022 16:46:09

6dB Bandwidth, High Channel


Date: 30.JUN.2022 16:49:15

99% Emission Bandwidth, Low Channel

Date: 30.JUN.2022 16:42:35

99% Emission Bandwidth, Middle Channel

Date: 30.JUN.2022 16:45:41

99% Emission Bandwidth, High Channel

Date: 30.JUN.2022 16:48:47


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Note: the Open Switch and Control Unit has a built-in power sensor.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang from 2022-06-30 to 2022-07-13.

EUT operation mode: Transmitting

Test Result: Compliant.

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b mode				
Low	2412	19.35	15.87	30
Middle	2437	19.55	16.01	30
High	2462	19.08	15.56	30
802.11g mode				
Low	2412	22.30	13.60	30
Middle	2437	22.52	13.68	30
High	2462	22.22	13.30	30
802.11n HT20 mode				
Low	2412	22.19	13.48	30
Middle	2437	22.52	13.70	30
High	2462	21.99	13.23	30
802.11n HT40 mode				
Low	2422	21.86	12.84	30
Middle	2437	21.71	12.68	30
High	2452	21.29	12.35	30


Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
BLE 1M			
Low	2402	-3.99	30
Middle	2440	-3.08	30
High	2480	-5.34	30
BLE 2M			
Low	2402	-4.00	30
Middle	2440	-3.07	30
High	2480	-5.32	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa


The testing was performed by Cat Kang from 2022-07-12 to 2022-07-23.

EUT operation mode: Transmitting

Test Result: Compliant.


802.11b:

Band Edge, 2412MHz



Date: 13.JUL.2022 17:30:29


Band Edge, 2462MHz



Date: 12.JUL.2022 15:23:57


802.11g:

Band Edge, 2412MHz



Date: 13.JUL.2022 17:32:51


Band Edge, 2462MHz



Date: 12.JUL.2022 15:36:49


802.11n20:

Band Edge, 2412MHz



Date: 13.JUL.2022 17:34:19


Band Edge, 2462MHz



Date: 12.JUL.2022 15:55:17


802.11n40:

Band Edge, 2422MHz



Date: 13.JUL.2022 17:36:16


Band Edge, 2452MHz



Date: 12.JUL.2022 16:38:40


BLE 1M:

Band Edge, Left Side



Date: 23.JUL.2022 16:05:22


Band Edge, Right Side



Date: 23.JUL.2022 16:07:21


BLE 2M:

Band Edge, Left Side



Date: 23.JUL.2022 16:11:03

Band Edge, Right Side



Date: 23.JUL.2022 16:09:58


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa


The testing was performed by Cat Kang from 2022-06-30 to 2022-07-23

EUT operation mode: Transmitting


Test Result: Compliant.

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-4.41	≤ 8
Middle	2437	-5.40	≤ 8
High	2462	-5.51	≤ 8
802.11g mode			
Low	2412	-8.39	≤ 8
Middle	2437	-9.60	≤ 8
High	2462	-9.41	≤ 8
802.11n-HT20 mode			
Low	2412	-11.00	≤ 8
Middle	2437	-10.95	≤ 8
High	2462	-10.70	≤ 8
802.11n-HT40 mode			
Low	2422	-13.60	≤ 8
Middle	2437	-14.05	≤ 8
High	2452	-14.43	≤ 8


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1M			
Low	2402	-22.63	≤ 8
Middle	2440	-21.69	≤ 8
High	2480	-24.01	≤ 8
BLE 2M			
Low	2402	-25.96	≤ 8
Middle	2440	-25.02	≤ 8
High	2480	-27.32	≤ 8

802.11b mode:**Power Spectral Density, Low Channel**


Date: 1.JUL.2022 10:40:15

Power Spectral Density, Middle Channel


Date: 12.JUL.2022 15:16:57

Power Spectral Density, High Channel


Date: 12.JUL.2022 15:23:28

802.11g mode:**Power Spectral Density, Low Channel**


Date: 1.JUL.2022 10:58:02

Power Spectral Density, Middle Channel


Date: 12.JUL.2022 15:32:33

Power Spectral Density, High Channel


Date: 12.JUL.2022 15:36:20

802.11n20 mode:**Power Spectral Density, Low Channel**


Date: 1.JUL.2022 11:13:29

Power Spectral Density, Middle Channel


Date: 12.JUL.2022 15:50:37

Power Spectral Density, High Channel


Date: 12.JUL.2022 15:54:48

802.11n40 mode:**Power Spectral Density, Low Channel**


Date: 1.JUL.2022 11:32:10

Power Spectral Density, Middle Channel


Date: 23.JUL.2022 16:24:37

Power Spectral Density, High Channel


Date: 12.JUL.2022 16:55:57

BLE 1M:**Power Spectral Density, Low Channel**


Date: 30.JUN.2022 16:32:01

Power Spectral Density, Middle Channel


Date: 30.JUN.2022 16:35:19

Power Spectral Density, High Channel


Date: 30.JUN.2022 16:38:35

BLE 2M:**Power Spectral Density, Low Channel**

Date: 30.JUN.2022 16:43:31

Power Spectral Density, Middle Channel

Date: 30.JUN.2022 16:46:37

Power Spectral Density, High Channel

Date: 30.JUN.2022 16:49:43

******* END OF REPORT *******