

RF Test Report

Applicant : EmWicon Corporation

Product Type : Wi-Fi 5 802.11ac 2x2 dual-band Mini PCIe Module

Trade Name :  emwicon

Model Number : WMX6218

Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013

Received Date : Dec. 17, 2021

Test Period : Dec. 30, 2021 ~ Jan. 08, 2022

Issued Date : Feb. 10, 2022

Issued by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 334025, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
Frequency Range : 9 kHz to 40 GHz
Test Firm MRA designation number: TW0010

Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Revision History

Rev.	Issued Date	Revisions	Revised By
00	Feb. 10, 2022	Initial Issue	Nina Lin

Verification of Compliance

Applicant : EmWicon Corporation

Product Type : Wi-Fi 5 802.11ac 2x2 dual-band Mini PCIe Module

Trade Name : 

Model Number : WMX6218

FCC ID : 2A3G3-WMX6218

Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013

Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 334025, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190
 
Taiwan Accreditation Foundation accreditation number: 1330
<http://www.atl-lab.com.tw/e-index.htm>

A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By : _____
(Kai Yu Yang)

TABLE OF CONTENTS

1	General Information	5
1.1.	Summary of Test Result	5
1.2.	Measurement Uncertainty	6
2	EUT Description.....	7
3	Test Methodology.....	8
3.1.	Mode of Operation.....	8
3.2.	EUT Test Step.....	12
3.3.	Configuration of Test System Details.....	12
3.4.	Test Instruments	13
3.5.	Test Site Environment.....	16
4	Measurement Procedure.....	17
4.1.	AC Power Line Conducted Emission Measurement.....	17
4.2.	Radiated Emission Measurement.....	19
4.3.	Maximum Conducted Output Power Measurement.....	23
4.4.	6 dB RF Bandwidth Measurement.....	24
4.5.	Maximum Power Spectral Density Measurement	25
4.6.	Out of Band Conducted Emissions Measurement.....	26
4.7.	Antenna Measurement	27
5	Test Results	28
5.1	Conducted Emission.....	28
5.2	Conducted Test Results.....	30
5.3	Radiated Emission Measurement.....	119
Appendix A. Test Setup Photographs		

1 General Information

1.1. Summary of Test Result

Standard	Item	Result	Remark
15.207	AC Power Conducted Emission	PASS	-----
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	Max. Output Power	PASS	-----
15.247(a)(2)	6 dB RF Bandwidth	PASS	-----
15.247(e)	Maximum Power Spectral Density	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.203	Antenna Requirement	PASS	-----

Decision Rule

- ☒ Uncertainty is not included.
- ☐ Uncertainty is included.

Standard	Description
CFR47, Part 15, Subpart C	Intentional Radiators
ANSI C63. 10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
KDB 662911 D01 v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)

1.2. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Conducted Emission	150 kHz ~ 30 MHz	2.7 dB
Radiated Emission	9 kHz ~ 30 MHz	2.2 dB
	30 MHz ~ 1000 MHz	5.1 dB
	1000 MHz ~ 18000 MHz	5.2 dB
	18000 MHz ~ 26500 MHz	4.6 dB
	26500 MHz ~ 40000 MHz	4.6 dB
Conducted Output Power	1.1 dB	
RF Bandwidth	4.7 %	
Power Spectral Density	1.1 dB	

2 EUT Description

Applicant	EmWicon Corporation 7F.-5, No. 258, Liancheng Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)			
Product Type	Wi-Fi 5 802.11ac 2x2 dual-band Mini PCIe Module			
Trade Name				
Model Number	WMX6218			
FCC ID	2A3G3-WMX6218			
Operate Freq. Band	Frequency Range (MHz)	Modulation	Channel Bandwidth	Data Rate 400 / 800 GI (ns)
IEEE 802.11b	2412 ~ 2472	DSSS	20 MHz	Up to 11 Mbps
IEEE 802.11g	2412 ~ 2472	OFDM	20 MHz	Up to 54 Mbps
IEEE 802.11n 2.4 GHz 20 MHz	2412 ~ 2472	OFDM (64QAM)	20 MHz	Up to 144.4 Mbps
IEEE 802.11n 2.4 GHz 40 MHz	2422 ~ 2462	OFDM (64QAM)	40 MHz	Up to 300 Mbps
IEEE 802.11n 2.4 GHz 20 MHz	2412 ~ 2472	OFDM (256QAM)	20 MHz	Up to 173.4 Mbps
IEEE 802.11n 2.4 GHz 40 MHz	2422 ~ 2462	OFDM (256QAM)	40 MHz	Up to 400 Mbps
Antenna information	Antenna	Model Number	Type	Max. Gain (dBi)
	ANT-0 / ANT-1	1461530150	Dipole antenna	2.8
		ATD6251	Dipole antenna	2
		ATD6351	Dipole antenna	3
		ATD6551(*)	Dipole antenna	5
	GANT			5
	Directional Gain			8.01
Antenna Delivery	See section 3.1			
Operate Temp. Range	-40 ~ +85 ℃			
EUT Power Rating	DC 3.3 V			
Note : (*)This is the antenna worst.				

Frequency Band	Max. RF Output Power (W)
IEEE 802.11b	0.393
IEEE 802.11g	0.964
IEEE 802.11n 2.4 GHz 20 MHz(64QAM)	0.920
IEEE 802.11n 2.4 GHz 40 MHz(64QAM)	0.564
IEEE 802.11n 2.4 GHz 20 MHz(256QAM)	0.946
IEEE 802.11n 2.4 GHz 40 MHz(256QAM)	0.575

3 Test Methodology

3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Pre-Test mode
Mode 1: Transmit mode
Mode 2: IEEE 802.11b Continuous TX mode
Mode 3: IEEE 802.11g Continuous TX mode
Mode 4: IEEE 802.11n 2.4 GHz 20 MHz(64QAM) Continuous TX mode
Mode 5: IEEE 802.11n 2.4 GHz 40 MHz(64QAM) Continuous TX mode
Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode
Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode

Final-Test Mode
Mode 1: Transmit mode
Mode 2: IEEE 802.11b Continuous TX mode
Mode 3: IEEE 802.11g Continuous TX mode
Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode
Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

Test Mode	ANT-0	ANT-1	ANT-0+1
Mode 2	V	V	V
Mode 3	V	V	V
Mode 4	V	V	V
Mode 5	V	V	V
Mode 6	V	V	V
Mode 7	V	V	V


Test Mode	Antenna Delivery	Data Rate (Mbps)	Test Channel
Mode 2	2TX (CDD)	1	1, 6, 11, 12, 13
Mode 3	2TX (CDD)	6	1, 6, 11, 12, 13
Mode 4	2TX (CDD)	13	1, 6, 11, 12, 13
Mode 5	2TX (CDD)	27	3, 6, 9, 10, 11
Mode 6	2TX (CDD)	13	1, 6, 11, 12, 13
Mode 7	2TX (CDD)	27	3, 6, 9, 10, 11

Duty cycle


Test Mode	Frequency (MHz)	on time (ms)	on+off time (ms)	Duty cycle	Duty Factor (dB)	1/T Minimum VBW (kHz)
Mode 2	2412	20.000	20.000	1.000	0.000	0.010
Mode 3	2412	20.000	20.000	1.000	0.000	0.010
Mode 6	2412	20.000	20.000	1.000	0.000	0.010
Mode 7	2422	20.000	20.000	1.000	0.000	0.010

Duty Cycle Graphs


Mode 2: IEEE 802.11b Continuous TX mode




Mode 3: IEEE 802.11g Continuous TX mode



Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode



Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode




3.2. EUT Test Step

1.	Setup the EUT shown on "Configuration of Test System Details".
2.	Turn on the power of all equipment.
3.	Turn on TX function.
4.	EUT run test program.

3.3. Configuration of Test System Details

Radiated Emission & Conducted Emission



	Product	Manufacturer	Model Number	Serial Number	Power Cord
(1)	Mouse	ASUS	MOBTUOA	---	---
(2)	HDMI Cable	Avier	K48GHS	---	---
(3)	Monitor	ViewSonic	VA2719	---	---
(4)	Fixture	AAEON	UP SQUARED	---	---
(5)	Adapter	Jiangsu Sunward Electronics Technology Corp Ltd	AD36AM050600	---	---

3.4. Test Instruments

For Conducted Emission

Test Period: Jan. 08, 2022

Testing Engineer: Brian Lin

Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Test Receiver	R&S	ESCI	100367	May 21, 2021	1 year
☐	Test Receiver	R&S	ESCI	100722	Nov. 02, 2021	1 year
☐	Test Receiver	R&S	ESCI	101000	Nov. 26, 2021	1 year
☒	LISN	R&S	ENV216	101040	Mar. 29, 2021	1 year
☒	LISN	R&S	ENV216	101041	Apr. 08, 2021	1 year
☒	RF Cable	Woken	00100D1380194M	TE-02-03	May 28, 2021	1 year
☒	Software	EZ EMC	1.1.4.3	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request.

For Conducted

Test Period: Dec. 30, 2021 ~ Jan. 07, 2022

Testing Engineer: Brian Lin, Peter Shui

Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☐	Power Sensor	Anritsu	MA2411B	1126022	Sep. 03, 2021	1 year
☐	Power Meter	Anritsu	ML2495A	1135009	Sep. 03, 2021	1 year
☒	Power Sensor	Agilent	N1921A	MY45241957	Dec. 06, 2021	1 year
☒	Power Meter	Agilent	N1911A	MY45101619	Dec. 06, 2021	1 year
☒	Spectrum Analyzer (10 Hz~26.5 GHz)	Keysight	N9010B	MY59071418	Mar. 17, 2021	1 year
☐	Spectrum Analyzer (9 kHz~26.5 GHz)	Agilent	N9010A	MY48030518	Jul. 23, 2021	1 year
☐	Spectrum Analyzer (20 Hz~26.5 GHz)	Agilent	N9020A	US47520902	Sep. 09, 2021	1 year
☐	Spectrum Analyzer (3 Hz~50 GHz)	Agilent	N9030A	MY53120541	Jan. 08, 2021 Jan. 05, 2022	1 year
☐	Temperature & Humidity Chamber	TAICHY	MHU-225LA	980729	Mar. 30, 2021	1 year
☐	Signal Generator	Keysight	N5182B	MY53052569	Apr. 20, 2021	1 year
☐	Signal Generator	Keysight	N5182BX07	MY59360221	Apr. 20, 2021	1 year
☐	Bluetooth Tester	R&S	CBT	100350	Mar. 17, 2021	2 years
☐	Wireless Connectivity Tester	R&S	CMW270	102208	Jun. 02, 2021	1 year
☐	Power Supply	KEITHLEY	2303	4045290	Feb. 01, 2021	1 year
☐	RF Communication Test Set	HP	8920A	3344A03297	Aug. 10, 2021	1 year

Note: N.C.R. = No Calibration Request.

For Radiated Emissions

Test Period: Jan. 04 ~ Jan. 06, 2022

Testing Engineer: Marc Yeh, Pink Li

Radiation test sites		Semi Anechoic Room				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☐	Spectrum Analyzer (10 Hz~44 GHz)	Keysight	N9010A	MY52221312	Jan. 18, 2021	1 year
☐	Spectrum Analyzer (3 Hz~50 GHz)	Agilent	N9030A	MY53120541	Jan. 08, 2021	1 year
☒	Spectrum Analyzer (2 Hz~50 GHz)	Keysight	N9030B	MY57143537	Apr. 19, 2021	1 year
☒	Amplifier (100 kHz~1.3 GHz)	Agilent	8447D	2944A11119	Jan. 15, 2021	1 year
☐	Amplifier (100 kHz~1.3 GHz)	Agilent	8447D	2944A10961	Jul. 06, 2021	1 year
☐	Broadband Amplifier (100 kHz~1 GHz)	Titan	T0910E00014330A1F	001	Jul. 23, 2021	1 year
☐	Amplifier (1 GHz~26.5 GHz)	Agilent	8449B	3008A02237	Oct. 21, 2021	1 year
☒	Broadband Amplifier (1 GHz~26.5 GHz)	Titan	T0912E01263025A1F	002	Jul. 26, 2021	1 year
☐	Preamplifier (26.5 GHz~40 GHz)	EMCI	EMC2654045	980028	Aug. 19, 2021	1 year
☒	Loop Antenna (9 kHz~30 MHz)	COM-POWER CORPORATION	AL-130	121014	Apr. 07, 2021	1 year
☒	Trilog Broadband Antenna (30 kHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	01146	Jul. 19, 2021	1 year
☐	Trilog Broadband Antenna (30 kHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	416	Nov. 17, 2021	1 year
☒	Broadband Horn Antenna (1 GHz~18 GHz)	Schwarzbeck Mess-Elektronik	9120D	02207	Jul. 09, 2021	1 year
☐	Broadband Horn Antenna (1 GHz~18 GHz)	Schwarzbeck Mess-Elektronik	9120D	9120D-550	Aug. 24, 2021	1 year
☒	Broadband Horn Antenna (18 GHz~40 GHz)	Schwarzbeck Mess-Elektronik	9170	9170-320	Aug. 24, 2021	1 year
☐	Horn Antenna (18 GHz~40 GHz)	ETS	3116	00086467	Dec. 03, 2021	1 year
☐	RF Cable	EMCI	EMC104-N-N-6000	TE01-1	Feb. 19, 2021	1 year
☐	Microwave Cable	EMCI	EMC104-SM-SM-13000	170814	Feb. 19, 2021	1 year
☐	Microwave Cable	EMCI	EMC102-KM-KM-14000	151001	Feb. 19, 2021	1 year

Note: N.C.R. = No Calibration Request.

For Radiated Emissions
Test Period: Jan. 04 ~ Jan. 06, 2022
Testing Engineer: Marc Yeh, Pink Li

Radiation test sites		Semi Anechoic Room				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Coaxial Cable	Titan	T0710AT327A10A 100	J11005	Aug. 06, 2021	1 year
☒	Coaxial Cable	Titan	T0710AT327A10A 900	J11004	Aug. 06, 2021	1 year
☒	Coaxial Cable	Titan	CFD400NL-LW	001	Aug. 06, 2021	1 year
☐	Bluetooth Tester	R&S	CBT	100350	Mar. 17, 2021	2 years
☐	Wireless Connectivity Tester	R&S	CMW270	102208	Jun. 02, 2021	1 year
☐	Power Supply	KEITHLEY	2303	4045290	Feb. 01, 2021	1 year
☒	Software	EZ EMC	1.1.4.4	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request.

3.5. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	20-30
Humidity (%RH)	25-75	45-75


4 Measurement Procedure

4.1. AC Power Line Conducted Emission Measurement

■ Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

■ Test Setup



■ Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance with 50 ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40 cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80 cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12 mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150 kHz to 30 MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8 m from the AMN. If the mains power cable is longer than 1 m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4 m. All of interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1 m. All $50\ \Omega$ ports of the LISN shall be resistively terminated into $50\ \Omega$ loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.

4.2. Radiated Emission Measurement

■ Limit


According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	$2400 / F$ (kHz)	300
0.490 – 1.705	$24000 / F$ (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3


** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

■ Setup


9 kHz ~ 30 MHz



Below 1 GHz



Above 1 GHz



■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements and 10 Hz for average measurements when Duty cycle >0.98 / $1/T$ for average measurements when Duty cycle <0.98 . A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna was used in frequencies 1 –26.5 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field is intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) +AF (dBuV) +CL (dBuV)-Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV)-Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30 dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.


4.3. Maximum Conducted Output Power Measurement

■ Limit

For systems using digital modulation in the 2400-2483.5 MHz, the limit for maximum output power is 30 dBm.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Test Setup



■ Test Procedure

The testing follows the Measurement Procedure of ANSI C63.10:2013 section 11.9.2.3.2 Method AVGPM.


The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor.

4.4. 6 dB RF Bandwidth Measurement

■ Limit

6 dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

■ Test Setup



■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10:2013 section 11.8.2 option2 for compliance to FCC 47CFR 15.247 requirements.

6 dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels (Channel low, middle, high)

4.5. Maximum Power Spectral Density Measurement

■ Limit


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

CDD mode:

Directional Gain = $10 \cdot \log\{[10^{(G1/20)} + 10^{(G2/20)} + \dots + 10^{(Gn/20)}]^2 / NANT\} = 8.01 \text{ dBi} > 6 \text{ dBi}$

power spectral density limit shall be reduced = $8 - 2.01 = 5.99 \text{ dBm/3 kHz}$

■ Test Setup



■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10:2013 section 11.10.2 Method PKPSD for compliance to FCC 47CFR 15.247 requirements.


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.6. Out of Band Conducted Emissions Measurement

■ Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

■ Test Setup



■ Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function. All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels.

4.7. Antenna Measurement

■ Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Antenna Description

See section 2 – antenna information.

■ Directional Gain Calculated

For Maximum Conducted Output Power

$$\text{Directional Gain} = 10 \cdot \log\{[10^{(G1/10)} + 10^{(G2/10)} + \dots + 10^{(Gn/10)}] / NANT\}$$

Operate Freq. Band	Directional Gain (dBi)
IEEE 802.11b	5
IEEE 802.11g	5
IEEE 802.11n 2.4 GHz 20 MHz(64QAM)	5
IEEE 802.11n 2.4 GHz 40 MHz(64QAM)	5
IEEE 802.11n 2.4 GHz 20 MHz(256QAM)	5
IEEE 802.11n 2.4 GHz 40 MHz(256QAM)	5

For Maximum Power Density


$$\text{Directional Gain} = 10 \cdot \log\{[10^{(G1/20)} + 10^{(G2/20)} + \dots + 10^{(Gn/20)}]^2 / NANT\}$$

Operate Freq. Band	Directional Gain (dBi)
IEEE 802.11b	8.01
IEEE 802.11g	8.01
IEEE 802.11n 2.4 GHz 20 MHz(64QAM)	8.01
IEEE 802.11n 2.4 GHz 40 MHz(64QAM)	8.01
IEEE 802.11n 2.4 GHz 20 MHz(256QAM)	8.01
IEEE 802.11n 2.4 GHz 40 MHz(256QAM)	8.01

5 Test Results

5.1 Conducted Emission


Standard:	FCC Part 15.247	Line:	L1
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Mode:	Mode 1	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1500	43.16	21.10	9.74	52.90	30.84	66.00	56.00	-13.10	-25.16	Pass
2	0.1620	42.92	20.98	9.74	52.66	30.72	65.36	55.36	-12.70	-24.64	Pass
3	0.1700	41.79	20.86	9.74	51.53	30.60	64.96	54.96	-13.43	-24.36	Pass
4	0.1940	44.77	20.89	9.74	54.51	30.63	63.86	53.86	-9.35	-23.23	Pass
5	0.2020	40.59	17.55	9.74	50.33	27.29	63.53	53.53	-13.20	-26.24	Pass
6	0.7140	31.89	19.74	9.75	41.64	29.49	56.00	46.00	-14.36	-16.51	Pass
7	0.7700	32.74	20.20	9.75	42.49	29.95	56.00	46.00	-13.51	-16.05	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).
2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15.247	Line:	N
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Mode:	Mode 1	Temp.(°C)/Hum.(%RH):	26(°C)/60 %RH
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1500	43.42	21.58	9.74	53.16	31.32	66.00	56.00	-12.84	-24.68	Pass
2	0.1820	45.36	21.08	9.73	55.09	30.81	64.39	54.39	-9.30	-23.58	Pass
3	0.1940	44.89	21.15	9.73	54.62	30.88	63.86	53.86	-9.24	-22.98	Pass
4	0.7380	35.61	23.77	9.75	45.36	33.52	56.00	46.00	-10.64	-12.48	Pass
5	0.8220	27.74	14.66	9.75	37.49	24.41	56.00	46.00	-18.51	-21.59	Pass
6	1.2060	29.58	14.52	9.77	39.35	24.29	56.00	46.00	-16.65	-21.71	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).
2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

5.2 Conducted Test Results

Maximum Conducted Output Power Measurement

Test Mode	Frequency (MHz)	RF Power setting in Test Software		Test Software Version
		ANT-0	ANT-1	
Mode 2	2412	100.0	110.0	RTL8822CE MP Version 0.000.1020.2018
	2437	107.0	117.0	
	2462	98.0	108.0	
	2467	78.0	88.0	
	2472	57.0	71.0	
Mode 3	2412	62.0	68.0	
	2437	93.0	99.0	
	2462	65.0	70.0	
	2467	54.0	60.0	
	2472	40.0	49.0	
Mode 4	2412	64.0	68.0	
	2437	94.0	100.0	
	2462	66.0	72.0	
	2467	55.0	61.0	
	2472	41.0	50.0	
Mode 5	2422	57.0	64.0	
	2437	75.0	81.0	
	2452	65.0	71.0	
	2457	53.0	59.0	
	2462	39.0	47.0	
Mode 6	2412	64.0	68.0	
	2437	94.0	100.0	
	2462	66.0	72.0	
	2467	55.0	61.0	
	2472	41.0	50.0	
Mode 7	2422	57.0	64.0	
	2437	75.0	81.0	
	2452	65.0	71.0	
	2457	53.0	59.0	
	2462	39.0	47.0	

ANT-0							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 2	2412	1 M	19.73	0.094	21.87	0.154	≤ 30
	2437		20.83	0.121	22.91	0.195	≤ 30
	2462		19.31	0.085	21.29	0.135	≤ 30
	2467		14.44	0.028	16.71	0.047	≤ 30
	2472		9.96	0.010	12.06	0.016	≤ 30
Mode 3	2412	6 M	13.93	0.025	22.86	0.193	≤ 30
	2437		20.87	0.122	27.00	0.501	≤ 30
	2462		13.89	0.024	22.64	0.184	≤ 30
	2467		10.96	0.012	19.91	0.098	≤ 30
	2472		8.03	0.006	16.79	0.048	≤ 30
Mode 4	2412	13 M	14.10	0.026	22.93	0.196	≤ 30
	2437		20.86	0.122	26.62	0.459	≤ 30
	2462		13.82	0.024	22.79	0.190	≤ 30
	2467		11.00	0.013	19.97	0.099	≤ 30
	2472		7.89	0.006	16.63	0.046	≤ 30
Mode 5	2422	27 M	12.80	0.019	22.02	0.159	≤ 30
	2437		16.86	0.049	24.46	0.279	≤ 30
	2452		14.10	0.026	22.34	0.171	≤ 30
	2457		10.93	0.012	18.92	0.078	≤ 30
	2462		7.43	0.006	15.98	0.040	≤ 30
Mode 6	2412	13 M	14.19	0.026	22.98	0.199	≤ 30
	2437		20.90	0.123	26.73	0.471	≤ 30
	2462		13.93	0.025	22.81	0.191	≤ 30
	2467		11.05	0.013	20.08	0.102	≤ 30
	2472		8.03	0.006	16.75	0.047	≤ 30
Mode 7	2422	27 M	12.83	0.019	22.04	0.160	≤ 30
	2437		16.91	0.049	24.60	0.288	≤ 30
	2452		14.13	0.026	22.47	0.177	≤ 30
	2457		10.98	0.013	19.03	0.080	≤ 30
	2462		7.46	0.006	16.05	0.040	≤ 30

Note: The relevant measured result has the offset with cable loss already.

ANT-1							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 2	2412	1 M	19.65	0.092	21.62	0.145	≤ 30
	2437		21.01	0.126	22.95	0.197	≤ 30
	2462		19.02	0.080	21.01	0.126	≤ 30
	2467		14.18	0.026	16.11	0.041	≤ 30
	2472		9.92	0.010	11.88	0.015	≤ 30
Mode 3	2412	6 M	13.99	0.025	22.81	0.191	≤ 30
	2437		20.98	0.125	26.66	0.463	≤ 30
	2462		13.85	0.024	22.87	0.194	≤ 30
	2467		10.92	0.012	19.61	0.091	≤ 30
	2472		8.04	0.006	16.72	0.047	≤ 30
Mode 4	2412	13 M	13.99	0.025	22.77	0.189	≤ 30
	2437		20.82	0.121	26.63	0.460	≤ 30
	2462		13.89	0.024	22.91	0.195	≤ 30
	2467		10.90	0.012	19.93	0.098	≤ 30
	2472		7.98	0.006	16.78	0.048	≤ 30
Mode 5	2422	27 M	12.69	0.019	21.85	0.153	≤ 30
	2437		16.81	0.048	24.53	0.284	≤ 30
	2452		14.04	0.025	22.49	0.177	≤ 30
	2457		10.74	0.012	18.83	0.076	≤ 30
	2462		7.23	0.005	15.93	0.039	≤ 30
Mode 6	2412	13 M	14.08	0.026	22.90	0.195	≤ 30
	2437		20.94	0.124	26.76	0.474	≤ 30
	2462		14.01	0.025	22.97	0.198	≤ 30
	2467		10.99	0.013	19.99	0.100	≤ 30
	2472		8.11	0.006	16.81	0.048	≤ 30
Mode 7	2422	27 M	12.79	0.019	21.98	0.158	≤ 30
	2437		16.87	0.049	24.57	0.286	≤ 30
	2452		14.18	0.026	22.59	0.182	≤ 30
	2457		10.88	0.012	18.91	0.078	≤ 30
	2462		7.36	0.005	15.95	0.039	≤ 30

Note: The relevant measured result has the offset with cable loss already.

ANT-0+1							
Test Mode	Frequency (MHz)	Data Rate	Average Output Power		Peak Output Power		
			Measurement Results		Measurement Results		Limit
			dBm	W	dBm	W	dBm
Mode 2	2412	1 M	22.70	0.186	24.76	0.299	≤ 30
	2437		23.93	0.247	25.94	0.393	≤ 30
	2462		22.18	0.165	24.16	0.261	≤ 30
	2467		17.32	0.054	19.43	0.088	≤ 30
	2472		12.95	0.020	14.98	0.031	≤ 30
Mode 3	2412	6 M	16.97	0.050	25.85	0.385	≤ 30
	2437		23.94	0.248	29.84	0.964	≤ 30
	2462		16.88	0.049	25.77	0.378	≤ 30
	2467		13.95	0.025	22.77	0.189	≤ 30
	2472		11.05	0.013	19.77	0.095	≤ 30
Mode 4	2412	13 M	17.06	0.051	25.86	0.385	≤ 30
	2437		23.85	0.243	29.64	0.920	≤ 30
	2462		16.87	0.049	25.86	0.385	≤ 30
	2467		13.96	0.025	22.96	0.198	≤ 30
	2472		10.95	0.012	19.72	0.094	≤ 30
Mode 5	2422	27 M	15.76	0.038	24.95	0.313	≤ 30
	2437		19.85	0.097	27.51	0.564	≤ 30
	2452		17.08	0.051	25.43	0.349	≤ 30
	2457		13.85	0.024	21.89	0.155	≤ 30
	2462		10.34	0.011	18.97	0.079	≤ 30
Mode 6	2412	13 M	17.15	0.052	25.95	0.394	≤ 30
	2437		23.93	0.247	29.76	0.946	≤ 30
	2462		16.98	0.050	25.90	0.389	≤ 30
	2467		14.03	0.025	23.05	0.202	≤ 30
	2472		11.08	0.013	19.79	0.095	≤ 30
Mode 7	2422	27 M	15.82	0.038	25.02	0.318	≤ 30
	2437		19.90	0.098	27.60	0.575	≤ 30
	2452		17.17	0.052	25.54	0.358	≤ 30
	2457		13.94	0.025	21.98	0.158	≤ 30
	2462		10.42	0.011	19.01	0.080	≤ 30

Note: The relevant measured result has the offset with cable loss already.

6 dB RF Bandwidth Measurement

ANT-0			
Test Mode	Frequency (MHz)	Measurement (kHz)	Limit (kHz)
Mode 2	2412	10166	≥ 500
	2437	10166	≥ 500
	2462	10167	≥ 500
	2467	10171	≥ 500
	2472	10168	≥ 500
Mode 3	2412	16450	≥ 500
	2437	16460	≥ 500
	2462	16450	≥ 500
	2467	16460	≥ 500
	2472	16530	≥ 500
Mode 6	2412	17640	≥ 500
	2437	17650	≥ 500
	2462	17640	≥ 500
	2467	17650	≥ 500
	2472	17700	≥ 500
Mode 7	2422	36460	≥ 500
	2437	36450	≥ 500
	2452	36440	≥ 500
	2457	36450	≥ 500
	2462	36470	≥ 500

ANT-1			
Test Mode	Frequency (MHz)	Measurement (kHz)	Limit (kHz)
Mode 2	2412	10169	≥ 500
	2437	10167	≥ 500
	2462	10165	≥ 500
	2467	10169	≥ 500
	2472	10169	≥ 500
Mode 3	2412	16450	≥ 500
	2437	16430	≥ 500
	2462	16450	≥ 500
	2467	16440	≥ 500
	2472	16490	≥ 500
Mode 6	2412	17650	≥ 500
	2437	17650	≥ 500
	2462	17640	≥ 500
	2467	17650	≥ 500
	2472	17690	≥ 500
Mode 7	2422	36460	≥ 500
	2437	36450	≥ 500
	2452	36450	≥ 500
	2457	36450	≥ 500
	2462	36460	≥ 500

■ Test Graphs

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz



Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2467 MHz



2472 MHz



Mode 3: IEEE 802.11g Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz



Mode 3: IEEE 802.11g Continuous TX mode_ANT-0

2467 MHz



2472 MHz



Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz




Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-0

2467 MHz



2472 MHz




Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-0

2422 MHz



2437 MHz



2452 MHz



Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-0

2457 MHz



2462 MHz



Mode 2: IEEE 802.11b Continuous TX mode_ANT-1

2412 MHz



2437 MHz



2462 MHz



Mode 2: IEEE 802.11b Continuous TX mode_ANT-1

2467 MHz



2472 MHz



Mode 3: IEEE 802.11g Continuous TX mode_ANT-1


2412 MHz



2437 MHz



2462 MHz



Mode 3: IEEE 802.11g Continuous TX mode_ANT-1

2467 MHz



2472 MHz



Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-1

2412 MHz



2437 MHz



2462 MHz



Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-1

2467 MHz



2472 MHz



Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-1

2422 MHz



2437 MHz



2452 MHz



Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-1

2457 MHz



2462 MHz



Maximum Power Spectral Density Measurement

ANT-0			
Test Mode	Frequency (MHz)	Measurement (dBm/3 kHz)	Limit (dBm/ 3 kHz)
Mode 2	2412	-10.720	≤ 5.99
	2437	-10.000	≤ 5.99
	2462	-11.560	≤ 5.99
	2467	-15.740	≤ 5.99
	2472	-20.380	≤ 5.99
Mode 3	2412	-14.450	≤ 5.99
	2437	-7.850	≤ 5.99
	2462	-14.580	≤ 5.99
	2467	-17.340	≤ 5.99
	2472	-20.790	≤ 5.99
Mode 6	2412	-13.730	≤ 5.99
	2437	-7.570	≤ 5.99
	2462	-14.150	≤ 5.99
	2467	-16.910	≤ 5.99
	2472	-19.570	≤ 5.99
Mode 7	2422	-16.790	≤ 5.99
	2437	-13.330	≤ 5.99
	2452	-16.120	≤ 5.99
	2457	-18.920	≤ 5.99
	2462	-22.250	≤ 5.99

ANT-1			
Test Mode	Frequency (MHz)	Measurement (dBm/3 kHz)	Limit (dBm/ 3 kHz)
Mode 2	2412	-10.890	≤ 5.99
	2437	-10.190	≤ 5.99
	2462	-12.370	≤ 5.99
	2467	-16.810	≤ 5.99
	2472	-20.740	≤ 5.99
Mode 3	2412	-14.600	≤ 5.99
	2437	-8.610	≤ 5.99
	2462	-15.190	≤ 5.99
	2467	-17.940	≤ 5.99
	2472	-20.840	≤ 5.99
Mode 6	2412	-14.400	≤ 5.99
	2437	-8.010	≤ 5.99
	2462	-14.570	≤ 5.99
	2467	-17.400	≤ 5.99
	2472	-19.940	≤ 5.99
Mode 7	2422	-16.850	≤ 5.99
	2437	-13.300	≤ 5.99
	2452	-15.820	≤ 5.99
	2457	-18.750	≤ 5.99
	2462	-22.700	≤ 5.99

ANT-0+1			
Test Mode	Frequency (MHz)	Measurement (dBm/3 kHz)	Limit (dBm/ 3 kHz)
Mode 2	2412	-7.794	≤ 5.99
	2437	-7.084	≤ 5.99
	2462	-8.936	≤ 5.99
	2467	-13.232	≤ 5.99
	2472	-17.546	≤ 5.99
Mode 3	2412	-11.514	≤ 5.99
	2437	-5.203	≤ 5.99
	2462	-11.864	≤ 5.99
	2467	-14.619	≤ 5.99
	2472	-17.805	≤ 5.99
Mode 6	2412	-11.042	≤ 5.99
	2437	-4.774	≤ 5.99
	2462	-11.345	≤ 5.99
	2467	-14.138	≤ 5.99
	2472	-16.741	≤ 5.99
Mode 7	2422	-13.810	≤ 5.99
	2437	-10.305	≤ 5.99
	2452	-12.957	≤ 5.99
	2457	-15.824	≤ 5.99
	2462	-19.459	≤ 5.99


■ Test Graphs

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz




Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2467 MHz




2472 MHz




Mode 3: IEEE 802.11g Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz




Mode 3: IEEE 802.11g Continuous TX mode_ANT-0

2467 MHz




2472 MHz




Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-0


2412 MHz



2437 MHz




2462 MHz




Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-0

2467 MHz



2472 MHz




Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-0


2422 MHz



2437 MHz



2452 MHz




Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-0

2457 MHz



2462 MHz




Mode 2: IEEE 802.11b Continuous TX mode_ANT-1


2412 MHz



2437 MHz



2462 MHz




Mode 2: IEEE 802.11b Continuous TX mode_ANT-1

2467 MHz




2472 MHz




Mode 3: IEEE 802.11g Continuous TX mode_ANT-1


2412 MHz



2437 MHz



2462 MHz




Mode 3: IEEE 802.11g Continuous TX mode_ANT-1

2467 MHz




2472 MHz




Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-1


2412 MHz



2437 MHz




2462 MHz




Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-1

2467 MHz



2472 MHz




Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-1


2422 MHz



2437 MHz



2452 MHz




Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-1

2457 MHz



2462 MHz




Out of Band Conducted Emissions Measurement

■ Test Graphs


Reference level

Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz



Mode 2: IEEE 802.11b Continuous TX mode_ANT-0

2467 MHz



2472 MHz



Mode 3: IEEE 802.11g Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz




Mode 3: IEEE 802.11g Continuous TX mode_ANT-0

2467 MHz



2472 MHz



Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-0

2412 MHz



2437 MHz



2462 MHz




Mode 6: IEEE 802.11n 2.4 GHz 20 MHz(256QAM) Continuous TX mode_ANT-0

2467 MHz



2472 MHz



Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-0


2422 MHz



2437 MHz



2452 MHz




Mode 7: IEEE 802.11n 2.4 GHz 40 MHz(256QAM) Continuous TX mode_ANT-0

2457 MHz



2462 MHz




Mode 2: IEEE 802.11b Continuous TX mode_ANT-1

2412 MHz



2437 MHz



2462 MHz



Mode 2: IEEE 802.11b Continuous TX mode_ANT-1

2467 MHz



2472 MHz

