

Test Report

Report No.: MTi220418013-03E2

Date of issue: 2022-07-18

Applicant: Dongguan DBK Energy Technology Co., Ltd

Product: Magnetic Wireless Power

Model(s): MS-P3

FCC ID: 2A3GQ-MSP3

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Contents

1 General Description	5
1.1 Description of the EUT	5
1.2 Description of test modes	6
1.3 Description of support units	7
2 Test facilities and accreditations.....	8
2.1 Test laboratory	8
3 List of test equipment	9
4 Test result	10
4.2 Test setup	11
4.3 Test Procedures.....	12
4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01	13
4.5 Test results	14
Photographs of the Test Setup.....	18
Photographs of the EUT.....	18

Test Result Certification

Applicant:	Dongguan DBK Energy Technology Co., Ltd
Address:	No. 252, Zhangmutou Section, Dongshen Rd., Zhangmutou Town, Dongguan City, Guangdong Province, China
Manufacturer:	Dongguan DBK Energy Technology Co., Ltd
Address:	No. 252, Zhangmutou Section, Dongshen Rd., Zhangmutou Town, Dongguan City, Guangdong Province, China

Product description

Product name:	Magnetic Wireless Power
Trademark:	imuto
Model name:	MS-P3
Serial Model:	N/A
Standards:	FCC CFR 47 PART 1, § 1.1310
Test method:	KDB 680106 v03r01

Date of Test

Date of test:	2022-06-08 ~ 2022-07-17
Test result:	Pass

Test Engineer :



(Yanice Xie)

Reviewed By :



(Leon Chen)

Approved By :



(Tom Xue)

1 General Description

1.1 Description of the EUT

Product name:	Magnetic Wireless Power
Model name:	MS-P3
Series Model:	N/A
Model difference:	N/A
Electrical rating:	Input: USB-C DC 5V 2A Output: USB-C DC 5V 2.4A Wireless Output: 10W Total Output: 12W(Max) Capacity: 3.8V 5000mAh 19Wh
Accessories:	Cable: USB-A & C to USB-C cable
Hardware version:	V1.1
Software version:	V1.1
Test sample number:	MTi220418013-03-S0001
RF specification:	
Operation frequency:	115 kHz – 205 kHz
Modulation type:	ASK
Antenna type:	Coil Antenna

1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode 1	Charging + Wireless charger(5W)
Mode 2	Wireless charger(5W)
Mode 3	Wireless charger (7.5W)
Mode 4	Wireless charger(10W)
Mode 5	Stand-by

The test data only show worst test mode: Mode 4

1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
Mobile phone	iPhone 12 Mini	/	Apple
Mobile phone	S9	/	Samsung
Adapter	/	/	Xiaomi

Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Test facilities and accreditations

2.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

3 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E115	Electric and Magnetic Field Probe – Analyzer	Narda	EHP-200A	101166	2022/05/05	2023/05/04

4 Test result

4.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30

f = frequency in MHz

* = Plane-wave equivalent power density


Note 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

Note 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.




4.2 Test setup

For mobile exposure conditions:



For portable exposure conditions:



4.3 Test Procedures

For mobile exposure conditions:

- a. The RF exposure test was performed in anechoic chamber.
- b. E and H-field measurements should be made with the center of the probe at a distance of 15 cm surrounding the EUT and 20 cm above the top surface of the primary/client pair.
- c. The highest emission level was recorded and compared with limit.
- d. The EUT was measured according to the dictates of KDB 680106 v03r01.

For portable exposure conditions:

- a. The RF exposure test was performed in anechoic chamber.
- b. Perform H-field measurements for each edge/top surface of the host/client pair at every 2 cm, starting from as close as possible out to 20 cm
- c. The highest emission level was recorded and compared with limit.

4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01

Requirement	Device
1. Power transfer frequency is less than 1 MHz.	Yes. The operating frequencies: 115 kHz – 205 kHz
2. Output power from each primary coil is less than or equal to 15 watts	Yes. The maximum output power: 10W
3. The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes. The EUT have one source primary coil.
4. Client device is placed directly in contact with the transmitter.	Yes. The client device is placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes. Mobile exposure conditions only.
6. The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes. See the test result in item 4.5.

4.5 Test results

For portable exposure condition:

Note: operating modes with client device (1 %, 50%, 99% battery status of client device) have been test, only show the data of worst case of 1% battery status of client device.

Test condition 1: Mode 4 operating mode with client device (1 % battery status of client device)

-test distance: 0cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.6902	1.63	43.85%
	Left	0.2102		
	Right	0.4203		
	Front	0.2977		
	Rear	0.2128		
	Bottom	0.7147		

Test condition 2: Mode 4 operating mode with client device (1 % battery status of client device)

-test distance: 2cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.3153	1.63	31.49%
	Left	0.5133		
	Right	0.2378		
	Front	0.3243		
	Rear	0.1270		
	Bottom	0.3102		



Test condition 3: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 4cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.2464	1.63	22.95%
	Left	0.3741		
	Right	0.1865		
	Front	0.2740		
	Rear	0.0977		
	Bottom	0.2647		

Test condition 4: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 6cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0689	1.63	16.34%
	Left	0.1213		
	Right	0.0671		
	Front	0.2664		
	Rear	0.0659		
	Bottom	0.0993		

Test condition 5: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 8cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0518	1.63	8.44%
	Left	0.0859		
	Right	0.0532		
	Front	0.1376		
	Rear	0.0495		
	Bottom	0.0769		



Test condition 6: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 10cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0513	1.63	5.93%
	Left	0.0604		
	Right	0.0495		
	Front	0.0967		
	Rear	0.0540		
	Bottom	0.0563		

Test condition 7: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 12cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0482	1.63	3.54%
	Left	0.0540		
	Right	0.0482		
	Front	0.0577		
	Rear	0.0513		
	Bottom	0.0513		

Test condition 8: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 14cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0482	1.63	3.24%
	Left	0.0482		
	Right	0.0495		
	Front	0.0528		
	Rear	0.0502		
	Bottom	0.0474		



Test condition 9: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 16cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0495	1.63	3.31%
	Left	0.0513		
	Right	0.0498		
	Front	0.0495		
	Rear	0.0540		
	Bottom	0.0493		

Test condition 10: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 18cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0495	1.63	3.24%
	Left	0.0528		
	Right	0.0482		
	Front	0.0495		
	Rear	0.0498		
	Bottom	0.0513		

Test condition 11: Mode 4 operating mode with client device (1 % battery status of client device)

- Test distance 20cm

Antenna	Probe Position	H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)
1	Z axis	0.0501	1.63	3.24%
	Left	0.0528		
	Right	0.0482		
	Front	0.0495		
	Rear	0.0513		
	Bottom	0.0495		

Photographs of the Test Setup

See the Appendix - Test Setup Photos.

Photographs of the EUT

See the Appendix - EUT Photos.

----End of Report----