



Aibo Standard Technology (Shenzhen) Co., Ltd.

101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +(86) 0755 85250797

E-mail: Aibonorm@aibonorm.com

Website: www.Aibonorm.com

FCC TEST REPORT

Report No.....: AB25060016FW03

FCC ID.....: **2A3GU-GS2PLUS**

Applicant.....: tempmate GmbH

Address.....: Wannenäckerstrasse 41, 74078 Heilbronn, Germany

Manufacturer.....: tempmate GmbH

Address.....: Wannenäckerstrasse 41, 74078 Heilbronn, Germany

Product Name.....: tempmate-GS2+

Trade Mark.....: tempmate

Test Model.....: tempmate-GS2+ TH

Additional Model(s).....: See section 1.1(page 6)

Standard.....: FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1

Date of Receipt.....: 2025.06.05

Date of Issue.....: 2025.07.17

Test Result.....: Pass

Compiled by:
(Printed Name + Signature)

Huaijie Li

Huaijie Li

Supervised by:
(Printed Name + Signature)

Jay Liu

Jay Liu

Approved by:
(Printed Name + Signature)

Mic Cheng

Mic Cheng

Testing Laboratory Name.....: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address.....: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Aibo. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to Aibo within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

FCC TEST REPORT

Test Report No.: AB25060016FW03	<u>2025.07.17</u> Date of issue
--	------------------------------------

EUT.....	: tempmate-GS2+
Test Model.....	: tempmate-GS2+ TH
Applicant.....	: tempmate GmbH
Address.....	: Wannenäckerstrasse 41, 74078 Heilbronn, Germany
Telephone.....	: 49-7131-6354-121
Fax.....	: /
Manufacturer.....	: tempmate GmbH
Address.....	: Wannenäckerstrasse 41, 74078 Heilbronn, Germany
Telephone.....	: 49-7131-6354-121
Fax.....	: /
Factory.....	: tempmate GmbH
Address.....	: Wannenäckerstrasse 41, 74078 Heilbronn, Germany
Telephone.....	: 49-7131-6354-121
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



FCC ID: 2A3GU-GS2PLUS

Report No.: AB25060016FW02

REPORT VERSION

Version No.	Issue Date	Description
01	2025.07.17	Initial Issue

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. GENERAL DESCRIPTION OF EUT	5
1.2. DESCRIPTION OF TEST FACILITY	6
2. RF EXPOSURE EVALUATION	7
2.1 LIMIT	7
2.2 EVALUATION RESULT	8

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name:	tempmate-GS2+	
Trade Mark:	tempmate	
Test Model:	tempmate-GS2+ TH	
Additional Model(s):	tempmate-GS2+ T,tempmate-GS2+ TE,tempmate-GS2+ TH(Non Li),tempmate-GS2+ T(Non Li),tempmate-GS2+ TE(Non Li)	
Model Difference:	All models are the same circuit and RF module, except the model name.	
Hardware Version:	V59MR41	
Software Version:	GS2LH_V3.1.2	
Power Supply:	DC 3.7V by battery(2400mAh) or DC 5V 1A from AC/DC adapter	
EUT Supports Function: (Provided by the customer)	E-UTRA Bands:	LTE Band 2/4/5/7/38/40/41
Test Sample(s) Number:	AB25060016-01 (Engineer Sample) AB25060016-02 (Normal Sample)	
Radio Specification Subject to this Report		
2G Band		
Support Networks:	GPRS, EDGE	
Frequency Range:	GSM 850:	824.2MHz~848.8MHz
	GSM 1900:	1850.2MHz~1909.8MHz
Modulation Type:	GPRS:	GMSK
	EDGE:	GMSK, 8PSK
GPRS/EDGE Class:	Class 12	
Antenna Type:	Integral Antenna	
Antenna Gain:	GSM 850:	0.3dBi (Max.)
	PCS 1900:	0.12dBi (Max.)
4G Band		
Support Networks:	Band 2 / 4 / 5 / 7 / 38 / 40 / 41	
Frequency Range:	Band 2	1850MHz~1910MHz
	Band 4	1710MHz~1755MHz
	Band 5	824MHz~849MHz
	Band 7	2500MHz~2570MHz
	Band 38	2570MHz~2620MHz
	Band 40-1	2305MHz~2315MHz
	Band 40-2	2350MHz~2360MHz
	Band 41	2496MHz~2690MHz
Modulation Type:	QPSK, 16QAM	

1.2. DESCRIPTION OF TEST FACILITY

Test Lab: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +(86) 0755 85250797

E-mail: Aibonorm@aibonorm.com

Website: www.Aibonorm.com

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Certificate No.: 7514.01

Aibo Standard Technology (Shenzhen) Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.

Designation Number: CN1411

Test Firm Registration Number: 567066

ISED Wireless Device Testing Laboratories

CAB identifier: CN0185

2. RF EXPOSURE EVALUATION

2.1 Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm², P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale, $\pi = 3.1416$;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.2 Evaluation Result

GSM 850

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GMSK	33.0	1995.262	0.396945	0.56	PASS

GSM 1900

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
8PSK	30.0	1000.000	0.198944	1.0	PASS

LTE Band2

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
QPSK	23.0	199.526	0.039694	1.0	PASS

LTE Band4

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
QPSK	23.0	199.526	0.039694	1.0	PASS

LTE Band5

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
QPSK	23.0	199.526	0.039694	0.56	PASS

LTE Band7

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
QPSK	24.0	251.189	0.049972	1.0	PASS

LTE Band38

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
QPSK	24.0	251.189	0.049972	1.0	PASS

LTE Band40

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
QPSK	24.0	251.189	0.049972	1.0	PASS

LTE Band41

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
QPSK	24.0	251.189	0.049972	1.0	PASS

So a SAR test is not required

*****THE END*****