


## Test Model

## Power Spectral Density

802.11b

Channel 1: 2412MHz




Date: 2.NOV.2021 20:09:44

## Test Model

## Power Spectral Density


802.11b

Channel 6: 2437MHz



Date: 2.NOV.2021 20:10:57

Test Model

 Power Spectral Density  
 802.11b  
 Channel 11: 2462MHz


Date: 2.NOV.2021 20:11:34

Test Model


 Power Spectral Density  
 802.11g  
 Channel 1: 2412MHz

## Test Model

## Power Spectral Density

802.11g

Channel 6: 2437MHz




Date: 2.NOV.2021 20:13:25

## Test Model

## Power Spectral Density


802.11g

Channel 11: 2462MHz




Date: 2.NOV.2021 20:13:55

## Test Model

 Power Spectral Density  
 802.11n (HT20)  
 Channel 1: 2412MHz



Date: 2.NOV.2021 20:14:58

## Test Model

 Power Spectral Density  
 802.11n (HT20)  
 Channel 6: 2437MHz



Date: 2.NOV.2021 20:15:27

## Test Model

 Power Spectral Density  
 802.11n (HT20)  
 Channel 11: 2462MHz


Date: 2.NOV.2021 20:15:56

## Test Model

 Power Spectral Density  
 802.11n (HT40)  
 Channel 3: 2422MHz



Date: 2.NOV.2021 20:17:11

## Test Model

## Power Spectral Density

802.11n (HT40)

Channel 6: 2437MHz




Date: 2.NOV.2021 20:17:36

## Test Model

## Power Spectral Density

802.11n (HT40)

Channel 9: 2452MHz



Date: 2.NOV.2021 20:18:04

## For 2T2R

Temperature : 26°C

ATM Pressure:: 1011 mbar

Humidity : 55 %

Test By: Lily

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11n (HT20)	1	2412	-8.30	8	PASS
	6	2437	-9.06	8	PASS
	11	2462	-8.38	8	PASS
802.11n (HT40)	3	2422	-10.63	8	PASS
	6	2437	-11.06	8	PASS
	9	2452	-11.33	8	PASS

## 7.4 UNWANTED SPURIOUS EMISSIONS

### 7.4.1 Applicable Standard

According to FCC Part15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 7.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### 7.4.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

### 7.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to  $\geq$  1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW  $\geq$  3 x RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

#### ■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW =300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.



Use the peak marker function to determine the maximum amplitude level.



Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements . Report the three highest emissions relative to the limit.


### 7.4.5 Test Results

All modulation modes were tested, and the worst data is shown in the table below:



For 1T1R









Date: 29.OCT.2021 20:03:17



Date: 29.OCT.2021 20:05:11



Date: 29.OCT.2021 20:06:27



Date: 29.OCT.2021 20:06:05

## 7.5 RADIATED EMISSION

### 7.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

### 7.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205 the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength (dB $\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ( $\mu$ V/m)	300
0.490-1.705	24000/F(KHz)	20 log ( $\mu$ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 7.5.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

### 7.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit. Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

### 7.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### ■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})(\text{ dB})$ ;

Limit line=Specific limits(dBuV) + distance extrapolation factor

- Spurious Emission Above 1GHz(1GHz to 25GHz)
- All antenna modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

## For 1T1R

Test mode:	802.11 b	Frequency:	Channel 1: 2412MHz			
------------	----------	------------	--------------------	--	--	--

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		H/V	PK	AV	PK	AV	PK
11909.51	V	57.47	41.4	74.00	54.00	-16.53	-12.6
14867.44	V	59.41	43.3	74.00	54.00	-14.59	-10.7
17885.9	V	67.23	47.2	74.00	54.00	-6.77	-6.8
11576.9	H	57.47	40.2	74.00	54.00	-16.53	-13.8
14418.84	H	60.15	42.2	74.00	54.00	-13.85	-11.8
17929.9	H	67.12	45.7	74.00	54.00	-6.88	-8.3

Test mode:	802.11 b	Frequency:	Channel 6: 2437MHz			
------------	----------	------------	--------------------	--	--	--

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		H/V	PK	AV	PK	AV	PK
11962.99	V	57.78	41.6	74.00	54.00	-16.22	-12.4
14841.68	V	61.02	47.3	74.00	54.00	-12.98	-6.7
17929.9	V	65.68	48.5	74.00	54.00	-8.32	-5.5
11837.44	H	57.93	42.8	74.00	54.00	-16.07	-11.2
14437.6	H	59.91	43.3	74.00	54.00	-14.09	-10.7
17994.79	H	64.62	48.6	74.00	54.00	-9.38	-5.4

Test mode:	802.11 b	Frequency:	Channel 11: 2462MHz			
------------	----------	------------	---------------------	--	--	--

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		H/V	PK	AV	PK	AV	PK
11654.12	V	57.52	40.2	74.00	54.00	-16.48	-13.8
14427.17	V	59.26	41.5	74.00	54.00	-14.74	-12.5
18000	V	64.57	45.7	74.00	54.00	-9.43	-8.3
11719.99	H	57.75	41.3	74.00	54.00	-16.25	-12.7
14450.13	H	59.97	42.8	74.00	54.00	-14.03	-11.2
17904	H	64.88	47.6	74.00	54.00	-9.12	-6.4

**Note:**

- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
- (2) Emission Level= Reading Level+Correct Factor.
- (3) Correct Factor= Ant\_F + Cab\_L - Preamp
- (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz  
 All antenna modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

For 1T1R

Test mode: 802.11n(20MHz) Frequency: Channel 1: 2412MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2386.772	H	52.20	74	36.50	54
2387.312	V	52.84	74	38.40	54

Test mode: 802.11n(20MHz) Frequency: Channel 11: 2462MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.819	H	52.28	74	37.50	54
2483.686	V	53.52	74	37.80	54

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Test Model	Spurious Emission in Restricted Band 2310-2390MHz			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input checked="" type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
VBW=3MHz	<input checked="" type="checkbox"/> Channel 1:2412MHz	<input type="checkbox"/> Channel 3: 2422MHz		Polarity: H





Test Model	Spurious Emission in Restricted Band 2310-2390MHz			
	<input type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input checked="" type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
VBW=3MHz	<input checked="" type="checkbox"/> Channel 1:2412MHz	<input type="checkbox"/> Channel 3: 2422MHz		Polarity: V




Spurious Emission in Restricted Band 2483.5-2500MHz

Test Model  802.11b  802.11g  802.11n(HT20)  802.11n(HT40)  
 Channel 11: 2462MHz  Channel 9: 2452MHz Polarity: H  
 VBW=3MHz




■ Spurious Emission below 1GHz (30MHz to 1GHz)


All antenna modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11n20 recorded was report as below:




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Degree	Comment
			MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		116.4380	39.97	-14.25	25.72	43.50	-17.78	QP			
2		154.3461	36.57	-13.90	22.67	43.50	-20.83	QP			
3		189.9050	35.42	-13.90	21.52	43.50	-21.98	QP			
4		220.0377	34.46	-13.16	21.30	46.00	-24.70	QP			
5		360.1320	30.61	-7.44	23.17	46.00	-22.83	QP			
6	*	936.3668	37.40	0.37	37.77	46.00	-8.23	QP			





No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	
1	33.0660	47.45	-14.29	33.16	40.00	-6.84	QP		
2 *	38.8708	47.67	-13.13	34.54	40.00	-5.46	QP		
3	52.7370	41.42	-11.84	29.58	40.00	-10.42	QP		
4	65.8608	37.43	-12.30	25.13	40.00	-14.87	QP		
5	99.7902	41.02	-14.76	26.26	43.50	-17.24	QP		
6	114.2640	38.83	-14.27	24.56	43.50	-18.94	QP		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		38.8368	34.18	-13.13	21.05	40.00	-18.95	QP		
2	*	115.6242	40.89	-14.22	26.67	43.50	-16.83	QP		
3		153.2676	35.38	-13.86	21.52	43.50	-21.98	QP		
4		191.4931	35.55	-13.77	21.78	43.50	-21.72	QP		
5		220.6171	34.54	-13.11	21.43	46.00	-24.57	QP		
6		359.8163	31.18	-7.45	23.73	46.00	-22.27	QP		







Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 23.8 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 39 %

Mode: WIFI2.4G2462

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		33.4302	47.84	-14.24	33.60	40.00	-6.40	QP		
2	*	39.0587	49.02	-13.09	35.93	40.00	-4.07	QP		
3		51.0090	42.71	-11.89	30.82	40.00	-9.18	QP		
4		100.0092	39.72	-14.77	24.95	43.50	-18.55	QP		
5		150.8020	38.55	-13.78	24.77	43.50	-18.73	QP		
6		188.3300	34.49	-13.81	20.68	43.50	-22.82	QP		

## 7.6 CONDUCTED EMISSION TEST

### 7.6.1 Applicable Standard

According to IC RSS-Gen 8.8

### 7.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 7.6.3 Test Configuration

Test according to clause 6.3 conducted emission test setup

### 7.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.


Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

### 7.6.5 Test Results

Pass

The AC120V &240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #1

 Phase: **L1**

Temperature: 22.8

Limit: (CE)FCC PART 15 class B\_QP


Power: AC 120V/60Hz

Humidity: 48 %

Mode: Wifi mode

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1580	24.01	9.44	33.45	65.57	-32.12	QP	
2		0.1580	12.51	9.44	21.95	55.57	-33.62	AVG	
3		0.2020	24.75	9.44	34.19	63.53	-29.34	QP	
4		0.2020	13.42	9.44	22.86	53.53	-30.67	AVG	
5		0.5100	19.34	9.27	28.61	56.00	-27.39	QP	
6		0.5100	15.38	9.27	24.65	46.00	-21.35	AVG	
7		0.6180	20.23	9.28	29.51	56.00	-26.49	QP	
8		0.6180	16.29	9.28	25.57	46.00	-20.43	AVG	
9		0.7580	22.84	9.38	32.22	56.00	-23.78	QP	
10	*	0.7580	20.44	9.38	29.82	46.00	-16.18	AVG	
11		13.7460	22.58	10.08	32.66	60.00	-27.34	QP	
12		13.7460	18.41	10.08	28.49	50.00	-21.51	AVG	



Site Conduction #1

 Phase: **N**

Temperature: 22.8

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz

Humidity: 48 %

Mode: Wifi mode

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dB			
1		0.2020	24.81	9.44	34.25	63.53	-29.28		QP
2		0.2020	13.23	9.44	22.67	53.53	-30.86		AVG
3		0.3900	18.58	9.31	27.89	58.06	-30.17		QP
4		0.3900	9.97	9.31	19.28	48.06	-28.78		AVG
5		0.5100	20.42	9.27	29.69	56.00	-26.31		QP
6		0.5100	14.85	9.27	24.12	46.00	-21.88		AVG
7		0.7420	23.84	9.35	33.19	56.00	-22.81		QP
8	*	0.7420	20.92	9.35	30.27	46.00	-15.73		AVG
9		1.2460	19.21	9.77	28.98	56.00	-27.02		QP
10		1.2460	13.69	9.77	23.46	46.00	-22.54		AVG
11		13.9580	21.79	10.09	31.88	60.00	-28.12		QP
12		13.9580	17.02	10.09	27.11	50.00	-22.89		AVG

## 7.7 ANTENNA APPLICATION

### 7.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi..

### 7.7.2 Result

PASS.

- The EUT has two Internal Antennas: antenna 1 gains are 3.33 dBi; antenna 2 gains are 1.91 dBi
  - Antenna uses a permanently attached antenna which is not replaceable.
  - Not using a standard antenna jack or electrical connector for antenna replacement
  - The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos

## Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

\*\*\* End of Report \*\*\*