

MPE ESTIMATION

FCC ID: 2A3IN-SM-2411

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/cm ²)	Averaging time (minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

2, Estimation Result

Mode	Max PK Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
BT	-6.17	-7±1(-6)	0.25	-0.1	0.98	0.00005
2.4GWIFI	14.86	14±1(15)	31.62	0.71	1.18	0.00741
$Pd = \frac{P_{out} * G}{4\pi r^2}$;						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power = conducted power.						
Conducted power see the test report HK2411056538-1E/2E,						
BT antenna gain = -0.1dBi, WIFI antenna gain = 0.71dBi.						
Synchronous launch evaluation: BT+WIFI=0.00005+0.00741=0.00746mW/cm ² .						

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.00746 which is < 1.0, RF Exposure testing is not required.

-----The End-----