

制造商:Shenzhen Lianchuang Circuit Co., LTD

地址: 2F, Building E5, Yanchuan North Industrial Park, Songgang, Shenzhen

Antenna Test Report

For

Project MB661

Version: V1

Customer	博陆科	Project	MB661
Band	BT	Color	
Issued by	马工	Checked by	
Confirmed by		Date	2023.11.15

This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it propely, without our company and related clients allowed, anybody has no rights to reval it to public.




一. Test Instrumentation and item(测试设备及项目)


类别 (Class)	测试项目 (Test item)	设备 (Equipment)
1. S parameter	1. 回波损耗(RL) 2. 驻波比 (VSWR) 3.斯密斯原图(Smith chart)	网分 (VNA) : Agilent E5071B R&S ZVB8 Protek A333
2. 耦合测试 (Coupling testing)	1. 发射功率 (MAX Power) 2. 接收灵敏度 (MIN Sens)	1.2G/3G Tester: Agilent 8960 2.The coupling box: TESCOM TC-5060A 3. 3D Chamber: ETS 3D Chamber (5x3x3)
3. 3D 无源测试 (Passive Test)	1. 效率 (Effeciency) 2. 增益 (Gain) 3.辐射方向图 (radiation pattern)	1. 3D Chamber: TEM24 3D Chamber (5x5x5) ETS 3D Chamber (5x3x3) 2. 网分 (VNA) : Agilent E5071B R&S ZVB8
4.3D 有源测试 (Active Test)	1. 3D 功率 (TRP) 2. 3D 灵敏度 (TIS) 3.吞吐率 (Throughput rate)	1. 3D Chamber: TEM24 3D Chamber (5x5x5) ETS 3D Chamber (5x3x3) 2.2G/3G Tester: Agilent 8960 3.4G Tester: MT8820C/CMW500 4.WIFI/BT/NB-iot Tester: CMW500 5. 5G Tester: SP9500-CTS 6.Head: HEAD-P10 (FACE-P10)



深圳市国质信网络通讯有限公司
ShenZhen NQI network communication ltd




二. Chamber coordinate axis (暗室坐标)



This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it propely, without our company and related clients allowed, anybody has no rights to reval it to public.



深圳市国质信网络通讯有限公司
ShenZhen NQI network communication ltd



三. Definitions (定义)

VSWR: Voltage Standing Wave Rate

RL: Return loss

TRP: total radiated power

TIS: total isotropic sensitivity

四. Cell-Phone Photo and Dealing Method (手机图片及环境处理)




This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it properly, without our company and related clients allowed, anybody has no rights to reveal it to public.





深圳市国质信网络通讯有限公司

ShenZhen NQI network communication ltd

五. Matching Circuit Description (匹配描述)




位号	参数
E1	原始匹配
E2	原始匹配
E3	NC



This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it propely, without our company and related clients allowed, anybody has no rights to reval it to public.

六. Passive Test (无源测试)

6.1.1.RL/VSWR/Smith chart




6.1.2.天线效率/增益/方向图

Frequency/Mhz	Efficiency / %	Gain/dBi
2400	63.62	4.12
2410	62.78	3.74
2420	66.03	3.98
2430	61.61	3.54
2440	65.16	3.85

This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it propely, without our company and related clients allowed, anybody has no rights to reval it to public.



2450	62.44	3.63
2460	60.14	3.6
2470	61.3	3.72
2480	62.14	3.68
2490	62.11	3.79
2500	60.99	2.92



七. TRP&TIS

NQI ANT TRP&TIS parameter Summary of MB661					
Free space (自由状态) Head and ear (二代人头耳)		Test	Bluetooth TRP&TIS		
		Result	0	39	78
	R	TRP (dBm)	5.02	5.19	4.53
		TIS (dBm)	-89.03	-88.91	-87.84
	R	TRP (dBm)	3.1	3.88	3.53
		TIS (dBm)	-87.25	-87.47	-87.1

This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it properly, without our company and related clients allowed, anybody has no rights to reveal it to public.

八. Field testing (场测或实测)

Headphone field test result (耳机场测结果)		
Test site (测试场地): Vacant lot outside the company gate (国质信门口空地)		
Cell-phone (测试手机): 苹果 6		
The teser (测试员): 马工		
Height of mobile phone stand (手机支架高度): 1.2m		
Test methods and criteria (测试方法及判定标准): The headset is tested with its back to the phone, Up and down, left and right 180° rotation without stuck. (耳机背向手机, 上下, 左右 180° 旋转无卡顿)		
测试结果		
	L/R	Actual test distance (实测测试距离)
	The left ear (左耳)	/
	The right ear (右耳)	25m
备注:		

PCB 天线制造商及地址:

制造商:Shenzhen Lianchuang Circuit Co., LTD

地址: 2F, Building E5, Yanchuan North Industrial Park, Songgang, Shenzhen