



Maximum Permissible Exposure Evaluation

FCC ID: 2A3LP-WXT28M2511

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

Product Name:	Wireless Module
Trade Mark:	/
Model/Type reference:	WXT28M2511
Listed Model(s):	/
Frequency band (Operating)	BT: 2.402GHz ~ 2.480GHz 2.4G WIFI: 2.412GHz ~ 2.462GHz 5G WIFI: 5.150GHz ~ 5.350GHz, 5.470GHz ~ 5.850GHz
Device category	<input type="checkbox"/> Portable (<5mm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> Fixed (>20cm separation) <input type="checkbox"/> Others _____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S=5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antenna <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Antenna gain (Max)	BT ANT: 2.0dBi 2.4G WIFI ANT1: 2.93dBi, ANT2: 3.27dBi, Directional gain: 6.11dBi 5G WIFI ANT1: 3.72dBi, ANT2: 3.86dBi, Directional gain: 6.80dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

**Limits for Maximum Permissible Exposure (MPE)**

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * R^2)$

Where

Pd= Power density in mW/cm²

Pout= output power to antenna in mW

G= gain of antenna in linear scale

Pi= 3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Only show the value of the worst antenna.

BLE - Worst case

Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2440	6.67	7.00	2.0	0.00158	1

BR/EDR - Worst case

Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
8-DPSK	2441	11.61	12.00	2.0	0.00500	1

2.4G WIFI - Worst case

Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11 B	2462	17.91	18.00	3.27	0.02665	1



5G WIFI - Worst case						
Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11 AX80	5210	15.25	15.50	6.80	0.03379	1

The BT and WIFI can transmit simultaneously.

Type	Channel Frequency (MHz)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	BT+WIFI Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
8-DPSK	2441	2.0	0.00500	0.06544	1
802.11 B	2462	3.27	0.02665		
802.11 AX80	5210	6.80	0.03379		

Note:

1. Calculate by Worst-case mode
2. Max. Tune Up Power by Manufacturer's Declaration, and Max. Tune Up Power is used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****