



Report No.: FCS202209114W01

# FCC RF Exposure

EUT Description:Wi-Fi TV LED Backlight

ModelNo.:BW-LB2

FCC ID: 2A3LZ-BW-LB2

Equipment type: fixed equipment

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)	
	(A) Limit	ts for Occupational/Controlled E	xposures		
0.3-3.0	614	1.63 *(100)		6	
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6	
30–300	61.4	0.163	1.0	6	
300–1500			f/300	6	
1500-100,000			5	6	
	(B) Limits fo	r General Population/Uncontroll	ed Exposure		
0.3-1.34	614	614 1.63 *(100)		30	
1.34–30	824/f	2.19/f *(180/f²)		30	
30–300	27.5	0.073 0.2		30	
300–1500			f/1500	30	
1500-100,000			1.0	30	

F = frequency in MHz

Formula: Pd = (Pout\*G)/(4\*  $\pi$  \*r<sup>2</sup>)

Where:

Pd = power density in mW/cm<sup>2</sup>,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

 $\pi = 3.14$ ;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: FCS202209114W01

## 3. Test Result of RF Exposure Evaluation

Modulation	Channel Freq. (MHz)	Conduct ed power (dBm)	Max tune-up power (mW)	Antenna Gain (dBi)	Antenna gain numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
802.11b	2412	12.29	16.94	2.21	1.66	0.00560	1
	2437	11.00	12.58	2.21	1.66	0.00417	1
	2462	10.20	10.47	2.21	1.66	0.00347	1
802.11g	2412	11.85	15.31	2.21	1.66	0.00507	1
	2437	10.21	10.49	2.21	1.66	0.00347	1
	2462	9.64	9.20	2.21	1.66	0.00304	1
802.11n	2412	12.15	16.40	2.21	1.66	0.00543	1
	2437	10.65	11.61	2.21	1.66	0.00384	1
	2462	9.84	9.63	2.21	1.66	0.00319	1

Conclusion: the max result :0.00559≤ 1.0 compliance with FCC's RF Exposure.