



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No. : CQASZ20211101902E-02

Applicant: JDS Labs, Inc

Address of Applicant: 909 N Bluff Rd, Collinsville, IL 62234, United States

Equipment Under Test (EUT):

Product: DIGITAL-TO-ANALOG CONVERTER

Model No.: EL DAC II+

Test Model No.: EL DAC II+

Brand Name: N/A

FCC ID: 2A3MK-ELDACII

Standards: 47 CFR Part 1.1307

47 CFR Part 1.1310

KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2021-11-03

Date of Test: 2021-11-03 to 2021-11-26

Date of Issue: 2021-11-29

Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: lewis zhou
(Lewis Zhou)

Reviewed By: Rock Huang
(Rock Huang)

Approved By: James
(Jack ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20211001902E-02	Rev.01	Initial report	2021-11-29

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 <i>Standard Requirement</i>	错误! 未定义书签。
4.1.2 <i>Limits</i>	错误! 未定义书签。
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	JDS Labs, Inc
Address of Applicant:	909 N Bluff Rd, Collinsville, IL 62234, United States
Manufacturer:	JDS Labs, Inc
Address of Manufacturer:	909 N Bluff Rd, Collinsville, IL 62234, United States
Factory:	JDS Labs, Inc
Address of Factory:	909 N Bluff Rd, Collinsville, IL 62234, United States

3.2 General Description of EUT

Product Name:	DIGITAL-TO-ANALOG CONVERTER
Model No.:	EL DAC II+
Test Model No.:	EL DAC II+
Trade Mark:	N/A
Software Version:	Firmware v1.A.0
Hardware Version:	v2.51E
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth 5.1
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	Blue Test3
Antenna Type:	RP-SMA antenna
Antenna Gain:	0dBi
Power Supply:	16Vac 1000mA 16VA by Adapter
Adapter:	Model NO.: XY-16001000AU INPUT:120VAC 60Hz OUTPUT:16VAC 1000mA 16W

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.110	1.0±1	2	1.585
Middle(2441MHz)	1.790	1.5±1	2.5	1.778
Highest(2480MHz)	1.910	1.5±1	2.5	1.778
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.180	1.5±1	2.5	1.778
Middle(2441MHz)	2.030	2.0±1	3.0	1.995
Highest(2480MHz)	1.530	1.5±1	2.5	1.778
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.780	1±1	2	1.585
Middle(2441MHz)	1.590	1.5±1	2.5	1.778
Highest(2480MHz)	1.330	1.5±1	2.5	1.778

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
1.995	0	0.000397	1.0	PASS

Note: 1) Refer to report No. CQASZ20210901525E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (1.995 \cdot 1) / (4 \cdot 3.1416 \cdot 20^2) = 0.000397 \text{ mW/cm}^2$

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20211001902E-01

*** End of Report ***