# FCC RF EXPOSURE REPORT

Applicant : Hangzhou Cheego Technology Co., Ltd.

Address Room 603, Bldg. E2, 3# Xiyuan 8 Road ,Hangzhou,

China

Equipment : Cheego Smart Baby Monitor

CCA3-C, CCA3-\*(\*can be 0-9, A, B, D-Z or blank,

Report No.: DEFJ2112010

Model No. : means the color of appearance and Sales area are

differences)

Trade Name : Cheego

FCC ID. : 2A3MM-CCA3

#### I HEREBY CERTIFY THAT:

The sample was received on Dec. 07, 2021 and the testing was completed on Dec. 21, 2021 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Leevin Li /Supervisor

Cerpass Technology Corp. Issued date : Dec. 21, 2021

D-FD-511-0 V1.1 Page No. : 1 of 7

### Contents

Report No.: DEFJ2112010

1. Test Configuration of Equipment under Test	. 4
1.1 Feature of Equipment	. 4
1.2 General Information of Test	
2. Radio Frequency Exposure	

D-FD-511-0 V1.1 Page No. : 2 of 7

## History of this test report

Report No.: DEFJ2112010

Issued date : Dec. 21, 2021

### ■ Original.

 $\square$  Additional attachment as following record:

Attachment No.	Issue Date	Description
DEFJ2112010	Dec. 21, 2021	Original

D-FD-511-0 V1.1 Page No. : 3 of 7

## 1. Test Configuration of Equipment under Test

## 1.1 Feature of Equipment

Equipment	Cheego Smart Baby Monitor				
Model Name	CCA3-C, CCA3-*(*can be 0-9, A, B, D-Z or blank, means the color of appearance and Sales area are differences)  Model CCA3-C is the representative for final test.				
Model Discrepancy	The differences are the color of appearance and Sales area.				
Frequency Range	802.11b/g/n(20MHz): 2412-2462MHz 802.11n(40MHz): 2422-2452MHz				
Modulation Type	802.11b: CCK, DQPSK, DBPSK 802.11g/ n: 64-QAM,16-QAM, QPSK, BPSK				
Data Rate	802.11b: 1, 2 ,5.5,11Mbps 802.11g: 6,9,12,18,24,36,48,54Mbps 802.11n: HT20 reach up to 72.2Mbps, HT40 reach up to 150Mbps				
Antenna Spec.	PCB Antenna with 2.5dBi				
Power Supply	12V == 1A				
Adapter Information	Model: GA-1201000 Input: AC 100-240V~50/60Hz 0.6A Output: 12.0V === 1000mA				

Report No.: DEFJ2112010

Note: For more details, please refer to the User's manual of the EUT.

Cerpass Technology Corp. Issued date : Dec. 21, 2021

D-FD-511-0 V1.1 Page No. : 4 of 7

### 1.2 General Information of Test

Test Site	Cerpass Technology Corporation(Cerpass Laboratory) Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288

Report No.: DEFJ2112010

Cerpass Technology Corp. Issued date : Dec. 21, 2021

D-FD-511-0 V1.1 Page No. : 5 of 7

### 2. Radio Frequency Exposure

Device category	Portable (<20cm separation)			
Device category				
	☐ Occupational/Controlled exposure (S = 5mW/cm²)			
Exposure classification	☐ General Population/Uncontrolled exposure			
	(S=1mW/cm <sup>2</sup> )			
	Single antenna			
	☐ Multiple antennas			
Antenna diversity	☐ Tx diversity			
•	Rx diversity			
	☐ Tx/Rx diversity			
Evaluation applied				
	☐ SAR Evaluation			

Report No.: DEFJ2112010

#### **TEST RESULTS**

No non-compliance noted.

#### **Calculation**

Given

$$E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

*d* = *Distance in meters* 

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and  $d(cm) = d(m) / 100$ 

**Yields** 

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$
 Equation 1

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW / cm^2$ 

D-FD-511-0 V1.1

Issued date : Dec. 21, 2021

Page No. : 6 of 7

#### Maximum Permissible Exposure

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
2412-2462	22.02	23.02	2.50	20	0.071	1

Report No.: DEFJ2112010

Issued date : Dec. 21, 2021

#### Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.



Cerpass Technology Corp.

D-FD-511-0 V1.1 Page No. : 7 of 7