

FCC - TEST REPORT

Report Number	: 68.940.23.0078.01	Date of Issue: 2023-10-27
Model	: ERV-I, BCU1, BCU2, BCU3, BCU4, BCU5, BCU6, BCU7, BCU8, BCU9, BCU10, ERV-II, ERV-III, ERV-IV, ERV-V, ERV-VI, ERV-VII, ERV-VIII, ERV-IX, ERV-X, ERV1, ERV2, ERV3, ERV4, ERV5, ERV6, ERV7, ERV8, ERV9, ERV10	
Product Type	: Bumper Car	
Applicant	: MAXLEAD INTERNATIONAL LIMITED	
Address	: Unit 503, 5/F., Silvercord Tower 2, 30 Canton Rd., Tsimshatsui, Kowloon, Hong Kong	
Manufacturer	: SHENZHEN JINRUI IMPORT&EXPORT CO.,LTD	
Address	: 14-A1, Building 3, Zhongke R&D Park, No. 009, Gaoxin South Road, Gaoxin District, Yuehai Street, Nanshan District, Shenzhen, Guangdong, China	
Test Result	: <input checked="" type="checkbox"/> Positive <input type="checkbox"/> Negative	
Total pages including Appendices	: 58	

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.

1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks.....	7
7	Test Setups.....	8
8	Systems test configuration	10
9	Technical Requirement	11
9.1	Conducted Emission.....	11
9.2	Conducted peak output power.....	14
9.3	20 dB bandwidth and 99% Occupied Bandwidth.....	19
9.4	Carrier Frequency Separation.....	24
9.5	Number of hopping frequencies	27
9.6	Dwell Time	30
9.7	Spurious RF conducted emissions.....	34
9.8	Band edge testing	45
9.9	Spurious radiated emissions for transmitter	53
10	Test Equipment List.....	57
11	System Measurement Uncertainty	58

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park, Guankou Erlu,
Nantou, Nanshan District, Shenzhen City, 518052, P. R. China

Telephone: 86 755 8828 6998
Fax: 86 755 8828 5299

FCC Registration
No.: 514049

FCC Designation
Number: CN5009

IC Registration
No.: 10320A

3 Description of the Equipment Under Test

Product:	Bumper Car
Model no.:	ERV-I
FCC ID:	2A3NW-ERV-I
Options and accessories:	Adapter
Rating:	Supplied by 12VDC Li-ion Rechargeable Battery 7Ah Charged by 12.0Vdc, 1.0A external adapter
Adapter information:	Adapter Model: HKP18-1201000dU Input: 100-240Vac, 50/60Hz; 0.45A Max Output: 12.0Vdc, 1.0A
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, π/4-DQPSK, 8DPSK
Antenna Type:	PCB Antenna
Antenna Gain:	-0.58dBi
Description of the EUT:	EUT is a Bumper Car with Bluetooth and 2.4G Hopping function which operated at 2.4GHz.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2021 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2020).

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C		Pages	Test Site	Test Result		
Test Condition				Pass	Fail	N/A
§15.207	Conducted emission AC power port	10	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247 (b) (1)	Conducted peak output power	13	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1)	20dB bandwidth	19	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1)	Carrier frequency separation	30	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1)(iii)	Number of hopping frequencies	33	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1)(iii)	Dwell Time	36	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(e)	Power spectral density	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(d)	Spurious RF conducted emissions	46	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Band edge	61	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Spurious radiated emissions for transmitter	69	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203	Antenna requirement	See note 2		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Note 1: N/A=Not Applicable.

Note 2: The EUT uses a PCB antenna, which gain is -0.58dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2A3NW-ERV-I complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- Not Performed

The Equipment Under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: 2023-10-10

Testing Start Date: 2023-10-10

Testing End Date: 2023-10-20

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:

Prepared by:


Tested by:



Jessie He
Project Manager





Richard He
Project Engineer



Carry Cai
Test Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


9KHz - 30MHz




30MHz - 1GHz



Above 1GHz



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Notebook	Lenovo	X240	---
Adapter	HUNG KAY	HKP18-1201000dU	--

Test software information:

Test Software Version	1.0.2.2	
Modulation	Setting TX Power	Packet Type
GFSK	0	PRBS9
$\pi/4$ -DQPSK	0	PRBS9
8DPSK	0	PRBS9

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Conducted Emission

Model : ERV-I
 Test Mode : transmitting
 Test Voltage : 120VAC, 60Hz (for external adapter)
 Remark : Power Line, Live



Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Corr. (dB)
0.190000	47.58	---	64.04	16.46	L1	9.54
0.506000	---	34.71	46.00	11.29	L1	9.59
0.506000	41.72	---	56.00	14.28	L1	9.59
1.506000	36.31	---	56.00	19.69	L1	9.61
2.874000	35.18	---	56.00	20.82	L1	9.65
6.506000	33.53	---	60.00	26.47	L1	9.82
19.898000	44.39	---	60.00	15.61	L1	10.01

Final_Result


Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---	---	---

Remark:

Level=Reading Level + Correction Factor
 Correction Factor=LISN Factor + Cable Loss
 (The Reading Level is recorded by software which is not shown in the sheet)

Conducted Emission

Model : ERV-I
 Test Mode : transmitting
 Test Voltage : 120VAC, 60Hz (for external adapter)
 Remark : Power Line, Neutral



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.186000	43.83	---	64.21	20.38	N	9.57
0.478000	---	34.25	46.37	12.12	N	9.61
0.482000	43.82	---	56.31	12.48	N	9.61
0.786000	37.31	---	56.00	18.69	N	9.63
1.482000	35.80	---	56.00	20.20	N	9.64
14.798000	39.19	---	60.00	20.81	N	10.01
19.466000	45.88	---	60.00	14.12	N	9.95

Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---		---

Remark:

Level=Reading Level + Correction Factor
 Correction Factor=LISN Factor + Cable Loss

(The Reading Level is recorded by software which is not shown in the sheet)

9.2 Conducted peak output power

Test Method

1. The RF output of EUT was connected to the test spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following test receiver settings:
Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel
RBW > the 20dB bandwidth of the emission being measured, $VBW \geq RBW$,
Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power and record the results in the test report.
5. Repeat above procedures until all frequencies measured were completed.

Limits

According to §15.247 (b) (1), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Conducted Peak Output Power

Test result as below table

Bluetooth Mode GFSK modulation Test Result


Frequency MHz	Conducted Peak		Result
	Output Power	dBm	
Low channel 2402MHz	-4.16		Pass
Middle channel 2441MHz	-5.06		Pass
High channel 2480MHz	-6.04		Pass


Bluetooth Mode π/4-DQPSK modulation Test Result


Frequency MHz	Conducted Peak		Result
	Output Power	dBm	
Low channel 2402MHz	-3.57		Pass
Middle channel 2441MHz	-4.42		Pass
High channel 2480MHz	-5.29		Pass

Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak		Result
	Output Power	dBm	
Low channel 2402MHz	-3.34		Pass
Middle channel 2441MHz	-4.19		Pass
High channel 2480MHz	-5.01		Pass







9.3 20 dB bandwidth

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following test receiver settings:
Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel
RBW > the 20dB bandwidth of the emission being measured, $VBW \geq RBW$,
Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth. Record the results.
5. Repeat above procedures until all frequencies measured were complete.

Limit


Limit [kHz]


N/A


20 dB bandwidth

Bluetooth Mode GFSK Modulation test result

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	20dB Bandwidth (MHz)	Verdict
					Result	
GFSK	SISO	2402	DH5	1	1.023	Pass
		2441	DH5	1	1.028	Pass
		2480	DH5	1	1.039	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.398	Pass
		2441	2DH5	1	1.407	Pass
		2480	2DH5	1	1.412	Pass
8DPSK	SISO	2402	3DH5	1	1.387	Pass
		2441	3DH5	1	1.401	Pass
		2480	3DH5	1	1.412	Pass







9.4 Carrier Frequency Separation

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit to hopping mode.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, RBW $\geq 1\%$ of the span, VBW) \geq RBW, Sweep = auto, Detector function = peak
4. By using the Max-Hold function record the separation of two adjacent channels.
5. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function. Record the results.
6. Repeat above procedures until all frequencies measured were complete.

Limit

Limit kHz
$\geq 25\text{KHz}$ or $2/3$ of the 20 dB bandwidth which is greater


Limit


Modulation	Frequency MHz	2/3 of 20 dB Bandwidth	
			kHz
GFSK	2441		742
$\pi/4$ -DQPSK	2441		922
8DPSK	2441		922

Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status).

Ant1							
Mode	TX Type	Frequency (MHz)	Packet Type	Channel Separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Verdict
GFSK	SISO	HOPP	DH5	1.000	1.039	>=0.693	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	1.001	1.412	>=0.941	Pass
8DPSK	SISO	HOPP	3DH5	1.001	1.412	>=0.941	Pass





9.5 Number of hopping frequencies

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit to hopping mode.
3. Use the following spectrum analyzer settings:
Span = the frequency band of operation, RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace=Max hold.
4. Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).


Limit


Limit number
≥ 15

Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification.

Mode	TX Type	Frequency (MHz)	Packet Type	Num of Hopping Frequencies		Verdict
				ANT1	Limit	
GFSK	SISO	HOPP	DH5	79	>=15	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	79	>=15	Pass
8DPSK	SISO	HOPP	3DH5	79	>=15	Pass





9.6 Dwell Time

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit to hopping mode.
3. Span: Zero span, centered on a hopping channel.
4. RBW shall be \ channel spacing and where possible RBW should be set $>> 1 / T$, where T is the expected dwell time per channel.
5. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
6. Detector function: Peak.
7. Trace: Max hold. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Limit

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Dwell Time


Dwell time


The maximum dwell time shall be 0.4 s.


The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:
 The duration for dwell time calculation: $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 79 \text{ [ch]} = 31.6 \text{ [s*ch]}$;

Test result as below:

Ant1									
Mode	TX Type	Frequency (MHz)	Packet Type	Duration of Single Pulse (ms)	Observation Period (s)	Num of Pulse in Observation Period	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	SISO	HOPP	DH5	2.884	31.600	106	305.704	<=400	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	2.892	31.600	114	329.688	<=400	Pass
8DPSK	SISO	HOPP	3DH5	2.890	31.600	103	297.670	<=400	Pass







9.7 Spurious RF conducted emissions

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency

Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20


Spurious RF conducted emissions

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)
GFSK	SISO	2402	DH5	1	-4.32
		2441	DH5	1	-5.24
		2480	DH5	1	-6.27
Pi/4DQPSK	SISO	2402	2DH5	1	-4.30
		2441	2DH5	1	-5.22
		2480	2DH5	1	-6.26
8DPSK	SISO	2402	3DH5	1	-4.33
		2441	3DH5	1	-5.24
		2480	3DH5	1	-6.27


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
GFSK	SISO	2402	DH5	1	-4.32	-24.32	Pass
		2441	DH5	1	-4.32	-24.32	Pass
		2480	DH5	1	-4.32	-24.32	Pass
		HOPP	DH5	1	-4.32	-24.32	Pass
					-4.32	-24.32	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	-4.30	-24.30	Pass
		2441	2DH5	1	-4.30	-24.30	Pass
		2480	2DH5	1	-4.30	-24.30	Pass
		HOPP	2DH5	1	-4.30	-24.30	Pass
					-4.30	-24.30	Pass
8DPSK	SISO	2402	3DH5	1	-4.33	-24.33	Pass
		2441	3DH5	1	-4.33	-24.33	Pass
		2480	3DH5	1	-4.33	-24.33	Pass
		HOPP	3DH5	1	-4.33	-24.33	Pass
					-4.33	-24.33	Pass


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.





GFSK_DH5_HCH_2480MHz_Ant1_NTNV







Pi/4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV























9.8 Band edge testing

Test Method

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency
6. Set to the maximum power setting and enable the EUT hopping mode, repeat the test.

Limit:

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


Band edge

Test Result as below:


Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
GFSK	SISO	2402	DH5	1	-4.32	-24.32	Pass
		2441	DH5	1	-4.32	-24.32	Pass
		2480	DH5	1	-4.32	-24.32	Pass
		HOPP	DH5	1	-4.32	-24.32	Pass
					-4.32	-24.32	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	-4.30	-24.30	Pass
		2441	2DH5	1	-4.30	-24.30	Pass
		2480	2DH5	1	-4.30	-24.30	Pass
		HOPP	2DH5	1	-4.30	-24.30	Pass
					-4.30	-24.30	Pass
8DPSK	SISO	2402	3DH5	1	-4.33	-24.33	Pass
		2441	3DH5	1	-4.33	-24.33	Pass
		2480	3DH5	1	-4.33	-24.33	Pass
		HOPP	3DH5	1	-4.33	-24.33	Pass
					-4.33	-24.33	Pass


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.


DH5_Ant1_Low_2402





DH5_Ant1_High_2480














9.9 Spurious radiated emissions for transmitter

Test Method

1. The EUT was place on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
4. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
6. Use the following spectrum analyzer settings According to C63.10:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:

VBW = 10 Hz, when duty cycle is no less than 98 percent.

VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

7. Repeat above procedures until all frequencies measured were complete.

Note:

- 1: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
- 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($20\log(1/\text{duty cycle})$)).
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.

Spurious radiated emissions for transmitter

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 & RSS-GEN 8.10, must comply with the radiated emission limits specified in section 15.209 & RSS-Gen 6.13.

Frequency MHz	Field Strength µV/m	Field Strength dBµV/m	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit 3m(dBµV/m)=Limit 300m(dBµV/m)+40Log(300m/3m) (Below 30MHz)

Note 2: Limit 3m(dBµV/m)=Limit 30m(dBµV/m)+40Log(30m/3m) (Below 30MHz)

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

Transmitting spurious emission test result as below:

Frequency Band	Frequency	Emission Level	Polarization	Limit	Detector	Margin	Correct factor	Result
	MHz	dB μ V/m		dB μ V/m		dB μ V/m	(dB)	
30-1000MHz	292.923889	34.70	H	46.00	QP	11.30	18.36	Pass
	377.313889	36.10	H	46.00	QP	9.90	20.75	Pass
	884.192778	37.70	H	46.00	QP	8.30	29.16	Pass
	958.773756	39.10	H	46.00	QP	6.90	29.80	Pass
	Other Frequencies	--	H	--	QP	--	--	Pass
	304.456111	39.08	V	46.00	QP	6.92	18.66	Pass
	206.216667	34.60	V	43.50	QP	8.90	15.61	Pass
	370.800556	36.88	V	46.00	QP	9.12	20.43	Pass
	767.200000	35.80	V	46.00	QP	10.20	27.45	Pass
	Other Frequencies	--	V	--	QP	--	--	Pass

GFSK Modulation 2402MHz Test Result

Frequency Band	Frequency	Emission Level	Polarization	Limit	Detector	Margin	Correct factor	Result
	MHz	dB μ V/m		dB μ V/m		dB μ V/m	(dB)	
1000-25000MHz	2352.182000	41.01	H	74	PK	32.99	-6.28	Pass
	7206.000000	47.12	H	74	PK	26.88	7.97	Pass
	14131.000000	46.12	H	74	PK	27.88	16.04	Pass
	Other Frequencies	--	H	--	PK	--	--	Pass
	2359.501000*	41.93	V	74	PK	32.07	-6.30	Pass
	4804.500000*	54.83	V	74	PK	19.17	5.14	Pass
	4804.500000*	48.56	V	54	AV	5.44	5.14	Pass
	14936.500000	46.95	V	74	PK	27.05	17.14	Pass
	Other Frequencies	--	V	--	PK	--	--	Pass

GFSK Modulation 2441MHz Test Result

Frequency Band	Frequency	Emission Level	Polarization	Limit	Detector	Margin	Correct factor	Result
	MHz	dB μ V/m		dB μ V/m		dB μ V/m	(dB)	
1000-25000MHz	4882.500000*	54.47	H	74	PK	19.53	5.68	Pass
	4882.500000*	45.89	H	54	AV	8.11	5.68	Pass
	7323.000000*	41.90	H	74	PK	32.10	7.97	Pass
	9764.500000	45.73	H	74	PK	28.27	11.20	Pass
	Other Frequencies	--	H	--	PK	--	--	Pass
	7877.000000	41.56	V	74	PK	32.44	8.98	Pass
	9764.000000	46.06	V	74	PK	27.94	11.20	Pass
	14422.000000	45.97	V	74	PK	28.03	16.58	Pass
	Other Frequencies	--	V	--	PK	--	--	Pass

GFSK Modulation 2480MHz Test Result

Frequency Band	Frequency	Emission Level	Polarization	Limit	Detector	Margin	Correct factor	Result
	MHz	dB μ V/m		dB μ V/m		dB μ V/m	(dB)	
1000-25000MHz	3907.500000	48.67	H	74	PK	25.33	2.99	Pass
	4960.000000*	54.25	H	74	PK	19.75	5.76	Pass
	4960.000000*	39.56	H	54	AV	14.44	5.76	Pass
	7440.500000	41.49	H	74	PK	32.51	8.14	Pass
	Other Frequencies	--	H	--	PK	--	--	Pass
	4960.500000*	54.67	V	74	PK	19.33	5.76	Pass
	4960.500000*	38.23	V	54	AV	15.77	5.76	Pass
	7618.500000*	41.33	V	74	PK	32.67	8.80	Pass
	9920.500000	47.37	V	74	PK	26.63	11.20	Pass
	Other Frequencies	--	V	--	PK	--	--	Pass

Remark:

- (1) Data of measurement within frequency range 9kHz-30MHz is the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.
- (2) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are the noise floor or attenuated more than 10dB below the permissible limits or the field strength is too small to be measured.
- (3) Level=Reading Level + Correction Factor
Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss
(The Reading Level is recorded by software which is not shown in the sheet)
- (4) “*” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.

10 Test Equipment List

List of Test Instruments

Conducted Emission 2# Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-19-002	102590	1	2024-5-19
LISN	Rohde & Schwarz	ENV216	68-4-87-19-001	102472	1	2024-5-20
Attenuator	Shanghai Huaxiang	TS2-26-3	68-4-81-16-003	080928189	1	2024-5-19
Test software	Rohde & Schwarz	EMC32	68-4-90-19-005-A01	Version10.35.02	N/A	N/A
Shielding Room	TDK	CSR #2	68-4-90-19-005	----	3	2025-10-15

Radiated Emission Test 1# Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 7	68-4-74-19-001	102176	1	2024-5-20
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	68-4-80-14-002	707	1	2024-7-18
Pre-amplifier	Rohde & Schwarz	SCU 18	68-4-29-14-001	102230	1	2024-5-19
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-001	15542	1	2024-5-19
3m Semi-anechoic chamber	TDK	SAC-3 #1	68-4-90-14-001	----	3	2024-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-14-001-A10	Version10.35.02	N/A	N/A

Radiated Emission 2# Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2024-5-20
Wave Guide Antenna	ETS	3117	68-4-80-19-001	00218954	1	2024-4-26
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2024-5-19
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-002	100746	1	2024-5-19
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2024-7-11
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2024-8-1
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	1	2024-5-19
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2	2024-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A	N/A

RF conducted test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2024-5-19
RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157W	68-4-93-14-003	101226/100929	1	2024-5-20
Test software	Rohde & Schwarz	EMC32	68-4-48-14-003-A10	Version 10.60.10	N/A	N/A
Test software	Tonscend	System for BT/WIFI	68-4-74-14-006-A13	Version 2.6.77.0518	N/A	N/A
Shielding Room	TDK	TS8997	68-4-90-19-003	----	3	2025-10-15

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission in new shielding room (68-4-90-19-005) 150kHz-30MHz (for test using AMN ENV216)	3.33dB
Uncertainty for Radiated Emission in 3m chamber (68-4-90-14-001) 9kHz-30MHz	4.70dB
Uncertainty for Radiated Emission in 3m chamber (68-4-90-14-001) 30MHz-1000MHz	Horizontal: 4.64dB; Vertical: 4.79dB;
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 1000MHz-18000MHz	Horizontal: 5.08dB; Vertical: 5.09dB;
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 18GHz-40GHz	Horizontal: 3.14dB; Vertical: 3.12dB;
Uncertainty for Conducted RF test with TS 8997	RF Power Conducted: 1.31dB Frequency test involved: 0.6×10^{-8} or 1%

Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2021, clause 4.4.3 and 4.5.1.

---The End---