



Caper Shopping cart


LTE WIFI 1 antenna specification

Project name:	Shopping cart II		Freq:	2400-2500MHz;5200-5850Mhz	
Internal material number:	Y07100204KA		Version number:	A.0	
Data:	2022/11/17				
Futen technology （Shanghai）CO.,LTD					
Audit	RF	Frank wu	Design	RF	Frank wu
	ME	Xiaofang wu			
	quality	Shengbin wang		ME	Xiaofang wu
	Sales	Qiao wang			
Data:	2022-11-17				
confirm	RF				
	ME				
remarks					

Directory

1. Project picture
2. Antenna specifications
3. Match the circuit
4. S11 test
 - 4.0 S11 Test Method
 - 4.1 S11 Parameters
 - 4.2 Parameter Picture
 - 4.2.1 Return loss
 - 4.2.2 V.S.W.R
5. Darkroom test data
 - 5.0 Testing Devices
 - 5.1 Active Data
 - 5.2 Passive Data
6. Ground the prototype
7. Antenna surface

1. Project picture



Ant photograph

2. Antenna specifications


Antenna Type	Antenna structure	Antenna mounting	wire diameter and color	Total length (mm)	Connector type
WIFI1 Ant	FPC+Cable+Connector	The antenna is attached to the housing	Φ1.13 black	170	Ipex1 terminal with buckle

3. Matching the circuit

NO Matching

4. S11 test

4.0 S11Test method




4.1 S11 参数

Freq (MHZ)	2400	2500	5200	5880
VSWR	1.14	1.25	2.41	1.34
RL	-23.4	-19.1	-7.60	-16.7

4.2 Parameters picture

4.2.1 Return loss



4.2.2 V.S.W.R



5. Darkroom test data

5.0 Testing Devices

Test equipment

Test system: shielded darkroom

Test environment: Temperature $22^{\circ}\text{C} \pm 3^{\circ}\text{C}$, humidity $50\% \pm 15\%$

Test equipment: When testing passive data, use network analyzer

Agilent E5071C

5.1 Active Data

There is no

5.2 Passive Data

Gain&Efficiency 增益和效率					
frequency 频率 (MHz)	gain 增益 (dBi)	efficiency 效率(%)	frequency 频率(MHz)	gain 增益 (dBi)	efficiency 效率(%)
2400	3.48	38.99	5150	6.15	47.68
2410	3.57	38.36	5200	5.81	44.93
2420	3.61	38.24	5250	5.22	43.50
2430	3.32	36.03	5300	5.82	47.36
2440	3.12	33.71	5350	5.46	45.29
2450	2.54	31.85	5400	4.58	40.25
2460	2.18	30.22	5450	4.59	46.76
2470	2.56	33.82	5500	3.67	38.21
2480	2.14	32.00	5550	3.45	40.96
2490	1.86	30.43	5600	2.87	38.72
2500	2.17	31.25	5650	3.64	40.51
			5700	3.72	39.23
			5750	4.55	43.00
			5800	4.53	43.44
			5850	4.06	42.80
			5900	4.17	42.53

6. Ground the prototype

No processing

7. Antenna surface

