

KRUG & PRIESTER GmbH & Co. KG, D-72336 Balingen

RF Exposure Considerations for the AP60 PRO

FCC ID: 2A3QI-8741119

The AP60 PRO operates at 13.56MHz, and also uses a 2.4GHz pre-certified module (FCC ID: 2ACSVHF-LTP120). The 13.56MHz and 2.4GHz, transmitters can transmit simultaneously.

The FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from a device to the body of a user.

The following FCC Rule Parts and procedures are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

Part 2.1091 – Radiofrequency radiation exposure evaluation: mobile devices

KDB447498 D01 v06

Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies

AP60 PRO MAXIMUM TRANSMITTER POWER CONSIDERATIONS

13.56MHz:

Tx Power: +65dBuV/m @3m (maximum stated power from Operational Description).
EIRP = 65 - 95.3dBm = -30.3dBm

2412 – 2462MHz:

Tx Power: 0.0442W (16.45dBm) conducted (From FCC Grant 2ACSVHF-LPT120)

Antenna gain: 1.5dBi

EIRP = 17.95dBm



KRUG & PRIESTER GmbH & Co. KG, D-72336 Balingen

MPE CALCULATIONS

The MPE calculation to calculate the safe operating distance for the user is.

$$S = \text{EIRP} / 4 \pi R^2$$

Where S = Power density
 EIRP = Effective Isotropic Radiated Power
 R = distance to the centre of radiation of the antenna (safe operating distance)

For 13.56MHz :Values:

EIRP = -30.3dBm

= 0.00093mW

R = 20cm

Power Density RequirementFrom table 1 (e) - Limits for General Population/ Uncontrolled Exposure of
FCC Rule Part 1.1310 for 13.56MHz

$$S_{\text{req1}} = 180/f^2 = 0.98 \text{ mW/cm}^2$$

Calculation:

$$S = 0.00093 / 4 \pi R^2$$

$$S = 0.00093 / (12.56 \times 20^2)$$

$$S = 0.00093 / (5024)$$

$$S_1 = 1.9 \times 10^{-7} \text{ mW/cm}^2 (< 0.98 \text{ mW/cm}^2)$$



KRUG & PRIESTER GmbH & Co. KG, D-72336 Balingen

For 2.4GHz:**Values:**

Transmitter frequency range = 2412 MHz to 2462 MHz

EIRP = 17.95dBm

= 62.34mW

R = 20cm

Power Density RequirementFrom table 1 (b) - Limits for General Population/ Uncontrolled Exposure of
FCC Rule Part 1.1310 for 2.4GHz

$$S_{req2} = 1.0 \text{ mW/cm}^2$$

Calculation:

$$S = 62.34 / 4 \pi R^2$$

$$S = 62.34 / (12.56 \times 20^2)$$

$$S = 62.34 / (5024)$$

$$S_2 = 0.012 \text{ mW/cm}^2 (< 1.0 \text{ mW/cm}^2)$$

KDB447498 D01 v05 Section 7.2 SIMULTANEOUS TRANSMISSION CONSIDERATIONS

The equipment operates from a single antenna. All transmitters can transmit simultaneously.

As per KDB, summation of calculated MPE ratios for WLAN 2.4GHz + 5GHz:

$$\begin{aligned} \Sigma \text{MPE}_{ratios} &= (S_1 / S_{req1}) + (S_2 / S_{req2}) \\ &= (1.9 \times 10^{-7} / 0.98) + (0.012 / 1.0) \\ &= 0.012 \end{aligned}$$

Σ of MPE ratios < 1.0, so in accordance with KDB447498 Section 7.2, simultaneous transmission test exclusion applies for the transmitters.

Conclusion

The required 20cm RF exposure limits for General Population/ Uncontrolled Exposure will not be exceeded for the AP60

PRO
Krug & Priester GmbH & Co. KG
Simon-Schweitzer-Str. 34
D-72336 Balingen
Telefon 0 74 33 / 269-0
Telefax 0 74 33 / 269-200
info@krug-priester.com

GF: Dr. Ralf Krohn, Daniel Priester
KG: Registergericht Stuttgart
HRA 410147; PhG Priester GmbH
Balingen: Registergericht
Stuttgart HRB 410079
Steuer-Nr.: 53088/06369

Sparkasse Zollernalb, Nr. 24 000 433, BLZ 653 512 60,
IBAN: DE02 6535 1260 0024 0004 33, BIC: SOLADES1BAL
Commerzbank Balingen, Nr. 1211 283, BLZ 653 412 04,
IBAN: DE70 6534 1204 0121 1283 00, BIC: COBADEFFXXX
Deutsche Bank Albstadt, Nr. 811 000, BLZ 653 700 75,
IBAN: DE03 6537 0075 0081 1000 00, BIC: DEUTDESS653

Unsere Marken:
Our Brands:

IDEAL
EBA

