

FCC SAR Exclusion Report

Product name : SC 358 E3 Connect
Applicant : Lukas Hydraulik GmbH
FCC ID : 2A3RJ-E3CS

Test report No. : 210300633 003 Ver 5.00



Report number: 210300633 003 Ver 5.00

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

| | |
|---------------------------|---|
| Test Site | Kiwa Telefication BV |
| Test Site location | Wilmersdorf 50 7327 AC Apeldoorn The Netherlands Tel. +31 88998 3393 |
| Test Site FCC | NL0001 |
| CABID | NL0001 |



Report number: 210300633 003 Ver 5.00

Revision History

| Version | Date | Remarks | By |
|---------|------------|--|-----|
| v1.00 | 07-07-2021 | Release version | R.T |
| v2.00 | 22-12-2021 | Updated FCC +ISED ID | R.T |
| v3.00 | 23-03-2022 | Updated Clause 1.4 from mobile to portable Clause 1.4.1 updated Wi-Fi output power | R.T |
| V4.00 | 1-12-2023 | Updated model list | LdG |
| V5.00 | 07-12-2023 | Updated model list | LdG |

Table of Contents

| | |
|---|----------|
| Revision History | 2 |
| 1 General Description | 4 |
| 1.1 Applicant | 4 |
| 1.2 Manufacturer | 4 |
| 1.3 Tested Equipment Under Test (EUT)..... | 4 |
| 2 SAR exclusion Evaluation | 6 |
| 2.1 Transmitter specifications..... | 6 |
| 2.2 Evaluation calculations..... | 7 |
| 2.3 Conclusion | 9 |

1 General Description

1.1 Applicant

Client name: Lukas Hydraulik GmbH
Address: Weinstrasse 39, 91058 Erlangen, Germany
Telephone: +49 9131 / 698 - 274
E-mail: tlittwin@idexcorp.com
Contact name: Thomas Littwin

1.2 Manufacturer

Manufacturer name: Hurst Jaws of Life INC
Address: 711 North Post Road, 28150, NC, Shelby, USA
Telephone: +1 800 537 3646
E-mail: afinch@idexcorp.com
Contact name: Adam Finch

1.3 Tested Equipment Under Test (EUT)

| | |
|--------------------------------|-----------------------|
| Product name: | SC 358 E3 Connect |
| Brand name: | HURST Jaws of Life |
| FCC ID: | 2A3RJ-E3CS |
| Product type: | Hydraulic Rescue Tool |
| Model(s): | See next page |
| Batch and/or serial No. | See next page |
| Software version: | - |
| Hardware version: | - |
| Date of receipt | 08-06-2021 |
| Tests started: | 14-06-2021 |
| Testing ended: | 17-06-2021 |

Overview of variant models

Model overview

| OEM/Variant | Description | Trademark | Type Designation |
|-------------|-----------------------|-----------|-------------------|
| Variant | Hydraulic Rescue Tool | HURST | S 378 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | S 789 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | S 799 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | SC 258 E3 Connect |
| OEM | Hydraulic Rescue Tool | HURST | SC 358 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | SC 758 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | SP 333 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | SP 555 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | SP 775 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | SP 777 E3 Connect |
| Variant | Hydraulic Rescue Tool | HURST | M 40 E3 Connect |

2 SAR exclusion Evaluation

2.1 Transmitter specifications

Transmitter 1 (WIFI B)

| Variable (unit) | Value | Symbol |
|---|-------|------------------|
| Conducted time-averaged output power (mW) | 70,79 | P |
| Time-averaged output power ERP (mW) | 70,79 | P _{ERP} |
| Operating frequency range (MHz) | 2412 | f |
| Separation distance (cm) | 3.5 | d |
| Separation distance (m) | 0.035 | R |

Note: The output power of the WIFI B module can be found in test report 210300633 001

Transmitter 2 (BT)

| Variable (unit) | Value | Symbol |
|---|-------|------------------|
| Conducted time-averaged output power (mW) | 10 | P |
| Time-averaged output power ERP (mW) | 10 | P _{ERP} |
| Operating frequency range (MHz) | 2402 | f |
| Separation distance (cm) | 3.5 | D |
| Separation distance (m) | 0.035 | R |

Note: The output power of the BT module can be found in test report test report No. RSHD200218007-00A

2.2 Evaluation calculations

Transmitter 1

Transmitter 1 is evaluated according to method B of KDB 447498 D04 v01

Method B:

$$P_{th}(mW) = \begin{cases} ERP_{20cm} \left(\frac{d}{20cm} \right)^x & d \leq 20 \text{ cm} \\ ERP_{20cm} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} * \sqrt{f}} \right)$$

$$ERP_{20cm}(mW) = \begin{cases} 2040 * f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6.0 \text{ GHz} \end{cases}$$

Filling in the values of d (cm) and f (GHz) as reported in clause 2.1 in the equations above gives the result:

$P_{th} = 113 \text{ mW}$

P or $P_{ERP} = 70.79 \text{ mW}$ which is less than the calculated P_{th} so the EUT complies with the SAR based exemption requirement.

Transmitter 2

Transmitter 2 is evaluated according to method B of KDB 447498 D04 v01

Method B:

$$P_{th}(mW) = \begin{cases} ERP_{20cm} \left(\frac{d}{20cm} \right)^x & d \leq 20 \text{ cm} \\ ERP_{20cm} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} * \sqrt{f}} \right)$$

$$ERP_{20cm}(mW) = \begin{cases} 2040 * f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6.0 \text{ GHz} \end{cases}$$

Filling in the values of d (cm) and f (GHz) as reported in clause 2.1 in the equations above gives the result:

 $P_{th} = 113 \text{ mW}$ P or $P_{ERP} = 10 \text{ mW}$ which is less than the calculated P_{th} so the EUT complies with the SAR based exemption requirement.

2.3 Conclusion

Since the EUT does not cause exposure in excess of the general population limit, no additional mitigation actions are required.