



11G_Ant1_2462




Date: 23.JAN.2025 11:26:49

11N20SISO_Ant1_2412




Date: 23.JAN.2025 11:30:50

11N20SISO_Ant1_2437




Date: 23 JAN 2025 11:51:50

11N20SISO_Ant1_2462



Date: 23 JAN 2025 12:02:42


5.6 Power Spectral Density


Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass

Test Result


TestMode	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	-16.25	≤8.00	PASS
	2437	-16.60	≤8.00	PASS
	2462	-16.65	≤8.00	PASS
11G	2412	-13.53	≤8.00	PASS
	2437	-13.54	≤8.00	PASS
	2462	-14.15	≤8.00	PASS
11N20SISO	2412	-13.20	≤8.00	PASS
	2437	-13.90	≤8.00	PASS
	2462	-13.80	≤8.00	PASS

Test Graphs







11G_Ant1_2412



11G_Ant1_2437




11G_Ant1_2462




Date: 23.JAN.2025 11:27:07

11N20SISO_Ant1_2412




Date: 23.JAN.2025 11:31:10


11N20SISO_Ant1_2437



11N20SISO_Ant1_2462




5.7 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test Result

TestMode	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Low	2412	-0.97	-47.01	≤ -30.97	PASS
	High	2462	-1.44	-47.33	≤ -31.44	PASS
11G	Low	2412	-7.77	-47.18	≤ -37.77	PASS
	High	2462	-8.45	-46.61	≤ -38.45	PASS
11N20SISO	Low	2412	-5.71	-46.53	≤ -35.71	PASS
	High	2462	-6.07	-47.05	≤ -36.07	PASS


5.7.1 Test Graphs





Date: 23 JAN 2025 11:19:50

11G_Ant1_High_2462




Date: 23 JAN 2025 11:27:15

11N20SISO_Ant1_Low_2412




Date: 23 JAN 2025 11:31:18

11N20SISO_Ant1_High_2462



Date: 23.JAN.2025 12:03:08


5.8 RF Conducted Spurious Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test Result

TestMode	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	Reference	0.03	0.03	---	PASS
		30~1000	0.03	-53.97	≤ -29.97	PASS
		1000~26500	0.03	-48.81	≤ -29.97	PASS
	2437	Reference	-1.50	-1.50	---	PASS
		30~1000	-1.50	-54.94	≤ -31.5	PASS
		1000~26500	-1.50	-49.14	≤ -31.5	PASS
	2462	Reference	-1.83	-1.83	---	PASS
		30~1000	-1.83	-55.08	≤ -31.83	PASS
		1000~26500	-1.83	-49.09	≤ -31.83	PASS
11G	2412	Reference	-7.93	-7.93	---	PASS
		30~1000	-7.93	-54.5	≤ -37.93	PASS
		1000~26500	-7.93	-50.55	≤ -37.93	PASS
	2437	Reference	-7.78	-7.78	---	PASS
		30~1000	-7.78	-54.38	≤ -37.78	PASS
		1000~26500	-7.78	-49.95	≤ -37.78	PASS
	2462	Reference	-8.32	-8.32	---	PASS
		30~1000	-8.32	-55.3	≤ -38.32	PASS
		1000~26500	-8.32	-50.83	≤ -38.32	PASS
11N20SISO	2412	Reference	-4.86	-4.86	---	PASS
		30~1000	-4.86	-53.96	≤ -34.86	PASS
		1000~26500	-4.86	-50.28	≤ -34.86	PASS
	2437	Reference	-8.35	-8.35	---	PASS
		30~1000	-8.35	-52.48	≤ -38.35	PASS
		1000~26500	-8.35	-49.59	≤ -38.35	PASS
	2462	Reference	-9.46	-9.46	---	PASS
		30~1000	-9.46	-54.03	≤ -39.46	PASS
		1000~26500	-9.46	-51.06	≤ -39.46	PASS


Test Graphs






Date: 23 JAN 2025 11:12:47

11B_Ant1_2437_0~Reference




Date: 23 JAN 2025 11:14:12

11B_Ant1_2437_30~1000




Date: 23 JAN 2025 11:14:16

11B_Ant1_2437_1000~26500




Date: 23.JAN.2025 11:14:27

11B_Ant1_2462_0~Reference




Date: 23.JAN.2025 11:17:33

11B_Ant1_2462_30~1000



11B_Ant1_2462_1000~26500



11G_Ant1_2412_0~Reference

