

可编程胎压传感器说明书

TPS800-1 Programmable Tire Pressure Sensor Manual

1. 产品特点 Product Characteristics

TPS800-1 型可编程胎压传感器是配合 TPS800 胎压编程器使用的胎压传感器，该胎压传感器具有体积小，重量轻的特点。

The TPS800-1 programmable tire pressure sensor is a tire pressure sensor used with the TPS800 tire pressure programmer. The tire pressure sensor has the characteristics of small size and light weight.

TPS800-1 型可编程胎压传感器可以通过 TPS800 胎压编程器根据用户车型需求编程各种车型的胎压传感器软件，从而支持市面上 95% 车型使用。

The TPS800-1 programmable tire pressure sensor can be used to program the tire pressure sensor software of various models according to the needs of the user's model through the TPS800 tire pressure programmer, so as to support the use of 95% of the models on the market.

2. 产品参数 Product Parameters

电压 Voltage	:	3.0V
电流 Current	静态 Static	500mA
	发送 Send	8mA
防护等级 Protection Class	:	IP67
主要材质 Main Material	:	PA66 + GF30
使用寿命 Service life	:	3 Years

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction

FCC ID: 2A3UN-TPS800-1