

FCC TEST REPORT

FCC ID:2A3WB-S100

Report Number..... : ZKT-211130L6558-01

Date of Test..... Nov. 11, 2021 -- Dec. 08, 2021

Date of issue : Dec. 08, 2021

Total number of pages 88

Test Result : PASS

Testing Laboratory..... : **Shenzhen ZKT Technology Co., Ltd.**

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : KMS Partner

Address : 1127, 205-7, Gasan digital 1-ro, Geumcheon-gu, Seoul, Republic of Korea

Manufacturer's name : ShenZhen Homan Technology Co., LTD

Address : Room 808A, Block A, Zhihui Chuangxin Center, Baoan, Shenzhen

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

KDB558074 D0115.247 Meas Guidance v 05r02

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-110_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : PROJECTOR


Trademark : /

Model/Type reference : S100, S90, S180, S60, S500, H150, H90, H180, FS180, FS280, FS500

Ratings..... : DC 7.4V from battery / DC 15V from adapter

Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.
Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature): Alen He 

Reviewer (name + signature).....: Joe Liu 

Approved (name + signature): Lake Xie 

Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	9
4. EMC EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
4.1.2 TEST PROCEDURE	11
4.1.3 DEVIATION FROM TEST STANDARD	11
4.1.4 TEST SETUP	12
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 TEST RESULT	13
4.2 RADIATED EMISSION MEASUREMENT	15
4.2.1 RADIATED EMISSION LIMITS	15
4.2.2 TEST PROCEDURE	15
4.2.3 DEVIATION FROM TEST STANDARD	16
4.2.4 TEST SETUP	16
4.2.5 EUT OPERATING CONDITIONS	17
4.2.6 TEST RESULTS	18
5.RADIATED BAND EMISSIONMEASUREMENT	31
5.1 TEST REQUIREMENT:	31
5.2 TEST PROCEDURE	31
5.3 DEVIATION FROM TEST STANDARD	31
5.4 TEST SETUP	32
5.5 EUT OPERATING CONDITIONS	32
5.6 TEST RESULT	33
6.POWER SPECTRAL DENSITY TEST	38
6.1 APPLIED PROCEDURES / LIMIT	38
6.2 TEST PROCEDURE	38
6.3 DEVIATION FROM STANDARD	38
6.4 TEST SETUP	38
6.5 EUT OPERATION CONDITIONS	38

6.6 TEST RESULT	39
7. CHANNEL BANDWIDTH	44
7.1 APPLIED PROCEDURES / LIMIT	44
7.2 TEST PROCEDURE	44
7.3 DEVIATION FROM STANDARD	44
7.4 TEST SETUP	44
7.5 EUT OPERATION CONDITIONS	44
7.6 TEST RESULT	45
8.OUTPUT POWER TEST	50
8.1 APPLIED PROCEDURES/LIMIT	50
8.2 TEST PROCEDURE	50
8.3 DEVIATION FROM STANDARD	50
8.4 TEST SETUP	50
8.5 EUT OPERATION CONDITIONS	50
8.6 TEST RESULT	51
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	52
9.1 APPLICABLE STANDARD	52
9.2 TEST PROCEDURE	52
9.3 DEVIATION FROM STANDARD	52
9.4 TEST SETUP	52
9.5 EUT OPERATION CONDITIONS	52
9.6 TEST RESULTS	52
10. ANTENNA REQUIREMENT	85
11. TEST SETUP PHOTO	86
12. EUT CONSTRUCTIONAL DETAILS	88

1. VERSION

ReportNo.	Version	Description	Approved
ZKT-211130L6558-01	Rev.01	Initial issue of report	Dec. 08, 2021

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth& 99% OCB	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF powerconducted	$\pm 0.16\text{dB}$
3	Spurious emissionsconducted	$\pm 0.21\text{dB}$
4	All emissionsradiated(<1G)	$\pm 4.68\text{dB}$
5	All emissionsradiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	PROJECTOR	
Model No.:	S100	
Model Different.:	All models have the same functionality, software and electronics, only the model names may differ. Test sample model: S100	
Serial No.:	S90, S180, S60, S500, H150, H90, H180, FS180, FS280, FS500	
Sample(s) Status:	Engineer sample	
Channel numbers:	802.11b/802.11g /802.11n(HT20):11 802.11n(HT40):7	
Channel separation:	5MHz	
Modulation technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/802.11n(H20)/802.11 n(HT40): Orthogonal Frequency Division Multiplexing(OFDM)	
Antenna Type:	FPC antenna	
Antenna gain:	WIFI ANT1: 3dBi; WIFI ANT2:: 3dBi ;	MIMO: 6.01dBi
Power supply:	DC 7.4V from battery	
POWER ADAPTER:	MODEL NO.:FJ-SW126G1501500N INPUT:100-240V ~ 50/60Hz 0.6A Max	

OUTPUT: 15.0V $\approx$ 1.5A, 22.52w

NOTE: The product has two wifi modules that support 2.4GWIFI. In order to distinguish the test data and results, they will be divided into module A and module B

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

Test channel	Frequency (MHz)
	802.11n(HT40)
Lowest channel	2422MHz
Middle channel	2437MHz
Highest channel	2452MHz

WorstCase Configuration

Description	MIMO (802.11N-HT20 low channel)
Antenna	MIMO
Channel	1
Operating Frequency (MHz)	2412
Data Rate (Mbps)	6.5Mbps

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test,the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	MCS0

Test Software	Realtek Test Tool
Powerlevelsetup	<20dBm

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	adapter	/	INPUT:100-240V ~ 50/60Hz 0.6A Max OUTPUT: 15.0V  1.5A, 22.52w	MODEL NO.: FJ-SW126G1501500N	Provide by client

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
------	-----------	--------------	----------	------------	------------------	------------------

1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 21, 2021	Sep. 22, 2022
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 21, 2021	Sep. 22, 2022
3	Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Sep. 21, 2021	Sep. 22, 2022
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 21, 2021	Sep. 22, 2022
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 21, 2021	Sep. 22, 2022
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 21, 2021	Sep. 22, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 21, 2021	Sep. 22, 2022
8	Amplifier (1GHz-40GHz)	QUANJUDA	DLE-161	097	Sep. 21, 2021	Sep. 22, 2022
9	Loop Antenna (9kHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 21, 2021	Sep. 22, 2022
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 21, 2021	Sep. 22, 2022
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
13	CMW500 Test	R&S	CMW500	106504	Sep. 21, 2021	Sep. 22, 2022
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 21, 2021	Sep. 22, 2022
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 21, 2021	Sep. 22, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
17	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 21, 2021	Sep. 22, 2022
2	LISN	CYBERTEK	EM5040A	E185040014 9	Sep. 21, 2021	Sep. 22, 2022
3	Test Cable	N/A	C01	N/A	Sep. 21, 2021	Sep. 22, 2022
4	Test Cable	N/A	C02	N/A	Sep. 21, 2021	Sep. 22, 2022
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 21, 2021	Sep. 22, 2022
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 21, 2021	Sep. 22, 2022

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.e.
8. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT


Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase	L
Test Voltage :	AC 120V/60Hz		



Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	36.20	9.75	45.95	65.99	-20.04	QP	
2		0.1700	18.55	9.75	28.30	54.96	-26.66	AVG	
3	*	0.2140	34.15	9.76	43.91	63.04	-19.13	QP	
4		0.2260	17.58	9.76	27.34	52.59	-25.25	AVG	
5		0.3860	25.57	9.87	35.44	58.15	-22.71	QP	
6		0.3980	10.21	9.87	20.08	47.89	-27.81	AVG	
7		1.9140	6.21	9.66	15.87	46.00	-30.13	AVG	
8		2.4860	20.52	9.70	30.22	56.00	-25.78	QP	
9		4.3700	5.51	9.67	15.18	46.00	-30.82	AVG	
10		5.2819	20.11	9.65	29.76	60.00	-30.24	QP	
11		13.7820	4.71	9.72	14.43	50.00	-35.57	AVG	
12		14.1340	18.32	9.70	28.02	60.00	-31.98	QP	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different from above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 metre to 1.5 metre (Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case-MIMO -802.11N-HT20 highest channel

1GHz~25GHz

802.11b-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	53.47	30.55	5.77	24.66	53.35	74.00	-20.65	PK
V	4824	44.90	30.55	5.77	24.66	44.78	54.00	-9.22	AV
V	7236	55.43	30.33	6.32	24.55	55.97	74.00	-18.03	PK
V	7236	47.41	30.33	6.32	24.55	47.95	54.00	-6.05	AV
V	9648	44.50	30.85	7.45	24.69	45.79	74.00	-28.21	PK
V	9648	45.95	30.85	7.45	24.69	47.24	54.00	-6.76	AV
H	4824	43.63	31.02	8.99	25.57	47.17	74.00	-26.83	PK
H	4824	43.69	31.02	8.99	25.57	47.23	54.00	-6.77	AV
H	7236	45.91	30.55	5.77	24.66	45.79	74.00	-28.21	PK
H	7236	44.40	30.55	5.77	24.66	44.28	54.00	-9.72	AV
H	9648	44.89	30.33	6.32	24.55	45.43	74.00	-28.57	PK
H	9648	45.05	30.33	6.32	24.55	45.59	54.00	-8.41	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	58.28	30.55	5.77	24.66	58.16	74.00	-15.84	PK
V	4874	45.29	30.55	5.77	24.66	45.17	54.00	-8.83	AV
V	7311	57.29	30.33	6.32	24.55	57.83	74.00	-16.17	PK
V	7311	44.73	30.33	6.32	24.55	45.27	54.00	-8.73	AV
V	9748	46.51	30.85	7.45	24.69	47.80	74.00	-26.20	PK
V	9748	45.37	30.85	7.45	24.69	46.66	54.00	-7.34	AV
H	4874	45.48	31.02	8.99	25.57	49.02	74.00	-24.98	PK
H	4874	44.90	31.02	8.99	25.57	48.44	54.00	-5.56	AV
H	7311	44.83	30.55	5.77	24.66	44.71	74.00	-29.29	PK
H	7311	45.74	30.55	5.77	24.66	45.62	54.00	-8.38	AV
H	9748	44.32	30.33	6.32	24.55	44.86	74.00	-29.14	PK
H	9748	46.23	30.33	6.32	24.55	46.77	54.00	-7.23	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	56.71	30.55	5.77	24.66	56.59	74.00	-17.41	PK
V	4924	45.44	30.55	5.77	24.66	45.32	54.00	-8.68	AV
V	7386	57.13	30.33	6.32	24.55	57.67	74.00	-16.33	PK
V	7386	46.50	30.33	6.32	24.55	47.04	54.00	-6.96	AV
V	9848	45.25	30.85	7.45	24.69	46.54	74.00	-27.46	PK
V	9848	44.06	30.85	7.45	24.69	45.35	54.00	-8.65	AV
H	4924	45.64	31.02	8.99	25.57	49.18	74.00	-24.82	PK
H	4924	45.35	31.02	8.99	25.57	48.89	54.00	-5.11	AV
H	7386	44.17	30.55	5.77	24.66	44.05	74.00	-29.95	PK
H	7386	43.92	30.55	5.77	24.66	43.80	54.00	-10.20	AV
H	9848	44.96	30.33	6.32	24.55	45.50	74.00	-28.50	PK
H	9848	46.26	30.33	6.32	24.55	46.80	54.00	-7.20	AV

802.11g-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	57.69	30.55	5.77	24.66	57.57	74.00	-16.43	PK
V	4824	44.92	30.55	5.77	24.66	44.80	54.00	-9.20	AV
V	7236	56.17	30.33	6.32	24.55	56.71	74.00	-17.29	PK
V	7236	47.53	30.33	6.32	24.55	48.07	54.00	-5.93	AV
V	9648	44.94	30.85	7.45	24.69	46.23	74.00	-27.77	PK
V	9648	45.14	30.85	7.45	24.69	46.43	54.00	-7.57	AV
H	4824	45.48	31.02	8.99	25.57	49.02	74.00	-24.98	PK
H	4824	46.32	31.02	8.99	25.57	49.86	54.00	-4.14	AV
H	7236	43.83	30.55	5.77	24.66	43.71	74.00	-30.29	PK
H	7236	46.06	30.55	5.77	24.66	45.94	54.00	-8.06	AV
H	9648	45.01	30.33	6.32	24.55	45.55	74.00	-28.45	PK
H	9648	44.01	30.33	6.32	24.55	44.55	54.00	-9.45	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	55.56	30.55	5.77	24.66	55.44	74.00	-18.56	PK
V	4874	45.21	30.55	5.77	24.66	45.09	54.00	-8.91	AV
V	7311	55.60	30.33	6.32	24.55	56.14	74.00	-17.86	PK
V	7311	44.88	30.33	6.32	24.55	45.42	54.00	-8.58	AV
V	9748	45.93	30.85	7.45	24.69	47.22	74.00	-26.78	PK
V	9748	44.93	30.85	7.45	24.69	46.22	54.00	-7.78	AV
H	4874	44.60	31.02	8.99	25.57	48.14	74.00	-25.86	PK
H	4874	46.39	31.02	8.99	25.57	49.93	54.00	-4.07	AV
H	7311	46.22	30.55	5.77	24.66	46.10	74.00	-27.90	PK
H	7311	46.31	30.55	5.77	24.66	46.19	54.00	-7.81	AV
H	9748	44.13	30.33	6.32	24.55	44.67	74.00	-29.33	PK
H	9748	44.26	30.33	6.32	24.55	44.80	54.00	-9.20	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2462MHz									
V	4924	52.37	30.55	5.77	24.66	52.25	74.00	-21.75	PK
V	4924	45.16	30.55	5.77	24.66	45.04	54.00	-8.96	AV
V	7386	55.23	30.33	6.32	24.55	55.77	74.00	-18.23	PK
V	7386	46.48	30.33	6.32	24.55	47.02	54.00	-6.98	AV
V	9848	45.96	30.85	7.45	24.69	47.25	74.00	-26.75	PK
V	9848	44.25	30.85	7.45	24.69	45.54	54.00	-8.46	AV
H	4924	45.76	31.02	8.99	25.57	49.30	74.00	-24.70	PK
H	4924	44.87	31.02	8.99	25.57	48.41	54.00	-5.59	AV
H	7386	46.44	30.55	5.77	24.66	46.32	74.00	-27.68	PK
H	7386	43.87	30.55	5.77	24.66	43.75	54.00	-10.25	AV
H	9848	45.69	30.33	6.32	24.55	46.23	74.00	-27.77	PK
H	9848	44.69	30.33	6.32	24.55	45.23	54.00	-8.77	AV

802.11n20-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	52.86	30.55	5.77	24.66	52.74	74.00	-21.26	PK
V	4824	44.54	30.55	5.77	24.66	44.42	54.00	-9.58	AV
V	7236	56.35	30.33	6.32	24.55	56.89	74.00	-17.11	PK
V	7236	46.52	30.33	6.32	24.55	47.06	54.00	-6.94	AV
V	9648	43.61	30.85	7.45	24.69	44.90	74.00	-29.10	PK
V	9648	45.15	30.85	7.45	24.69	46.44	54.00	-7.56	AV
H	4824	43.89	31.02	8.99	25.57	47.43	74.00	-26.57	PK
H	4824	44.03	31.02	8.99	25.57	47.57	54.00	-6.43	AV
H	7236	46.22	30.55	5.77	24.66	46.10	74.00	-27.90	PK
H	7236	43.74	30.55	5.77	24.66	43.62	54.00	-10.38	AV
H	9648	45.49	30.33	6.32	24.55	46.03	74.00	-27.97	PK
H	9648	46.23	30.33	6.32	24.55	46.77	54.00	-7.23	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	55.16	30.55	5.77	24.66	55.04	74.00	-18.96	PK
V	4874	43.47	30.55	5.77	24.66	43.35	54.00	-10.65	AV
V	7311	55.88	30.33	6.32	24.55	56.42	74.00	-17.58	PK
V	7311	45.55	30.33	6.32	24.55	46.09	54.00	-7.91	AV
V	9748	45.61	30.85	7.45	24.69	46.90	74.00	-27.10	PK
V	9748	43.98	30.85	7.45	24.69	45.27	54.00	-8.73	AV
H	4874	44.68	31.02	8.99	25.57	48.22	74.00	-25.78	PK
H	4874	45.84	31.02	8.99	25.57	49.38	54.00	-4.62	AV
H	7311	44.33	30.55	5.77	24.66	44.21	74.00	-29.79	PK
H	7311	43.72	30.55	5.77	24.66	43.60	54.00	-10.40	AV
H	9748	43.92	30.33	6.32	24.55	44.46	74.00	-29.54	PK
H	9748	43.82	30.33	6.32	24.55	44.36	54.00	-9.64	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	57.20	30.55	5.77	24.66	57.08	74.00	-16.92	PK
V	4924	43.27	30.55	5.77	24.66	43.15	54.00	-10.85	AV
V	7386	54.78	30.33	6.32	24.55	55.32	74.00	-18.68	PK
V	7386	46.05	30.33	6.32	24.55	46.59	54.00	-7.41	AV
V	9848	45.65	30.85	7.45	24.69	46.94	74.00	-27.06	PK
V	9848	45.34	30.85	7.45	24.69	46.63	54.00	-7.37	AV
H	4924	45.34	31.02	8.99	25.57	48.88	74.00	-25.12	PK
H	4924	43.78	31.02	8.99	25.57	47.32	54.00	-6.68	AV
H	7386	45.64	30.55	5.77	24.66	45.52	74.00	-28.48	PK
H	7386	43.83	30.55	5.77	24.66	43.71	54.00	-10.29	AV
H	9848	45.55	30.33	6.32	24.55	46.09	74.00	-27.91	PK
H	9848	43.97	30.33	6.32	24.55	44.51	54.00	-9.49	AV

802.11n40-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844	57.84	30.55	5.77	24.66	57.72	74.00	-16.28	PK
V	4844	42.69	30.55	5.77	24.66	42.57	54.00	-11.43	AV
V	7266	56.91	30.33	6.32	24.55	57.45	74.00	-16.55	PK
V	7266	45.23	30.33	6.32	24.55	45.77	54.00	-8.23	AV
V	9688	43.84	30.85	7.45	24.69	45.13	74.00	-28.87	PK
V	9688	45.87	30.85	7.45	24.69	47.16	54.00	-6.84	AV
H	4844	45.36	31.02	8.99	25.57	48.90	74.00	-25.10	PK
H	4844	44.63	31.02	8.99	25.57	48.17	54.00	-5.83	AV
H	7266	43.88	30.55	5.77	24.66	43.76	74.00	-30.24	PK
H	7266	43.96	30.55	5.77	24.66	43.84	54.00	-10.16	AV
H	9688	43.68	30.33	6.32	24.55	44.22	74.00	-29.78	PK
H	9688	45.98	30.33	6.32	24.55	46.52	54.00	-7.48	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	52.99	30.55	5.77	24.66	52.87	74.00	-21.13	PK
V	4874	43.24	30.55	5.77	24.66	43.12	54.00	-10.88	AV
V	7311	54.62	30.33	6.32	24.55	55.16	74.00	-18.84	PK
V	7311	45.76	30.33	6.32	24.55	46.30	54.00	-7.70	AV
V	9748	45.52	30.85	7.45	24.69	46.81	74.00	-27.19	PK
V	9748	43.79	30.85	7.45	24.69	45.08	54.00	-8.92	AV
H	4874	43.63	31.02	8.99	25.57	47.17	74.00	-26.83	PK
H	4874	46.21	31.02	8.99	25.57	49.75	54.00	-4.25	AV
H	7311	44.71	30.55	5.77	24.66	44.59	74.00	-29.41	PK
H	7311	44.56	30.55	5.77	24.66	44.44	54.00	-9.56	AV
H	9748	44.56	30.33	6.32	24.55	45.10	74.00	-28.90	PK
H	9748	45.86	30.33	6.32	24.55	46.40	54.00	-7.60	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904	52.71	30.55	5.77	24.66	52.59	74.00	-21.41	PK
V	4904	42.91	30.55	5.77	24.66	42.79	54.00	-11.21	AV
V	7356	55.18	30.33	6.32	24.55	55.72	74.00	-18.28	PK
V	7356	46.61	30.33	6.32	24.55	47.15	54.00	-6.85	AV
V	9808	46.53	30.85	7.45	24.69	47.82	74.00	-26.18	PK
V	9808	46.26	30.85	7.45	24.69	47.55	54.00	-6.45	AV
H	4904	44.35	31.02	8.99	25.57	47.89	74.00	-26.11	PK
H	4904	45.59	31.02	8.99	25.57	49.13	54.00	-4.87	AV
H	7356	46.53	30.55	5.77	24.66	46.41	74.00	-27.59	PK
H	7356	44.04	30.55	5.77	24.66	43.92	54.00	-10.08	AV
H	9808	44.43	30.33	6.32	24.55	44.97	74.00	-29.03	PK
H	9808	45.15	30.33	6.32	24.55	45.69	54.00	-8.31	AV

802.11b-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	57.63	30.55	5.77	24.66	57.51	74.00	-16.49	PK
V	4824	43.25	30.55	5.77	24.66	43.13	54.00	-10.87	AV
V	7236	56.48	30.33	6.32	24.55	57.02	74.00	-16.98	PK
V	7236	47.18	30.33	6.32	24.55	47.72	54.00	-6.28	AV
V	9648	45.36	30.85	7.45	24.69	46.65	74.00	-27.35	PK
V	9648	45.19	30.85	7.45	24.69	46.48	54.00	-7.52	AV
H	4824	45.50	31.02	8.99	25.57	49.04	74.00	-24.96	PK
H	4824	45.41	31.02	8.99	25.57	48.95	54.00	-5.05	AV
H	7236	45.52	30.55	5.77	24.66	45.40	74.00	-28.60	PK
H	7236	44.19	30.55	5.77	24.66	44.07	54.00	-9.93	AV
H	9648	45.27	30.33	6.32	24.55	45.81	74.00	-28.19	PK
H	9648	45.88	30.33	6.32	24.55	46.42	54.00	-7.58	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	56.58	30.55	5.77	24.66	56.46	74.00	-17.54	PK
V	4874	44.06	30.55	5.77	24.66	43.94	54.00	-10.06	AV
V	7311	57.23	30.33	6.32	24.55	57.77	74.00	-16.23	PK
V	7311	46.25	30.33	6.32	24.55	46.79	54.00	-7.21	AV
V	9748	43.72	30.85	7.45	24.69	45.01	74.00	-28.99	PK
V	9748	44.18	30.85	7.45	24.69	45.47	54.00	-8.53	AV
H	4874	45.81	31.02	8.99	25.57	49.35	74.00	-24.65	PK
H	4874	45.23	31.02	8.99	25.57	48.77	54.00	-5.23	AV
H	7311	44.95	30.55	5.77	24.66	44.83	74.00	-29.17	PK
H	7311	44.84	30.55	5.77	24.66	44.72	54.00	-9.28	AV
H	9748	45.67	30.33	6.32	24.55	46.21	74.00	-27.79	PK
H	9748	46.23	30.33	6.32	24.55	46.77	54.00	-7.23	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	52.08	30.55	5.77	24.66	51.96	74.00	-22.04	PK
V	4924	43.53	30.55	5.77	24.66	43.41	54.00	-10.59	AV
V	7386	56.58	30.33	6.32	24.55	57.12	74.00	-16.88	PK
V	7386	47.49	30.33	6.32	24.55	48.03	54.00	-5.97	AV
V	9848	43.65	30.85	7.45	24.69	44.94	74.00	-29.06	PK
V	9848	45.44	30.85	7.45	24.69	46.73	54.00	-7.27	AV
H	4924	45.87	31.02	8.99	25.57	49.41	74.00	-24.59	PK
H	4924	46.05	31.02	8.99	25.57	49.59	54.00	-4.41	AV
H	7386	44.04	30.55	5.77	24.66	43.92	74.00	-30.08	PK
H	7386	44.90	30.55	5.77	24.66	44.78	54.00	-9.22	AV
H	9848	45.59	30.33	6.32	24.55	46.13	74.00	-27.87	PK
H	9848	44.62	30.33	6.32	24.55	45.16	54.00	-8.84	AV

802.11g-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	54.66	30.55	5.77	24.66	54.54	74.00	-19.46	PK
V	4824	45.39	30.55	5.77	24.66	45.27	54.00	-8.73	AV
V	7236	55.41	30.33	6.32	24.55	55.95	74.00	-18.05	PK
V	7236	46.74	30.33	6.32	24.55	47.28	54.00	-6.72	AV
V	9648	45.07	30.85	7.45	24.69	46.36	74.00	-27.64	PK
V	9648	46.13	30.85	7.45	24.69	47.42	54.00	-6.58	AV
H	4824	46.05	31.02	8.99	25.57	49.59	74.00	-24.41	PK
H	4824	44.69	31.02	8.99	25.57	48.23	54.00	-5.77	AV
H	7236	44.70	30.55	5.77	24.66	44.58	74.00	-29.42	PK
H	7236	44.07	30.55	5.77	24.66	43.95	54.00	-10.05	AV
H	9648	44.74	30.33	6.32	24.55	45.28	74.00	-28.72	PK
H	9648	43.99	30.33	6.32	24.55	44.53	54.00	-9.47	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	54.83	30.55	5.77	24.66	54.71	74.00	-19.29	PK
V	4874	45.52	30.55	5.77	24.66	45.40	54.00	-8.60	AV
V	7311	56.22	30.33	6.32	24.55	56.76	74.00	-17.24	PK
V	7311	45.32	30.33	6.32	24.55	45.86	54.00	-8.14	AV
V	9748	44.39	30.85	7.45	24.69	45.68	74.00	-28.32	PK
V	9748	46.46	30.85	7.45	24.69	47.75	54.00	-6.25	AV
H	4874	43.73	31.02	8.99	25.57	47.27	74.00	-26.73	PK
H	4874	46.33	31.02	8.99	25.57	49.87	54.00	-4.13	AV
H	7311	45.33	30.55	5.77	24.66	45.21	74.00	-28.79	PK
H	7311	43.94	30.55	5.77	24.66	43.82	54.00	-10.18	AV
H	9748	44.09	30.33	6.32	24.55	44.63	74.00	-29.37	PK
H	9748	46.46	30.33	6.32	24.55	47.00	54.00	-7.00	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	53.16	30.55	5.77	24.66	53.04	74.00	-20.96	PK
V	4924	45.16	30.55	5.77	24.66	45.04	54.00	-8.96	AV
V	7386	55.84	30.33	6.32	24.55	56.38	74.00	-17.62	PK
V	7386	45.84	30.33	6.32	24.55	46.38	54.00	-7.62	AV
V	9848	46.15	30.85	7.45	24.69	47.44	74.00	-26.56	PK
V	9848	43.77	30.85	7.45	24.69	45.06	54.00	-8.94	AV
H	4924	46.45	31.02	8.99	25.57	49.99	74.00	-24.01	PK
H	4924	44.66	31.02	8.99	25.57	48.20	54.00	-5.80	AV
H	7386	43.66	30.55	5.77	24.66	43.54	74.00	-30.46	PK
H	7386	45.88	30.55	5.77	24.66	45.76	54.00	-8.24	AV
H	9848	45.78	30.33	6.32	24.55	46.32	74.00	-27.68	PK
H	9848	43.61	30.33	6.32	24.55	44.15	54.00	-9.85	AV

802.11n-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	58.18	30.55	5.77	24.66	58.06	74.00	-15.94	PK
V	4824	44.89	30.55	5.77	24.66	44.77	54.00	-9.23	AV
V	7236	55.18	30.33	6.32	24.55	55.72	74.00	-18.28	PK
V	7236	45.06	30.33	6.32	24.55	45.60	54.00	-8.40	AV
V	9648	45.41	30.85	7.45	24.69	46.70	74.00	-27.30	PK
V	9648	46.22	30.85	7.45	24.69	47.51	54.00	-6.49	AV
H	4824	45.05	31.02	8.99	25.57	48.59	74.00	-25.41	PK
H	4824	43.69	31.02	8.99	25.57	47.23	54.00	-6.77	AV
H	7236	44.72	30.55	5.77	24.66	44.60	74.00	-29.40	PK
H	7236	44.31	30.55	5.77	24.66	44.19	54.00	-9.81	AV
H	9648	46.52	30.33	6.32	24.55	47.06	74.00	-26.94	PK
H	9648	46.37	30.33	6.32	24.55	46.91	54.00	-7.09	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	58.34	30.55	5.77	24.66	58.22	74.00	-15.78	PK
V	4874	45.09	30.55	5.77	24.66	44.97	54.00	-9.03	AV
V	7311	55.76	30.33	6.32	24.55	56.30	74.00	-17.70	PK
V	7311	46.02	30.33	6.32	24.55	46.56	54.00	-7.44	AV
V	9748	44.08	30.85	7.45	24.69	45.37	74.00	-28.63	PK
V	9748	45.07	30.85	7.45	24.69	46.36	54.00	-7.64	AV
H	4874	45.47	31.02	8.99	25.57	49.01	74.00	-24.99	PK
H	4874	45.81	31.02	8.99	25.57	49.35	54.00	-4.65	AV
H	7311	46.21	30.55	5.77	24.66	46.09	74.00	-27.91	PK
H	7311	44.70	30.55	5.77	24.66	44.58	54.00	-9.42	AV
H	9748	44.50	30.33	6.32	24.55	45.04	74.00	-28.96	PK
H	9748	44.10	30.33	6.32	24.55	44.64	54.00	-9.36	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	51.76	30.55	5.77	24.66	51.64	74.00	-22.36	PK
V	4924	44.29	30.55	5.77	24.66	44.17	54.00	-9.83	AV
V	7386	57.52	30.33	6.32	24.55	58.06	74.00	-15.94	PK
V	7386	47.30	30.33	6.32	24.55	47.84	54.00	-6.16	AV
V	9848	45.17	30.85	7.45	24.69	46.46	74.00	-27.54	PK
V	9848	45.39	30.85	7.45	24.69	46.68	54.00	-7.32	AV
H	4924	46.39	31.02	8.99	25.57	49.93	74.00	-24.07	PK
H	4924	46.46	31.02	8.99	25.57	50.00	54.00	-4.00	AV
H	7386	43.99	30.55	5.77	24.66	43.87	74.00	-30.13	PK
H	7386	44.39	30.55	5.77	24.66	44.27	54.00	-9.73	AV
H	9848	44.86	30.33	6.32	24.55	45.40	74.00	-28.60	PK
H	9848	46.23	30.33	6.32	24.55	46.77	54.00	-7.23	AV

802.11n40-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844	53.17	30.55	5.77	24.66	53.05	74.00	-20.95	PK
V	4844	42.96	30.55	5.77	24.66	42.84	54.00	-11.16	AV
V	7266	57.53	30.33	6.32	24.55	58.07	74.00	-15.93	PK
V	7266	46.33	30.33	6.32	24.55	46.87	54.00	-7.13	AV
V	9688	45.67	30.85	7.45	24.69	46.96	74.00	-27.04	PK
V	9688	44.49	30.85	7.45	24.69	45.78	54.00	-8.22	AV
H	4844	43.68	31.02	8.99	25.57	47.22	74.00	-26.78	PK
H	4844	44.21	31.02	8.99	25.57	47.75	54.00	-6.25	AV
H	7266	45.65	30.55	5.77	24.66	45.53	74.00	-28.47	PK
H	7266	45.93	30.55	5.77	24.66	45.81	54.00	-8.19	AV
H	9688	44.51	30.33	6.32	24.55	45.05	74.00	-28.95	PK
H	9688	43.71	30.33	6.32	24.55	44.25	54.00	-9.75	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	53.12	30.55	5.77	24.66	53.00	74.00	-21.00	PK
V	4874	43.36	30.55	5.77	24.66	43.24	54.00	-10.76	AV
V	7311	56.92	30.33	6.32	24.55	57.46	74.00	-16.54	PK
V	7311	47.18	30.33	6.32	24.55	47.72	54.00	-6.28	AV
V	9748	44.67	30.85	7.45	24.69	45.96	74.00	-28.04	PK
V	9748	44.60	30.85	7.45	24.69	45.89	54.00	-8.11	AV
H	4874	43.72	31.02	8.99	25.57	47.26	74.00	-26.74	PK
H	4874	45.96	31.02	8.99	25.57	49.50	54.00	-4.50	AV
H	7311	43.70	30.55	5.77	24.66	43.58	74.00	-30.42	PK
H	7311	45.68	30.55	5.77	24.66	45.56	54.00	-8.44	AV
H	9748	45.64	30.33	6.32	24.55	46.18	74.00	-27.82	PK
H	9748	45.46	30.33	6.32	24.55	46.00	54.00	-8.00	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904	57.36	30.55	5.77	24.66	57.24	74.00	-16.76	PK
V	4904	43.44	30.55	5.77	24.66	43.32	54.00	-10.68	AV
V	7356	56.73	30.33	6.32	24.55	57.27	74.00	-16.73	PK
V	7356	46.21	30.33	6.32	24.55	46.75	54.00	-7.25	AV
V	9808	46.43	30.85	7.45	24.69	47.72	74.00	-26.28	PK
V	9808	46.11	30.85	7.45	24.69	47.40	54.00	-6.60	AV
H	4904	46.29	31.02	8.99	25.57	49.83	74.00	-24.17	PK
H	4904	46.44	31.02	8.99	25.57	49.98	54.00	-4.02	AV
H	7356	44.61	30.55	5.77	24.66	44.49	74.00	-29.51	PK
H	7356	45.03	30.55	5.77	24.66	44.91	54.00	-9.09	AV
H	9808	46.12	30.33	6.32	24.55	46.66	74.00	-27.34	PK
H	9808	46.16	30.33	6.32	24.55	46.70	54.00	-7.30	AV

MIMO-802.11n

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	54.69	30.55	5.77	24.66	54.57	74.00	-19.43	PK
V	4824	44.84	30.55	5.77	24.66	44.72	54.00	-9.28	AV
V	7236	56.89	30.33	6.32	24.55	57.43	74.00	-16.57	PK
V	7236	45.48	30.33	6.32	24.55	46.02	54.00	-7.98	AV
V	9648	44.70	30.85	7.45	24.69	45.99	74.00	-28.01	PK
V	9648	46.29	30.85	7.45	24.69	47.58	54.00	-6.42	AV
H	4824	44.40	31.02	8.99	25.57	47.94	74.00	-26.06	PK
H	4824	46.12	31.02	8.99	25.57	49.66	54.00	-4.34	AV
H	7236	43.72	30.55	5.77	24.66	43.60	74.00	-30.40	PK
H	7236	45.61	30.55	5.77	24.66	45.49	54.00	-8.51	AV
H	9648	45.40	30.33	6.32	24.55	45.94	74.00	-28.06	PK
H	9648	45.29	30.33	6.32	24.55	45.83	54.00	-8.17	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	54.71	30.55	5.77	24.66	54.59	74.00	-19.41	PK
V	4874	45.02	30.55	5.77	24.66	44.90	54.00	-9.10	AV
V	7311	56.13	30.33	6.32	24.55	56.67	74.00	-17.33	PK
V	7311	44.87	30.33	6.32	24.55	45.41	54.00	-8.59	AV
V	9748	44.72	30.85	7.45	24.69	46.01	74.00	-27.99	PK
V	9748	44.91	30.85	7.45	24.69	46.20	54.00	-7.80	AV
H	4874	44.49	31.02	8.99	25.57	48.03	74.00	-25.97	PK
H	4874	43.82	31.02	8.99	25.57	47.36	54.00	-6.64	AV
H	7311	45.17	30.55	5.77	24.66	45.05	74.00	-28.95	PK
H	7311	43.88	30.55	5.77	24.66	43.76	54.00	-10.24	AV
H	9748	46.11	30.33	6.32	24.55	46.65	74.00	-27.35	PK
H	9748	45.70	30.33	6.32	24.55	46.24	54.00	-7.76	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	54.97	30.55	5.77	24.66	54.85	74.00	-19.15	PK
V	4924	44.01	30.55	5.77	24.66	43.89	54.00	-10.11	AV
V	7386	57.44	30.33	6.32	24.55	57.98	74.00	-16.02	PK
V	7386	45.87	30.33	6.32	24.55	46.41	54.00	-7.59	AV
V	9848	45.70	30.85	7.45	24.69	46.99	74.00	-27.01	PK
V	9848	44.36	30.85	7.45	24.69	45.65	54.00	-8.35	AV
H	4924	43.98	31.02	8.99	25.57	47.52	74.00	-26.48	PK
H	4924	45.05	31.02	8.99	25.57	48.59	54.00	-5.41	AV
H	7386	45.57	30.55	5.77	24.66	45.45	74.00	-28.55	PK
H	7386	45.81	30.55	5.77	24.66	45.69	54.00	-8.31	AV
H	9848	44.11	30.33	6.32	24.55	44.65	74.00	-29.35	PK
H	9848	43.63	30.33	6.32	24.55	44.17	54.00	-9.83	AV

MIMO-802.11n40

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844	52.10	30.55	5.77	24.66	51.98	74.00	-22.02	PK
V	4844	44.19	30.55	5.77	24.66	44.07	54.00	-9.93	AV
V	7266	57.57	30.33	6.32	24.55	58.11	74.00	-15.89	PK
V	7266	47.01	30.33	6.32	24.55	47.55	54.00	-6.45	AV
V	9688	44.09	30.85	7.45	24.69	45.38	74.00	-28.62	PK
V	9688	43.74	30.85	7.45	24.69	45.03	54.00	-8.97	AV
H	4844	44.16	31.02	8.99	25.57	47.70	74.00	-26.30	PK
H	4844	44.62	31.02	8.99	25.57	48.16	54.00	-5.84	AV
H	7266	46.06	30.55	5.77	24.66	45.94	74.00	-28.06	PK
H	7266	45.22	30.55	5.77	24.66	45.10	54.00	-8.90	AV
H	9688	44.40	30.33	6.32	24.55	44.94	74.00	-29.06	PK
H	9688	44.49	30.33	6.32	24.55	45.03	54.00	-8.97	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	51.83	30.55	5.77	24.66	51.71	74.00	-22.29	PK
V	4874	45.17	30.55	5.77	24.66	45.05	54.00	-8.95	AV
V	7311	55.15	30.33	6.32	24.55	55.69	74.00	-18.31	PK
V	7311	45.55	30.33	6.32	24.55	46.09	54.00	-7.91	AV
V	9748	45.60	30.85	7.45	24.69	46.89	74.00	-27.11	PK
V	9748	46.17	30.85	7.45	24.69	47.46	54.00	-6.54	AV
H	4874	45.45	31.02	8.99	25.57	48.99	74.00	-25.01	PK
H	4874	46.33	31.02	8.99	25.57	49.87	54.00	-4.13	AV
H	7311	43.96	30.55	5.77	24.66	43.84	74.00	-30.16	PK
H	7311	45.00	30.55	5.77	24.66	44.88	54.00	-9.12	AV
H	9748	44.48	30.33	6.32	24.55	45.02	74.00	-28.98	PK
H	9748	44.78	30.33	6.32	24.55	45.32	54.00	-8.68	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904	57.57	30.55	5.77	24.66	57.45	74.00	-16.55	PK
V	4904	43.84	30.55	5.77	24.66	43.72	54.00	-10.28	AV
V	7356	55.35	30.33	6.32	24.55	55.89	74.00	-18.11	PK
V	7356	46.42	30.33	6.32	24.55	46.96	54.00	-7.04	AV
V	9808	46.17	30.85	7.45	24.69	47.46	74.00	-26.54	PK
V	9808	44.03	30.85	7.45	24.69	45.32	54.00	-8.68	AV
H	4904	44.76	31.02	8.99	25.57	48.30	74.00	-25.70	PK
H	4904	45.58	31.02	8.99	25.57	49.12	54.00	-4.88	AV
H	7356	45.59	30.55	5.77	24.66	45.47	74.00	-28.53	PK
H	7356	43.80	30.55	5.77	24.66	43.68	54.00	-10.32	AV
H	9808	46.28	30.33	6.32	24.55	46.82	74.00	-27.18	PK
H	9808	43.87	30.33	6.32	24.55	44.41	54.00	-9.59	AV

5.RADIATED BAND EMISSIONMEASUREMENT**5.1 TEST REQUIREMENT:**

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

ANT1

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
802.11b	LowChannel 2412MHz									
	H	2390.00	52.86	30.22	4.85	23.98	51.47	74.00	PK	PASS
	H	2390.00	42.66	30.22	4.85	23.98	41.27	54.00	AV	PASS
	H	2400.00	55.77	30.22	4.85	23.98	54.38	74.00	PK	PASS
	H	2400.00	46.36	30.22	4.85	23.98	44.97	54.00	AV	PASS
	V	2390.00	55.89	30.22	4.85	23.98	54.50	74.00	PK	PASS
	V	2390.00	42.79	30.22	4.85	23.98	41.40	54.00	AV	PASS
	V	2400.00	54.69	30.22	4.85	23.98	53.30	74.00	PK	PASS
	V	2400.00	47.37	30.22	4.85	23.98	45.98	54.00	AV	PASS
	HighChannel 2462MHz									
	H	2483.50	54.91	30.22	4.85	23.98	53.52	74.00	PK	PASS
	H	2485.50	44.68	30.22	4.85	23.98	43.29	54.00	AV	PASS
	H	2483.50	56.43	30.22	4.85	23.98	55.04	74.00	PK	PASS
	H	2485.50	46.50	30.22	4.85	23.98	45.11	54.00	AV	PASS
	V	2483.50	55.48	30.22	4.85	23.98	54.09	74.00	PK	PASS
	V	2485.50	45.14	30.22	4.85	23.98	43.75	54.00	AV	PASS
	V	2483.50	55.26	30.22	4.85	23.98	53.87	74.00	PK	PASS
	V	2485.50	45.08	30.22	4.85	23.98	43.69	54.00	AV	PASS

802.11g	LowChannel 2412MHz									
	H	2390.00	54.13	30.22	4.85	23.98	52.74	74.00	PK	PASS
	H	2390.00	44.44	30.22	4.85	23.98	43.05	54.00	AV	PASS
	H	2400.00	54.91	30.22	4.85	23.98	53.52	74.00	PK	PASS
	H	2400.00	44.83	30.22	4.85	23.98	43.44	54.00	AV	PASS
	V	2390.00	55.53	30.22	4.85	23.98	54.14	74.00	PK	PASS
	V	2390.00	43.42	30.22	4.85	23.98	42.03	54.00	AV	PASS
	V	2400.00	56.34	30.22	4.85	23.98	54.95	74.00	PK	PASS
	V	2400.00	46.51	30.22	4.85	23.98	45.12	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	53.25	30.22	4.85	23.98	51.86	74.00	PK	PASS
	H	2485.50	43.75	30.22	4.85	23.98	42.36	54.00	AV	PASS
	H	2483.50	57.30	30.22	4.85	23.98	55.91	74.00	PK	PASS
	H	2485.50	45.14	30.22	4.85	23.98	43.75	54.00	AV	PASS
	V	2483.50	53.72	30.22	4.85	23.98	52.33	74.00	PK	PASS
	V	2485.50	42.62	30.22	4.85	23.98	41.23	54.00	AV	PASS
	V	2483.50	56.15	30.22	4.85	23.98	54.76	74.00	PK	PASS
	V	2485.50	46.53	30.22	4.85	23.98	45.14	54.00	AV	PASS

802.11n20	LowChannel 2412MHz									
	H	2390.00	54.75	30.22	4.85	23.98	53.36	74.00	PK	PASS
	H	2390.00	42.92	30.22	4.85	23.98	41.53	54.00	AV	PASS
	H	2400.00	56.65	30.22	4.85	23.98	55.26	74.00	PK	PASS
	H	2400.00	44.90	30.22	4.85	23.98	43.51	54.00	AV	PASS
	V	2390.00	55.16	30.22	4.85	23.98	53.77	74.00	PK	PASS
	V	2390.00	44.69	30.22	4.85	23.98	43.30	54.00	AV	PASS
	V	2400.00	55.15	30.22	4.85	23.98	53.76	74.00	PK	PASS
	V	2400.00	47.02	30.22	4.85	23.98	45.63	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	52.33	30.22	4.85	23.98	50.94	74.00	PK	PASS
	H	2485.50	43.95	30.22	4.85	23.98	42.56	54.00	AV	PASS
	H	2483.50	56.29	30.22	4.85	23.98	54.90	74.00	PK	PASS
	H	2485.50	45.70	30.22	4.85	23.98	44.31	54.00	AV	PASS
	V	2483.50	56.37	30.22	4.85	23.98	54.98	74.00	PK	PASS
	V	2485.50	44.59	30.22	4.85	23.98	43.20	54.00	AV	PASS
	V	2483.50	57.55	30.22	4.85	23.98	56.16	74.00	PK	PASS
	V	2485.50	45.24	30.22	4.85	23.98	43.85	54.00	AV	PASS
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

802.11n40	LowChannel 2422MHz									
	H	2390.00	57.69	30.22	4.85	23.98	56.30	74.00	PK	PASS
	H	2390.00	44.85	30.22	4.85	23.98	43.46	54.00	AV	PASS
	H	2400.00	55.80	30.22	4.85	23.98	54.41	74.00	PK	PASS
	H	2400.00	47.50	30.22	4.85	23.98	46.11	54.00	AV	PASS
	V	2390.00	56.68	30.22	4.85	23.98	55.29	74.00	PK	PASS
	V	2390.00	44.52	30.22	4.85	23.98	43.13	54.00	AV	PASS
	V	2400.00	56.84	30.22	4.85	23.98	55.45	74.00	PK	PASS
	V	2400.00	46.69	30.22	4.85	23.98	45.30	54.00	AV	PASS
	High Channel 2452MHz									
	H	2483.50	58.36	30.22	4.85	23.98	56.97	74.00	PK	PASS
	H	2485.50	43.77	30.22	4.85	23.98	42.38	54.00	AV	PASS
	H	2483.50	56.24	30.22	4.85	23.98	54.85	74.00	PK	PASS
	H	2485.50	45.96	30.22	4.85	23.98	44.57	54.00	AV	PASS
	V	2483.50	52.97	30.22	4.85	23.98	51.58	74.00	PK	PASS
	V	2485.50	43.63	30.22	4.85	23.98	42.24	54.00	AV	PASS
V	2483.50	55.60	30.22	4.85	23.98	54.21	74.00	PK	PASS	
V	2485.50	46.01	30.22	4.85	23.98	44.62	54.00	AV	PASS	
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

ANT2

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Result
802.11b	LowChannel 2412MHz									
	H	2390.00	58.06	30.22	4.85	23.98	56.67	74.00	PK	PASS
	H	2390.00	43.47	30.22	4.85	23.98	42.08	54.00	AV	PASS
	H	2400.00	56.31	30.22	4.85	23.98	54.92	74.00	PK	PASS
	H	2400.00	45.99	30.22	4.85	23.98	44.60	54.00	AV	PASS
	V	2390.00	57.94	30.22	4.85	23.98	56.55	74.00	PK	PASS
	V	2390.00	43.84	30.22	4.85	23.98	42.45	54.00	AV	PASS
	V	2400.00	57.42	30.22	4.85	23.98	56.03	74.00	PK	PASS
	V	2400.00	45.48	30.22	4.85	23.98	44.09	54.00	AV	PASS
	HighChannel 2462MHz									
	H	2483.50	52.59	30.22	4.85	23.98	51.20	74.00	PK	PASS
	H	2485.50	42.84	30.22	4.85	23.98	41.45	54.00	AV	PASS
	H	2483.50	57.17	30.22	4.85	23.98	55.78	74.00	PK	PASS
	H	2485.50	44.71	30.22	4.85	23.98	43.32	54.00	AV	PASS
	V	2483.50	51.73	30.22	4.85	23.98	50.34	74.00	PK	PASS
	V	2485.50	45.06	30.22	4.85	23.98	43.67	54.00	AV	PASS
	V	2483.50	55.69	30.22	4.85	23.98	54.30	74.00	PK	PASS
	V	2485.50	46.18	30.22	4.85	23.98	44.79	54.00	AV	PASS

802.11g	LowChannel 2412MHz									
	H	2390.00	53.58	30.22	4.85	23.98	52.19	74.00	PK	PASS
	H	2390.00	44.41	30.22	4.85	23.98	43.02	54.00	AV	PASS
	H	2400.00	55.84	30.22	4.85	23.98	54.45	74.00	PK	PASS
	H	2400.00	45.72	30.22	4.85	23.98	44.33	54.00	AV	PASS
	V	2390.00	56.95	30.22	4.85	23.98	55.56	74.00	PK	PASS
	V	2390.00	45.08	30.22	4.85	23.98	43.69	54.00	AV	PASS
	V	2400.00	54.95	30.22	4.85	23.98	53.56	74.00	PK	PASS
	V	2400.00	47.17	30.22	4.85	23.98	45.78	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	56.74	30.22	4.85	23.98	55.35	74.00	PK	PASS
	H	2485.50	42.74	30.22	4.85	23.98	41.35	54.00	AV	PASS
	H	2483.50	55.65	30.22	4.85	23.98	54.26	74.00	PK	PASS
	H	2485.50	45.41	30.22	4.85	23.98	44.02	54.00	AV	PASS
	V	2483.50	54.02	30.22	4.85	23.98	52.63	74.00	PK	PASS
	V	2485.50	43.54	30.22	4.85	23.98	42.15	54.00	AV	PASS
	V	2483.50	54.82	30.22	4.85	23.98	53.43	74.00	PK	PASS
	V	2485.50	47.57	30.22	4.85	23.98	46.18	54.00	AV	PASS

802.11n20	LowChannel 2412MHz									
	H	2390.00	53.96	30.22	4.85	23.98	52.57	74.00	PK	PASS
	H	2390.00	43.81	30.22	4.85	23.98	42.42	54.00	AV	PASS
	H	2400.00	57.59	30.22	4.85	23.98	56.20	74.00	PK	PASS
	H	2400.00	46.35	30.22	4.85	23.98	44.96	54.00	AV	PASS
	V	2390.00	53.27	30.22	4.85	23.98	51.88	74.00	PK	PASS
	V	2390.00	43.69	30.22	4.85	23.98	42.30	54.00	AV	PASS
	V	2400.00	55.81	30.22	4.85	23.98	54.42	74.00	PK	PASS
	V	2400.00	44.70	30.22	4.85	23.98	43.31	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	53.07	30.22	4.85	23.98	51.68	74.00	PK	PASS
	H	2485.50	42.81	30.22	4.85	23.98	41.42	54.00	AV	PASS
	H	2483.50	54.60	30.22	4.85	23.98	53.21	74.00	PK	PASS
	H	2485.50	46.42	30.22	4.85	23.98	45.03	54.00	AV	PASS
	V	2483.50	57.49	30.22	4.85	23.98	56.10	74.00	PK	PASS
	V	2485.50	43.99	30.22	4.85	23.98	42.60	54.00	AV	PASS
	V	2483.50	56.94	30.22	4.85	23.98	55.55	74.00	PK	PASS
V	2485.50	47.17	30.22	4.85	23.98	45.78	54.00	AV	PASS	
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

802.11n40	LowChannel 2422MHz									
	H	2390.00	55.61	30.22	4.85	23.98	54.22	74.00	PK	PASS
	H	2390.00	43.53	30.22	4.85	23.98	42.14	54.00	AV	PASS
	H	2400.00	55.89	30.22	4.85	23.98	54.50	74.00	PK	PASS
	H	2400.00	46.93	30.22	4.85	23.98	45.54	54.00	AV	PASS
	V	2390.00	56.73	30.22	4.85	23.98	55.34	74.00	PK	PASS
	V	2390.00	44.38	30.22	4.85	23.98	42.99	54.00	AV	PASS
	V	2400.00	57.40	30.22	4.85	23.98	56.01	74.00	PK	PASS
	V	2400.00	46.11	30.22	4.85	23.98	44.72	54.00	AV	PASS
	High Channel 2452MHz									
	H	2483.50	52.97	30.22	4.85	23.98	51.58	74.00	PK	PASS
	H	2485.50	45.26	30.22	4.85	23.98	43.87	54.00	AV	PASS
	H	2483.50	56.50	30.22	4.85	23.98	55.11	74.00	PK	PASS
	H	2485.50	46.18	30.22	4.85	23.98	44.79	54.00	AV	PASS
	V	2483.50	54.39	30.22	4.85	23.98	53.00	74.00	PK	PASS
	V	2485.50	43.27	30.22	4.85	23.98	41.88	54.00	AV	PASS
	V	2483.50	56.33	30.22	4.85	23.98	54.94	74.00	PK	PASS
V	2485.50	47.15	30.22	4.85	23.98	45.76	54.00	AV	PASS	
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

MIMO-802.11n20	LowChannel 2412MHz									
	H	2390.00	55.09	30.22	4.85	23.98	53.70	74.00	PK	PASS
	H	2390.00	43.33	30.22	4.85	23.98	41.94	54.00	AV	PASS
	H	2400.00	54.73	30.22	4.85	23.98	53.34	74.00	PK	PASS
	H	2400.00	44.64	30.22	4.85	23.98	43.25	54.00	AV	PASS
	V	2390.00	57.26	30.22	4.85	23.98	55.87	74.00	PK	PASS
	V	2390.00	44.24	30.22	4.85	23.98	42.85	54.00	AV	PASS
	V	2400.00	55.90	30.22	4.85	23.98	54.51	74.00	PK	PASS
	V	2400.00	47.40	30.22	4.85	23.98	46.01	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	54.82	30.22	4.85	23.98	53.43	74.00	PK	PASS
	H	2485.50	44.73	30.22	4.85	23.98	43.34	54.00	AV	PASS
	H	2483.50	56.48	30.22	4.85	23.98	55.09	74.00	PK	PASS
	H	2485.50	47.50	30.22	4.85	23.98	46.11	54.00	AV	PASS
	V	2483.50	55.37	30.22	4.85	23.98	53.98	74.00	PK	PASS
	V	2485.50	45.00	30.22	4.85	23.98	43.61	54.00	AV	PASS
	V	2483.50	56.33	30.22	4.85	23.98	54.94	74.00	PK	PASS
	V	2485.50	47.19	30.22	4.85	23.98	45.80	54.00	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

MIMO-802.11n40	LowChannel 2422MHz									
	H	2390.00	53.71	30.22	4.85	23.98	52.32	74.00	PK	PASS
	H	2390.00	45.58	30.22	4.85	23.98	44.19	54.00	AV	PASS
	H	2400.00	57.35	30.22	4.85	23.98	55.96	74.00	PK	PASS
	H	2400.00	47.39	30.22	4.85	23.98	46.00	54.00	AV	PASS
	V	2390.00	53.59	30.22	4.85	23.98	52.20	74.00	PK	PASS
	V	2390.00	45.06	30.22	4.85	23.98	43.67	54.00	AV	PASS
	V	2400.00	55.39	30.22	4.85	23.98	54.00	74.00	PK	PASS
	V	2400.00	44.88	30.22	4.85	23.98	43.49	54.00	AV	PASS
	High Channel 2452MHz									
	H	2483.50	56.48	30.22	4.85	23.98	55.09	74.00	PK	PASS
	H	2485.50	44.70	30.22	4.85	23.98	43.31	54.00	AV	PASS
	H	2483.50	56.98	30.22	4.85	23.98	55.59	74.00	PK	PASS
	H	2485.50	45.75	30.22	4.85	23.98	44.36	54.00	AV	PASS
	V	2483.50	54.22	30.22	4.85	23.98	52.83	74.00	PK	PASS
	V	2485.50	44.47	30.22	4.85	23.98	43.08	54.00	AV	PASS
	V	2483.50	54.92	30.22	4.85	23.98	53.53	74.00	PK	PASS
	V	2485.50	45.84	30.22	4.85	23.98	44.45	54.00	AV	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6.POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP**6.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.


6.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC7.4V

Test mode	Test channel	Power Spectral Density (dBm/MHz)			Limit:	Result
		ANT1	ANT2	SUM		
802.11b	Lowest	-14.789	-15.451	/	8dBm	PASS
	Middle	-15.332	-15.149	/		
	Highest	-13.834	-13.818	/		
802.11g	Lowest	-21.186	-21.076	/	8dBm	PASS
	Middle	-20.259	-20.796	/		
	Highest	-19.787	-19.184	/		
802.11n(HT20)	Lowest	-22.155	-21.047	-18.56	7.99dBm	PASS
	Middle	-21.034	-20.872	-17.94		
	Highest	-21.861	-21.607	-18.72		
802.11n(HT40)	Lowest	-21.856	-19.934	-17.78	7.99dBm	PASS
	Middle	-22.863	-21.309	-19.01		
	Highest	-23.05	-23.03	-20.03		

Remark:

1. Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Please refer to following plots;
4. The PSD limits of IEEE 802.11n HT20 and IEEE 802.11 n HT40 for MIMO with CDD technology should be reduce $10 \cdot \log(2) = 3.010\text{dB}$ according to KDB662911D01;
5. For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;
Array gain = $10 \log (N_{\text{ant}})$, where N_{ant} is the number of transmit antennas.





Highest channel



Highest channel



ANT1
802.11g
Lowest channel




ANT2
802.11g
Lowest channel



Middle channel




Middle channel




Highest channel




Highest channel




ANT1
802.11n(HT20)
Lowest channel




ANT2
802.11n(HT20)
Lowest channel




Middle channel




Middle channel




Highest channel




Highest channel




ANT1
802.11n(HT40)
Lowest channel




ANT2
802.11n(HT40)
Lowest channel




Middle channel




Middle channel



Highest channel



Highest channel



7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


7.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC7.4V
Test Mode :	TX Mode		


Test mode	Test channel	6dB Emission Bandwidth (MHz)		Limit:	Test Result:
		ANT1	ANT2		
802.11b	Lowest	8.593	8.023	>500kHz	PASS
	Middle	8.575	8.577		
	Highest	8.577	8.123		
802.11g	Lowest	16.38	16.38	>500kHz	PASS
	Middle	16.39	16.37		
	Highest	16.41	16.34		
802.11n(HT20)	Lowest	17.59	17.59	>500kHz	PASS
	Middle	17.59	17.59		
	Highest	17.58	17.58		
802.11n(HT40)	Lowest	35.72	36.10	>500kHz	PASS
	Middle	36.33	35.89		
	Highest	35.85	36.17		

Test plot as follows:






Highest channel




Highest channel



ANT1

802.11g


Lowest channel




ANT2

802.11g


Lowest channel




Middle channel




Middle channel




Highest channel




Highest channel




ANT1
802.11n(HT20)
Lowest channel




ANT2
802.11n(HT20)
Lowest channel




Middle channel




Middle channel




Highest channel




Highest channel




ANT1
802.11n(HT40)
Lowest channel




ANT2
802.11n(HT40)
Lowest channel




Middle channel





Middle channel



Highest channel



Highest channel



8.OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V

Test	Frequency	Maximum Peak Conducted Output Power(dBm)		LIMIT
Channel	(MHz)	Antenna 1	Antenna 2	dBm
TX 802.11b Mode				
CH01	2412	11.53	11.624	30
CH06	2437	11.65	11.678	30
CH11	2462	11.88	11.271	30
TX 802.11g Mode				
CH01	2412	10.29	10.459	30
CH06	2437	10.53	10.703	30
CH11	2462	11.24	11.362	30
TX 802.11n20 Mode				
CH01	2412	10.87	10.365	30
CH06	2437	10.86	10.733	30
CH11	2462	11.01	11.258	30
TX 802.11n40 Mode				
CH03	2422	9.30	9.411	30
CH06	2437	9.55	10.454	30
CH09	2452	9.06	9.144	30

TX 802.11n20 Mode					
Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)		MIMO dBm	LIMIT dBm
		Antenna 1	Antenna 2		
CH01	2412	10.87	10.365	13.64	29.99
CH06	2437	10.86	10.733	13.81	29.99
CH11	2462	11.01	11.258	14.15	29.99
TX 802.11n40 Mode					
CH03	2422	9.30	9.411	12.37	29.99
CH06	2437	9.55	10.454	13.04	29.99
CH09	2452	9.06	9.144	12.11	29.99
Note: This product supports antenna 1 and antenna 2 launch, but only support 802.11 N20/N40 for MIMO mode, not support 802.11 b and 802.11 g for MIMO mode. LIMIT=30-(6.01-6)=29.99 dbm					

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Test plot as follows:

ANT1




802.11b Modulation

Spurious emission



Low Channel




Middle Channel




High Channel



Lowest Channel



Highest Channel



Left Band Edge

Right Band Edge



802.11g Modulation

Spurious emission

Low Channel




Middle Channel



High Channel





802.11n20 Modulation

Spurious emission




Low Channel




Middle Channel



High Channel





Left Band Edge

Right Band Edge

802.11n40 Modulation

Spurious emission

Low Channel




Middle Channel




High Channel



Lowest Channel



Highest Channel






Left Band Edge


Right Band Edge

ANT2

802.11b Modulation

Spurious emission	
Low Channel	
	
	


Middle Channel




High Channel



Lowest Channel



Highest Channel



Left Band Edge

Right Band Edge

802.11g Modulation

Spurious emission

Low Channel




Middle Channel




High Channel



Lowest Channel



Highest Channel



Left Band Edge

Right Band Edge

802.11n20 Modulation

Spurious emission




Low Channel




Middle Channel




High Channel



Lowest Channel






Highest Channel



Left Band Edge


Right Band Edge

Middle Channel




High Channel







10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. Refer to statement below for compliance. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed. Antenna Connected Construction The antenna used in this product is aGlue stick antenna, and the best case gain of the antenna is antenna port 1:3dBi and Antenna port 2:3dBi, and MIMO: 6.01dBi	
FPC Antenna: 2.4Gwifi 	

11. TEST SETUP PHOTO





12. EUT CONSTRUCTIONAL DETAILS

Please refer to external photos file and internal photos file

***** END OF REPORT *****