



RADIO TEST REPORT

Report No.: SHATBL2201003W01

Applicant:

VINO FONTAINE PTE. LTD

Address:

Room333, Ascendas Innovation Plaza, 660-686 Jiujiang
Road,ShangHai,China

Product Name : Andante Uno Lite

Brand Name : N/A

Model Name : ADT-UNO-A2

Series Model : N/A

Test Standard : FCC Part15.247

FCC ID : 2A3XBADT-UNO-A2

"Shanghai ATBL Technology Co., Ltd." hereby certifies that according to actual testing conditions. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, ATBL shall not assume any responsibility. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material. This report will be void without authorized signature or special seal for testing report. Do not copied without authorization.

TEST RESULT CERTIFICATION

Applicant's Name..... : VINO FONTAINE PTE. LTD
Address : Room333, Ascendas Innovation Plaza, 660-686 Jiujiang Road,ShangHai,China
Manufacture's Name..... : VINO FONTAINE PTE. LTD
Address : Room333, Ascendas Innovation Plaza, 660-686 Jiujiang Road,ShangHai,China

Product Description

Product Name : Andante Uno Lite
Brand Name : N/A
Model Name..... : ADT-UNO-A2
Series Model : N/A
Test Standards : FCC Part15.247
Test Procedure : ANSI C63.10-2013

This device described above has been tested by ATBL, the test results show that the equipment under test (EUT) is in compliance with the FCC/IC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATBL, this document may be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.

Date of Test :
Date of receipt of test item..... : 16 Nov. 2021
Date (s) of performance of tests : 16 Nov. 2021 ~ 01 Dec. 2021
Date of Issue : 13 Jan. 2022
Test Result..... : Pass

Report Prepared by :

Eric liu

(Eric liu)

Report Approved by :

Ghost Li.

(Ghost.Li)

Authorized Signatory :

Terry yang

(Terry yang)



Table of Contents

1. SUMMARY OF TEST RESULTS	6
2. GENERAL INFORMATION.....	7
2.1 GENERAL DESCRIPTION OF THE EUT.....	7
2.2 DESCRIPTION OF THE TEST MODES.....	9
2.3 TEST SOFTWARE AND POWER LEVEL	9
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED.....	10
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS.....	11
2.6 LABORATORY INFORMATION	12
2.7 MEASUREMENT UNCERTAINTY	12
2.8 EQUIPMENTS LIST.....	13
3. EMC EMISSION TEST.....	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 TEST PROCEDURE	15
3.3 TEST SETUP.....	15
3.4 EUT OPERATING CONDITIONS.....	15
3.5 TEST RESULTS	16
4. RADIATED EMISSION MEASUREMENT	18
4.1 RADIATED EMISSION LIMITS	18
4.2 TEST PROCEDURE	20
4.3 TEST SETUP.....	21
4.4 EUT OPERATING CONDITIONS.....	21
4.5 FIELD STRENGTH CALCULATION.....	22
4.6 TEST RESULTS	23
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION.....	39
5.1 LIMIT	39
5.2 TEST PROCEDURE.....	39
5.3 TEST SETUP.....	39
5.4 EUT OPERATION CONDITIONS.....	39
5.5 TEST RESULTS	40
6. POWER SPECTRAL DENSITY TEST	44
6.1 LIMIT	44
6.2 TEST PROCEDURE.....	44
6.3 TEST SETUP.....	44

Table of Contents

6.4 EUT OPERATION CONDITIONS.....	44
6.5 TEST RESULTS	45
7. BANDWIDTH TEST	47
7.1 LIMIT	47
7.2 TEST PROCEDURE.....	47
7.3 TEST SETUP.....	47
7.4 EUT OPERATION CONDITIONS.....	47
7.5 TEST RESULTS	48
8. PEAK OUTPUT POWER TEST	52
8.1 LIMIT	52
8.2 TEST PROCEDURE.....	52
8.3 TEST SETUP.....	52
8.4 EUT OPERATION CONDITIONS.....	52
8.5 TEST RESULTS	52
9. ANTENNA REQUIREMENT.....	54
9.1 STANDARD REQUIREMENT	54
9.2 EUT ANTENNA.....	54
APPENDIX-PHOTOS OF TEST SETUP.....	55

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	13 Jan. 2022	SHATBL2201003W01	ALL	Initial Issue

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part15.247			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB&99% Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.247(d) & 15.209 & 15.205	Radiated Spurious Emission	PASS	--
15.247(d) & 15.205	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted bands of operation	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Andante Uno Lite	
Trade Name	N/A	
Model Name	ADT-UNO-A2	
Series Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Andante Uno Lite	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Version:	5.0
	Bluetooth Configuration:	LE(Support 1M PHY)
	Number Of Channel:	40
	Antenna Designation:	Please refer to the Note 3.
Antenna Gain (dBi)	1 dBi	
Channel List	Please refer to the Note 2.	
Power Rating	12V 5A	
Battery	N/A	
Hardware version number	hjbxi_main_rev1.2	
Software version number	hlbxi_v1.0	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.

2.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	ADT-UNO-A2	On-board antenna	N/A	1 dBi	BLE ANT

2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions
 Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Worst Mode	Description	Data/Modulation
Mode 1	TX CH00(2402MHz)	1 Mbps/GFSK
Mode 2	TX CH19(2440MHz)	1 Mbps/GFSK
Mode 3	TX CH39(2480MHz)	1 Mbps/GFSK

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

For Conducted Emission

Test Case	
Conducted Emission	Mode 4 : Keeping BT TX


2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	Ant Gain(dBi)	Power Class	Software For Testing
BLE	BLE	GFSK	1dBi	default	sscom5.13.1

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conduction Emission Test



2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model	Type No.	Note
E-2	Notebook	Lenovo	DESKTOP-USDEO9	00326-10000-00000-AA636	N/A
C-1	USB Cable	N/A	100cm	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.6 LABORATORY INFORMATION

Company Name:	Shanghai ATBL Technology Co., Ltd.
Address:	Building 8, No. 160, Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone:	+86(0)21-51298625
The FCC Registration Number (FRN):	0031025281
A2LA Number:	6184.01
CNAS Number:	CNAS L14531

2.7 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.958\text{dB}$
2	Conducted spurious emissions	$\pm 2.988\text{dB}$
3	All emissions, radiated 30MHz-1GHz	$\pm 2.50\text{dB}$
4	All emissions, radiated 1GHz-18GHz	$\pm 3.51\text{dB}$
5	Occupied bandwidth	$\pm 23.20\text{dB}$
6	Power spectral density	$\pm 0.886\text{dB}$

2.8 EQUIPMENTS LIST

2.8.1 Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Management number	Calibrated until
Test Receiver	R&S	ESCI	100469	SHATBL-E003	2022.07.13
Spectrum Analyzer	Agilent	N9020A	MY50200811	SHATBL-E017	2022.07.13
Bilog Antenna	SCHWARZBECK	VLUB 9168	01174	SHATBL-E008	2023.09.27
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	SHATBL-E009	2023.09.27
Pre-Amplifier (0.1M-3GHz)	JPT	JPA-10M1G35	21010100035001	SHATBL-E005	2022.10.07
Pre-Amplifier (1G-18GHz)	JPT	JPA0118-55-303A	1910001800055000	SHATBL-E006	2022.07.13
Temperature & Humidity	DeLi	DeLi	N/A	SHATBL-E016	2022.10.08
Antenna/Turntable Controller	Brilliant	N/A	N/A	SHATBL-E007	N/A
Test SW	FALA	EMC-RI(Ver.4A2)		SHATBL-E046	N/A

2.8.2 RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	equipment number	Calibrated until
MIMO Power measurement test Set	DARE	RPR3006W	16I00054SN016	SHATBL-W006	2022.10.07
			RPR6W-20001005	SHATBL-W013	2022.10.07
Signal Analyzer	Agilent	N9020A	MY57300196	SHATBL-W004	2022.10.07
Signal Generator	Agilent	N5182B	MY46240556	SHATBL-W005	2022.10.07
Wireless Communications Test Set	R&S	CMW500	101331	SHATBL-W007	2022.10.07
Temperature & Humidity	Deli	deli	N/A	SHATBL-W011	2022.10.07
Attenuator	Agilent	8494B	DC-18G	SHATBL-W009	2022.10.07
Attenuator	Agilent	8496B	DC-18G	SHATBL-W010	2022.10.07
power splitter	MNK	MPD-DC/6-2S	62315 G51	SHATBL-W015	2022.10.07
			62315 G52	SHATBL-W016	2022.10.07
Filter	Chengdu kangmaiwei	ZBSF-C2400-2483.5-T3	N/A	SHATBL-W021	N/A
Constant temperature and humidity box	KSON	THS-B6C-150	6159K	SHATBL-W019	2022.01.26
Test SW	FALA	LZ-RF(Ver.LzRF-03A3.1)		SHATBL-W020	N/A

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a)&RSS-Gen Issue 5 limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- a. The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN is at least 80 cm from the nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



- Note: 1.Support units were connected to second LISN.**
- 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support.**

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.5 TEST RESULTS

Temperature:	26 °C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode :	Mode 4		

No.	Frequency (MHz)	Reading (dBUV)	Correct Factor(dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Remark
1	0.1539	42.30	10.14	52.44	65.79	-13.35	QP
2	0.1539	25.18	10.14	35.32	55.79	-20.47	AVG
3	0.2690	35.71	10.08	45.79	61.15	-15.36	QP
4	0.2690	24.52	10.08	34.60	51.15	-16.55	AVG
5	0.9550	31.08	9.95	41.03	56.00	-14.97	QP
6	0.9550	22.09	9.95	32.04	46.00	-13.96	AVG
7	4.1850	36.04	10.05	46.09	56.00	-9.91	QP
8	4.1850	26.01	10.05	36.06	46.00	-9.94	AVG
9	7.3560	35.62	10.11	45.73	60.00	-14.27	QP
10	7.3560	24.05	10.11	34.16	50.00	-15.84	AVG
11	24.9150	28.19	11.05	39.24	60.00	-20.76	QP
12	24.9150	18.77	11.05	29.82	50.00	-20.18	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor)-Limit




Temperature:	26 °C	Relative Humidity:	54%
Test Voltage	AC 120V/60Hz	Phase:	N
Test Mode	Mode 4		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1819	47.84	10.40	58.24	64.40	-6.16	QP
2	0.1819	39.23	10.40	49.63	54.40	-4.77	AVG
3	0.4840	39.88	10.20	50.08	56.27	-6.19	QP
4	0.4840	35.64	10.20	45.84	46.27	-0.43	AVG
5	2.1760	37.78	10.23	48.01	56.00	-7.99	QP
6	2.1760	27.44	10.23	37.67	46.00	-8.33	AVG
7	4.3659	36.33	10.20	46.53	56.00	-9.47	QP
8	4.3659	22.81	10.20	33.01	46.00	-12.99	AVG
9	13.6660	33.91	10.27	44.18	60.00	-15.82	QP
10	13.6660	23.34	10.27	33.61	50.00	-16.39	AVG
11	24.7460	30.36	10.95	41.31	60.00	-18.69	QP
12	24.7460	21.10	10.95	32.05	50.00	-17.95	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor)–Limit



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a), RSS-Gen Issue 5 and RSS-247 Issue 2, February 2017 (5.5) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (Frequency Range 9kHz-1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2475 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency (MHz)	FS (dB μ V/m)	RA (dB μ V/m)	AF (dB)	CL (dB)	AG (dB)	Factor (dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

4.6 TEST RESULTS

Temperature:	23.0 °C	Relative Humidity:	59%RH
Test Voltage:	AC 230V/50Hz	Polarization:	--
Test Mode:	TX Mode1/2/3		

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = 40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

(30MHz -1000MHz)

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Horizontal
Test Mode	Mode 1		


Mode 1- Horizontal



Mk.	Freq.(MHz)	Level(d BuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L (.dB)	Pol.
1	72.084342	35.0	40.0	5.0	10.5	32.8	0.8	H
2	96.436153	32.0	43.5	11.5	9.9	32.9	1.3	H
3	120.276626	35.2	43.5	8.3	12.3	32.9	1.4	H
4	144.841766	37.7	43.5	5.8	13.8	32.9	1.3	H
5	168.709305	35.2	43.5	8.3	13.3	32.9	1.7	H
6	192.756232	36.9	43.5	6.6	10.3	32.8	2.2	H

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Vertical
Test Mode	Mode 1		

Mode 1- Vertical




Mk.	Freq.(MHz)	Level(d BuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L (.dB)	Pol.
1	72.084342	39.0	40.0	1.0	10.5	32.8	0.8	V
2	96.436153	32.6	43.5	10.9	9.9	32.9	1.3	V
3	120.487690	32.2	43.5	11.3	12.3	32.9	1.4	V
4	144.841766	32.0	43.5	11.5	13.8	32.9	1.3	V
5	192.756232	30.5	43.5	13.0	10.3	32.8	2.2	V
6	311.632553	28.6	46.0	17.4	13.0	32.7	2.7	V

(30MHz -1000MHz)

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Horizontal
Test Mode	Mode 2		


Mode 2- Horizontal



Mk.	Freq.(MHz)	Level(d BuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L (.dB)	Pol.
1	72.084342	35.3	40.0	4.7	10.5	32.8	0.8	H
2	96.436153	32.2	43.5	11.3	9.9	32.9	1.3	H
3	120.487690	35.4	43.5	8.1	12.3	32.9	1.4	H
4	144.841766	37.2	43.5	6.3	13.8	32.9	1.3	H
5	193.433330	37.2	43.5	6.3	10.3	32.8	2.2	H
6	323.887721	31.6	46.0	14.4	13.1	32.6	2.7	H

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Vertical
Test Mode	Mode 2		

Mode 2-Vertical




Mk.	Freq.(MHz)	Level(d BuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L (.dB)	Pol.
1	72.084342	38.6	40.0	1.4	10.5	32.8	0.8	V
2	96.436153	33.9	43.5	9.6	9.9	32.9	1.3	V
3	144.841766	33.1	43.5	10.4	13.8	32.9	1.3	V
4	181.283406	24.6	43.5	18.9	11.5	32.8	2.0	V
5	311.632553	30.4	46.0	15.6	13.0	32.7	2.7	V
6	419.843574	35.4	46.0	10.6	15.2	32.3	2.7	V

(30MHz -1000MHz)

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Horizontal
Test Mode	Mode 3		


Mode 3- Horizontal



Mk.	Freq.(MHz)	Level(d BuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L (.dB)	Pol.
1	72.084342	35.0	40.0	5.0	10.5	32.8	0.8	H
2	96.436153	31.8	43.5	11.7	9.9	32.9	1.3	H
3	120.487690	35.7	43.5	7.8	12.3	32.9	1.4	H
4	144.841766	37.7	43.5	5.8	13.8	32.9	1.3	H
5	169.005359	35.0	43.5	8.5	13.3	32.9	1.7	H
6	311.632553	32.2	46.0	13.8	12.9	32.7	2.7	H

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Vertical
Test Mode	Mode 3		

Mode 3-Vertical




Mk.	Freq.(MHz)	Level(d BuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L (.dB)	Pol.
1	72.084342	39.3	40.0	0.7	10.5	32.8	0.8	V
2	96.436153	33.8	43.5	9.7	9.9	32.9	1.3	V
3	144.841766	32.8	43.5	10.7	13.8	32.9	1.3	V
4	192.756232	29.8	43.5	13.7	10.3	32.8	2.2	V
5	311.632553	28.1	46.0	17.9	13.0	32.7	2.7	V
6	431.787972	33.9	46.0	12.1	15.5	32.4	2.7	V

(1000MHz -18000MHz)

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Horizontal
Test Mode	Mode 1		


Mode1-Horizontal



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak								
1	1135.000000	31.8	74.0	42.2	20.7	57.3	2.2	H
2	1814.000000	39.9	74.0	34.1	21.7	52.8	2.6	H
3	2512.000000	41.7	74.0	32.3	22.9	50.2	2.8	H
4	4095.750000	42.5	74.0	31.5	24.4	50.1	3.3	H
5	7396.500000	47.1	74.0	26.9	25.7	48.8	4.6	H
6	16836.000000	59.2	74.0	14.8	30.9	47.4	6.8	H
Avg								
1	1135.000000	20.8	54.0	33.2	20.7	57.3	2.2	H
2	1814.000000	28.1	54.0	25.9	21.7	52.8	2.6	H
3	2512.000000	30.3	54.0	23.7	22.9	50.2	2.8	H
4	4095.750000	33.4	54.0	20.6	24.4	50.1	3.3	H
5	7396.500000	38.3	54.0	15.7	25.7	48.8	4.6	H
6	16836.000000	51.1	54.0	2.9	30.9	47.4	6.8	H

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Vertical
Test Mode	Mode 1		

Mode 1- Vertical




Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak								
1	1147.000000	32.0	74.0	42.0	20.7	57.3	2.2	V
2	1843.000000	38.6	74.0	35.4	21.7	52.4	2.6	V
3	2434.000000	42.5	74.0	31.5	23.2	50.2	2.8	V
4	3996.000000	42.7	74.0	31.3	24.8	50.1	3.3	V
5	7977.000000	49.1	74.0	24.9	26.9	48.6	4.9	V
6	15364.500000	58.7	74.0	15.3	31.2	47.4	6.4	V
Avg								
1	1147.000000	21.1	54.0	32.9	20.7	57.3	2.2	V
2	1843.000000	27.4	54.0	26.6	21.7	52.4	2.6	V
3	2434.000000	30.8	54.0	23.2	23.2	50.2	2.8	V
4	3996.000000	33.7	54.0	20.3	24.8	50.1	3.3	V
5	7977.000000	39.4	54.0	14.6	26.9	48.6	4.9	V
6	15364.500000	49.7	54.0	4.3	31.2	47.4	6.4	V

(1000MHz -18000MHz)

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Horizontal
Test Mode	Mode 2		


Mode2-Horizontal



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak								
1	1146.000000	32.6	74.0	41.4	20.8	57.3	2.2	H
2	1984.000000	39.9	74.0	34.1	21.9	50.3	2.7	H
3	2550.000000	40.9	74.0	33.1	23.0	50.4	2.8	H
4	3774.000000	41.4	74.0	32.6	24.3	50.3	3.2	H
5	9452.250000	52.3	74.0	21.7	27.2	48.6	5.4	H
6	16899.750000	59.1	74.0	14.9	31.0	47.3	6.9	H
Avg								
1	1146.000000	21.4	54.0	32.6	20.8	57.3	2.2	H
2	1984.000000	28.9	54.0	25.1	21.9	50.3	2.7	H
3	2550.000000	30.1	54.0	23.9	23.0	50.4	2.8	H
4	3774.000000	31.8	54.0	22.2	24.3	50.3	3.2	H
5	9452.250000	43.6	54.0	10.4	27.2	48.6	5.4	H
6	16899.750000	49.2	54.0	4.8	31.0	47.3	6.9	H

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Vertical
Test Mode	Mode 2		

Mode2-Vertical




Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak								
1	1154.000000	31.9	74.0	42.1	20.8	57.3	2.2	V
2	1705.000000	35.9	74.0	38.1	21.5	54.3	2.6	V
3	2409.000000	42.5	74.0	31.5	23.2	50.2	2.8	V
4	4279.500000	42.6	74.0	31.4	24.8	50.1	3.4	V
5	10023.750000	54.5	74.0	19.5	28.4	48.5	5.4	V
6	16828.500000	60.0	74.0	14.0	31.4	47.4	6.8	V
Avg								
1	1154.000000	21.1	54.0	32.9	20.8	57.3	2.2	V
2	1705.000000	24.7	54.0	29.3	21.5	54.3	2.6	V
3	2409.000000	34.6	54.0	19.4	23.2	50.2	2.8	V
4	4279.500000	33.7	54.0	20.3	24.8	50.1	3.4	V
5	10023.750000	44.4	54.0	9.6	28.4	48.5	5.4	V
6	16828.500000	51.9	54.0	2.1	31.4	47.4	6.8	V

(1000MHz -18000MHz)

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Horizontal
Test Mode	Mode 3		


Mode 3- Horizontal



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak								
1	1151.000000	32.1	74.0	41.9	20.8	57.3	2.2	H
2	1824.000000	38.2	74.0	35.8	21.7	52.6	2.6	H
3	2520.000000	41.1	74.0	32.9	22.9	50.3	2.8	H
4	3702.750000	42.9	74.0	31.1	24.3	50.3	3.2	H
5	7405.500000	47.2	74.0	26.8	25.7	48.8	4.6	H
6	16842.750000	59.1	74.0	14.9	30.9	47.4	6.8	H
Avg								
1	1151.000000	21.2	54.0	32.8	20.8	57.3	2.2	H
2	1824.000000	27.1	54.0	26.9	21.7	52.6	2.6	H
3	2520.000000	30.2	54.0	23.8	22.9	50.3	2.8	H
4	3702.750000	31.9	54.0	22.1	24.3	50.3	3.2	H
5	7405.500000	39.1	54.0	14.9	25.7	48.8	4.6	H
6	16842.750000	51.5	54.0	2.5	30.9	47.4	6.8	H

Temperature	26 °C	Relative Humidity	56%
Test Voltage	AC 120V/60Hz	Polarization	Vertical
Test Mode	Mode 3		

Mode 3- Vertical




Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dB uV/m)	Margin (dB)	Ant.F/G.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak								
1	1235.000000	32.2	74.0	41.8	20.7	57.3	2.3	V
2	1628.000000	35.6	74.0	38.4	21.3	55.5	2.5	V
3	2440.000000	44.8	74.0	29.2	23.2	50.2	2.8	V
4	3588.750000	41.9	74.0	32.1	24.6	50.4	3.2	V
5	6140.250000	46.8	74.0	27.2	25.7	48.9	4.1	V
6	10315.500000	54.2	74.0	19.8	28.7	48.6	5.5	V
Avg								
1	1235.000000	21.3	54.0	32.7	20.7	57.3	2.3	V
2	1628.000000	24.2	54.0	29.8	21.3	55.5	2.5	V
3	2440.000000	38.5	54.0	15.5	23.2	50.2	2.8	V
4	3588.750000	32.7	54.0	21.3	24.6	50.4	3.2	V
5	6140.250000	38.5	54.0	15.5	25.7	48.9	4.1	V
6	10315.500000	45.3	54.0	8.7	28.7	48.6	5.5	V

Note:

1. Factor=Ant.Factor+cable loss-Amp.Gain .
2. Level contains the factor; Margin=Limit-Level.
- 3.Other 18G-25G Emission detected are more than 20dB below the limit.


4.6 TEST RESULTS (Restricted Bands Requirements)

GFSK-Low
Horizontal




Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
AVG								
1	2353.403785	30.9	54.0	23.1	22.7	50.2	2.8	H
2	2390.000000	40.8	54.0	13.2	22.8	50.2	2.8	H

Vertical




Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
AVG								
1	2343.374910	31.2	54.0	22.8	23.0	50.2	2.8	V
2	2390.000000	41.0	54.0	13.0	23.1	50.2	2.8	V




Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
Peak:								
1	2386.229678	48.6	74.0	25.4	22.8	50.2	2.8	H
2	2390.000000	41.0	74.0	33.0	22.8	50.2	2.8	H

Vertical




Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
Peak:								
1	2353.661500	42.3	74.0	31.7	23.0	50.2	2.8	V
2	2390.000000	40.8	74.0	33.2	23.1	50.2	2.8	V

GFSK-High
Horizontal




Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
AVG								
1	2483.500000	39.5	54.0	14.5	22.9	50.2	2.8	H
2	2492.843917	34.1	54.0	19.9	22.9	50.2	2.8	H

Vertical




Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
AVG								
1	2483.500000	40.1	54.0	13.9	23.3	50.2	2.8	V
2	2491.814646	35.1	54.0	18.9	23.3	50.2	2.8	V

GFSK-High Horizontal



Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
Peak:								
1	2483.500000	45.7	74.0	28.3	22.9	50.2	2.8	H
2	2493.388998	42.4	74.0	31.6	22.9	50.2	2.8	H

Vertical



Mk.	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F/G. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
Peak:								
1	2483.500000	47.3	74.0	26.7	23.3	50.2	2.8	V
2	2493.570718	43.2	74.0	30.8	23.3	50.2	2.8	V

5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 LIMIT

According to FCC section 15.247(d)&RSS-247 Issue 2, in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 – 2407 MHz Upper Band Edge: 2475 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 TEST SETUP



The EUT which is powered by the Battery, is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.


5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	50%RH
Test Voltage:	AC120V	Test Mode:	TX Mode 1/2/3


Mode1 CH00



Mode2 CH19




Mode3 CH39




For Band edge(it's also the reference level for conducted spurious emission)

Mode1 CH00



Mode3 CH39



6. POWER SPECTRAL DENSITY TEST


6.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤8 dBm (RBW≥3KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: 100 kHz ≥ RBW ≥ 3 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%RH
Test Voltage:	AC120V	Test Mode:	TX Mode1/2/3

Frequency	Power Density	Limit (3KHz/dBm)	Result
	(dBm/3kHz)		
2402 MHz	-15.115	≤8	PASS
2440 MHz	-14.402	≤8	PASS
2480 MHz	-13.785	≤8	PASS

Mode1 CH00



Mode2 CH19



Mode3 CH39



7. BANDWIDTH TEST

7.1 LIMIT

FCC Part 15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6 dB Bandwidth :100KHz For 99% Bandwidth :1% to 5% of the occupied bandwidth
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$ For 99% Bandwidth : approximately $3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB and 99% relative to the maximum level measured in the fundamental emission.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

7.5 TEST RESULTS


Temperature:	25 °C	Relative Humidity:	60%RH
Test Voltage:	AC120V	Test Mode:	TX Mode1/2/3

Frequency	6dB Bandwidth (KHz)	99% Bandwidth (KHz)	6dB Bandwidth Limit(KHz)	Result
2402 MHz	703.9	1034.4	≥500KHz	PASS
2440 MHz	725.0	1029.2	≥500KHz	PASS
2480 MHz	747.9	1045.5	≥500KHz	PASS


6dB Bandwidth Mode1 CH00




6dB Bandwidth Mode2 CH19




6dB Bandwidth Mode3 CH39



99% Bandwidth Mode1 CH00



99% Bandwidth Mode2 CH19



99% Bandwidth Mode3 CH39



8. PEAK OUTPUT POWER TEST

8.1 LIMIT

FCC Part15.247				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

8.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%RH
Test Voltage:	AC120V	Test Mode:	TX Mode1/2/3

Test Channel	Frequency	Peak Conducted Output Power	Average Conducted Output Power	LIMIT
	(MHz)	(dBm)	(dBm)	dBm
Mode1 CH00	2402	7.88	1.05	30
Mode2 CH19	2440	8.35	1.64	30
Mode3 CH39	2480	9.02	2.28	30


EIRP Power

Test Channel	Frequency	Peak Conducted Output Power	Antenna Gain	EIRP Power	LIMIT
	(MHz)	(dBm)	(dBi)	(dBm)	dBm
Mode1 CH00	2402	7.88	1	8.88	36
Mode2 CH19	2440	8.35	1	9.35	36

Mode3 CH39	2480	9.02	1	10.02	36
------------	------	------	---	-------	----

Note: Our power sensor test AVG power has no duty cycle display. The power sensor measures AVG power is Burst power. The software has considered the factor of the duty cycle factor, so it is unnecessary to add it again.

BLE 1M Duty cycle



Ton	Tp	Duty cycle(%)	Duty factor(dB)
/	/	100.00	0

9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA


The EUT antenna is On-board antenna. It comply with the standard requirement.

APPENDIX-PHOTOS OF TEST SETUP

Conducted for RF




Conduction Emission




Radiated Emission
30MHz-1000MHz




1GHz-18GHz



Radiated Spurious Emission
30MHz-1000MHz



1GHz-18GHz



*****END OF THE REPORT*****