




## RF EXPOSURE REPORT

For

### FUJIAN YESOUL HEALTH TECHNOLOGY CO.,LTD

RM-B616, BLDG., NO.1, STRAIT ECONOMIC AND TRADE PLAZA, FUZHOU FREE TRADE  
ZONE, FUZHOU, FUJIAN, China

**FCC ID: 2A3YB-YS-TT1MPLUS**

|                                        |                                                                                                                                                                                                                                                                                |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report | <b>Product Name:</b><br>YESOUL TREADMILL                                                                                                                                                                                                                                       |
| <b>Report Number:</b>                  | 2407X35401E-RF-04                                                                                                                                                                                                                                                              |
| <b>Report Date:</b>                    | 2025-06-11                                                                                                                                                                                                                                                                     |
| <b>Reviewed By:</b>                    | Ash Lin                                                                                                                                                                                     |
| <b>Approved By:</b>                    | Miles Chen                                                                                                                                                                                                                                                                     |
| <b>Prepared By:</b>                    | Bay Area Compliance Laboratories Corp. (Xiamen)<br>Unit 102, No. 902 Meifeng South Road, Binhai West Avenue,<br>Science and Technology Innovation Park, Torch High tech<br>Zone XiaMen<br>Tel: +86-592-3200111<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |

**TABLE OF CONTENTS**

**REPORT REVISION HISTORY.....3**

**GENERAL INFORMATION.....4**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....4

**MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....5**

    CALCULATED DATA.....6

**APPENDIX A - EUT PHOTOGRAPHS .....7**

REPORT REVISION HISTORY

| Number of Revisions | Report No.        | Version | Issue Date | Description     |
|---------------------|-------------------|---------|------------|-----------------|
| 0                   | 2407X35401E-RF-04 | R1V1    | 2025-06-11 | Initial Release |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                                                                                                                                                                                                                                                                      |                                                                                                                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:                                                                                                                                                                                                                                                                        | YESOUL TREADMILL                                                                                                                         |
| Tested Model:                                                                                                                                                                                                                                                                        | YS-TT1MPLUS                                                                                                                              |
| Power Supply:                                                                                                                                                                                                                                                                        | AC 100-240V, 50/60Hz                                                                                                                     |
| Maximum Peak Conducted Output Power:                                                                                                                                                                                                                                                 | <b>Classic BT:</b> 5.78dBm<br><b>BLE:</b> -0.15dBm<br><b>2.4G WIFI:</b> 18.22dBm                                                         |
| Operating Band/Frequency:                                                                                                                                                                                                                                                            | <b>Classic BT:</b> 2402-2480 MHz<br><b>BLE:</b> 2402-2480MHz<br><b>2.4G WIFI:</b> 802.11b/g/n20: 2412-2462 MHz; 802.11n40: 2422-2452 MHz |
| Antenna Type:                                                                                                                                                                                                                                                                        | PCB Antenna                                                                                                                              |
| ★Maximum Antenna Gain:                                                                                                                                                                                                                                                               | <b>Classic BT:</b> 3.71 dBi<br><b>BLE:</b> 3.71 dBi<br><b>2.4G WIFI:</b> 3.71 dBi                                                        |
| EUT Received Status:                                                                                                                                                                                                                                                                 | Good                                                                                                                                     |
| <i>Note:</i><br>1. The Maximum Antenna Gain was declared by manufacturer.<br>2. All measurement and test data in this report was gathered from production sample serial number: 2RG3-2 (Assigned by the BACL (Xiamen). The EUT supplied by the applicant was received on 2024-09-09) |                                                                                                                                          |

## MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to FCC §1.1307(b)(1) & §2.1091, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Limits for Maximum Permissible Exposure (MPE)

| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz)                                   | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
| 0.3-1.34                                                | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30                                                 | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500                                                | /                             | /                             | f/1500                              | 30                       |
| 1500-100,000                                            | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz; \* = Plane-wave equivalent power density;  
According to §1.1307(b)(1) & §2.1091 RF exposure is calculated.

### Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

$$\sum_i \frac{S_i}{S_{\text{limit},i}} \leq 1$$

**Calculated Data**

| Mode       | Frequency<br>(MHz) | Antenna Gain |           | ★Tune-up<br>Output Power |       | Evaluation<br>Distance<br>(cm) | Power<br>Density<br>(mW/cm <sup>2</sup> ) | MPE Limit<br>(mW/cm <sup>2</sup> ) |
|------------|--------------------|--------------|-----------|--------------------------|-------|--------------------------------|-------------------------------------------|------------------------------------|
|            |                    | (dBi)        | (numeric) | (dBm)                    | (mW)  |                                |                                           |                                    |
| BT         | 2402-2480          | 3.71         | 2.35      | 6.0                      | 3.98  | 20                             | 0.0019                                    | 1                                  |
| BLE        | 2402-2480          | 3.71         | 2.35      | 0                        | 1     | 20                             | 0.0005                                    | 1                                  |
| 2.4G Wi-Fi | 2412-2462          | 3.71         | 2.35      | 18.5                     | 70.79 | 20                             | 0.0331                                    | 1                                  |

Note:

1. The Tune-up output power was declared by the Manufacturer.
2. BLE, BT, 2.4G WiFi can not transmission simuntiously.

**Result:** The device meets MPE at distance 20cm.

## **APPENDIX A - EUT PHOTOGRAPHS**

---

Please refer to the attachment 2407X35401E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2407X35401E-RF-INP EUT INTERNAL PHOTOGRAPHS.

### **Declarations**

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $k=2$  with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***