

佛山市鑫逸丰电子有限公司

Foshan Xinyifeng Electronics Co., Ltd

Shop 1, Yongsan Lane, Xixi, Qicha Hongxing Village, Shiwan Town Street,
Chancheng District, Foshan, China

产品规格承认书

SPECIFICATION FOR APPROVAL

产品型号 DESC		42.5双槽背胶线圈6.8uh		版本 REV:A		Customer		海灵创																																					
						Model		ECP0-240010A																																					
						鑫逸丰料号																																							
一、尺寸 DIMENSION: (mm)						A		42.5±1.00																																					
D 线长可根据客户要求订做 此磁芯反面贴白膜双面胶 二、原理图 SCHEMATIC DIAGRAM: 三、绕线参数 Winding Specification: <table><thead><tr><th>序号 NO</th><th colspan="2">端子 TERMINAL</th><th>线径 WIRE</th><th>圈数 Tums</th><th>绕线方向 Winding Direction</th></tr></thead><tbody><tr><td>1</td><td>S</td><td>F</td><td>0.08*48P</td><td>10Ts</td><td>CCW</td></tr></tbody></table> 四、电子特性 ELECTRICAL CHARACTERISTICS: 温度TEMPERATURE:25±10°C, 湿度RELATIVE HUMIDITY:65±20% <table><thead><tr><th>序号 NO</th><th>项目 ITEM</th><th>端子 TERMINAL</th><th>标准 SPECIFICATION</th><th>测试条件 TEST FREQUENCY</th><th>测试仪器 TEST EQUIPMENTS</th></tr></thead><tbody><tr><td>1</td><td>L</td><td>S-F</td><td>6.80±10% μH</td><td>100KHz/1.0V</td><td>■TH2817B</td></tr><tr><td>2</td><td>Q Value</td><td>S-F</td><td>70 (Min)</td><td>100KHz/1.0V</td><td>■TH2817B</td></tr><tr><td>3</td><td>DCR</td><td>S-F</td><td>50mΩ (Max)</td><td>@ 25°C</td><td>■CH-502BC</td></tr></tbody></table>						序号 NO	端子 TERMINAL		线径 WIRE	圈数 Tums	绕线方向 Winding Direction	1	S	F	0.08*48P	10Ts	CCW	序号 NO	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS	1	L	S-F	6.80±10% μH	100KHz/1.0V	■TH2817B	2	Q Value	S-F	70 (Min)	100KHz/1.0V	■TH2817B	3	DCR	S-F	50mΩ (Max)	@ 25°C	■CH-502BC	B		39.5±0.50	
						序号 NO	端子 TERMINAL		线径 WIRE	圈数 Tums	绕线方向 Winding Direction																																		
						1	S	F	0.08*48P	10Ts	CCW																																		
						序号 NO	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS																																		
						1	L	S-F	6.80±10% μH	100KHz/1.0V	■TH2817B																																		
						2	Q Value	S-F	70 (Min)	100KHz/1.0V	■TH2817B																																		
						3	DCR	S-F	50mΩ (Max)	@ 25°C	■CH-502BC																																		
						C		20.5±1.00																																					
						D		40.00±2.00																																					
						D						线长可根据客户要求订做																																	
E		3.00±2.00																																											
T		1.80±0.50																																											
I		0.60±0.10																																											
备注																																													
1		线径: 0.08*24P*2漆包线																																											
2		绕线圈数:10TS																																											
3		起尾线是否交叉: 都是																																											
4		线圈包8mm宽左右高温胶带																																											
5		铁氧体磁片双面胶																																											
6																																													

We statement that All measurements were performed radiated and therefore additional antenna gain documentation is not required.