

# 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

---

## 1.1 General Information

### Client Information

Applicant: QAISE INC  
Address of applicant: 2626 N WEST LANE UNIT 1000, STOCKTON CA 95205, UNITED STATES

Manufacturer: GUANGZHOU MSH ELECTRONICS TECHNOLOGY CO LTD  
Address of manufacturer: UNIT 8,NO.28 JUFU WEST ROAD,YAYAO TOWN,HUADU DISTRICT,GUANGZHOU CITY,GUANGDONG PROVINCE, P.R.CHINA

### General Description of EUT:

Product Name: SPEAKER  
Trade Name: QAISE  
Model No.: SB-1500  
Adding Model(s): /  
Rated Voltage: Power Port:AC120V/60Hz  
Battery:DC7.4V  
Battery Capacity: 1800mAh  
Adapter Model: /  
FCC ID: 2A423-SB-1500  
Equipment Type: Fixed device

### Technical Characteristics of EUT:

#### Bluetooth

Bluetooth Version: V5.1 (BR/EDR mode)  
Frequency Range: 2402-2480MHz  
RF Output Power: -20.46dBm (Conducted)  
Data Rate: 1Mbps, 2Mbps, 3Mbps  
Modulation: GFSK,  $\pi/4$  DQPSK, 8DPSK  
Quantity of Channels: 79  
Channel Separation: 1MHz  
Type of Antenna: PCB Antenna  
Antenna Gain: 0dBi

## 1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

### (a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

### (b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; \* = Plane-wave equivalents power density

### 1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,  
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

### 1.4 MPE Calculation Result

For Bluetooth

Maximum Tune-Up output power: -20(dBm)

Maximum peak output power at antenna input terminal: 0.01(mW)

Prediction distance: >20(cm)

Prediction frequency: 2480(MHz)

Antenna gain: 0 (dBi)

Directional gain (numeric gain): 1.00

The worst case is power density at prediction frequency at 20cm: 0.0001(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

Result: Pass