



FCC TEST REPORT

Test report
On Behalf of
Zhongshan GaoWei Lighting manufactory Co.,Ltd
For
Desk Lamp
**Model No.: AT-288,AT-265, AT-285, AT-295, FT-755, FT-756, FT-758,
FT-775, FT-776**

FCC ID: 2A42QAT-288

Prepared for : **Zhongshan GaoWei Lighting manufactory Co.,Ltd**
701-5, Building 5, 20# of xinteng road, Guzhen town, Guangdong, China

Prepared By : **Shenzhen Tongzhou Testing Co.,Ltd**
**1th Floor, Building 1, Haomai High-tech Park, Huating Road 387, Dalang
Street, Longhua, Shenzhen, China**

Date of Test: **2022/3/1 ~ 2022/3/5**

Date of Report: **2022/3/7**

Report Number: **TZ220202988-E1**

The test report apply only to the specific sample(s) tested under stated test conditions
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



TEST RESULT CERTIFICATION

Applicant's name : Zhongshan GaoWei Lighting manufactory Co.,Ltd
Address : 701-5, Building 5, 20# of xinteng road, Guzhen town, Guangdong, China

Manufacture's Name : Zhongshan GaoWei Lighting manufactory Co.,Ltd
Address : 701-5, Building 5, 20# of xinteng road, Guzhen town, Guangdong, China

Product description

Trade Mark : AMBERTRONIX,FUGETEK
Product name : Desk Lamp
Model : AT-288,AT-265, AT-285, AT-295, FT-755, FT-756, FT-758, FT-775, FT-776
Standards : FCC Rules and Regulations Part 15 Subpart C (Section 15.209), ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Tongzhou Testing Co.,Ltd is acknowledged as copyright owner and source of the material. Shenzhen Tongzhou Testing Co.,Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test :

Date (s) of performance of tests : 2022/3/1 ~ 2022/3/5

Date of Issue : 2022/3/7

Test Result : **Pass**

Testing Engineer : Nancy Li

(Nancy Li)

Technical Manager : Hugo Chen

(Hugo Chen)

Authorized Signatory : Andy Zhang

(Andy Zhang)

1. GENERAL INFORMATION

1.1 General Description of EUT

Equipment	Desk Lamp
Model Name	AT-288,AT-265, AT-285, AT-295, FT-755, FT-756, FT-758, FT-775, FT-776
Model Difference	All the same except for the model name
Test Model	AT-288,
Trade Mark	AMBERTRONIX,FUGETEK
FCC ID	2A42QAT-288
Antenna Type	Coil Antenna
Antenna Gain	0dBi
Operation frequency	110.5– 205 KHz
Test Frequency	121.5 KHz
Modulation Type	ASK
Power Rating	Input: 5V---2A Output: 5V---1.0A(Wireless charger)
Test Sample ID	TZ220202988-1#

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.

2. SUMMARY OF TEST RESULTS

2.1 Test procedures according to the technical standards:

FCC KDB680106 D01 RF Exposure Wireless Charging Apps v03

FCC CFR 47			
Standard Section	Test Item	Judgment	Remark
FCC CFR 47 part1, 1.1310 KDB680106 D01v03 (3)(3)	Electric Field Strength (E) (V/m)	PASS	
	Magnetic Field Strength (H) (A/m)	PASS	

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2** , providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	All emissions, radiated(<30M)(9KHz-30MHz)	$\pm 2.45\text{dB}$
2	Temperature	$\pm 0.5^\circ\text{C}$
3	Humidity	$\pm 2\%$



2.3 Test Instruments

Equipment	Manufacturer	Model	Serial no.	Calibrated date	Calibrated Due
Exposure Level Tester	Narda	ELT-400	N-0713	2021-08-08	2022-08-07
B-Field Probe	Narda	ELT-400	M-1154	2021-08-08	2022-08-07

NOTE: 1. The calibration interval of the above test instruments is 12 months.

2.4 Special Accessories

No.	Equipment	Manufacturer	Model
1	Wireless charger tester	YBZ	YBZ
2	AC adapter	Xiaomi	MDY-10-EH

2.5 Operation of EUT during testing

Test Modes:		
Mode 1	AC/DC Adapter (5V/3A) + EUT + Wireless charger tester (5W Load)	Record
Mode 2	AC/DC Adapter (5V/3A) + EUT + Wireless charger tester (2.5W Load)	Pre-tested
Mode 3	AC/DC Adapter (5V/3A) + EUT + Wireless charger tester (Without Load)	Pre-tested
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		

3. MAXIMUM PERMISSIBLE EXPOSURE

Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03


Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table

1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

4. TEST PROCEDURE

a. For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device.

4.1 TEST SETUP



4.2 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE

Temperature	22.8°C	Humidity	55%
Test Engineer	Tony Luo	Configurations	Mode 1

E-Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

Test Mode	battery status	Unit	Frequency Range (MHz)	Measured E-Field Strength Values (V/m)					FCC E-Field Strength 50% Limits (V/m)	FCC E-Field Strength Limits (V/m)
				Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
1	<1%	V/m	0.1215	60.0184	19.0008	57.9072	37.0968	96.8136	307.0	614.0

Note: V/m= A/m *377



H-Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

Test Mode	battery status	Unit	Frequency Range (MHz)	Measured H-Field Strength Values (A/m)					FCC H-Field Strength 50% Limits (A/m)	FCC H-Field Strength Limits (A/m)
				Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
1	<1%	uT	0.1215	0.1990	0.0630	0.1920	0.1230	0.3210	--	--
	<1%	A/m	0.1215	0.1592	0.0504	0.1536	0.0984	0.2568	0.815	1.63

H-Field Strength at 20cm from the top surface of the EUT

Test Mode	Power Load	Unit	Frequency Range (MHz)	Measured H-Field Strength Values (A/m)		FCC H-Field Strength 50% Limits (A/m)	FCC H-Field Strength Limits (A/m)
				Test Position A	Test Position E		
1	<1%	uT	0.1215	0.1215	0.0950	--	--
	<1%	A/m	0.1215	0.1215	0.0760	0.815	1.63

Note: A/m=uT/1.25



4.3 Equipment Approval Considerations


The EUT does comply with KDB 680106 D01 as follow table.

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operate in the frequency range 110.5KHz~205KHz
Output power from each primary coil is less than 15 watts	Yes	The maximum output power for each primary coil is 5W.
The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes	The transfer system includes one primary coils and are able to detect and allow coupling only between individual pairs of coils.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

4.4 Conclusion

The detected emissions with a distance of 15cm surrounding the device and 20 cm above the top surface of the device are below the FCC E-Field Strength & H-Field Strength limits; and comply with the requirements of FCC KDB 680106 D01.

PHOTOGRAPH OF TEST



※※※※※THE END※※※※※