



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20220200254E-02
Applicant: shandong xiangzi keji fazhan youxiangongsi
Address of Applicant: xijinshidaidasha Bzuo 1207 jinanshi huaiyinqu shandongsheng
Equipment Under Test (EUT):
EUT Name: Video Game Console
Model No.: Super Console X PRO, Super Console X
Test Model No.: Super Console X PRO
Brand Name: Kinhank
FCC ID: 2A44C-XPRO
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2022-2-24
Date of Test: 2022-2-24 to 2022-3-1
Date of Issue: 2022-3-9
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: _____

(Lewis Zhou)

Reviewed By: _____

(Rock Huang)

Approved By: _____

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220200254E-02	Rev.01	Initial report	2022-3-9

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
3.3 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC.....	4
4 MPE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 Limits.....	5
4.1.2 Test Procedure.....	5
4.1.3 EUT RF Exposure.....	6

3 General Information

3.1 Client Information

Applicant:	shandong xiangzi ke jifazhan youxiangongsi
Address of Applicant:	xijinshidaidasha Bzuo 1207 jinanshi huaiyinqu shandongsheng
Manufacturer:	shandong xiangzi ke jifazhan youxiangongsi
Address of Manufacturer:	xijinshidaidasha Bzuo 1207 jinanshi huaiyinqu shandongsheng
Factory:	shandong xiangzi ke jifazhan youxiangongsi
Address of Factory:	xijinshidaidasha Bzuo 1207 jinanshi huaiyinqu shandongsheng

3.2 General Description of EUT

Product Name:	Video Game Console
Model No.:	Super Console X PRO, Super Console X
Test Model No.:	Super Console X PRO
Trade Mark:	Kinhank
Software Version:	V1
Hardware Version:	V1
EUT Power Supply:	INPUT:100-240V~ 50/60Hz 10W OUTPUT:5V= 2A

3.3 General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Sample Type:	☐ Mobile ☐ Portable ☒ Fix Location
Antenna Type:	Metal built-in antenna
Antenna Gain:	0 dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For 2.4G WIFI Classic

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

11B mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	7.11	7±1	8	6.31
Middle(2437MHz)	8.46	8±1	9	7.94
Highest(2462MHz)	7.79	7±1	8	6.31
11G mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	6.90	7±1	8	6.31
Middle(2437MHz)	8.15	8±1	9	7.94
Highest(2462MHz)	7.43	7±1	8	6.31
11N20 mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	7.11	7±1	8	6.31
Middle(2437MHz)	7.93	8±1	9	7.94
Highest(2462MHz)	7.61	7±1	8	6.31
11N40 mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2422MHz)	7.41	7±1	8	6.31
Middle(2437MHz)	7.70	7±1	8	6.31
Highest(2452MHz)	7.59	7±1	8	6.31

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
7.94	0	0.00158	1.0	PASS

Note: 1) Refer to report No. CQASZ20220200254E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (7.94 * 1) / (4 * 3.1416 * 20^2) = 0.00158$

3) EUT's WIFI module is more than 20cm away from the human body.

*** END OF REPORT ***