



11N20SISO_Ant1_2462




Date: 1.MAR.2022 01:52:43

11N40SISO_Ant1_2422




Date: 1.MAR.2022 02:05:04

11N40SISO_Ant1_2437




Date: 1.MAR.2022 02:08:05

11N40SISO_Ant1_2452



Date: 1.MAR.2022 02:09:42


5.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass


Test Result

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	-1.58	-46.21	≤ -31.58	PASS
		High	2462	-0.78	-47.33	≤ -30.78	PASS
11G	Ant1	Low	2412	-3.70	-37.01	≤ -33.7	PASS
		High	2462	-3.67	-47.54	≤ -33.67	PASS
11N20SISO	Ant1	Low	2412	-3.69	-36.02	≤ -33.69	PASS
		High	2462	-3.68	-47.36	≤ -33.68	PASS
11N40SISO	Ant1	Low	2422	-5.80	-38.46	≤ -35.8	PASS
		High	2452	-5.74	-47.04	≤ -35.74	PASS

Test Graphs




11G_Ant1_Low_2412



Date: 1.MAR.2022 01:36:44

11G_Ant1_High_2462




Date: 1.MAR.2022 01:42:05

11N20SISO_Ant1_Low_2412




Date: 1.MAR.2022 01:45:40

11N20SISO_Ant1_High_2462




Date: 1.MAR.2022 01:52:53

11N40SISO_Ant1_Low_2422




Date: 1.MAR.2022 02:05:14

11N40SISO_Ant1_High_2452



Date: 1.MAR.2022 02:09:51


5.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass


Test Result

TestMode	Antenna	Channel	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2437	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2462	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
11G	Ant1	2412	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2437	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2462	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
11N20SISO	Ant1	2412	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2437	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2462	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
11N40SISO	Ant1	2422	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2437	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS
		2452	Reference	Reference	Reference	Reference	PASS
			30~1000	30~1000	30~1000	30~1000	PASS
			1000~26500	1000~26500	1000~26500	1000~26500	PASS

Test Graphs




11B_Ant1_2412_1000~26500




Date: 1.MAR.2022 01:30:58

11B_Ant1_2437_0~Reference




Date: 1.MAR.2022 01:32:09

11B_Ant1_2437_30~1000




Date: 1.MAR.2022 01:32:13

11B_Ant1_2437_1000~26500




Date: 1.MAR.2022 01:32:35

11B_Ant1_2462_0~Reference




Date: 1.MAR.2022 01:34:49

11B_Ant1_2462_30~1000




Date: 1.MAR.2022 01:34:54

11B_Ant1_2462_1000~26500




Date: 1.MAR.2022 01:35:16

11G_Ant1_2412_0~Reference




Date: 1.MAR.2022 01:37:46

11G_Ant1_2412_30~1000




Date: 1.MAR.2022 01:37:51

11G_Ant1_2412_1000~26500




Date: 1.MAR.2022 01:38:13

11G_Ant1_2437_0~Reference




Date: 1.MAR.2022 01:39:23

11G_Ant1_2437_30~1000




Date: 1.MAR.2022 01:39:27

11G_Ant1_2437_1000~26500




Date: 1.MAR.2022 01:39:49

11G_Ant1_2462_0~Reference




Date: 1.MAR.2022 01:43:08

11G_Ant1_2462_30~1000




Date: 1.MAR.2022 01:43:12

11G_Ant1_2462_1000~26500




Date: 1.MAR.2022 01:43:34

11N20SISO_Ant1_2412_0~Reference




Date: 1.MAR.2022 01:46:43

11N20SISO_Ant1_2412_30~1000




Date: 1.MAR.2022 01:46:47

11N20SISO_Ant1_2412_1000~26500




Date: 1.MAR.2022 01:47:09

11N20SISO_Ant1_2437_0~Reference




Date: 1.MAR.2022 01:48:42

11N20SISO_Ant1_2437_30~1000




Date: 1.MAR.2022 01:48:46

11N20SISO_Ant1_2437_1000~26500




Date: 1.MAR.2022 01:49:08

11N20SISO_Ant1_2462_0~Reference




Date: 1.MAR.2022 01:53:56

11N20SISO_Ant1_2462_30~1000




Date: 1.MAR.2022 01:54:00

11N20SISO_Ant1_2462_1000~26500




Date: 1.MAR.2022 01:54:22

11N40SISO_Ant1_2422_0~Reference




Date: 1.MAR.2022 02:06:17

11N40SISO_Ant1_2422_30~1000




Date: 1.MAR.2022 02:06:21

11N40SISO_Ant1_2422_1000~26500




Date: 1.MAR.2022 02:06:43

11N40SISO_Ant1_2437_0~Reference





Date: 1.MAR.2022 02:08:12

11N40SISO_Ant1_2437_30~1000



Date: 1.MAR.2022 02:08:16





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Pretest the EUT at Transmitting mode and Charge +Transmitting mode, found the Charge +Transmitting mode which it is worse case. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Results:	Pass

5.8.1 Radiated emission below 1GHz

30MHz~1GHz
IHorizontal



	Read			Limit	Over		
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	31.51	9.71	15.52	25.23	40.00	-14.77 Peak	HORIZONTAL
2	50.41	13.81	8.00	21.81	40.00	-18.19 Peak	HORIZONTAL
3	127.66	9.09	10.41	19.50	43.50	-24.00 Peak	HORIZONTAL
4	292.06	8.47	13.46	21.93	46.00	-24.07 Peak	HORIZONTAL
5	568.61	9.57	18.99	28.56	46.00	-17.44 Peak	HORIZONTAL
6 pp	909.67	10.19	22.64	32.83	46.00	-13.17 Peak	HORIZONTAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Vertica



	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1 pp	31.95	16.18	15.41	31.59	40.00	-8.41	Peak	VERTICAL
2	49.71	19.88	8.23	28.11	40.00	-11.89	Peak	VERTICAL
3	100.93	8.69	10.60	19.29	43.50	-24.21	Peak	VERTICAL
4	123.27	8.37	10.58	18.95	43.50	-24.55	Peak	VERTICAL
5	295.15	9.65	13.57	23.22	46.00	-22.78	Peak	VERTICAL
6	890.73	9.37	23.88	33.25	46.00	-12.75	Peak	VERTICAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.8.2 Transmitter emission above 1GHz

Test mode:		802.11b(1Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4824.000	52.41	-4.26	48.15	74	-25.85	peak	H
4824.000	36.49	-4.26	32.23	54	-21.77	AVG	H
7236.000	51.62	1.18	52.80	74	-21.20	peak	H
7236.000	37.04	1.18	38.22	54	-15.78	AVG	H
4824.000	55.24	-4.26	50.98	74	-23.02	peak	V
4824.000	38.30	-4.26	34.04	54	-19.96	AVG	V
7236.000	51.91	1.18	53.09	74	-20.91	peak	V
7236.000	36.71	1.18	37.89	54	-16.11	AVG	V

Test mode:		802.11b(1Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	52.08	-4.12	47.96	74	-26.04	peak	H
4874.000	37.84	-4.12	33.72	54	-20.28	AVG	H
7311.000	49.55	1.46	51.01	74	-22.99	peak	H
7311.000	35.73	1.46	37.19	54	-16.81	AVG	H
4874.000	53.87	-4.12	49.75	74	-24.25	peak	V
4874.000	37.41	-4.12	33.29	54	-20.71	AVG	V
7311.000	49.22	1.46	50.68	74	-23.32	peak	V
7311.000	36.79	1.46	38.25	54	-15.75	AVG	V

Test mode:		802.11b(1Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	52.21	-4.03	48.18	74	-25.82	peak	H
4924.000	37.30	-4.03	33.27	54	-20.73	AVG	H
7386.000	50.33	1.66	51.99	74	-22.01	peak	H
7386.000	37.13	1.66	38.79	54	-15.21	AVG	H
4924.000	54.27	-4.03	50.24	74	-23.76	peak	V
4924.000	37.39	-4.03	33.36	54	-20.64	AVG	V
7386.000	50.94	1.66	52.60	74	-21.40	peak	V
7386.000	36.97	1.66	38.63	54	-15.37	AVG	V

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - For each suspected emission, the EUT was arranged to its worst case and

	then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Only the worst case is recorded in the report.
Test Results:	Pass

Test data:

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	58.63	-9.2	49.43	74	-24.57	peak	H
2390.000	44.80	-9.2	35.60	54	-18.40	AVG	H
2400.000	60.14	-9.39	50.75	74	-23.25	peak	H
2400.000	45.99	-9.39	36.60	54	-17.40	AVG	H
2390.000	58.62	-9.2	49.42	74	-24.58	peak	V
2390.000	44.69	-9.2	35.49	54	-18.51	AVG	V
2400.000	59.85	-9.39	50.46	74	-23.54	peak	V
2400.000	46.26	-9.39	36.87	54	-17.13	AVG	V

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	57.44	-9.29	48.15	74	-25.85	peak	H
2483.500	44.30	-9.29	35.01	54	-18.99	AVG	H
2483.500	58.40	-9.29	49.11	74	-24.89	peak	V
2483.500	46.12	-9.29	36.83	54	-17.17	AVG	V

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	59.15	-9.2	49.95	74	-24.05	peak	H
2390.000	44.94	-9.2	35.74	54	-18.26	AVG	H
2400.000	59.94	-9.39	50.55	74	-23.45	peak	H
2400.000	46.48	-9.39	37.09	54	-16.91	AVG	H
2390.000	58.36	-9.2	49.16	74	-24.84	peak	V
2390.000	44.74	-9.2	35.54	54	-18.46	AVG	V
2400.000	59.43	-9.39	50.04	74	-23.96	peak	V
2400.000	46.20	-9.39	36.81	54	-17.19	AVG	V

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	57.76	-9.29	48.47	74	-25.53	peak	H
2483.500	44.14	-9.29	34.85	54	-19.15	AVG	H
2483.500	57.65	-9.29	48.36	74	-25.64	peak	V
2483.500	45.89	-9.29	36.60	54	-17.40	AVG	V

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	58.81	-9.2	49.61	74	-24.39	peak	H
2390.000	44.28	-9.2	35.08	54	-18.92	AVG	H
2400.000	60.16	-9.39	50.77	74	-23.23	peak	H
2400.000	46.62	-9.39	37.23	54	-16.77	AVG	H
2390.000	58.64	-9.2	49.44	74	-24.56	peak	V
2390.000	44.13	-9.2	34.93	54	-19.07	AVG	V
2400.000	59.53	-9.39	50.14	74	-23.86	peak	V
2400.000	46.36	-9.39	36.97	54	-17.03	AVG	V

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	58.26	-9.29	48.97	74	-25.03	peak	H
2483.500	44.21	-9.29	34.92	54	-19.08	AVG	H
2483.500	57.96	-9.29	48.67	74	-25.33	peak	V
2483.500	46.22	-9.29	36.93	54	-17.07	AVG	V

Worse case mode:		802.11n(HT40)(13.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	59.11	-9.2	49.91	74	-24.09	peak	H
2390.000	44.53	-9.2	35.33	54	-18.67	AVG	H
2400.000	59.85	-9.39	50.46	74	-23.54	peak	H
2400.000	46.33	-9.39	36.94	54	-17.06	AVG	H
2390.000	58.96	-9.2	49.76	74	-24.24	peak	V
2390.000	44.43	-9.2	35.23	54	-18.77	AVG	V
2400.000	59.54	-9.39	50.15	74	-23.85	peak	V
2400.000	46.17	-9.39	36.78	54	-17.22	AVG	V

Worse case mode:		802.11n(HT40)(13.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	58.33	-9.29	49.04	74	-24.96	peak	H
2483.500	43.55	-9.29	34.26	54	-19.74	AVG	H
2483.500	58.19	-9.29	48.90	74	-25.10	peak	V
2483.500	45.76	-9.29	36.47	54	-17.53	AVG	V

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:




Above 1GHz:





6.2 Conducted Emission






7 Photographs - EUT Constructional Details











*** END OF REPORT***