

TEST REPORT

Product Name : Trenbader Bravo Gallery Wireless
Speaker
Brand Mark : Trenbader
FCC ID : 2A47UBGA
Model No. : BGA
TAS-NA, TAS-BU, TAS-YE, APUR-NA,
APUR-GN, APUR-OG, BGA-WHT,
BGA-BLK, BGO-BK, BGO-GN, BGO-VL,
Extension Model : BGO-OG, BCONF-BK, BCONF-WH,
BOOMX-BK, BOOMX-WH, BWM-GY,
BWM-WH, BGO2-BK, BGO2-GN,
BGO2-VL, BGO2-OG, BGO2-RD
Report Number : BLA-EMC-202201-A0402
Date of Sample Receipt : 2022/1/4
Date of Test : 2022/1/5 to 2022/2/26
Date of Issue : 2022/2/26
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

SUNRADO TECHNOLOGY LIMITED
Unit3, 6/F, Kam Hon Industrial Bldg, 8 Wang Kwun Rd,
Kowloon Bay, Hong Kong

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481



Compiled by: *hason*
Approved by: *Bluezhong*Review by: *Sueels*
Date: 2022/3/3

BlueAsia

REPORT REVISE RECORD

Version No.	Date	Description
00	2022/2/26	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY.....	7
2 GENERAL INFORMATION.....	8
3 GENERAL DESCRIPTION OF E.U.T.....	8
4 TEST ENVIRONMENT.....	9
5 TEST MODE.....	9
6 MEASUREMENT UNCERTAINTY.....	9
7 DESCRIPTION OF SUPPORT UNIT.....	10
8 LABORATORY LOCATION.....	10
9 TEST INSTRUMENTS LIST.....	11
10 ANTENNA REQUIREMENT.....	15
10.1 CONCLUSION.....	15
11 CONDUCTED SPURIOUS EMISSIONS.....	16
11.1 LIMITS.....	16
11.2 BLOCK DIAGRAM OF TEST SETUP.....	16
11.3 TEST DATA.....	17
12 CONDUCTED PEAK OUTPUT POWER.....	18
12.1 LIMITS.....	18
12.2 BLOCK DIAGRAM OF TEST SETUP.....	18
12.3 TEST DATA.....	19
13 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	20
13.1 LIMITS.....	20
13.2 BLOCK DIAGRAM OF TEST SETUP.....	20
13.3 PROCEDURE.....	20
13.4 TEST DATA.....	22
14 RADIATED SPURIOUS EMISSIONS.....	24
14.1 LIMITS.....	24
14.2 BLOCK DIAGRAM OF TEST SETUP.....	25
14.3 PROCEDURE.....	25
14.4 TEST DATA.....	27

15 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	35
15.1 LIMITS.....	35
15.2 BLOCK DIAGRAM OF TEST SETUP.....	36
15.3 PROCEDURE.....	36
15.4 TEST DATA.....	38
16 CONDUCTED BAND EDGES MEASUREMENT.....	42
16.1 LIMITS.....	42
16.2 BLOCK DIAGRAM OF TEST SETUP.....	42
16.3 TEST DATA.....	43
17 DWELL TIME.....	44
17.1 LIMITS.....	44
17.2 BLOCK DIAGRAM OF TEST SETUP.....	44
17.3 TEST DATA.....	45
18 HOPPING CHANNEL NUMBER.....	46
18.1 LIMITS.....	46
18.2 BLOCK DIAGRAM OF TEST SETUP.....	46
18.3 TEST DATA.....	46
19 CARRIER FREQUENCIES SEPARATION.....	47
19.1 LIMITS.....	47
19.2 BLOCK DIAGRAM OF TEST SETUP.....	47
19.3 TEST DATA.....	47
20 20DB BANDWIDTH.....	48
20.1 BLOCK DIAGRAM OF TEST SETUP.....	48
20.2 TEST DATA.....	48
21 APPENDIX.....	49
21.1 MAXIMUM CONDUCTED OUTPUT POWER.....	49
21.2 -20dB BANDWIDTH.....	51
21.3 OCCUPIED CHANNEL BANDWIDTH.....	53
21.4 BAND EDGE.....	55
21.5 BAND EDGE(HOPPING).....	58
21.6 CONDUCTED RF SPURIOUS EMISSION.....	61
21.7 CARRIER FREQUENCIES SEPARATION.....	65
21.8 NUMBER OF HOPPING CHANNEL.....	66

21.9 DWELL TIME.....	67
APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....	71
APPENDIX B: PHOTOGRAPHS OF EUT.....	73

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass

2 GENERAL INFORMATION

Applicant	SUNRADO TECHNOLOGY LIMITED
Address	Unit3, 6/F, Kam Hon Industrial Bldg, 8 Wang Kwun Rd, Kowloon Bay, Hong Kong
Manufacturer	ShenZhen ChuangDaRong KeJi YouXianGongSi
Address	6/F, Bldg A, TianRun Industry Zone, JiuWei, XiXiang, BaoAn Dist., ShenZhen, GuangDong, 518126, China
Factory	N/A
Address	N/A
Product Name	Trenbader Bravo Gallery Wireless Speaker
Test Model No.	BGA

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	1.0
Software Version	1.0
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	PCB Antenna
Antenna Gain:	2.81dBi (provided by applicant)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.8V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
<i>Remark: The EUT only has the GFSK modulation function and only the mode would be recorded in this report.DH1 DH3 DH5 all have been tested,only worse case DH1 is reported</i>	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	HASEE	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Conducted Peak Output Power					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	25/11/2020	24/11/2023
Receiver	R&S	ESPI3	101082	24/9/2021	23/9/2022
LISN	R&S	ENV216	3560.6550.15	24/9/2021	23/9/2022
LISN	AT	AT166-2	AKK1806000003	26/9/2021	25/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Conducted Band Edges Measurement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
-----------	--------------	-------	-----	----------	---------

Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Dwell Time

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Hopping Channel Number

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Carrier Frequencies Separation

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022

Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022
------------------	---------	--------	------------	-----------	-----------

Test Equipment Of 20dB Bandwidth					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


10.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.81dBi.




11 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


12 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

12.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq \text{hopping channels} < 50$
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

12.2 BLOCK DIAGRAM OF TEST SETUP



12.3 TEST DATA**Pass: Please Refer To Appendix: For Details**

BlueAsia

13 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

13.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

13.2 BLOCK DIAGRAM OF TEST SETUP



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

13.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,


4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $LISN = Read\ Level + Cable\ Loss + LISN\ Factor$

13.4 TEST DATA

[TestMode: TX]; [Line: Line] [Power:AC120V/60Hz]



Site: Phase: **L1** Temperature: (C)
Limit: FCC Class B Conduction(QP) Power: Humidity: %RH
EUT: TrenbaderBravoGalleryWirelessSpeak
M/N: BGA
Mode: TX mode
Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.5380	22.52	9.87	32.39	56.00	-23.61	QP	
2	0.5380	13.34	9.87	23.21	46.00	-22.79	AVG	
3 *	0.7420	25.26	9.89	35.15	56.00	-20.85	QP	
4	0.7420	14.13	9.89	24.02	46.00	-21.98	AVG	
5	1.7260	17.30	9.93	27.23	56.00	-28.77	QP	
6	1.7260	10.73	9.93	20.66	46.00	-25.34	AVG	
7	2.8980	14.87	9.97	24.84	56.00	-31.16	QP	
8	2.8980	4.54	9.97	14.51	46.00	-31.49	AVG	
9	4.4220	13.10	9.93	23.03	56.00	-32.97	QP	
10	4.4220	2.98	9.93	12.91	46.00	-33.09	AVG	
11	12.5300	28.40	10.26	38.66	60.00	-21.34	QP	
12	12.5300	15.55	10.26	25.81	50.00	-24.19	AVG	


*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX]; [Line: Nutral] [Power:AC120V/60Hz]

Conducted Emission Measurement



Site: Phase: **N** Temperature: (C)
Limit: FCC Class B Conduction(QP) Power: Humidity: %RH
EUT: TrenbaderBravoGalleryWirelessSpeak
M/N: BGA
Mode: TX mode
Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.7420	23.15	9.82	32.97	56.00	-23.03	QP	
2 *	0.7420	13.97	9.82	23.79	46.00	-22.21	AVG	
3	1.8380	16.17	9.86	26.03	56.00	-29.97	QP	
4	1.8380	10.04	9.86	19.90	46.00	-26.10	AVG	
5	4.1420	13.07	9.91	22.98	56.00	-33.02	QP	
6	4.1420	4.06	9.91	13.97	46.00	-32.03	AVG	
7	6.6700	12.80	10.01	22.81	60.00	-37.19	QP	
8	6.6700	1.98	10.01	11.99	50.00	-38.01	AVG	
9	12.4780	20.27	10.24	30.51	60.00	-29.49	QP	
10	12.4780	9.01	10.24	19.25	50.00	-30.75	AVG	
11	25.1780	2.41	10.47	12.88	60.00	-47.12	QP	
12	25.1780	-6.25	10.47	4.22	50.00	-45.78	AVG	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

14 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX middle channel;TX Low channel;TX high channel
Test Mode (Final Test)	TX middle channel;TX Low channel;TX high channel
Tester	Sven
Temperature	25℃
Humidity	52%

14.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

14.4 TEST DATA

[TestMode: TX]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202201-A04
EUT: Trenbader Bravo Gallery Wireless Speaker	Test Engineer: Leo
M/N: BGA	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2022-02-22 11:10:34




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	44.065MHz	40.0	25.0	-15.0	1.0	24.0	QP	Hor	100.0	0.0
2*	148.825MHz	43.5	25.2	-18.3	1.7	23.5	QP	Hor	100.0	24.0
3*	194.173MHz	43.5	28.7	-14.8	7.9	20.8	QP	Hor	100.0	0.0
4*	260.375MHz	46.0	34.9	-11.1	12.3	22.6	QP	Hor	100.0	0.0
5*	480.808MHz	46.0	33.4	-12.6	5.2	28.2	QP	Hor	100.0	167.0
6*	728.400MHz	46.0	34.9	-11.1	2.3	32.6	QP	Hor	100.0	130.0

Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]


Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202201-A04
EUT: Trenbader Bravo Gallery Wireless Speaker	Test Engineer: Leo
M/N: BGA	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2022-02-22 11:12:47



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	53.159MHz	40.0	31.9	-8.1	8.2	23.7	QP	Ver	100.0	241.0
2*	130.274MHz	43.5	24.3	-19.2	1.1	23.2	QP	Ver	100.0	141.0
3*	194.900MHz	43.5	24.5	-19.0	3.7	20.8	QP	Ver	100.0	106.0
4*	263.649MHz	46.0	27.8	-18.2	5.0	22.8	QP	Ver	100.0	110.0
5*	479.231MHz	46.0	31.5	-14.5	3.3	28.2	QP	Ver	100.0	157.0
6*	726.096MHz	46.0	34.4	-11.6	1.9	32.5	QP	Ver	100.0	6.0

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-L
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3679.000	41.43	7.73	49.16	74.00	-24.84	peak	
2	*	4807.000	48.61	3.71	52.32	74.00	-21.68	peak	
3		7206.000	39.90	5.96	45.86	74.00	-28.14	peak	
4		8026.500	42.26	7.98	50.24	74.00	-23.76	peak	
5		9608.000	39.55	9.29	48.84	74.00	-25.16	peak	
6		11316.500	39.58	11.88	51.46	74.00	-22.54	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-L
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3843.500	43.44	7.12	50.56	74.00	-23.44	peak	
2	*	4804.000	48.39	3.71	52.10	74.00	-21.90	peak	
3		7206.000	40.27	5.96	46.23	74.00	-27.77	peak	
4		8050.000	42.01	8.01	50.02	74.00	-23.98	peak	
5		9608.000	39.55	9.29	48.84	74.00	-25.16	peak	
6		10893.500	39.82	11.87	51.69	74.00	-22.31	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-M
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3867.000	42.45	6.82	49.27	74.00	-24.73	peak	
2	*	4877.500	48.06	3.37	51.43	74.00	-22.57	peak	
3		7323.000	37.68	6.43	44.11	74.00	-29.89	peak	
4		8003.000	41.16	7.94	49.10	74.00	-24.90	peak	
5		9764.000	38.59	9.63	48.22	74.00	-25.78	peak	
6		10964.000	39.15	11.94	51.09	74.00	-22.91	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-M
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3796.500	43.88	7.65	51.53	74.00	-22.47	peak	
2		4877.500	46.96	3.37	50.33	74.00	-23.67	peak	
3		7323.000	40.34	6.43	46.77	74.00	-27.23	peak	
4		8191.000	41.52	8.20	49.72	74.00	-24.28	peak	
5	*	9764.000	42.11	9.63	51.74	74.00	-22.26	peak	
6		11340.000	39.72	11.85	51.57	74.00	-22.43	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-H
Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3702.500	43.55	7.72	51.27	74.00	-22.73	peak	
2		4948.000	46.72	3.65	50.37	74.00	-23.63	peak	
3		7440.000	39.70	6.86	46.56	74.00	-27.44	peak	
4		8144.000	40.96	8.13	49.09	74.00	-24.91	peak	
5		9920.000	38.03	10.16	48.19	74.00	-25.81	peak	
6	*	11340.000	39.55	11.85	51.40	74.00	-22.60	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-H
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3843.500	42.50	7.12	49.62	74.00	-24.38	peak	
2		4960.000	39.70	3.75	43.45	74.00	-30.55	peak	
3		7440.000	39.75	6.86	46.61	74.00	-27.39	peak	
4		8238.000	40.92	8.22	49.14	74.00	-24.86	peak	
5		9920.000	37.06	10.16	47.22	74.00	-26.78	peak	
6	*	11763.000	39.98	11.63	51.61	74.00	-22.39	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

15 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX Low channel;TX high channel
Test Mode (Final Test)	TX Low channel;TX high channel
Tester	Sven
Temperature	25℃
Humidity	52%

15.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamplifier Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

15.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-L
Note:

Polarization: **Horizontal** Temperature: (C)
Power: Humidity: %RH


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2310.000	42.70	-3.93	38.77	74.00	-35.23	peak	
2	*	2390.000	43.27	-3.58	39.69	74.00	-34.31	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Trenbader Bravo Gallery Gallery Wi
M/N: BGA
Mode: TX-H
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	2483.500	42.68	-3.14	39.54	74.00	-34.46	peak	
2		2500.000	42.47	-3.08	39.39	74.00	-34.61	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass