

Condition	Mode	Frequency (MHz)	Conducted PSD (dBm)	Limit (dBm)	Verdict
NVNT	a	5500	-2.6	11	Pass
NVNT	a	5580	-1.59	11	Pass
NVNT	a	5700	-1.04	11	Pass
NVNT	n20	5500	-3.24	11	Pass
NVNT	n20	5580	-3.6	11	Pass
NVNT	n20	5700	-2.69	11	Pass
NVNT	n40	5510	-7.78	11	Pass
NVNT	n40	5550	-9.33	11	Pass
NVNT	n40	5670	-7.51	11	Pass
NVNT	ac20	5500	-3.78	11	Pass
NVNT	ac20	5580	-3.85	11	Pass
NVNT	ac20	5700	-2.27	11	Pass
NVNT	ac40	5510	-8.05	11	Pass
NVNT	ac40	5550	-9.36	11	Pass
NVNT	ac40	5670	-7.17	11	Pass
NVNT	ac80	5530	-11.03	11	Pass
NVNT	ax20	5500	-3.25	11	Pass
NVNT	ax20	5580	-3.67	11	Pass
NVNT	ax20	5700	-2.98	11	Pass
NVNT	ax40	5510	-9.06	11	Pass
NVNT	ax40	5550	-9.79	11	Pass
NVNT	ax40	5670	-7.36	11	Pass
NVNT	ax80	5530	-11.25	11	Pass

Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/510K Hz)	Conducted PSD (dBm/500K Hz)	Limit (dBm/500K Hz)	Verdict
NVNT	a	5745	-5.69	-5.776	30	Pass
NVNT	a	5785	-7.13	-7.216	30	Pass
NVNT	a	5825	-8.07	-8.156	30	Pass
NVNT	n20	5745	-7.56	-7.646	30	Pass
NVNT	n20	5785	-9.02	-9.106	30	Pass
NVNT	n20	5825	-9.74	-9.826	30	Pass
NVNT	n40	5755	-11.38	-11.466	30	Pass
NVNT	n40	5795	-12.89	-12.976	30	Pass
NVNT	ac20	5745	-7.64	-7.726	30	Pass
NVNT	ac20	5785	-9.4	-9.486	30	Pass
NVNT	ac20	5825	-9.95	-10.036	30	Pass
NVNT	ac40	5755	-11.33	-11.416	30	Pass
NVNT	ac40	5795	-12.95	-13.036	30	Pass
NVNT	ac80	5775	-14.73	-14.816	30	Pass
NVNT	ax20	5745	-7.9	-7.986	30	Pass
NVNT	ax20	5785	-9.12	-9.206	30	Pass
NVNT	ax20	5825	-10.1	-10.186	30	Pass
NVNT	ax40	5755	-11.41	-11.496	30	Pass
NVNT	ax40	5795	-13.63	-13.716	30	Pass
NVNT	ax80	5775	-15.1	-15.186	30	Pass

Note: Correction Factor = $10\log(500\text{KHz}/\text{RBW in measurement}) = -0.086$















































































