



MPE REPORT

FCC ID: 2A483-S7-8HQG-GPY6

Product	:	Electronic Cabinet Lock
Model Name	:	S7-8HQG-GPY6
Brand	:	CODACE
Report No.	:	PTC22021500501E-FC02
Prepared for		
GUANGZHOU LEITOU ZHINENGKEJI YOUXIANGONGSI		
Room 207, 2 / F, building 8, No. 87, Jiangxia East 1st Road, Huangshi street, Baiyun District, Guangzhou		
Prepared by		
Precise Testing & Certification Co., Ltd		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



1 TEST RESULT CERTIFICATION

Applicant's name : GUANGZHOU LEITOU ZHINENGKEJI YOUXIANGONGSI

Address : Room 207, 2 / F, building 8, No. 87, Jiangxia East 1st Road, Huangshi street, Baiyun District, Guangzhou

Manufacture's name : GUANGZHOU LEITOU ZHINENGKEJI YOUXIANGONGSI

Address : Room 207, 2 / F, building 8, No. 87, Jiangxia East 1st Road, Huangshi street, Baiyun District, Guangzhou

Product name : Electronic Cabinet Lock

Model name : S7-8HQQ-GPY6

Standards : FCC 1.1310 & §1.1307(b)

Test Date : Sept.06, 2021 to Sept. 26, 2021

Date of Issue : Mar. 12, 2022

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

Win Wang / Engineer

Technical Manager:

Wu Weimin / Manager

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

R=20cm BT:

Peak Power: [2480MHz, 0.42 ± 1 dBm (1.387mW) output power]

Gain:0dBi=1

$P_d = (P_{out} * G) / (4 * \pi * R^2)$

So , $P_d = 0.000276$ mW/cm²

Conclusion:

For the max result: $0.000276 \leq 1.0$, Compliance with RF Exposure requirement.

*****THE END REPORT*****