



SPECIFICATION

APPLICATION FOR APPROVAL

CUSTOMER MeiG Smart Technology Co., Ltd

Part No. M05. 08. F8BSC002

Vonder name Shenzhen Luxshare Acoustics Technology Ltd.

Supplier Address Block A,SANYO New Industrial Zone,West HaoYi,Shajing, Bao'an,Shenzhen,China

ICT P/N LZZRF041-DT-H

Description F8BSC WiFi AUX Antenna

Date 2025/4/16


Customer confirmation			
RF Engineer	ME Engineer	Manager	PM
LUXSHARE ICT			
RF Engineer	ME Engineer	Manager	PM
Zongming Song	Baojun Zhan	AllenMT Wu	Feixiang Qin

FM-RD-11A

目 录(index)

Item	页次
1	cover
2	index
3	The Basic Parameters
4	RF Performance Test Report
5	Product Drawing

The Basic Parameters


Item	Specifications
Antenna structure composition	FPC+CABLE
Frequency	2.4~2.5/5.15~5.85/5.925~7.125GHz
V. S. W. R	≤ 3
Gain	≤ 4
Polarization	Linear polarization
Impedance	50 Ω
Plastic material	not
Joint type	IPEX 4
Operation temperature	-40° C to 85° C
Storage temperature	-40° C to 85° C
Humidity	Non-condensing 65° C 95% RH
illustration	 Technical drawing of the antenna assembly. The drawing shows a side view of the antenna with dimensions: *38.7±0.2 (width), *8.7±0.2 (height), and *150±1.5 (length). A label 'FPC+ CABLE ANTENNA' is present. A callout (1) points to the antenna body, and a callout (3) points to the cable. A note '指示开口方向' (indicates opening direction) is shown with an arrow pointing to the cable end.

RF Performance Test Report



Internal use – confidential

Antenna VSWR




Efficiency & Gain


Aux Ant			
Fre. (MHz)	Efficiency (dB)	Peak Gain (dBi)	Efficiency (%)
2400	-5.64	0.11	27.29
2450	-5.64	-0.10	27.29
2500	-6.34	-1.94	23.23
5150	-4.72	0.54	33.73
5250	-4.74	1.81	33.59
5350	-4.13	2.62	38.67
5470	-3.62	2.75	43.47
5600	-4.26	2.12	37.46
5725	-5.20	0.97	30.19
5785	-5.10	0.86	30.91
5800	-5.16	0.70	30.44
5850	-5.31	0.76	29.46
5925	-5.16	1.01	30.47
6025	-4.85	1.64	32.77
6125	-4.88	1.32	32.54
6225	-4.58	1.82	34.84
6325	-4.60	1.01	34.69
6425	-4.27	1.79	37.42
6525	-4.85	1.41	32.71
6625	-4.84	1.59	32.80
6725	-4.71	2.20	33.79
6825	-4.11	3.37	38.80
6925	-4.26	3.10	37.46
7025	-4.61	2.36	34.59
7125	-5.17	1.43	30.38

AUX Antenna 3D Radiation Pattern


2450MHZ :



5470MHZ :




6525MHZ :




AUX Antenna 2D Radiation Pattern


2450MHZ :



5470MHZ :



6525MHZ :




RoHS + HF

REV	DESCRIPTION	DESIGN	DATE
X1	NEW DRAWING	BAOJUN.ZHAN	2025.01.03
X2	MODIFY DIMENSIONS	DWA	2025.02.11

前視圖說明

側視圖說明

後視圖說明



Note:

- 标注 “*” 为重点检查尺寸
- 焊点光滑,无假焊,无锡尖
- 本产品使用物料及制程必须符合“QW-Q-043”文件对应环境物质相关规定
- 此產品及其附屬包裝材料的均質成份須滿足無鹵管制要求:
Br<900ppm,Cl<900ppm,Br+Cl<1500ppm

5	---	ADHESIVE	DOUBLE SIDED SELF-ADHESIVE TAPE, 3M467, T=0.05MM	1	TOLERANCE(UNLESS SPECIFIED)	CUSTOMER P/N:	LUXSHARE-ICT
4	---	FTC	(THADH+ED CU(1-LAYER)	1	*K ±0.5	AP'D: ANDERSON	TITLE:FRBSC_AUX_ANTENNA_ASSY
3	---	TRANSPARENT TUBE	L=18MM	1	*KX ±0.25	CHK'D: BAOJUN.ZHAN	PART NO: LZZRF041-DT-H
2	---	CABLE	FET DIA. 1.13MM SINGLE ENDED COAXIAL LOW LOSS CABLE (COLOR: GRAYWA)	1	*KXX ±0.10	DRAW: BAOJUN.ZHAN	SCALE 1:1
1	---	CONNECTOR	SPEEDTECH CB7P115-00002-H FOR CABLE DIA. 1.13MM PLUG CONNECTOR	1	*KXXX ±0.05		SHEET 1/1
ITEM	PART NO	NAME	DESCRIPTION	Q'TY	UNIT		SIZE A4
1	---	---	---	---	---		REV X2