

TEST REPORT

EUT Description	WLAN and BT, 2x2 PCIe M.2 1216 SD adapter card
Brand Name	Intel® Wireless-AC 9560
Model Name	9560D2W
FCC ID	PD99560D2
ISED ID	1000M-9560D2
Date of Test Start/End	2017-10-10 / 2017-11-28
Features	802.11ac, Dual Band, 2x2 Wi-Fi + Bluetooth® 5 (see section 5)

Applicant	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200 Columbia, South Carolina 29210 USA
Contact Person	Steven Hackett
Telephone/Fax/ Email	steven.c.hackett@intel.com

Reference Standards	FCC CFR Title 47 Part 15 C RSS-247 issue 2, RSS-Gen issue 4 (see section 1)
---------------------	---

Test Report identification	170919-03.TR05
Revision Control	Rev. 00 This test report revision replaces any previous test report revision (see section 8)

The test results relate only to the samples tested.
The test report shall not be reproduced in full, without written approval of the laboratory.

Issued by

Reviewed by

Gregory ROUSTAN
(Test Engineer Lead)

Olivier FARGANT
(Technical Manager)

Intel Mobile Communications France S.A.S – WRF Lab
425 rue de Goa – Le Cargo B6 - 06600, Antibes, France
Tel. +33493001400 / Fax +33493001401

Table of Contents

1. Standards, reference documents and applicable test methods	3
2. General conditions, competences and guarantees	3
3. Environmental Conditions	3
4. Test samples	4
5. EUT Features	4
6. Remarks and comments	4
7. Test Verdicts summary	5
7.1. BT BASIC DATA RATE / ENHANCED DATA RATE	5
8. Document Revision History	5
Annex A. Test & System Description	6
A.1 MEASUREMENT SYSTEM	6
A.2 TEST EQUIPMENT LIST	8
A.3 MEASUREMENT UNCERTAINTY EVALUATION	9
Annex B. Test Results	10
B.1 20dB BANDWIDTH AND CARRIER FREQUENCY SEPARATION	10
B.2 NUMBER OF HOPPING CHANNELS	14
B.3 TIME OF OCCUPANCY (DWEIL TIME)	18
B.4 MAXIMUM PEAK OUTPUT POWER ANTENNA GAIN	25
B.5 OUT-OF-BAND EMISSION (CONDUCTED)	28
B.6 RADIATED SPURIOUS EMISSION	54
Annex C. Photographs	66
C.1 TEST SETUP	66
C.2 TEST SAMPLE	68

1. Standards, reference documents and applicable test methods

1. FCC 47 CFR part 15 - Subpart C – §15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
2. FCC 47 CFR part 15 - Subpart C – §15.209 Radiated emission limits; general requirements.
3. ANSI C63.10-2013 - American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
4. DA 00-705 Released March 30, 2000 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems
5. RSS-247 Issue 2 - Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
6. RSS-Gen Issue 4 - General Requirements for Compliance of Radio Apparatus.

2. General conditions, competences and guarantees

- ✓ Intel Mobile Communications France SAS Wireless RF Lab (Intel WRF Lab) is an ISO/IEC 17025:2005 testing laboratory accredited by the American Association for Laboratory Accreditation (A2LA) with the certificate number 3478.01.
- ✓ Intel Mobile Communications France SAS Wireless RF Lab (Intel WRF Lab) is an Accredited Test Firm recognized by the FCC, with Designation Number FR0011.
- ✓ Intel Mobile Communications France SAS Wireless RF Lab (Intel WRF Lab) is a Registered Test Site listed by ISED, with ISED Assigned Code 1000Y.
- ✓ Intel WRF Lab only provides testing services and is committed to providing reliable, unbiased test results and interpretations.
- ✓ Intel WRF Lab is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.
- ✓ Intel WRF Lab has developed calibration and proficiency programs for its measurement equipment to ensure correlated and reliable results to its customers.
- ✓ This report is only referred to the item that has undergone the test.
- ✓ This report does not imply an approval of the product by the Certification Bodies or competent Authorities.

3. Environmental Conditions

- ✓ At the site where the measurements were performed the following limits were not exceeded during the tests:

Temperature	23 °C ±3 °C
Humidity	40 % ± 10 %

4. Test samples

Sample	Control #	Description	Model	Serial #	Date of receipt	Note
#01	170919-03.S29	Module	9560D2W	WFM: 3413E8702821	2017-10-02	Used for conducted tests
	170524-02.S15	Extender Board	PCB00609_01	6092416-442	2017-05-30	
	170000-01.S01	Laptop	Latitude E5470	DPBLMC2	2017-03-28	
	170220-04.S04	Adapter 1216SD to M.2	JfP Adapter M2	N/A	2017-04-10	
#02	170919-03.S22	Module	9560D2W	WFM:3413 E870281C	2017-10-02	Used for radiated tests
	170220-02.S03	Extender Board	PCB00609_01	6092416-446	2017-02-20	
	170000-01.S13	Laptop	Latitude E5470	FT6LMC2	2017-05-30	
	170727-02.S11	Adapter 1216SD to M.2	JfP Adapter M2	N/A	2017-08-09	
#03	170919-03.S21	Module	9560D2W	WFM:3413 E8702826	2017-10-02	Used for radiated tests
	170220-02.S04	Extender Board	PCB00609_01	6092416-493	2017-02-20	
	170801-01.S10	Laptop	Latitude E7470	7KNOXF2	2017-09-13	
	170727-02.S13	Adapter 1216SD to M.2	JfP Adapter M2	N/A	2017-08-09	

5. EUT Features

Brand Name	Intel® Wireless-AC 9560		
Model Name	9560D2W		
FCC ID	PD99560D2		
ISED ID	1000M-9560D2		
Software Version	10.1739.0-06012		
Driver Version	99.0.28.6		
Prototype / Production	Production		
Supported Radios	802.11b/g/n 2.4GHz (2400.0 – 2483.5 MHz) 802.11a/n/ac 5.2GHz (5150.0 – 5350.0 MHz) 5.6GHz (5470.0 – 5725.0 MHz) 5.8GHz (5725.0 – 5850.0 MHz) Bluetooth 5 2.4GHz (2400.0 – 2483.5 MHz)		
Antenna Information	CHAIN A: PIFA antenna. WiFi 2.4GHz & 5GHz and BT CHAIN B: PIFA antenna. WiFi 2.4GHz & 5GHz		
Additional Information			

6. Remarks and comments

N/A

7. Test Verdicts summary

7.1. BT Basic Data Rate / Enhanced Data Rate

FCC part	RSS part	Test name	Verdict
15.247 (a) (1)	RSS-247 Clause 5.1 (a) and (b)	20dB Bandwidth and Carrier frequency separation	P
15.247 (a) (1) (iii)	RSS-247 Clause 5.1 (d)	Number of hopping channels	P
15.247 (a) (1) (iii)	RSS-247 Clause 5.1 (d)	Time of Occupancy (Dwell Time)	P
15.247 (b) (1)	RSS-247 Clause 5.4 (b)	Maximum Peak Output Power and antenna gain	P
15.247 (d)	RSS-247 Clause 5.5	Out-of-band Emissions (conducted)	P
15.247 (d) 15.209	RSS-247 Clause 5.5 RSS GEN Clause 8.9	Out-of-band Emissions (radiated)	P

8. Document Revision History

Revision #	Date	Modified by	Revision Details
Rev.00	2017-11-28	A.Sayoud	First Issue


Annex A. Test & System Description

A.1 Measurement System


Measurements were performed using the following setups.

The DUT was installed in a test fixture and this test fixture is connected to a laptop computer and AC/DC power adapter. The laptop computer was used to configure the EUT to continuously transmit at a specified output power using all different modes and modulation schemes.


Conducted Setup




Radiated Setup < 1GHz



Radiated Setup 1 GHz – 18 GHz



Radiated Setup > 18 GHz



A.2 Test Equipment List

Conducted Setup

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0316	Spectrum analyzer	FSV30	103309	Rohde & Schwarz	2017-09-22	2019-09-22

Radiated Setup-1

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0133	Spectrum analyzer	FSV40	101358	Rohde & Schwarz	2016-04-15	2018-04-15
0137	Log antenna 30 MHz – 1 GHz	3142E	00156946	ETS Lindgren	2015-12-11	2017-12-11
0135	Semi Anechoic chamber	FACT 3	5720	ETS Lindgren	2016-04-28	2018-04-28
0530	Measurement Software	EMC32	100623	Rohde & Schwarz	N/A	N/A
0296	Power Supply	6673A	MY41000318	Agilent	N/A	N/A
0346	Multimeter	34401A	US36054685	HP	2016-02-04	2018-02-04

N/A: Not Applicable

Radiated Setup-2

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0420	Spectrum analyzer	FSV40	101556	Rohde & Schwarz	2016-04-15	2018-04-15
0138	Horn antenna 1 GHz – 6.4 GHz	3117	00152266	ETS Lindgren	2016-03-14	2018-03-14
0141	Double Ridged Horn Antenna 1 GHz – 18 GHz	3117	00157736	ETS Lindgren	2016-04-13	2018-04-13
0409	PreAmplifier	3117-PA	00157993	ETS Lindgren	N/A	N/A
0334	Double Ridged Horn Antenna 18 GHz – 40 GHz	3116C-PA	00196308	ETS Lindgren	2017-08-22	2019-08-22
0337	Full Anechoic chamber	RFD_FA_100	5996	ETS Lindgren	2016-04-28	2018-04-28
0329	Measurement Software	EMC32	100401	Rohde & Schwarz	N/A	N/A

N/A: Not Applicable

Radiated Setup - shared equipments

ID#	Device	Type/Model	Serial #	Manufacturer	Cal. Date	Cal. Due Date
0617	Power Sensor 50MHz-18GHz	NRP-Z81	104386	Rohde & Schwarz	2017-05-24	2019-05-24
0618	Power Sensor 50MHz-18GHz	NRP-Z81	104382	Rohde & Schwarz	2017-05-24	2019-05-24

A.3 Measurement Uncertainty Evaluation

The system uncertainty evaluation is shown in the below table:


Measurement type	Uncertainty [$\pm$ dB]
Conducted Power	± 1.0
Conducted Spurious Emission	± 2.9
Radiated tests <1GHz	± 3.8
Radiated tests 1GHz - 40 GHz	± 4.7

Annex B. Test Results

B.1 20dB Bandwidth and carrier frequency separation

Test limits

FCC part	RSS part	Limits
15.247 (a) (1)	RSS-247 Clause 5.1 (a) and (b)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.




Results tables:

Mode	Packet Type	Channel Number	Frequency [MHz]	20dB BW [MHz]	Freq. Separation [kHz]
Basic Rate GFSK	DH5	0	2402	0.818	1000
		39	2441	0.816	
		78	2480	0.837	
EDR $\pi/4$ -DQPSK	2DH5	0	2402	1.445	1000
		39	2441	1.452	
		78	2480	1.420	
EDR 8-DPSK	3DH5	0	2402	1.409	1000
		39	2441	1.427	
		78	2480	1.422	


Results screenshot

Basic Rate - GFSK

20dB BW – CH78




Freq. Separation




EDR – $\pi/4$ -DQPSK

20dB BW – CH39




Freq. Separation




EDR – 8-DPSK

20dB BW – CH39



Freq. Separation




B.2 Number of hopping channels

Test limits

FCC part	RSS part	Limits
15.247 (a) (1) (iii)	RSS-247 Clause 5.1 (d)	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test procedure

The setup below was used to measure the number of hopping channels. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.




Results tables


Mode	Packet Type	Number of hopping channels
Basic Rate GFSK	DH5	79
EDR $\pi/4$ -DQPSK	2DH5	79
EDR 8-DPSK	3DH5	79


Number of hopping channels

Basic Rate – GFSK




Basic Rate – GFSK




EDR – $\pi/4$ -DPSK

EDR – $\pi/4$ -DPSK


EDR – 8-DPSK



EDR – 8-DPSK




B.3 Time of Occupancy (Dwell Time)

FCC part	RSS part	Limits
15.247 (a) (1) (iii)	RSS-247 Clause 5.1 (d)	The average time of occupancy (Dwell Time) on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test procedure

The setup below was used to measure the dwell time. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.



In the worst case, the system makes 1600 hops per second with 79 channels, providing a 1 timeslot length of 625µs.

A DH1 packet, with independence of the modulation, needs 1 time slot for transmitting and 1 time slot for receiving. Then, the system makes in the worst case $1600/2 = 800$ hops per second with 79 channels. So each channel appears $800/79 = 10.13$ times per second and, for a period of $0.4 \times 79 = 31.6$ seconds, each channel appears $10.13 \times 31.6 = 320.11$ times.

A DH3 packet, with independence of the modulation, needs 3 time slots for transmitting and 1 time slot for receiving. Then, the system makes in the worst case $1600/4 = 400$ hops per second with 79 channels. So each channel appears $400/79 = 5.1$ times per second and, for a period of $0.4 \times 79 = 31.6$ seconds, each channel appears $5.1 \times 31.6 = 161.16$ times.

A DH5 packet, with independence of the modulation, needs 5 time slots for transmitting and 1 time slot for receiving. Then, the system makes in the worst case $1600/6 = 266.67$ hops per second with 79 channels. So each channel appears $266.67/79 = 3.37$ times per second and, for a period of $0.4 \times 79 = 31.6$ seconds, each channel appears $3.37 \times 31.6 = 106.49$ times.

Thus, the total time of occupancy is obtained by multiplying the calculated maximum number of appearances per packet type and the measured Tx-time, as shown in the results screenshots.


Results tables

Mode	Packet Type	Times of appearance	Tx-time [ms]	Dwell Time [ms]
Basic Rate GFSK	DH1	320.11	0.386	123.562
	DH3	161.16	1.638	263.980
	DH5	106.49	2.886	307.330
EDR $\pi/4$ -DQPSK	2-DH1	320.11	0.395	126.443
	2-DH3	161.16	1.646	265.269
	2-DH5	106.49	2.890	307.756
EDR 8-DPSK	3-DH1	320.11	0.526	168.378
	3-DH3	161.16	1.638	263.980
	3-DH5	106.49	2.886	307.302

Results Screenshot:


BDR – GFSK

DH1 Tx-Time




Date: 2 NOV 2017 10:42:57

DH3 Tx-Time




DH5 Tx-Time




EDR – $\pi/4$ -DQPSK


2-DH1 Tx-Time



2-DH3 Tx-Time




2-DH5 Tx-Time





EDR – 8-DPSK

3-DH1 Tx-Time



3-DH3 Tx-Time






B.4 Maximum Peak Output Power antenna gain

Test Limits

FCC part	RSS part	Limits
15.247 (b) (1)	RSS-247 Clause 5.4 (b)	(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. (...) (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Test procedure

The setup below was used to measure the maximum peak output power. The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.



The declared maximum antenna gain is 3.24dBi.


Results tables

Mode	Packet Type	Channel Number	Frequency [MHz]	Peak Power [dBm]	Peak Power [mW]	Peak Power EIRP [dBm]	Peak Power EIRP [mW]
Basic Rate GFSK	DH5	0	2402	9.69	9.31	12.9	19.6
		39	2441	10.02	10.05	13.3	21.2
		78	2480	10.38	10.91	13.6	23.0
EDR $\pi/4$ -DQPSK	2DH5	0	2402	9.27	8.45	12.5	17.8
		39	2441	9.37	8.65	12.6	18.2
		78	2480	9.77	9.48	13.0	20.0
EDR 8-DPSK	3DH5	0	2402	9.32	8.55	12.6	18.0
		39	2441	9.41	8.73	12.7	18.4
		78	2480	9.81	9.57	13.1	20.2

Results Screenshot


Basic Rate - GFSK

Peak Power – CH78




EDR – $\pi/4$ -DQPSK

Peak Power – CH78



EDR – 8-DPSK

Peak Power – CH78




B.5 Out-of-band emission (conducted)

Test limits

FCC part	RSS part	Limits
15.247 (d)	RSS-247 Clause 5.5	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test procedure

The setup below was used to measure the out-of-band emissions (conducted). The antenna terminal of the EUT is connected to the spectrum through an attenuator, and the spectrum analyzer reading is compensated to include the RF path loss.




Note: these PSD_{Peak} values are shown just as a reference for the compliance of the Out-of-band Measurements. Thus the RBW used for these measurements was 100 kHz.


Mode	Packet Type	CH	Frequency [MHz]	PSD Peak [dBm]
Basic Rate - GFSK	DH5	0	2402	9.44
		39	2441	9.82
		78	2480	10.21
EDR – $\pi/4$ -DQPSK	2DH5	0	2402	8.32
		39	2441	8.27
		78	2480	8.73
EDR – 8-DPSK	3DH5	0	2402	8.32
		39	2441	8.28
		78	2480	8.76

Basic Rate - GFSK

BE Low Freq Section – CH0




BE High Freq Section – CH78



BE Low Freq Section – Hopping




BE High Freq Section – Hopping




EDR – $\pi/4$ -DQPSK

BE Low Freq Section – CH0



BE High Freq Section – CH78



BE Low Freq Section – Hopping




BE High Freq Section – Hopping




EDR – 8-DPSK

BE Low Freq Section – CH0



BE High Freq Section – CH78



BE Low Freq Section – Hopping




BE High Freq Section – Hopping




Conducted Spurious results Screenshot

Basic Rate - GFSK


Cond Spur – CH0 (30MHz - 9GHz)



Cond Spur – CH0 (9GHz - 18GHz)




Cond Spur – CH0 (18GHz – 26.5GHz)




Date: 2 NOV 2017 14:24:48


Cond Spur – CH39 (30MHz - 9GHz)



Cond Spur – CH39 (9GHz - 18GHz)




Cond Spur – CH39 (18GHz – 26.5GHz)




Date: 2 NOV 2017 14:34:18


Cond Spur – CH78 (30MHz - 9GHz)



Cond Spur – CH78 (9GHz - 18GHz)




Cond Spur – CH78 (18GHz – 26.5GHz)




Date: 2 NOV 2017 14:38:40

EDR – $\pi/4$ -DQPSK


Cond Spur – CH0 (30MHz - 9GHz)



Cond Spur – CH0 (9GHz - 18GHz)




Cond Spur – CH0 (18GHz – 26.5GHz)




Date: 2 NOV 2017 14:48:44


Cond Spur – CH39 (30MHz - 9GHz)



Cond Spur – CH39 (9GHz - 18GHz)




Cond Spur – CH39 (18GHz – 26.5GHz)




Date: 2 NOV 2017 14:51:47


Cond Spur – CH78 (30MHz - 9GHz)



Cond Spur – CH78 (9GHz - 18GHz)




Cond Spur – CH78 (18GHz – 26.5GHz)




Date: 2 NOV 2017 14:54:38

EDR – 8-DPSK


Cond Spur – CH0 (30MHz - 9GHz)



Cond Spur – CH0 (9GHz - 18GHz)



Cond Spur – CH0 (18GHz – 26.5GHz)



Date: 2 NOV 2017 15:02:58


Cond Spur – CH39 (30MHz - 9GHz)



Cond Spur – CH39 (9GHz - 18GHz)




Cond Spur – CH39 (18GHz – 26.5GHz)




Date: 2 NOV 2017 15:05:48


Cond Spur – CH78 (30MHz - 9GHz)



Cond Spur – CH78 (9GHz - 18GHz)



Cond Spur – CH78 (18GHz – 26.5GHz)



Date: 2 NOV 2017 15:10:30

B.6 Radiated spurious emission


Standards references

FCC part	RSS part	Limits																							
15.247 (d) 15.209 (a)	RSS-247 Clause 5.5 RSS GEN Clause 8.9	Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a):																							
		<table><tr><th>Freq Range (MHz)</th><th>Field Strength (μV/m)</th><th>Field Strength (dBμV/m)</th><th>Meas. Distance (m)</th></tr><tr><td>30-88</td><td>100</td><td>40</td><td>3</td></tr><tr><td>88-216</td><td>150</td><td>43.5</td><td>3</td></tr><tr><td>216-960</td><td>200</td><td>46</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>54</td><td>3</td></tr></table>				Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)	30-88	100	40	3	88-216	150	43.5	3	216-960	200	46	3	Above 960	500	54	3
		Freq Range (MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Meas. Distance (m)																				
		30-88	100	40	3																				
		88-216	150	43.5	3																				
		216-960	200	46	3																				
		Above 960	500	54	3																				
The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.																									
For average radiated emission measurements above 1000 MHz, there is also a limit specified when measuring with peak detector function, corresponding to 20 dB above the indicated values in the table.																									


Test procedure:

The setups below were used to measure the radiated spurious emissions. Depending of the frequency range and bands being tested, different antennas and filters were used. The final measurement is done by varying the antenna height as indicated in the setups below for each band, the EUT azimuth over 360° and for both Vertical and Horizontal polarizations. The radiated spurious emission was measured on the worst case configuration found.


Radiated Setup < 1GHz



Radiated Setup 1 GHz - 18 GHz



Radiated Setup > 18 GHz



Sample Calculation

The field strength is deduced from the radiated measurement using the following equation:

$$E = 126.8 - 20\log(\lambda) + P - G$$

where

E is the field strength of the emission at the measurement distance, in dBμV/m

P is the power measured at the output of the test antenna, in dBm

λ is the wavelength of the emission under investigation $[300/f_{MHz}]$, in m

G is the gain of the test antenna, in dBi

NOTE – The measured power P includes all applicable instrument correction factors up to the connection to the test Antenna e.g. cable losses, amplifier gains.

For field strength measurements made at other than the distance at which the applicable limit is specified, the field strength of the emission at the distance specified by the limit is deduced as follows:

$$E_{SpecLimit} = E_{Meas} + 20\log(D_{Meas}/D_{SpecLimit})$$

where

E_{SpecLimit} is the field strength of the emission at the distance specified by the limit, in dBμV/m

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

D_{Meas} is the measurement distance, in m

D_{SpecLimit} is the distance specified by the limit, in m

Test Results

30 MHz – 26.5 GHz, BR – GFSK

Radiated Spurious – CH0 DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
115.2	27.3	---	43.5	16.2
240.0	29.3	---	46.0	16.8
241.1	32.7	---	46.0	13.3
500.1	35.5	---	46.0	10.5
594.8	37.5	---	46.0	8.5
795.2	40.4	---	46.0	5.6
1190.3	---	43.4	54.0	10.6
2325.0	---	44.5	54.0	9.5
3297.8	60.9	---	74.0	13.1
6291.6	61.3	---	74.0	12.7
17499.8	---	45.4	54.0	8.6
17500.2	57.4	---	74.0	16.6
23952.6	---	36.0	54.0	18.0
23985.3	48.8	---	74.0	25.2
25985.5	---	36.6	54.0	17.4
25989.6	49.5	---	74.0	24.5

Radiated Spurious – CH39 DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
62.4	37.2	---	40.0	2.9
115.2	27.1	---	43.5	16.4
169.5	27.8	---	43.5	15.7
288.0	31.3	---	46.0	14.7
500.1	36.6	---	46.0	9.4
576.0	34.2	---	46.0	11.8
2364.4	---	44.9	54.0	9.1
2517.8	---	45.7	54.0	8.3
3360.3	59.9	---	74.0	14.1
6374.6	62.5	---	74.0	11.5
7322.7	---	38.2	54.0	15.8
7323.2	47.3	---	74.0	26.8
17498.8	---	45.4	54.0	8.6
17501.2	58.8	---	74.0	15.2
25284.3	---	36.0	54.0	18.0
25859.1	49.0	---	74.0	25.1
25940.1	---	36.8	54.0	17.2
25960.0	49.9	---	74.0	24.1

Radiated Spurious – CH78 DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
44.0	27.5	---	40.0	12.5
66.3	35.3	---	40.0	4.7
115.2	26.1	---	43.5	17.4
375.1	32.9	---	46.0	13.1
583.2	35.1	---	46.0	10.9
672.0	35.2	---	46.0	10.8
1190.3	---	42.7	54.0	11.3
2556.9	---	45.3	54.0	8.7
3342.5	59.9	---	74.0	14.1
6223.1	61.8	---	74.0	12.2
12399.6	---	41.4	54.0	12.6
12405.4	51.9	---	74.0	22.1
17029.0	---	44.3	54.0	9.7
17040.1	56.8	---	74.0	17.2
23532.6	49.2	---	74.0	24.8
25681.0	---	36.3	54.0	17.7
25965.3	49.3	---	74.0	24.7
25984.0	---	37.0	54.0	17.0

30 MHz – 26.5 GHz, EDR – $\pi/4$ -DQPSK

Radiated Spurious – CH0 2DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
44.1	27.0	---	40.0	13.0
65.6	36.4	---	40.0	3.6
115.2	26.9	---	43.5	16.6
500.0	36.2	---	46.0	9.8
576.1	35.0	---	46.0	11.0
672.0	36.3	---	46.0	9.8
1190.3	---	42.4	54.0	11.6
2325.3	---	44.1	54.0	9.9
3179.7	59.4	---	74.0	14.6
6229.3	61.8	---	74.0	12.2
7205.7	42.2	---	74.0	31.8
7205.7	---	32.1	54.0	21.9
17491.1	58.1	---	74.0	15.9
17492.0	---	45.4	54.0	8.6
22864.4	48.5	---	74.0	25.5
22873.0	---	36.3	54.0	17.7
25966.4	49.8	---	74.0	24.2
25969.8	---	37.1	54.0	16.9

Radiated Spurious – CH39 2DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
44.4	30.2	---	40.0	9.8
71.9	25.5	---	40.0	14.5
115.2	27.1	---	43.5	16.4
288.0	33.5	---	46.0	12.5
375.1	34.1	---	46.0	11.9
593.0	37.3	---	46.0	8.8
2364.4	---	44.6	54.0	9.4
2517.8	---	44.4	54.0	9.6
3481.3	60.3	---	74.0	13.7
6361.9	61.5	---	74.0	12.5
16980.2	56.6	---	74.0	17.4
17053.6	---	44.4	54.0	9.6
17488.6	58.3	---	74.0	15.7
17499.3	---	45.4	54.0	8.6
25209.6	---	36.4	54.0	17.6
25216.8	50.0	---	74.0	24.0
25980.3	---	37.2	54.0	16.8
25996.4	49.4	---	74.0	24.6

Radiated Spurious – CH78 2DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
44.5	28.1	---	40.0	11.9
72.0	24.6	---	40.0	15.4
115.2	26.8	---	43.5	16.7
173.8	27.6	---	43.5	15.9
375.0	33.0	---	46.0	13.0
576.1	35.4	---	46.0	10.6
1190.3	---	42.5	54.0	11.5
2556.9	---	44.3	54.0	9.7
3340.9	59.8	---	74.0	14.2
6368.8	61.0	---	74.0	13.0
17027.1	---	44.2	54.0	9.8
17063.8	57.6	---	74.0	16.4
17498.3	57.8	---	74.0	16.2
17499.8	---	45.7	54.0	8.3
23924.9	49.3	---	74.0	24.7
25244.9	---	36.4	54.0	17.6
25940.9	---	37.1	54.0	16.9
25978.4	49.7	---	74.0	24.3

30 MHz – 26.5 GHz, EDR – 8-DPSK

Radiated Spurious – CH0 3DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
72.0	24.6	---	40.0	15.4
115.2	26.8	---	43.5	16.7
192.0	25.9	---	43.5	17.6
375.0	34.2	---	46.0	11.8
500.0	35.2	---	46.0	10.8
823.9	39.6	---	46.0	6.4
1190.3	---	42.3	54.0	11.7
2325.3	---	44.1	54.0	9.9
3368.8	60.0	---	74.0	14.1
6067.2	61.0	---	74.0	13.0
17021.3	56.5	---	74.0	17.5
17026.6	---	44.3	54.0	9.7
17495.4	57.3	---	74.0	16.7
17496.9	---	45.4	54.0	8.6
25250.9	---	36.4	54.0	17.6
25271.9	48.7	---	74.0	25.3
25955.5	49.4	---	74.0	24.6
25986.3	---	37.3	54.0	16.7

Radiated Spurious – CH39 3DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
72.0	25.4	---	40.0	14.7
96.0	25.2	---	43.5	18.3
115.2	27.0	---	43.5	16.5
240.0	30.0	---	46.0	16.0
375.0	33.6	---	46.0	12.4
500.0	38.2	---	46.0	7.8
2364.7	---	44.1	54.0	9.9
2517.8	---	44.5	54.0	9.5
3293.1	59.6	---	74.0	14.4
6355.4	61.6	---	74.0	12.4
17012.1	56.9	---	74.0	17.1
17016.4	---	44.2	54.0	9.8
17492.5	58.2	---	74.0	15.8
17495.9	---	45.5	54.0	8.5
25240.0	---	36.5	54.0	17.5
25257.6	49.5	---	74.0	24.5
25919.1	---	37.3	54.0	16.8
25961.9	49.5	---	74.0	24.5

Radiated Spurious – CH78 3DH5

Frequency	MaxPeak	Avg	Limit	Margin
MHz	dBuV/m	dBuV/m	dBuV/m	dB
44.5	26.1	---	40.0	13.9
71.9	24.7	---	40.0	15.3
115.1	26.5	---	43.5	17.0
204.3	32.5	---	43.5	11.0
375.0	33.3	---	46.0	12.7
500.1	34.7	---	46.0	11.3
1190.3	---	42.6	54.0	11.4
2556.9	---	44.1	54.0	9.9
3445.9	59.7	---	74.0	14.3
6229.6	61.1	---	74.0	12.9
17023.7	---	44.3	54.0	9.8
17064.3	57.0	---	74.0	17.0
17480.9	57.9	---	74.0	16.1
17499.3	---	45.6	54.0	8.4
25274.1	---	36.4	54.0	17.6
25324.8	49.6	---	74.0	24.4
25931.9	49.9	---	74.0	24.2
25987.4	---	37.3	54.0	16.7