

RF TEST REPORT

FCC ID: 2A49R-V3

Test Report No.....: RF240307009-06-001

Product(s) Name.....: V3 3 in 1 tablet

Model(s).....: V3, V3-001, V3-002, V3-003, V3-004, V3-005, V3-006, V3-007, V3-008, V3-009, V3-010, V3-011, V3-012, V3-013, V3-014, V3-015, V3-016, V3-017, V3-018, V3-019, V3-020, V3 SE

Trade Mark.....: minisfourm

Applicant.....: MICRO COMPUTER (HK) TECH LIMITED

Address.....: RM 18, 28/F, Shui On Centre, 6-8 Harbour Road, WaterfRont, Wan Chai, HK

Receipt Date.....: 2024.03.26

Test Date.....: 2024.03.28~2024.04.25

Issued Date.....: 2024.05.06

Standards.....: 47 CFR FCC Part 15, Subpart C(Section 15.247);
ANSI C63.10:2013

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Jason Huang	Tim Zhang	Misue Su	
<i>Jason Huang</i>	<i>Tim Zhang</i>	<i>Misue Su</i>	

Table of Contents

History of this test report.....	4
1. General Information	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Basic Description of Equipment Under Test.....	5
1.4 Transmit Operating Mode.....	6
2. Summary of Test Results	7
2.1 Summary of Test Items	7
2.2 Application of Standard	7
2.3 Test Instruments.....	8
2.4 Test Mode.....	9
2.5 Test Condition	9
2.6 Duty Cycle of Test Signal	9
2.7 Measurement Uncertainty	10
2.8 Test Location	10
2.9 Description of Support Units.....	10
2.10 Deviation from Standards	10
3. Test Procedure And Results	11
3.1 AC Power Line Conducted Emission.....	11
3.1.1 Limit	11
3.1.2 Test Procedure	11
3.1.3 Test Setup	11
3.1.4 Test Result	12
3.2 Radiated Emission and Band Edge.....	14
3.2.1 Limit	14
3.2.2 Test Procedure	14
3.2.3 Test Setup	16
3.2.4 Test Result	17

3.3	Spurious Emission at Antenna Port.....	60
3.3.1	Limit	60
3.3.2	Test Procedure	60
3.3.3	Test Setup	60
3.3.4	The Result	60
3.4	6dB Bandwidth	61
3.4.1	Limit	61
3.4.2	Test Procedure	61
3.4.3	Test Setup	61
3.4.4	Test Result	61
3.5	Maximum conducted output power.....	62
3.5.1	Limit.....	62
3.5.2	Test Procedure	62
3.5.3	Test Setup	62
3.5.4	The Result	62
3.6	Power Spectral Density	63
3.6.1	Limit.....	63
3.6.2	Test Procedure	63
3.6.3	Test Setup	63
3.6.4	The Result	63

History of this test report

Original Report Issue Date: 2024.05.06

☐ No additional attachment

☒ Additional attachments were issued following record

Attachment No.	Issue Date	Description
200611-04.TR04	2020.11.03	Module report Module ID: PD9AX210D2
RF240307009-06-001	2024.05.06	Compared to the original report of this module, it was used for MINI PC, with antenna changes and reduced gain. Therefore, the radiation emission, band edge, and AC power conduction emission were tested with reference to the original report.

1. General Information

1.1 Applicant

MICRO COMPUTER (HK) TECH LIMITED

RM 18, 28/F, Shui On Centre, 6-8 Harbour Road, Waterfront, Wan Chai, HK, China

1.2 Manufacturer

MICRO COMPUTER (HK) TECH LIMITED

RM 18, 28/F, Shui On Centre, 6-8 Harbour Road, Waterfront, Wan Chai, HK, China

1.3 Basic Description of Equipment Under Test

Product No.	POC240307009-S002	
Equipment Name	V3 3 in 1 tablet	
Model Name	V3, V3-001, V3-002, V3-003, V3-004, V3-005, V3-006, V3-007, V3-008, V3-009, V3-010, V3-011, V3-012, V3-013, V3-014, V3-015, V3-016, V3-017, V3-018, V3-019, V3-020, V3 SE	
Test Model	V3	
Model Difference	Only the model name and color are different.	
Trade Mark	minisfourm	
Power Supply	DC 11.55V from battery	
Adapter Information	Model: PN651U Input: 100-240V~, 50/60Hz 1.5A Max Output: 5V===3A/9V===3A/12V===3A/15V===3A/20V===3.25A Max	
Operate temperature	0℃-45℃	
EUT Stage	○ Product Unit	● Final-Sample
Operating Band and Conducted Output Power (Max power)	2400MHz ~ 2483.5MHz	
Product Type	IEEE 802.11b: WLAN (SISO) IEEE 802.11g: WLAN(SISO) IEEE 802.11n: WLAN(MIMO) IEEE 802.11ax: WLAN (MIMO)	
Nominal Bandwidth	20MHz / 40MHz	
Modulation	IEEE 802.11b: DSSS (DBPSK / DQPSK / CCK) IEEE 802.11g: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ax: OFDMA (BPSK / QPSK / 16QAM / 64QAM)	
Data Rate (Mbps)	IEEE 802.11b mode: 1/2/5.5/11 IEEE 802.11g mode: 6/9/12/18/24/36/48/54 IEEE 802.11n mode: up to 300 IEEE 802.11ax mode: up to 573.5	
Antenna gain	Ant1: 2.41dBi, Ant2: 1.84dBi	
Antenna type	PIFA Antenna	

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz), 802.11ax (20MHz):

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400MHz ~ 2483.5 MHz	01	2412MHz	07	2442MHz
	02	2417MHz	08	2447MHz
	03	2422MHz	09	2452MHz
	04	2427MHz	10	2457MHz
	05	2432MHz	11	2462MHz
	06	2437MHz	/	/

Seven channels are provided for 802.11n (40MHz), 802.11ax (40MHz):

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400MHz ~ 2483.5 MHz	03	2422 MHz	07	2442MHz
	04	2427MHz	08	2447MHz
	05	2432MHz	09	2452MHz
	06	2437MHz	/	/

Note: For 802.11ax mode only support full RU mode.

1.4 Transmit Operating Mode

Transmit Operating Mode					Transmit Multiple Antennas			
☒	Operating mode 1 (single antenna)				☒	1TX		
☒	Operating mode 2 (multiple antenna, no beam forming)				☒	2TX	☐ 3TX	☐ 4TX
☐	Operating mode 3 (multiple antenna, with beam forming)				☐	2TX	☐ 3TX	☐ 4TX
☒	802.11b	Operating mode	☒	1TX	☐	2TX	☐	3TX
☒	802.11g	Operating mode	☒	1TX	☐	2TX	☐	3TX
☒	802.11n(20MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX
☒	802.11n(40MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX
☒	802.11ax(20MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX
☒	802.11ax(40MHz)	Operating mode	☐	1TX	☒	2TX	☐	3TX

2. Summary of Test Results

2.1 Summary of Test Items

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Test item	FCC Clause	Results	Remarks
AC Power Conducted Emission	15.207	Pass	Meet the requirement of the limit
Radiated Emission and Band Edge Measurement	15.205/15.209 /15.247(d)	Pass	Meet the requirement of the limit
Spurious Emission at Antenna Port	15.247(d)	Note2	Meet the requirement of the limit
6dB Bandwidth	15.247(a)(2)	Note2	Meet the requirement of the limit
Maximum Conducted Power	15.247(b)	Note2	Meet the requirement of the limit
Power Spectral Density	15.247(e)	Note2	Meet the requirement of the limit
Antenna Requirements	15.203	Compliance	Note1
Note:1. The EUT has 2 PIFA antennas arrangement which was permanently attached. 2. For test data, please refer to the report 200611-04.TR04.			

2.2 Application of Standard

47 CFR FCC Part 15, Subpart C (Section 15.247)

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10:2013

2.3 Test Instruments

Radiated Emissions						
No.	Equipment	Manufacturer	Type No.	Serial No.	Cal. date (yyyy/mm/dd)	Cal. Due date (yyyy/mm/dd)
1	Test receiver	Rohde&Schwarz	ESU	100184	2024/4/24	2025/4/23
2	Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D- 1273	2024/4/20	2025/4/19
3	Low frequency amplifier	Unknown	LNA 0920N	2014	2024/4/24	2025/4/23
4	High frequency amplifier	Schwarzbeck	BBV 9718	284	2024/4/24	2025/4/23
5	Loop Antenna	Schwarzbeck	FMZB1519 B	00029	2023/7/16	2024/7/15
6	Log periodic antenna	Schwarzbeck	VULB 9168	1151	2024/4/20	2025/4/19
7	Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D- 1273	2024/4/20	2025/4/19
8	Horn Antenna	Schwarzbeck	BBHA 9170	9170#685	2023/7/16	2024/7/15
9	Temp&Humidity Recorder	Meideshi	JR900	/	2024/4/24	2025/4/23
10	RF cable(966 chamber)9kHz- 1GHz	Unknown	Unknown	Unknown	2024/4/24	2025/4/23
11	RF cable(966 chamber)1GHz- 18GHz	Unknown	Unknown	Unknown	2024/4/24	2025/4/23
12	RF cable(966 chamber)18GHz -40GHz	Unknown	Unknown	Unknown	2024/4/24	2025/4/23
13	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2			
Conducted Emission						
1	Test receiver	Rohde&Schwarz	ESCI	100718	2024/4/24	2025/4/23
2	LISN	Rohde&Schwarz	ENV216	100075	2024/4/24	2025/4/23
3	Pulse limiter	Rohde&Schwarz	ESH3-Z2	102299	2024/4/24	2025/4/23
4	RF cable (9kHz-30MHz)	Unknown	Unknown	Unknown	2024/4/24	2025/4/23
5	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2			

2.4 Test Mode

Test Items	Mode	Data Rate	Channel
AC Power Conducted Emission	802.11N- MIMO	MCS0	01
Radiated Emission and Band Edge Measurement	802.11B- SISO	1Mbps	01/06/11
	802.11G- SISO	6Mbps	01/06/11
	802.11N20MIMO	MCS0	01/06/11
	802.11N40MIMO	MCS0	03/06/09
	802.11AX20MIMO	MCS0	01/06/11
	802.11AX40MIMO	MCS0	03/06/09

2.5 Test Condition

Applicable to	Environmental conditions	Input Power	Tested by
AC Power Conducted Emission	24.3°C, 51% RH	AC 120V/60Hz	Freedom Zhuo
Radiated Emission and Band Edge Measurement	24.5°C, 53% RH	AC 120V/60Hz	Freedom Zhuo

Note: Adapter supply voltage AC 120V/60Hz.

2.6 Duty Cycle of Test Signal

Test result: PASS

Note: For test data, please refer to the report 200611-04.TR04.

2.7 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty	
Parameter	Uncertainty
Conducted emission(9kHz~30MHz) AC main	$\pm 2.72\text{dB}$
Radiated emission(9kHz~30MHz)	$\pm 2.66\text{dB}$
Radiated emission (30MHz~1GHz)	$\pm 4.62\text{dB}$
Radiated emission (1GHz~18GHz)	$\pm 4.86\text{dB}$
Radiated emission (18GHz~40GHz)	$\pm 3.80\text{dB}$

2.8 Test Location

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier	CN0145
A2LA Certificate Number	6823.01
Telephone:	0755-26024411

2.9 Description of Support Units

None

2.10 Deviation from Standards

None

3. Test Procedure And Results

3.1 AC Power Line Conducted Emission

3.1.1 Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3.1.2 Test Procedure

Test Method	
☒ Conducted Measurement	☐ Radiated Measurement
Test Channels	
☐ Lowest, Middle and Highest Channel	☐ Lowest and Highest Channel
Environmental conditions	
☒ Normal	☐ Normal and Extreme

Note: ● : Test ○ : No Test

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

3.1.3 Test Setup



3.1.4 Test Result


Note:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Measurement = Reading + Correct Factor.
3. Over = Measurement – Limit

We only recorded the data of the worst mode. Please see the following:

150kHz~30MHz	Worst Case Operating Mode: 11n20-MIMO Channel 01
--------------	--

Line




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1580	37.47	20.07	57.54	65.57	-8.03	QP	
2		0.1580	8.06	20.07	28.13	55.57	-27.44	AVG	
3		0.2340	26.24	19.98	46.22	62.31	-16.09	QP	
4		0.2340	8.82	19.98	28.80	52.31	-23.51	AVG	
5		0.4540	11.51	20.28	31.79	56.80	-25.01	QP	
6		0.4540	-0.23	20.28	20.05	46.80	-26.75	AVG	
7		0.5780	17.50	20.08	37.58	56.00	-18.42	QP	
8		0.5780	5.73	20.08	25.81	46.00	-20.19	AVG	
9		0.7620	15.50	20.18	35.68	56.00	-20.32	QP	
10		0.7620	2.64	20.18	22.82	46.00	-23.18	AVG	
11		1.6700	10.12	20.03	30.15	56.00	-25.85	QP	
12		1.6700	2.72	20.03	22.75	46.00	-23.25	AVG	

150kHz~30MHz

Worst Case Operating Mode: 11n20-MIMO Channel 01

Neutral

Conducted Emission Measurement



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1500	39.05	20.30	59.35	66.00	-6.65	QP	
2		0.1500	11.05	20.30	31.35	56.00	-24.65	AVG	
3		0.2340	26.64	20.14	46.78	62.31	-15.53	QP	
4		0.2340	13.63	20.14	33.77	52.31	-18.54	AVG	
5		0.4740	18.36	20.09	38.45	56.44	-17.99	QP	
6		0.4740	9.75	20.09	29.84	46.44	-16.60	AVG	
7		0.5900	18.56	20.23	38.79	56.00	-17.21	QP	
8		0.5900	8.94	20.23	29.17	46.00	-16.83	AVG	
9		0.8300	16.15	20.07	36.22	56.00	-19.78	QP	
10		0.8300	6.50	20.07	26.57	46.00	-19.43	AVG	
11		6.3540	7.50	20.28	27.78	60.00	-32.22	QP	
12		6.3540	2.48	20.28	22.76	50.00	-27.24	AVG	

3.2 Radiated Emission and Band Edge

3.2.1 Limit

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Distance Meters(m)	Field Strength Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 – 0.49	300	2400/F(kHz)	-
0.490 – 1.705	30	24000/F(kHz)	-
1.705 – 30	30	30	-
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

3.2.2 Test Procedure

Test Method	
☐ Conducted Measurement	☒ Radiated Measurement
Test Channels	
☒ Lowest, Middle and Highest Channel	☐ Lowest and Highest Channel
Environmental conditions	
☒ Normal	☐ Normal and Extreme
Note: ☒ : Test ☐ : No Test	

- a) The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- b) The measuring distance of 3 m or 1.5m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c) The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of

the antenna are set to make the measurement.

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e) The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f) The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g) All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
- h) All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i) For the actual test configuration, please refer to the related Item -EUT Test Photos.


The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz


Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value

3.2.3 Test Setup


(A) Radiated Emission Test Set-Up Frequency Below 30MHz



(B) Radiated Emission Test Set-Up Frequency 30 MHz-1000 MHz



(C) Radiated Emission Test Set-Up Frequency Above 1 GHz



3.2.4 Test Result

1) Radiated emission: 9kHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

2) Radiated emission: 30MHz-1G

Note:

1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit


We only recorded the data of the worst mode. Please see the following:

Below 1G (30MHz~1GHz)

Worst Case Operating Mode: 11n20-MIMO Channel 01

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	40.8446	42.01	-9.60	32.41	40.00	-7.59	peak		
2		95.7622	45.10	-13.36	31.74	43.50	-11.76	peak		
3		155.9101	39.33	-8.06	31.27	43.50	-12.23	peak		
4		261.0583	45.23	-10.35	34.88	46.00	-11.12	peak		
5		355.4273	40.89	-7.45	33.44	46.00	-12.56	peak		
6		903.3094	32.71	3.32	36.03	46.00	-9.97	peak		

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		31.6202	37.99	-10.90	27.09	40.00	-12.91	peak		
2		61.3462	43.87	-10.74	33.13	40.00	-6.87	peak		
3		96.0985	49.86	-13.33	36.53	43.50	-6.97	peak		
4	*	155.9101	44.97	-8.06	36.91	43.50	-6.59	peak		
5		270.3748	46.84	-10.10	36.74	46.00	-9.26	peak		
6		455.9058	42.35	-4.34	38.01	46.00	-7.99	peak		



3) Radiated emission: Above 1G

Note:

1. Measurement = Reading + Correct Factor.
2. Over = Measurement – Limit


Above 1G (1GHz~18GHz)	Test mode:11B- Ant1	Test Channel:1
-----------------------	---------------------	----------------

VERTICAL




HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4824.000	50.99	-4.18	46.81	74.00	-27.19	peak

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	36.55	8.22	44.77	74.00	-29.23			peak
2		2390.000	46.25	8.46	54.71	74.00	-19.29			peak
3	*	2390.000	35.80	8.46	44.26	54.00	-9.74			AVG

Above 1G (1GHz~18GHz)


Test mode:11B- Ant1

Test Channel:6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11B- Ant1

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4924.000	50.67	-4.90	45.77	74.00	-28.23 peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		2483.500	52.28	9.10	61.38	74.00	-12.62	peak	
2	*	2483.500	41.28	9.10	50.38	54.00	-3.62	AVG	
3		2500.000	37.83	9.26	47.09	74.00	-26.91	peak	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	4924.000	51.51	-4.90	46.61	74.00	-27.39	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2483.500	42.55	9.10	51.65	74.00	-22.35	peak		
2		2500.000	36.14	9.26	45.40	74.00	-28.60	peak		


Above 1G (1GHz~18GHz)

Test mode:11B- Ant2

Test Channel:1


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4824.000	48.86	-4.18	44.68	74.00	-29.32	peak		


Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	36.64	8.22	44.86	74.00	-29.14	peak		
2		2390.000	53.12	8.46	61.58	74.00	-12.42	peak		
3	*	2390.000	41.78	8.46	50.24	54.00	-3.76	AVG		

HORIZONTAL

Radiated Emission



Radiated Emission




Above 1G (1GHz~18GHz)


Test mode:11B- Ant2

Test Channel:6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11B- Ant2

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	4924.000	49.27	-4.90	44.37	74.00	-29.63 peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		2483.500	51.28	9.10	60.38	74.00	-13.62 peak		
2	*	2483.500	40.75	9.10	49.85	54.00	-4.15 AVG		
3		2500.000	35.83	9.26	45.09	74.00	-28.91 peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	4924.000	50.19	-4.90	45.29	74.00	-28.71	peak	

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	2483.500	41.05	9.10	50.15	74.00	-23.85	peak	
2		2500.000	34.64	9.26	43.90	74.00	-30.10	peak	


Above 1G (1GHz~18GHz)

Test mode:11G- Ant1

Test Channel:1


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4824.000	34.01	10.00	44.01	74.00	-29.99 peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		2310.000	37.73	8.22	45.95	74.00	-28.05	peak	
2		2390.000	54.91	8.46	63.37	74.00	-10.63	peak	
3	*	2390.000	43.35	8.46	51.81	54.00	-2.19	AVG	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4824.000	35.84	10.00	45.84	74.00	-28.16	peak

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	37.12	8.22	45.34	74.00	-28.66			peak
2		2390.000	48.33	8.46	56.79	74.00	-17.21			peak
3	*	2390.000	36.78	8.46	45.24	54.00	-8.76			AVG

Above 1G (1GHz~18GHz)


Test mode: 11G- Ant1

Test Channel:6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11G- Ant1

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4924.000	35.01	10.00	45.01	74.00	-28.99	peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	52.46	9.10	61.56	74.00	-12.44			peak
2	*	2483.500	42.07	9.10	51.17	54.00	-2.83			AVG
3		2500.000	38.22	9.26	47.48	74.00	-26.52			peak


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4924.000	35.72	10.00	45.72	74.00	-28.28	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2483.500	43.10	9.10	52.20	74.00	-21.80	peak		
2		2500.000	35.65	9.26	44.91	74.00	-29.09	peak		


Above 1G (1GHz~18GHz)

Test mode:11G- Ant2

Test Channel:1


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	4824.000	33.57	10.00	43.57	74.00	-30.43 peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		2310.000	37.23	8.22	45.45	74.00	-28.55 peak		
2		2390.000	55.41	8.46	63.87	74.00	-10.13 peak		
3	*	2390.000	42.67	8.46	51.13	54.00	-2.87 AVG		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1	*	4824.000	34.68	10.00	44.68	74.00	-29.32	peak	

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree
1		2310.000	36.62	8.22	44.84	74.00	-29.16	peak	
2		2390.000	49.33	8.46	57.79	74.00	-16.21	peak	
3	*	2390.000	37.89	8.46	46.35	54.00	-7.65	AVG	


Above 1G (1GHz~18GHz)

Test mode: 11G- Ant2

Test Channel:6

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	4874.000	33.17	10.00	43.17	74.00	-30.83	peak		

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	4874.000	34.35	10.00	44.35	74.00	-29.65	peak		


Above 1G (1GHz~18GHz)

Test mode: 11G- Ant2

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	4924.000	34.12	10.00	44.12	74.00	-29.88	peak		


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	52.46	9.10	61.56	74.00	-12.44	peak		
2	*	2483.500	41.69	9.10	50.79	54.00	-3.21	AVG		
3		2500.000	39.72	9.26	48.98	74.00	-25.02	peak		


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	4924.000	34.81	10.00	44.81	74.00	-29.19	peak		Comment

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	2483.500	43.60	9.10	52.70	74.00	-21.30	peak		Comment
2		2500.000	36.15	9.26	45.41	74.00	-28.59	peak		Comment

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO


Test Channel:1

VERTICAL




HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4824.000	35.50	10.00	45.50	74.00	-28.50	peak

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	37.03	8.22	45.25	74.00	-28.75			peak
2	*	2390.000	44.20	8.46	52.66	74.00	-21.34			peak

Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:6

VERTICAL



HORIZONTAL




Above 1G (1GHz~18GHz)

Test mode: 11N20MIMO

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	4924.000	34.31	10.00	44.31	74.00	-29.69	peak

Radiated Emission




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2483.500	52.81	9.10	61.91	74.00	-12.09			peak
2	*	2483.500	41.26	9.10	50.36	54.00	-3.64			AVG
3		2500.000	35.11	9.26	44.37	74.00	-29.63			peak

HORIZONTAL

Radiated Emission



Radiated Emission




Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:3


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4844.000	34.61	10.00	44.61	74.00	-29.39 peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		2310.000	37.23	8.22	45.45	74.00	-28.55	peak	
2		2390.000	54.32	8.46	62.78	74.00	-11.22	peak	
3	*	2390.000	43.07	8.46	51.53	54.00	-2.47	AVG	


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4844.000	35.82	10.00	45.82	74.00	-28.18	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	37.28	8.22	45.50	74.00	-28.50	peak		
2	*	2390.000	44.70	8.46	53.16	74.00	-20.84	peak		


Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:6

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4874.000	33.83	10.00	43.83	74.00	-30.17 peak

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4874.000	35.19	10.00	45.19	74.00	-28.81 peak


Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:9


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4904.000	33.76	10.00	43.76	74.00	-30.24	peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	53.72	9.10	62.82	74.00	-11.18			peak
2	*	2483.500	42.11	9.10	51.21	54.00	-2.79			AVG
3		2500.000	35.73	9.26	44.99	74.00	-29.01			peak


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4904.000	35.69	10.00	45.69	74.00	-28.31	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	45.95	9.10	55.05	74.00	-18.95			peak
2	*	2483.500	36.21	9.10	45.31	54.00	-8.69			AVG
3		2500.000	35.09	9.26	44.35	74.00	-29.65			peak


Above 1G (1GHz~18GHz)

Test mode: 11AX20MIMO

Test Channel:1


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4824.000	34.17	10.00	44.17	74.00	-29.83 peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		2310.000	37.67	8.22	45.89	74.00	-28.11	peak	
2		2390.000	52.95	8.46	61.41	74.00	-12.59	peak	
3	*	2390.000	43.35	8.46	51.81	54.00	-2.19	AVG	


HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4824.000	36.03	10.00	46.03	74.00	-27.97	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	37.24	8.22	45.46	74.00	-28.54			peak
2	*	2390.000	43.97	8.46	52.43	74.00	-21.57			peak


Above 1G (1GHz~18GHz)

Test mode: 11AX20MIMO

Test Channel:6

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	*	4874.000	34.56	10.00	44.56	74.00	-29.44 peak

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	*	4874.000	36.25	10.00	46.25	74.00	-27.75 peak


Above 1G (1GHz~18GHz)

Test mode: 11AX20MIMO

Test Channel:11


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4924.000	33.77	10.00	43.77	74.00	-30.23	peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	54.07	9.10	63.17	74.00	-10.83			peak
2	*	2483.500	42.76	9.10	51.86	54.00	-2.14			AVG
3		2500.000	35.72	9.26	44.98	74.00	-29.02			peak


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4924.000	35.01	10.00	45.01	74.00	-28.99	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	2483.500	44.46	9.10	53.56	74.00	-20.44			peak
2		2500.000	36.30	9.26	45.56	74.00	-28.44			peak


Above 1G (1GHz~18GHz)

Test mode: 11AX40MIMO

Test Channel:3


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4844.000	33.78	10.00	43.78	74.00	-30.22	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	37.68	8.22	45.90	74.00	-28.10			peak
2		2390.000	52.96	8.46	61.42	74.00	-12.58			peak
3	*	2390.000	41.46	8.46	49.92	54.00	-4.08			AVG


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	4844.000	35.86	10.00	45.86	74.00	-28.14	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2310.000	36.58	8.22	44.80	74.00	-29.20	peak		
2	*	2390.000	44.84	8.46	53.30	74.00	-20.70	peak		


Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:6

VERTICAL


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4874.000	33.16	10.00	43.16	74.00	-30.84 peak

HORIZONTAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4874.000	35.58	10.00	45.58	74.00	-28.42 peak


Above 1G (1GHz~18GHz)

Test mode: 11N40MIMO

Test Channel:9


VERTICAL

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4904.000	34.27	10.00	44.27	74.00	-29.73	peak


Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2483.500	52.71	9.10	61.81	74.00	-12.19			peak
2	*	2483.500	42.46	9.10	51.56	54.00	-2.44			AVG
3		2500.000	37.41	9.26	46.67	74.00	-27.33			peak


HORIZONTALA

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	4904.000	35.21	10.00	45.21	74.00	-28.79	peak

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2483.500	44.04	9.10	53.14	74.00	-20.86	peak		
2		2500.000	36.81	9.26	46.07	74.00	-27.93	peak		

The high frequency, which started from 18GHz to 25GHz, was pre-scanned and the result which was 20dB lower than the limit line was not recorded in this report.

3.3 Spurious Emission at Antenna Port

3.3.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

3.3.2 Test Procedure

Note: For test data, please refer to the report 200611-04.TR04.

3.3.3 Test Setup

Note: For test data, please refer to the report 200611-04.TR04.

3.3.4 The Result

3.3.4.1 Conducted Spurious Emission

Test result: PASS

Note: For test data, please refer to the report 200611-04.TR04.

3.3.4.2 Band edge

Test result: PASS

Note: For test data, please refer to the report 200611-04.TR04.

3.4 6dB Bandwidth

3.4.1 Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

3.4.2 Test Procedure

Note: For test data, please refer to the report 200611-04.TR04.

3.4.3 Test Setup

Note: For test data, please refer to the report 200611-04.TR04.

3.4.4 Test Result

3.4.4.1 DTS Bandwidth

Test result: PASS

Note: For test data, please refer to the report 200611-04.TR04.

3.4.4.2 Occupied Channel Bandwidth

Test result: PASS

Note: For test data, please refer to the report 200611-04.TR04.

3.5 Maximum conducted output power

3.5.1 Limit

For systems using digital modulation in the 2400~2483.5MHz, The Maximum output Power shall not exceed 1W(30dBm)

3.5.2 Test Procedure

Note: For test data, please refer to the report 200611-04.TR04.

3.5.3 Test Setup

Note: For test data, please refer to the report 200611-04.TR04.

3.5.4 The Result

Test result: PASS

Note: For test data, please refer to the report 200611-04.TR04.

The EIRP power and PSD EIRP (dBm) is calculated by adding the declared maximum antenna gain (2.41dBi) to the measured conducted power in accordance with KDB 662911 D01 v02r01. All transmit signals are completely uncorrelated with each other. Therefore, Directional gain = GANT = 2.41 dBi.

Note: The current directional gain is lower than the original directional gain, which does not affect the judgment.

3.6 Power Spectral Density

3.6.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmitting.

3.6.2 Test Procedure

Note: For test data, please refer to the report 200611-04.TR04.

3.6.3 Test Setup

Note: For test data, please refer to the report 200611-04.TR04.

3.6.4 The Result

Test result: PASS

Note: For test data, please refer to the report 200611-04.TR04.

Note: The current directional gain is lower than the original directional gain, which does not affect the judgment.

Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technology Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

Shenzhen Haiyun Standard Technology Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

Tel: 0755-26024411

Email: service@hy-lab.cn

End of Test Report