

# TEST REPORT

Report No.: **BCTC2408940416-4E**

---

Applicant: **EZTECH DIGITAL INC.**

---

Product Name: **IP Camera**

---

Test Model: **Talon Pro**

---

Tested Date: **2024-08-14 to 2024-11-26**

---

Issued Date: **2024-11-26**

---

**Shenzhen BCTC Testing Co., Ltd.**



# FCC ID: 2A4AS-2407A

Product Name: IP Camera

Trademark: 

Model/Type reference: Talon Pro  
Talon, Talon Series T130, Talon Series T120

Prepared For: EZTECH DIGITAL INC.

Address: 251 Little Falls Drive Wilmington Delaware 19808 United States

Manufacturer: Reolink Innovation Limited

Address: FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN STREET  
MONG KOK KL HONG KONG

Factory: Shenzhen Reolink Technology Co., Ltd

Address: 2nd Floor, Building 2, Yuanling Industrial Zone, Shangwu Community, Shiyan  
Street, Bao'an District, Shenzhen

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road,  
Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2024-08-14

Sample tested Date: 2024-08-14 to 2024-11-26

Issue Date: 2024-11-26

Report No.: BCTC2408940416-4E

FCC CFR Title 47 Part 2

FCC CFR Title 47 Part22 Subpart H

FCC CFR Title 47 Part24 Subpart E

FCC CFR Title 47 Part27 Subpart L

ANSI/ TIA/ EIA-603-D-2010

FCC KDB 971168 D01 Power Meas. License Digital Systems v03v01

Test Results: PASS

Remark: This is GSM & WCDMAradio test report.

Tested by:



Brave Zeng/ Project Handler

Approved by:



Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.


## Table Of Content

Test Report Declaration	Page
1. Version .....	4
2. Test Summary.....	5
3. Measurement Uncertainty .....	6
4. Product Information And Test Setup .....	7
4.1 Product Information.....	7
4.2 Test Setup Configuration .....	8
4.3 Support Equipment .....	8
4.5 Test Mode .....	9
5. Test Facility And Test Instrument Used.....	10
5.1 Test Facility.....	10
5.2 Test Instrument Used.....	10
6. RF Output Power.....	11
6.1 Block Diagram Of Test Setup.....	11
6.2 Limit .....	12
6.3 Test procedure.....	13
6.4 Test Result.....	14
7. Peak-to-average Ratio(PAR) of Transmitter.....	19
7.1 Block Diagram Of Test Setup.....	19
7.2 Limit .....	19
7.3 Test procedure.....	19
7.4 Test Result.....	20
8. Emission Bandwidth .....	26
8.1 Block Diagram Of Test Setup.....	26
8.2 Limit .....	26
8.3 Test procedure.....	26
8.4 Test Result.....	27
9. Out of Band Emissions at Antenna Terminal.....	33
9.1 Block Diagram Of Test Setup.....	33
9.2 Limit .....	33
9.3 Test procedure.....	33
9.4 Test Result.....	33
10. Spurious Radiated Emissions.....	42
10.1 Block Diagram Of Test Setup.....	42
10.2 Limit .....	43
10.3 Test procedure.....	43
10.4 Test Result.....	44
11. Frequency Stability.....	49
11.1 Block Diagram Of Test Setup.....	49
11.2 Limit .....	49
11.3 Test procedure.....	49
11.4 Test Result.....	50
12. EUT Photographs.....	52
13. EUT Test Setup Photographs.....	53

(Note: N/A Means Not Applicable)

## 1. Version

Report No.	Issue Date	Description	Approved
BCTC2408940416-4E	2024-11-26	Original	Valid



## 2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	RF Exposure	§1.1307, §2.1093	PASS
2	RF Output Power	§22.913 (a), §24.232 (c), §27.50,	PASS
3	Peak-to-average Ratio(PAR) of Transmitter	§24.232(d), §22.913, §27.50,	PASS
4	Emission Bandwidth	§22.917 (b), §24.238(b), §27.53	PASS
5	Spurious Emissions at Antenna Terminal	§22.917 (a), §24.238 (a), §27.53	PASS
6	Spurious Radiation Emissions	§22.917 (a), §24.238 (a), §27.53	PASS
7	Out of Band Emissions	§22.917 (a), §24.238 (a), §27.53	PASS
8	Frequency Stability	§22.355, §24.235, §27.54	PASS

### 3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	$U=4.3\text{dB}$
2	3m chamber Radiated spurious emission(9KHz-30MHz)	$U=3.7\text{dB}$
3	3m chamber Radiated spurious emission(1GHz-18GHz)	$U=4.5\text{dB}$
4	3m chamber Radiated spurious emission(18GHz-40GHz)	$U=3.34\text{dB}$
5	Conducted Emission (150kHz-30MHz)	$U=3.20\text{dB}$
6	Conducted Adjacent channel power	$U=1.38\text{dB}$
7	Conducted output power uncertainty Above 1G	$U=1.576\text{dB}$
8	Conducted output power uncertainty below 1G	$U=1.28\text{dB}$
9	humidity uncertainty	$U=5.3\%$
10	Temperature uncertainty	$U=0.59^\circ\text{C}$

## 4. Product Information And Test Setup


### 4.1 Product Information

Model/Type reference:	Talon Pro Talon, Talon Series T130, Talon Series T120
Model differences:	All the model are the same circuit and RF module, except model names.
Hardware Version:	N/A
Software Version:	N/A
Operation Frequency:	WCDMA Band II: TX: 1852.40~1907.60MHz; Rx: 1932.60~1987.40MHz; WCDMA Band IV: TX: 1712.40~1752.60MHz; RX: 2112.60 – 2452.40MHz WCDMA Band V: TX: 826.40~846.60MHz; RX: 871.40~ 891.60MHz;
Max RF Output Power:	WCDMA Band II: 23.48 dBm WCDMA Band IV: 23.69 dBm WCDMA Band V: 22.91 dBm
Type of Modulation:	WCDMA Mode with BPSK Modulation HSDPA Mode with QPSK, 16QAM Modulation HSUPA Mode with QPSK, 16QAM Modulation
Type of Emission:	WCDMA Band II: 4M15F9W WCDMA Band IV: 4M14F9W WCDMA Band V: 4M18F9W
Antenna installation:	External antenna WCDMA Band II: 1.59 dBi WCDMA Band IV: 1.51 dBi WCDMA Band V: -1.69 dBi
Antenna Gain:	Remark: <input checked="" type="checkbox"/> The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. <input type="checkbox"/> The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
Ratings:	DC 5V from adapter / DC 1.5V*5 from battery

## 4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Radiated Spurious Emission



## 4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	IP Camera	<b>CAMOVUE</b>	Talon Pro	N/A	EUT
E-2	N/A	N/A	N/A	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	0M	DC cable unshielded

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

#### 4.5 Test Mode

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
WCDMA Band II	WCDMA/HSDPA/ HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
WCDMA Band IV	WCDMA/HSDPA/ HSUPA	1712.4 MHz	1312
		1740 MHz	1450
		1752.6 MHz	1513
WCDMA Band V	WCDMA/HSDPA/ HSUPA	826.4 MHz	4132
		836.4 MHz	4182
		846.6 MHz	4233

Note 1: the transmitter has been tested on the communications mode of WCDMA, HSDPA, HSUPA compliance test and record the worst case.

Note 2: Both the SIM 1 and SIM 2 were tested, the worst mode is the SIM 1, the data recording in the report.

#### EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/ Without Core
/	/	/	/
/	/	/	/

#### Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

#### Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/ Without Core
/	/	/	/

## 5. Test Facility And Test Instrument Used

### 5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583

ISED CAB identifier: CN0017


### 5.2 Test Instrument Used

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	\	May 16, 2024	May 15, 2025
Power Sensor (AV)	Keysight	E9300A	\	May 16, 2024	May 15, 2025
Signal Analyzer 20kHz - 26.5GHz	Keysight	N9020A	MY49100060	May 16, 2024	May 15, 2025
Spectrum Analyzer 9kHz - 40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025
Communication test set	R&S	CMW500	126173	Nov. 13. 2023	Nov. 12, 2024
Radio frequency control box	MAIWEI	MW200-RFCB	\	\	\
Software	MAIWEI	MTS 8200	\	\	\

## 6. RF Output Power


### 6.1 Block Diagram Of Test Setup

Conducted output power test method:




Radiated power test method:


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



## 6.2 Limit

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

### 6.3 Test procedure

Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.



## 6.4 Test Result

### EIRP For WCDMA Mode Band II

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1852.4	H	1.5	0	50.34	-26.92	23.42	33.00	PASS
1852.4	V	1.5	0	48.90	-26.92	21.98	33.00	PASS
Middle Channel								
1880	H	1.5	0	49.55	-26.86	22.69	33.00	PASS
1880	V	1.5	0	48.49	-26.86	21.63	33.00	PASS
High Channel								
1907.6	H	1.5	0	48.89	-26.80	22.09	33.00	PASS
1907.6	V	1.5	0	48.62	-26.80	21.82	33.00	PASS

### EIRP For HSDPA Mode Band II

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1852.4	H	1.5	0	49.39	-26.92	22.47	33.00	PASS
1852.4	V	1.5	0	49.25	-26.92	22.33	33.00	PASS
Middle Channel								
1880	H	1.5	0	49.69	-26.86	22.83	33.00	PASS
1880	V	1.5	0	48.70	-26.86	21.84	33.00	PASS
High Channel								
1907.6	H	1.5	0	48.55	-26.80	21.75	33.00	PASS
1907.6	V	1.5	0	48.64	-26.80	21.84	33.00	PASS

### EIRP For HSUPA Mode Band II

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1852.4	H	1.5	0	50.11	-26.92	23.19	33.00	PASS
1852.4	V	1.5	0	49.25	-26.92	22.33	33.00	PASS
Middle Channel								
1880	H	1.5	0	48.82	-26.86	21.96	33.00	PASS
1880	V	1.5	0	49.03	-26.86	22.17	33.00	PASS
High Channel								
1907.6	H	1.5	0	49.52	-26.80	22.72	33.00	PASS
1907.6	V	1.5	0	48.70	-26.80	21.90	33.00	PASS

**EIRP For WCDMA Mode Band IV**

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	Limits (dBm)	Result
Low Channel								
1712.4	H	1.5	0	48.98	-27.23	21.75	30	PASS
1712.4	V	1.5	0	49.11	-27.23	21.88	30	PASS
Middle Channel								
1740	H	1.5	0	49.80	-27.19	22.61	30	PASS
1740	V	1.5	0	49.22	-27.19	22.03	30	PASS
High Channel								
1752.6	H	1.5	0	49.37	-27.14	22.23	30	PASS
1752.6	V	1.5	0	49.24	-27.14	22.10	30	PASS

**EIRP For HSDPA Mode Band IV**

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	Limits (dBm)	Result
Low Channel								
1712.4	H	1.5	0	48.21	-27.23	20.98	30	PASS
1712.4	V	1.5	0	47.66	-27.23	20.43	30	PASS
Middle Channel								
1740	H	1.5	0	48.81	-27.19	21.62	30	PASS
1740	V	1.5	0	48.06	-27.19	20.87	30	PASS
High Channel								
1752.6	H	1.5	0	47.95	-27.14	20.81	30	PASS
1752.6	V	1.5	0	47.71	-27.14	20.57	30	PASS

**EIRP For HSUPA Mode Band IV**

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measurement (dBm)	Limits (dBm)	Result
Low Channel								
1712.4	H	1.5	0	49.98	-27.23	22.75	30	PASS
1712.4	V	1.5	0	48.41	-27.23	21.18	30	PASS
Middle Channel								
1740	H	1.5	0	50.00	-27.19	22.81	30	PASS
1740	V	1.5	0	48.98	-27.19	21.79	30	PASS
High Channel								
1752.6	H	1.5	0	48.84	-27.14	21.70	30	PASS
1752.6	V	1.5	0	48.75	-27.14	21.61	30	PASS

## ERP For WCDMA Mode Band V

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	Limits (dBm)	Result
Low Channel								
826.4	H	1.5	0	49.56	-26.29	23.27	38.45	PASS
826.4	V	1.5	0	48.87	-26.29	22.58	38.45	PASS
Middle Channel								
836.6	H	1.5	0	48.93	-26.35	22.58	38.45	PASS
836.6	V	1.5	0	48.84	-26.35	22.49	38.45	PASS
High Channel								
846.6	H	1.5	0	49.44	-26.42	23.02	38.45	PASS
846.6	V	1.5	0	48.73	-26.42	22.31	38.45	PASS

## ERP For HSDPA Mode Band V

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	Limits (dBm)	Result
Low Channel								
826.4	H	1.5	0	50.36	-26.29	24.07	38.45	PASS
826.4	V	1.5	0	48.55	-26.29	22.26	38.45	PASS
Middle Channel								
836.6	H	1.5	0	48.44	-26.35	22.09	38.45	PASS
836.6	V	1.5	0	48.88	-26.35	22.53	38.45	PASS
High Channel								
846.6	H	1.5	0	50.06	-26.42	23.64	38.45	PASS
846.6	V	1.5	0	48.54	-26.42	22.12	38.45	PASS

## ERP For HSUPA Mode Band V

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	Limits (dBm)	Result
Low Channel								
826.4	H	1.5	0	49.33	-26.29	23.04	38.45	PASS
826.4	V	1.5	0	48.59	-26.29	22.30	38.45	PASS
Middle Channel								
836.6	H	1.5	0	50.21	-26.35	23.86	38.45	PASS
836.6	V	1.5	0	48.62	-26.35	22.27	38.45	PASS
High Channel								
846.6	H	1.5	0	48.97	-26.42	22.55	38.45	PASS
846.6	V	1.5	0	48.54	-26.42	22.12	38.45	PASS

Correction Factor= S.G. Power - Cable loss + Antenna Gain- SPA. Reading

**Max. Conducted Output Power**


Band	WCDMA Band II		
<b>Channel</b>	<b>9262</b>	<b>9400</b>	<b>9538</b>
<b>Frequency(MHz)</b>	<b>1852.4</b>	<b>1880.0</b>	<b>1907.6</b>
WCDMA RMC 12.2K	23.03	<b>23.48</b>	23.15
HSDPA Subtest-1	22.03	22.28	22.09
HSDPA Subtest-2	21.87	21.99	21.89
HSDPA Subtest-3	20.93	21.32	21.03
HSDPA Subtest-4	20.49	20.59	20.97
HSUPA Subtest-1	21.18	21.65	21.46
HSUPA Subtest-2	22.07	22.21	22.14
HSUPA Subtest-3	21.54	21.84	21.77
HSUPA Subtest-4	22.14	22.33	22.16
HSUPA Subtest-5	21.40	21.60	21.47

Band	WCDMA Band IV		
<b>Channel</b>	<b>1312</b>	<b>1450</b>	<b>1513</b>
<b>Frequency(MHz)</b>	<b>1712.4</b>	<b>1740</b>	<b>1752.6</b>
WCDMA RMC 12.2K	23.22	23.38	<b>23.69</b>
HSDPA Subtest-1	22.39	22.42	22.69
HSDPA Subtest-2	22.40	22.36	22.45
HSDPA Subtest-3	21.20	21.54	21.70
HSDPA Subtest-4	21.32	21.17	21.59
HSUPA Subtest-1	21.71	21.76	22.11
HSUPA Subtest-2	22.40	22.40	22.70
HSUPA Subtest-3	22.07	22.26	22.20
HSUPA Subtest-4	22.55	22.48	22.72
HSUPA Subtest-5	21.90	21.77	22.03

Band	WCDMA Band V		
Channel	4132	4182	4233
Frequency(MHz)	826.4	836.4	846.6
WCDMA RMC 12.2K	22.72	22.91	22.84
HSDPA Subtest-1	21.72	21.88	21.78
HSDPA Subtest-2	21.47	21.54	21.55
HSDPA Subtest-3	20.36	20.73	20.65
HSDPA Subtest-4	20.57	20.53	20.25
HSUPA Subtest-1	21.12	21.30	21.18
HSUPA Subtest-2	21.67	21.84	21.75
HSUPA Subtest-3	21.20	21.43	21.30
HSUPA Subtest-4	21.79	22.01	21.86
HSUPA Subtest-5	21.18	21.24	21.15

## 7. Peak-to-average Ratio(PAR) of Transmitter

### 7.1 Block Diagram Of Test Setup



### 7.2 Limit

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.


### 7.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded. Record the maximum PAPR level associated with a probability of 0.1%.


## 7.4 Test Result

Band	Channel	Frequency (MHz)	Result (dB)	high Limit (dB)	Verdict
WCDMA Band2	9262	1852.4	3.77	13	PASS
WCDMA Band2	9400	1880	3.63	13	PASS
WCDMA Band2	9538	1907.6	3.81	13	PASS
WCDMA Band4	1312	1712.4	2.89	13	PASS
WCDMA Band4	1450	1740	3.17	13	PASS
WCDMA Band4	1513	1752.6	2.94	13	PASS
WCDMA Band5	4132	826.4	2.64	13	PASS
WCDMA Band5	4182	836.4	2.89	13	PASS
WCDMA Band5	4233	846.6	2.70	13	PASS


Note: In WCDMA, RMC, HSDPA and HSUPA all three tests only reflect the worst mode RMC.




## WCDMA Band2 Channel=9262




## WCDMA Band2 Channel=9400




## WCDMA Band2 Channel=9538




## WCDMA Band4 Channel=1312




## WCDMA Band4 Channel=1450




## WCDMA Band4 Channel=1513





## WCDMA Band5 Channel=4132



## WCDMA Band5 Channel=4182




## WCDMA Band5 Channel=4233



## 8. Emission Bandwidth

### 8.1 Block Diagram Of Test Setup



### 8.2 Limit

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 8.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 10kHz for GSM mode and 100kHz for WCDMA mode, VBW shall be at least 3 times the RBW, and the 26dB bandwidth was recorded.


## 8.4 Test Result

Band	Channel	Frequency (MHz)	99% OBW (kHz)	-26dB EBW (kHz)	Verdict
WCDMA Band2	9262	1852.4	4144.220	4696.428	PASS
WCDMA Band2	9400	1880	4150.146	4676.915	PASS
WCDMA Band2	9538	1907.6	4150.513	4717.809	PASS
WCDMA Band4	1312	1712.4	4136.129	4714.833	PASS
WCDMA Band4	1450	1740	4121.062	4730.448	PASS
WCDMA Band4	1513	1752.6	4132.431	4690.709	PASS
WCDMA Band5	4132	826.4	4175.898	4768.144	PASS
WCDMA Band5	4182	836.4	4181.442	4715.161	PASS
WCDMA Band5	4233	846.6	4176.976	4750.115	PASS


Note: In WCDMA, RMC, HSDPA and HSUPA all three tests only reflect the worst mode RMC.




## WCDMA Band2 Channel=9262




## WCDMA Band2 Channel=9400




## WCDMA Band2 Channel=9538




## WCDMA Band4 Channel=1312




## WCDMA Band4 Channel=1450




## WCDMA Band4 Channel=1513




## WCDMA Band5 Channel=4132



## WCDMA Band5 Channel=4182




## WCDMA Band5 Channel=4233



## 9. Out of Band Emissions at Antenna Terminal

### 9.1 Block Diagram Of Test Setup



### 9.2 Limit

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

### 9.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10<sup>th</sup> harmonic. At the edge of the authorized Frequency block/band: RBW set 1%-5%OBW.

### 9.4 Test Result


## WCDMA Band2 Channel=9262




## WCDMA Band2 Channel=9538




## WCDMA Band2 Channel=9262



## WCDMA Band2 Channel=9400



## WCDMA Band2 Channel=9538




## WCDMA Band4 Channel=1312




## WCDMA Band4 Channel=1513




## WCDMA Band4 Channel=1312




## WCDMA Band4 Channel=1450



## WCDMA Band4 Channel=1513




## WCDMA Band5 Channel=4132




## WCDMA Band5 Channel=4233





## WCDMA Band5 Channel=4132



## WCDMA Band5 Channel=4182




## WCDMA Band5 Channel=4233




## 10. Spurious Radiated Emissions

### 10.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



## 10.2 Limit

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10} (P)$  dB.

## 10.3 Test procedure

1. The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB =  $43 + 10 \log_{10}$  (power out in Watts)

## 10.4 Test Result

For Band WCDMA Band II Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1852.4MHz)						
88.67	-12.63	-30.60	-43.23	-13.00	-30.23	H
3704.80	-15.12	-22.19	-37.31	-13.00	-24.31	H
5557.20	-14.56	-19.32	-33.88	-13.00	-20.88	H
88.67	-12.01	-30.60	-42.61	-13.00	-29.61	V
3704.80	-7.33	-22.19	-29.52	-13.00	-16.52	V
5557.20	-9.56	-19.32	-28.88	-13.00	-15.88	V
Middle Channel (1880MHz)						
88.67	-10.20	-30.60	-40.80	-13.00	-27.80	H
3760.00	-15.27	-22.08	-37.35	-13.00	-24.35	H
5640.00	-11.21	-19.28	-30.49	-13.00	-17.49	H
88.67	-9.75	-30.60	-40.35	-13.00	-27.35	V
3760.00	-10.36	-22.08	-32.44	-13.00	-19.44	V
5640.00	-10.23	-19.28	-29.51	-13.00	-16.51	V
High Channel (1907.6MHz)						
88.67	-11.34	-30.60	-41.94	-13.00	-28.94	H
3815.20	-9.40	-21.97	-31.37	-13.00	-18.37	H
5722.80	-12.29	-19.24	-31.53	-13.00	-18.53	H
88.67	-12.19	-30.60	-42.79	-13.00	-29.79	V
3815.20	-5.78	-21.97	-27.75	-13.00	-14.75	V
5722.80	-11.33	-19.24	-30.57	-13.00	-17.57	V

Note: Result=Reading+ Correct, Margin= Result- Limit

For Band WCDMA Band IV Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1712.4MHz)						
88.67	-12.43	-30.60	-43.03	-13.00	-30.03	H
3424.80	-9.65	-22.75	-32.40	-13.00	-19.40	H
5137.20	-14.39	-19.53	-33.92	-13.00	-20.92	H
88.67	-12.23	-30.60	-42.83	-13.00	-29.83	V
3424.80	-6.81	-22.75	-29.56	-13.00	-16.56	V
5137.20	-7.80	-19.53	-27.33	-13.00	-14.33	V
Middle Channel (1740MHz)						
88.67	-9.69	-30.60	-40.29	-13.00	-27.29	H
3480.00	-12.98	-22.64	-35.62	-13.00	-22.62	H
5220.00	-13.13	-19.49	-32.62	-13.00	-19.62	H
88.67	-12.83	-30.60	-43.43	-13.00	-30.43	V
3480.00	-9.11	-22.64	-31.75	-13.00	-18.75	V
5220.00	-8.30	-19.49	-27.79	-13.00	-14.79	V
High Channel (1752.6MHz)						
88.67	-13.97	-30.60	-44.57	-13.00	-31.57	H
3505.20	-10.98	-22.59	-33.57	-13.00	-20.57	H
5257.80	-13.40	-19.47	-32.87	-13.00	-19.87	H
88.67	-11.68	-30.60	-42.28	-13.00	-29.28	V
3505.20	-5.71	-22.59	-28.30	-13.00	-15.30	V
5257.80	-12.74	-19.47	-32.21	-13.00	-19.21	V

Note: Result=Reading+ Correct, Margin= Result- Limit

For Band WCDMA Band V Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (826.4MHz)						
88.67	-11.78	-30.60	-42.38	-13.00	-29.38	H
1652.80	-9.31	-27.36	-36.67	-13.00	-23.67	H
2479.20	-12.86	-25.16	-38.02	-13.00	-25.02	H
88.67	-12.19	-30.60	-42.79	-13.00	-29.79	V
1652.80	-5.65	-27.36	-33.01	-13.00	-20.01	V
2479.20	-7.22	-25.16	-32.38	-13.00	-19.38	V
Middle Channel (836.4MHz)						
88.67	-12.26	-30.60	-42.86	-13.00	-29.86	H
1672.80	-15.05	-27.32	-42.37	-13.00	-29.37	H
2509.20	-11.77	-25.07	-36.84	-13.00	-23.84	H
88.67	-12.97	-30.60	-43.57	-13.00	-30.57	V
1672.80	-6.51	-27.32	-33.83	-13.00	-20.83	V
2509.20	-11.70	-25.07	-36.77	-13.00	-23.77	V
High Channel (846.6MHz)						
88.67	-15.20	-30.60	-45.80	-13.00	-32.80	H
1693.20	-13.65	-27.27	-40.92	-13.00	-27.92	H
2539.80	-12.66	-24.98	-37.64	-13.00	-24.64	H
88.67	-7.88	-30.60	-38.48	-13.00	-25.48	V
1693.20	-9.15	-27.27	-36.42	-13.00	-23.42	V
2539.80	-12.58	-24.98	-37.56	-13.00	-24.56	V

Note: Result=Reading+ Correct, Margin= Result- Limit


Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Receiver spurious emissions

The worst mode is WCDMA Band5, so only the worst mode is displayed

Between 30MHz – 1GHz

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Horizontal




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		50.2324	25.31	-13.93	11.38	40.00	-28.62	QP
2		106.3850	26.01	-16.38	9.63	43.50	-33.87	QP
3	*	199.9856	37.80	-15.72	22.08	43.50	-21.42	QP
4		250.3012	37.14	-14.28	22.86	46.00	-23.14	QP
5		354.1831	31.30	-11.43	19.87	46.00	-26.13	QP
6		881.4067	27.05	-3.44	23.61	46.00	-22.39	QP

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Vertical


**Remark:**

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1	55.8047	35.94	-14.68	21.26	40.00	-18.74	QP	
2	225.3080	31.72	-15.00	16.72	46.00	-29.28	QP	
3	354.1831	33.85	-11.43	22.42	46.00	-23.58	QP	
4	438.6554	34.37	-10.08	24.29	46.00	-21.71	QP	
5 *	560.6928	40.30	-9.66	30.64	46.00	-15.36	QP	
6	881.4067	27.71	-3.44	24.27	46.00	-21.73	QP	

Above 1G (The worst mode is WCDMA Band5, so only the worst mode is displayed)

Polar (H/V)	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low channel							
V	1652.80	62.64	-10.62	52.02	74.00	-21.98	PK
V	1652.80	55.32	-10.62	44.70	54.00	-9.30	AV
V	2479.20	52.72	-2.64	50.08	74.00	-23.92	PK
V	2479.20	43.01	-2.64	40.37	54.00	-13.63	AV
H	1652.80	58.48	-10.62	47.86	74.00	-26.14	PK
H	1652.80	47.75	-10.62	37.13	54.00	-16.87	AV
H	2479.20	51.59	-2.64	48.95	74.00	-25.05	PK
H	2479.20	44.31	-2.64	41.67	54.00	-12.33	AV


Remark:

1. Measurement = Reading Level + Correct Factor,  
Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier,  
Over= Measurement – Limit
2. If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



## 11. Frequency Stability

### 11.1 Block Diagram Of Test Setup



### 11.2 Limit

FCC Part 22.355:  $\pm 2.5$  ppm

FCC Part 24.235:

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

FCC Part 27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

### 11.3 Test procedure

1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0.
2. The EUT was placed in a temperature chamber at  $25 \pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

## 11.4 Test Result

All modes have been tested, and the worst result recorded was report as below

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (°C)				
WCDMA8 50	4132	VN	-30	826.40	18.86	0.0228	2.5
			-20	826.40	15.80	0.0191	2.5
			-10	826.40	16.03	0.0194	2.5
			0	826.40	16.38	0.0198	2.5
			10	826.40	18.18	0.0220	2.5
			20	826.40	15.04	0.0182	2.5
			30	826.40	13.72	0.0166	2.5
			40	826.40	11.85	0.0143	2.5
			50	826.40	14.32	0.0173	2.5
		VL	20	826.40	11.20	0.0136	2.5
		VH	20	826.40	19.93	0.0241	2.5
VERDICT				PASS			

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (°C)				
WCDMA1 700	1312	VN	-30	1712.40	19.46	0.0114	Note 4
			-20	1712.40	17.71	0.0103	Note 4
			-10	1712.40	15.05	0.0088	Note 4
			0	1712.40	15.72	0.0092	Note 4
			10	1712.40	10.80	0.0063	Note 4
			20	1712.40	14.31	0.0084	Note 4
			30	1712.40	16.38	0.0096	Note 4
			40	1712.40	11.35	0.0066	Note 4
			50	1712.40	16.98	0.0099	Note 4
		VL	20	1712.40	15.57	0.0091	Note 4
		VH	20	1712.40	18.29	0.0107	Note 4
VERDICT				PASS			

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (°C)				
WCDMA1 900	9262	VN	-30	1852.40	10.82	0.0058	Note 4
			-20	1852.40	12.46	0.0067	Note 4
			-10	1852.40	10.15	0.0055	Note 4
			0	1852.40	16.37	0.0088	Note 4
			10	1852.40	19.62	0.0106	Note 4
			20	1852.40	10.16	0.0055	Note 4
			30	1852.40	17.94	0.0097	Note 4
			40	1852.40	11.27	0.0061	Note 4
			50	1852.40	17.88	0.0097	Note 4
			VL	20	1852.40	14.39	0.0078
			VH	20	1852.40	18.81	0.0102
VERDICT				PASS			

Note 1: All modes have been tested with GSM.

Note 2: All modes have been tested, and the worst result recorded was report as below

Note 3: The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.


Note 4: The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

## 12. EUT Photographs

**EUT Photo 1**



**EUT Photo 2**



NOTE: Appendix-Photographs Of EUT Constructional Details.

### 13. EUT Test Setup Photographs

#### Radiated Measurement Photos



**STATEMENT**

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

**Address:**

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: [bctc@bctc-lab.com.cn](mailto:bctc@bctc-lab.com.cn)

Complaint/Advice E-mail: [advice@bctc-lab.com.cn](mailto:advice@bctc-lab.com.cn)

\*\*\*\*\* END \*\*\*\*\*