



Test report No. : 4790260569-US-R0-V0
Page : 1 of 8
Issued date : 2022/5/25
FCC ID : 2A4CG-GC285686

Maximum Permissible Exposure Report

Product : 1CH Hub
Model Name : Thread-1P-AC
FCC ID : 2A4CG-GC285686
Test Regulation : 47 CFR FCC Part 2.1091
Received Date : 2022/2/25
Test Date : 2022/2/25 ~ 2022/4/27
Issued Date : 2022/5/25
Applicant : WideSky.Cloud Pty Ltd
38b Douglas St Milton, QLD 4064, Australia
Issued By : Underwriters Laboratories Taiwan Co., Ltd.
Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,
Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Test report No. : 4790260569-US-R0-V0
Page : 2 of 8
Issued date : 2022/5/25
FCC ID : 2A4CG-GC285686

REVISION HISTORY

Original Test Report No.: 4790260569-US-R0-V0

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Building B and Building E, No. 3727,
Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Paesline (PAX) :+886-3-585-7948

Doc No: 17-EM-F0864 / 5.0



Test report No. : 4790260569-US-R0-V0
Page : 3 of 8
Issued date : 2022/5/25
FCC ID : 2A4CG-GC285686

Table of Contents

| | |
|---|----------|
| 1. Attestation of Test Results..... | 4 |
| 2. Test Methodology and Reference Procedures | 5 |
| 3. Facilities and Accreditation | 5 |
| 4. Equipment Under Test | 6 |
| 4.1. Description of EUT..... | 6 |
| 4.2. Description of Available Antennas | 6 |
| 5. Requirement | 7 |
| 6. Radio Frequency Radiation Exposure Evaluation | 8 |

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Test report No. : 4790260569-US-R0-V0
Page : 4 of 8
Issued date : 2022/5/25
FCC ID : 2A4CG-GC285686

1. Attestation of Test Results

APPLICANT: WideSky.Cloud Pty Ltd
38b Douglas St Milton, QLD 4064, Australia

MANUFACTURER: WideSky.Cloud Pty Ltd
38b Douglas St Milton, QLD 4064, Australia

EUT DESCRIPTION: 1CH Hub

MODEL: Thread-1P-AC


SAMPLE STAGE: Identical Prototype

| APPLICABLE STANDARDS | |
|------------------------|--------------|
| STANDARD | Test Results |
| 47 CFR FCC PART 2.1091 | PASS |

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:


Sally Lu
Project Handler

Date : 2022/5/25

Approved and Authorized By:


Kent Liu
Senior Laboratory Engineer

Date : 2022/5/25

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Test report No. : 4790260569-US-R0-V0
Page : 5 of 8
Issued date : 2022/5/25
FCC ID : 2A4CG-GC285686

2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

3. Facilities and Accreditation

| | |
|----------------------------------|---|
| Test Location | Underwriters Laboratories Taiwan Co., Ltd. |
| Address | Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan |
| Accreditation Certificate | Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398. |

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Test report No. : 4790260569-US-R0-V0
Page : 6 of 8
Issued date : 2022/5/25
FCC ID : 2A4CG-GC285686

4. Equipment Under Test

4.1. Description of EUT

| | |
|----------------------------|------------------------|
| Product Name | 1CH Hub |
| Model Name | Thread-1P-AC |
| Operating Frequency | 2400MHz ~ 2483.5MHz |
| Modulation | O-QPSK |
| Number of Channel | 16 |
| Normal Voltage | 85ACV -264ACV |
| Sample ID | RF Test Sample 03 & 04 |

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.

4.2. Description of Available Antennas

| Ant. No. | Transmitter Circuit | Ant. Type | Maximum Gain (dBi) |
|-----------------|----------------------------|------------------|---------------------------|
| 1 | Chain (0) | Dipole | 2 |

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



5. Requirement

Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure | | | | |
|---|-----------------------------------|-----------------------------------|---|---|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (minutes) |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 |
| 1.34-30 | 824/f | 2.19/f | *180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | -- | -- | f/1500 | 30 |
| 1500-100,000 | -- | -- | 1.0 | 30 |

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



6. Radio Frequency Radiation Exposure Evaluation

| Evaluation Frequency (MHz) | Max. Average power (dBm) | Antenna Gain (dBi) | Max. EIRP (dBm) | Max. EIRP (mW) | Power density @ 20 cm (mW/cm ²) | Limit (mW/cm ²) |
|-------------------------------|-----------------------------|-----------------------|--------------------|-------------------|--|--------------------------------|
| 2400 ~ 2483.5 | 15.60 | 2.00 | 17.60 | 57.544 | 0.01145 | 1 |

Note:

1. Max. EIRP (dBm) = Max. Average power (dBm) + Antenna Gain (dBi)
2. Max. EIRP (mW) = $10^{(\text{Max. EIRP (dBm)} / 10)}$
3. Power density (mW/cm²) = Max. EIRP (mW) / [$4 \times \pi \times (\text{calculated distance})^2$], the calculated distance is 20 cm.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

END OF REPORT

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0