

TEST REPORT

Application No.: GZCR2209001150AT
Applicant: BLUE FROG ROBOTICS
Address of Applicant: 10 rue Mercoeur, 75011 Paris, FRANCE
Manufacturer: OMWAVE
Address of Manufacturer: 5 rue Barbès, 92120 Montrouge, FRANCE
Factory: OMWAVE
Address of Factory: 36 Avenue Salvador Allende, Batiment D - Village Mykonos, 60000 Beauvais, FRANCE

Equipment Under Test (EUT):

EUT Name: Buddy the Robot
Model No.: B01-US
Trade Mark: BLUE FROG ROBOTICS
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2022-09-15
Date of Test: 2022-11-01 to 2022-12-25
Date of Issue: 2023-04-27

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Ricky Liu
Manager





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. No.198 Kexhu Road, Solentech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
 Guangzhou Branch Testing Laboratory 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Revision Record			
Version	Report No.	Date	Remark
01	GZCR220900115005	2023-04-27	Original

Authorized for issue by:			
			
		Jim Li/Project Engineer	
			
		Ricky Liu/Reviewer	

2 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Radiated Emissions (Above 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Below 1GHz)		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

***Remark:**

This report is based on original modular report RF190522W005-8A with FCC ID: XMR201908SC66A C2PC for add host: Buddy the Robot; Model number: B01-US to the modular and C2PC change the modular antenna.

The replaced new Ceramic antenna with less gain than the antenna previously authorized under the certification FCC ID: XMR201908SC66A.

For verify the new antenna have similar in-band and out-of-band characteristics, only the Conducted Emissions at AC Power Line (150kHz-30MHz), Radiated Spurious Emissions Below 1GHz & Radiated Spurious Emissions Above 1GHz were performed with new antenna.

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Measurement Uncertainty	5
4.4 Test Location	5
4.5 Test Facility	6
4.6 Deviation from Standards	6
4.7 Abnormalities from Standard Conditions	6
5 Equipment List	7
6 Radio Spectrum Matter Test Results	9
6.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	9
6.1.1 E.U.T. Operation	9
6.1.2 Test Mode Description	9
6.1.3 Test Setup Diagram	9
6.1.4 Measurement Procedure and Data	10
6.2 Radiated Emissions (Below 1GHz)	13
6.2.1 E.U.T. Operation	13
6.2.2 Test Mode Description	13
6.2.3 Test Setup Diagram	14
6.2.4 Measurement Procedure and Data	15
6.3 Radiated Emissions (Above 1GHz)	18
6.3.1 E.U.T. Operation	18
6.3.2 Test Mode Description	19
6.3.3 Test Setup Diagram	19
6.3.4 Measurement Procedure and Data	20
7 Test Setup Photo	73
8 EUT Constructional Details (EUT Photos)	73



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply: AC/DC SWITCHING ADAPTER
MODEL NO.: GST90A19
INPUT:100-240VAC, 50/60Hz, 1.3A
OUTPUT:19V, 4.74A, 90W Max

Test voltage: AC 120V, 60Hz

Cable(s): AC input cable, 3 wires, 1.8m, unshielded.
DC output cable, 2 wires, 1.2m, with ferrite bead.
USB Port for debugging.
SIM Slot Port x 1.

RF Character(s): Refer to test report RF190522W005-8(Issue by BV 7Layers Communications Technology (Shenzhen) Co. Ltd) for 5G Wi-Fi details.

DFS Function: Slave without Radar detection

Antenna Type: Ceramic Antenna

Antenna Gain: 2.6 dBi

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Note Book Computer	LENOVO	ThinkPad T490	PF1D1MVJ
Wireless Router	Honor	HiRouter-CD30	AWTEQ20C04001295

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 2.76\text{dB}$
Radiated Emissions (Below 1GHz)	$\pm 5.00\text{dB}$ (3m); $\pm 4.38\text{dB}$ (10m)
Radiated Emissions (Above 1GHz)	$\pm 5.12\text{ dB}$ (1GHz-6 GHz); $\pm 5.38\text{ dB}$ (6GHz-18GHz); ± 5.61 (18GHz-40GHz)

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555

Fax: +86 20 82075059

No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No. 198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

● FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

● ISED (Registration No.: 4620B, CAB identifier: CN0052)

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

● VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou branch EMC Laboratory

No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Coaxial Cable	HangTianXing	2m	EMC0107	2022-08-24	2023-08-23
Shielding Room	ChangZhou ZhongYu	8m x 3m x 3.8m	EMC0306	2022-10-16	2025-10-15
Two-Line V-Network-GZ	Rohde & Schwarz	ENV216	EMC2135	2022-09-09	2023-09-08
EMI Test Receiver (9kHz-3.6GHz)	Rohde & Schwarz	ESR3	EMC2221	2022-05-20	2023-05-19
Test Software E3r	Audix	Ver.6.11812	GZE100-77	N/A	N/A

Radiated Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2022-12-16	2023-12-15
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2022-12-16	2023-12-15
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2022-08-24	2024-08-23
Horn Antenna (1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2022-09-23	2025-09-22
Horn Antenna (14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2022-09-08	2023-09-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
Notch Filter (5150-5880)	Mico-Tronics	BRM50716	EMC2168	2022-07-29	2023-07-28
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2022-08-24	2023-08-23
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Radiated Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2022-10-16	2025-10-15
Chamber cable	HangTianXing	N/A	EMC0542	2022-08-24	2023-08-23
Amplifier (9kHz-1.3GHz)	HP	8447F	EMC2065	2022-06-21	2023-06-20
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2022-04-06	2024-04-05
EMI Test Receiver (1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2220	2022-05-20	2023-05-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Trilog Broadband Antenna (25MHz-1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	EMC2174	2022-06-19	2025-06-18

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2022-06-24	2023-06-23



6 Radio Spectrum Matter Test Results

6.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C

Humidity: 50.3 % RH


Atmospheric Pressure: 1008 mbar

6.1.2 Test Mode Description

Pre-scan / Mode
Final test Code Description

Final test 09 Normal working_keep the EUT in charging mode.

6.1.3 Test Setup Diagram




6.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor


Test Mode: 09; Line: Live line



Pol : LINE
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.182	14.50	0.06	9.61	24.17	54.42	-30.25	Average
2	0.182	30.33	0.06	9.61	40.00	64.42	-24.42	QP
3	0.363	19.80	0.06	9.60	29.46	48.65	-19.19	Average
4	0.363	30.95	0.06	9.60	40.61	58.65	-18.04	QP
5	1.054	13.42	0.07	9.59	23.08	46.00	-22.92	Average
6	1.054	23.78	0.07	9.59	33.44	56.00	-22.56	QP
7	12.784	35.84	0.27	9.69	45.80	50.00	-4.20	Average
8	12.784	35.97	0.27	9.69	45.93	60.00	-14.07	QP
9	15.801	35.16	0.30	9.70	45.16	50.00	-4.84	Average
10	15.801	35.94	0.30	9.70	45.94	60.00	-14.06	QP
11	22.535	36.60	0.37	9.66	46.63	50.00	-3.37	Average
12	22.535	37.05	0.37	9.66	47.08	60.00	-12.92	QP

Test Mode: 09; Line: Neutral Line



Pol : NEUTRAL
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.204	14.90	0.06	9.60	24.56	53.45	-28.89	Average
2	0.204	26.44	0.06	9.60	36.10	63.45	-27.35	QP
3	0.410	15.26	0.06	9.61	24.93	47.64	-22.71	Average
4	0.410	26.42	0.06	9.61	36.09	57.64	-21.55	QP
5	0.611	19.15	0.07	9.62	28.84	46.00	-17.16	Average
6	0.611	28.17	0.07	9.62	37.86	56.00	-18.14	QP
7	12.124	35.25	0.25	9.75	45.25	50.00	-4.75	Average
8	12.124	35.39	0.25	9.75	45.39	60.00	-14.61	QP
9	15.226	35.31	0.30	9.80	45.41	50.00	-4.59	Average
10	15.226	35.33	0.30	9.80	45.43	60.00	-14.57	QP
11	21.830	36.39	0.37	9.86	46.62	50.00	-3.38	Average
12	21.830	37.44	0.37	9.86	47.67	60.00	-12.33	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

6.2 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency (MHz)	Field strength(microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.1 °C

Humidity: 56.9 % RH

Atmospheric Pressure: 1008 mbar

6.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
--------------------------	--------------	-------------

Final test	02	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
------------	----	--

Pre-scan	03	TX mode (U-NII-2A)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
----------	----	--

Pre-scan	04	TX mode (U-NII-2C)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE
----------	----	--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Pre-scan 05

802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

TX mode (U-NII-3)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

6.2.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
3. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Test Mode: 02; Polarity: Horizontal



Site : SGS
Job :
Model :
Power :
Test Mode : 5G Wi-Fi

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	40.845	23.06	13.58	1.09	27.61	10.12	29.54	-19.42	HORIZONTAL	QP
2	57.999	24.52	13.56	1.22	27.60	11.70	29.54	-17.84	HORIZONTAL	QP
3	159.225	23.40	13.67	2.32	27.36	12.03	33.06	-21.03	HORIZONTAL	QP
4	315.481	24.15	13.90	3.33	27.28	14.10	35.56	-21.46	HORIZONTAL	QP
5	601.427	25.91	20.19	4.98	28.80	22.28	35.56	-13.28	HORIZONTAL	QP
6	798.980	26.36	22.79	6.04	28.60	26.59	35.56	-8.97	HORIZONTAL	QP




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, Testing Service, EEC Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Test Mode: 02; Polarity: Vertical



Site : SGS
Job :
Model :
Power :
Test Mode : 5G Wi-Fi

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	41.132	23.85	13.58	1.09	27.61	10.91	29.54	-18.63	VERTICAL	QP
2	55.805	23.89	13.74	1.19	27.60	11.22	29.54	-18.32	VERTICAL	QP
3	146.888	24.93	13.40	2.19	27.40	13.12	33.06	-19.94	VERTICAL	QP
4	336.035	24.68	14.31	3.47	27.45	15.01	35.56	-20.55	VERTICAL	QP
5	601.427	26.23	20.19	4.98	28.80	22.60	35.56	-12.96	VERTICAL	QP
6	818.834	26.11	23.39	6.11	28.54	27.07	35.56	-8.49	VERTICAL	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, Testing Services, EEC Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

6.3 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1GHz	500	3
<p>*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.</p> <p>(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.</p> <p>(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.</p> <p>(4) For transmitters operating in the 5.725-5.85 GHz band:</p> <p>(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.</p> <p>Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.</p>		

6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.9 °C Humidity: 51.9 % RH Atmospheric Pressure: 1015 mbar




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
Final test	03	TX mode (U-NII-2A)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
Final test	04	TX mode (U-NII-2C)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
Final test	05	TX mode (U-NII-3)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

6.3.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch
No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com


6.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.


Test Mode: 02; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1168.920	51.92	24.55	2.56	38.17	40.86	74.00	-33.14	VERTICAL peak
2	1542.733	49.07	25.53	2.96	37.66	39.90	74.00	-34.10	VERTICAL peak
3	3969.767	49.49	29.77	5.18	36.70	47.74	74.00	-26.26	VERTICAL peak
4	7158.806	42.65	35.40	6.37	36.88	47.54	68.20	-20.66	VERTICAL peak
5	10360.000	40.02	39.28	6.35	36.77	48.88	68.20	-19.32	VERTICAL peak
6	15540.000	39.73	39.05	8.42	36.15	51.05	74.00	-22.95	VERTICAL peak


Test Mode: 02; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1203.199	56.01	24.70	2.58	38.14	45.15	74.00	-28.85	HORIZONTAL	peak
2	1644.019	47.98	25.63	3.11	37.51	39.21	68.20	-28.99	HORIZONTAL	peak
3	4430.628	45.70	30.72	5.36	36.62	45.16	68.20	-23.04	HORIZONTAL	peak
4	7117.542	42.74	35.28	6.38	36.85	47.55	68.20	-20.65	HORIZONTAL	peak
5	10360.000	41.06	39.28	6.35	36.77	49.92	68.20	-18.28	HORIZONTAL	peak
6	15540.000	40.73	39.05	8.42	36.15	52.05	74.00	-21.95	HORIZONTAL	peak


Test Mode: 02; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1122.563	50.56	24.42	2.52	38.21	39.29	74.00	-34.71	VERTICAL peak
2	1672.779	48.44	25.67	3.21	37.48	39.84	74.00	-34.16	VERTICAL peak
3	4482.150	46.11	30.78	5.34	36.61	45.62	68.20	-22.58	VERTICAL peak
4	7015.420	42.81	35.04	6.41	36.74	47.52	68.20	-20.68	VERTICAL peak
5	10440.000	40.54	39.42	6.31	36.76	49.51	68.20	-18.69	VERTICAL peak
6	15660.000	40.40	38.86	8.16	36.19	51.23	74.00	-22.77	VERTICAL peak


Test Mode: 02; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1245.663	54.16	25.00	2.61	38.10	43.67	68.20	-24.53	HORIZONTAL peak
2	1692.231	48.13	25.70	3.30	37.46	39.67	74.00	-34.33	HORIZONTAL peak
3	4329.354	46.36	30.54	5.31	36.64	45.57	74.00	-28.43	HORIZONTAL peak
4	7015.420	43.00	35.04	6.41	36.74	47.71	68.20	-20.49	HORIZONTAL peak
5	10440.000	43.06	39.42	6.31	36.76	52.03	68.20	-16.17	HORIZONTAL peak
6	15660.000	43.11	38.86	8.16	36.19	53.94	74.00	-20.06	HORIZONTAL peak


Test Mode: 02; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1274.802	48.33	25.12	2.64	38.07	38.02	68.20	-30.18	VERTICAL peak
2	1682.477	48.43	25.68	3.25	37.48	39.88	74.00	-34.12	VERTICAL peak
3	4379.699	45.70	30.64	5.35	36.63	45.06	74.00	-28.94	VERTICAL peak
4	7015.420	43.49	35.04	6.41	36.74	48.20	68.20	-20.00	VERTICAL peak
5	10480.000	40.34	39.46	6.29	36.76	49.33	68.20	-18.87	VERTICAL peak
6	15720.000	40.16	38.78	8.06	36.22	50.78	74.00	-23.22	VERTICAL peak


Test Mode: 02; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1267.454	51.71	25.10	2.63	38.07	41.37	68.20	-26.83	HORIZONTAL peak
2	1653.550	48.60	25.64	3.14	37.51	39.87	68.20	-28.33	HORIZONTAL peak
3	4329.354	45.38	30.54	5.31	36.64	44.59	74.00	-29.41	HORIZONTAL peak
4	7158.806	42.95	35.40	6.37	36.88	47.84	68.20	-20.36	HORIZONTAL peak
5	10480.000	40.68	39.46	6.29	36.76	49.67	68.20	-18.53	HORIZONTAL peak
6	15720.000	42.06	38.78	8.06	36.22	52.68	74.00	-21.32	HORIZONTAL peak


Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1122.563	50.30	24.42	2.52	38.21	39.03	74.00	-34.97	VERTICAL peak
2	1606.441	48.73	25.59	3.02	37.58	39.76	74.00	-34.24	VERTICAL peak
3	4430.628	45.23	30.72	5.36	36.62	44.69	68.20	-23.51	VERTICAL peak
4	7158.806	42.21	35.40	6.37	36.88	47.10	68.20	-21.10	VERTICAL peak
5	10380.000	39.52	39.33	6.33	36.77	48.41	68.20	-19.79	VERTICAL peak
6	15570.000	39.93	38.99	8.34	36.16	51.10	74.00	-22.90	VERTICAL peak


Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1267.454	49.05	25.10	2.63	38.07	38.71	68.20	-29.49	HORIZONTAL peak
2	1644.019	48.53	25.63	3.11	37.51	39.76	68.20	-28.44	HORIZONTAL peak
3	4379.699	45.62	30.64	5.35	36.63	44.98	74.00	-29.02	HORIZONTAL peak
4	7117.542	43.18	35.28	6.38	36.85	47.99	68.20	-20.21	HORIZONTAL peak
5	10380.000	39.84	39.33	6.33	36.77	48.73	68.20	-19.47	HORIZONTAL peak
6	15570.000	39.52	38.99	8.34	36.16	50.69	74.00	-23.31	HORIZONTAL peak


Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1129.072	50.50	24.43	2.53	38.21	39.25	74.00	-34.75	VERTICAL	peak
2	1682.477	50.68	25.68	3.25	37.48	42.13	74.00	-31.87	VERTICAL	peak
3	3992.781	52.01	29.79	5.25	36.70	50.35	74.00	-23.65	VERTICAL	peak
4	8995.123	40.80	37.40	7.09	37.05	48.24	68.20	-19.96	VERTICAL	peak
5	10460.000	40.43	39.42	6.31	36.76	49.40	68.20	-18.80	VERTICAL	peak
6	15690.000	40.73	38.86	8.16	36.21	51.54	74.00	-22.46	VERTICAL	peak


Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1274.802	48.68	25.12	2.64	38.07	38.37	68.20	-29.83	HORIZONTAL peak
2	1560.673	49.61	25.54	2.98	37.66	40.47	74.00	-33.53	HORIZONTAL peak
3	4482.150	45.28	30.78	5.34	36.61	44.79	68.20	-23.41	HORIZONTAL peak
4	8995.123	41.05	37.40	7.09	37.05	48.49	68.20	-19.71	HORIZONTAL peak
5	10460.000	40.47	39.42	6.31	36.76	49.44	68.20	-18.76	HORIZONTAL peak
6	15690.000	41.03	38.86	8.16	36.21	51.84	74.00	-22.16	HORIZONTAL peak


Test Mode: 02; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1168.920	53.82	24.55	2.56	38.17	42.76	74.00	-31.24	VERTICAL	peak
2	1644.019	49.24	25.63	3.11	37.51	40.47	68.20	-27.73	VERTICAL	peak
3	3992.781	47.76	29.79	5.25	36.70	46.10	74.00	-27.90	VERTICAL	peak
4	7158.806	42.55	35.40	6.37	36.88	47.44	68.20	-20.76	VERTICAL	peak
5	10420.000	40.07	39.38	6.32	36.76	49.01	68.20	-19.19	VERTICAL	peak
6	15630.000	39.84	38.92	8.26	36.18	50.84	74.00	-23.16	VERTICAL	peak


Test Mode: 02; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1274.802	48.65	25.12	2.64	38.07	38.34	68.20	-29.86	HORIZONTAL	peak
2	1682.477	47.96	25.68	3.25	37.48	39.41	74.00	-34.59	HORIZONTAL	peak
3	4379.699	46.00	30.64	5.35	36.63	45.36	74.00	-28.64	HORIZONTAL	peak
4	7200.309	42.92	35.54	6.36	36.92	47.90	68.20	-20.30	HORIZONTAL	peak
5	10420.000	40.07	39.38	6.32	36.76	49.01	68.20	-19.19	HORIZONTAL	peak
6	15630.000	39.87	38.92	8.26	36.18	50.87	74.00	-23.13	HORIZONTAL	peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1162.182	51.23	24.53	2.56	38.19	40.13	74.00	-33.87	VERTICAL peak
2	1525.000	49.80	25.52	2.94	37.70	40.56	74.00	-33.44	VERTICAL peak
3	3992.781	50.82	29.79	5.25	36.70	49.16	74.00	-24.84	VERTICAL peak
4	7242.052	43.31	35.70	6.35	36.96	48.40	68.20	-19.80	VERTICAL peak
5	10520.000	40.65	39.50	6.28	36.75	49.68	68.20	-18.52	VERTICAL peak
6	15780.000	41.26	38.70	7.95	36.23	51.68	74.00	-22.32	VERTICAL peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1148.823	49.85	24.49	2.55	38.19	38.70	74.00	-35.30	HORIZONTAL peak
2	1692.231	49.37	25.70	3.30	37.46	40.91	74.00	-33.09	HORIZONTAL peak
3	4495.125	45.93	30.80	5.33	36.60	45.46	68.20	-22.74	HORIZONTAL peak
4	7158.806	42.67	35.40	6.37	36.88	47.56	68.20	-20.64	HORIZONTAL peak
5	10520.000	41.79	39.50	6.28	36.75	50.82	68.20	-17.38	HORIZONTAL peak
6	15780.000	42.06	38.70	7.95	36.23	52.48	74.00	-21.52	HORIZONTAL peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1196.264	50.08	24.67	2.58	38.14	39.19	74.00	-34.81	VERTICAL peak
2	1525.000	49.51	25.52	2.94	37.70	40.27	74.00	-33.73	VERTICAL peak
3	4482.150	46.62	30.78	5.34	36.61	46.13	68.20	-22.07	VERTICAL peak
4	7158.806	42.69	35.40	6.37	36.88	47.58	68.20	-20.62	VERTICAL peak
5	10600.000	40.89	39.59	6.45	36.74	50.19	68.20	-18.01	VERTICAL peak
6	15900.000	40.68	38.44	7.59	36.27	50.44	74.00	-23.56	VERTICAL peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1245.663	51.45	25.00	2.61	38.10	40.96	68.20	-27.24	HORIZONTAL	peak
2	1692.231	47.97	25.70	3.30	37.46	39.51	74.00	-34.49	HORIZONTAL	peak
3	3969.767	46.97	29.77	5.18	36.70	45.22	74.00	-28.78	HORIZONTAL	peak
4	7200.309	42.69	35.54	6.36	36.92	47.67	68.20	-20.53	HORIZONTAL	peak
5	10600.000	40.36	39.59	6.45	36.74	49.66	68.20	-18.54	HORIZONTAL	peak
6	15900.000	40.63	38.44	7.59	36.27	50.39	74.00	-23.61	HORIZONTAL	peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1224.247	49.43	24.85	2.60	38.12	38.76	74.00	-35.24	VERTICAL peak
2	1615.754	48.71	25.60	3.04	37.55	39.80	74.00	-34.20	VERTICAL peak
3	3992.781	47.40	29.79	5.25	36.70	45.74	74.00	-28.26	VERTICAL peak
4	7200.309	42.88	35.54	6.36	36.92	47.86	68.20	-20.34	VERTICAL peak
5	10640.000	39.39	39.63	6.51	36.73	48.80	74.00	-25.20	VERTICAL peak
6	15960.000	40.73	38.37	7.49	36.29	50.30	74.00	-23.70	VERTICAL peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1175.697	50.42	24.58	2.57	38.17	39.40	74.00	-34.60	HORIZONTAL	peak
2	1525.000	48.27	25.52	2.94	37.70	39.03	74.00	-34.97	HORIZONTAL	peak
3	4354.454	45.77	30.59	5.34	36.64	45.06	74.00	-28.94	HORIZONTAL	peak
4	7158.806	43.04	35.40	6.37	36.88	47.93	68.20	-20.27	HORIZONTAL	peak
5	10640.000	38.86	39.63	6.51	36.73	48.27	74.00	-25.73	HORIZONTAL	peak
6	15960.000	40.47	38.37	7.49	36.29	50.04	74.00	-23.96	HORIZONTAL	peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1175.697	52.32	24.58	2.57	38.17	41.30	74.00	-32.70	VERTICAL peak
2	1682.477	49.61	25.68	3.25	37.48	41.06	74.00	-32.94	VERTICAL peak
3	3969.767	48.57	29.77	5.18	36.70	46.82	74.00	-27.18	VERTICAL peak
4	7158.806	42.59	35.40	6.37	36.88	47.48	68.20	-20.72	VERTICAL peak
5	10540.000	39.92	39.53	6.33	36.75	49.03	68.20	-19.17	VERTICAL peak
6	15810.000	40.84	38.61	7.82	36.24	51.03	74.00	-22.97	VERTICAL peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1245.663	50.30	25.00	2.61	38.10	39.81	68.20	-28.39	HORIZONTAL peak
2	1625.121	48.42	25.61	3.06	37.55	39.54	74.00	-34.46	HORIZONTAL peak
3	4405.090	45.66	30.68	5.37	36.63	45.08	68.20	-23.12	HORIZONTAL peak
4	8995.123	39.94	37.40	7.09	37.05	47.38	68.20	-20.82	HORIZONTAL peak
5	10540.000	39.87	39.53	6.33	36.75	48.98	68.20	-19.22	HORIZONTAL peak
6	15810.000	41.24	38.61	7.82	36.24	51.43	74.00	-22.57	HORIZONTAL peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1148.823	50.11	24.49	2.55	38.19	38.96	74.00	-35.04	VERTICAL	peak
2	1398.336	49.93	25.39	2.77	37.92	40.17	74.00	-33.83	VERTICAL	peak
3	3969.767	54.59	29.77	5.18	36.70	52.84	74.00	-21.16	VERTICAL	peak
4	7117.542	43.06	35.28	6.38	36.85	47.87	68.20	-20.33	VERTICAL	peak
5	10620.000	39.55	39.59	6.45	36.74	48.85	74.00	-25.15	VERTICAL	peak
6	15930.000	40.40	38.37	7.49	36.28	49.98	74.00	-24.02	VERTICAL	peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1148.823	49.49	24.49	2.55	38.19	38.34	74.00	-35.66	HORIZONTAL	peak
2	1634.543	48.83	25.62	3.09	37.55	39.99	68.20	-28.21	HORIZONTAL	peak
3	4157.664	46.46	30.06	5.22	36.68	45.06	74.00	-28.94	HORIZONTAL	peak
4	7158.806	42.32	35.40	6.37	36.88	47.21	68.20	-20.99	HORIZONTAL	peak
5	10620.000	40.13	39.59	6.45	36.74	49.43	74.00	-24.57	HORIZONTAL	peak
6	15930.000	39.94	38.37	7.49	36.28	49.52	74.00	-24.48	HORIZONTAL	peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1260.149	48.94	25.07	2.62	38.10	38.53	68.20	-29.67	VERTICAL	peak
2	1542.733	52.94	25.53	2.96	37.66	43.77	74.00	-30.23	VERTICAL	peak
3	4482.150	45.27	30.78	5.34	36.61	44.78	68.20	-23.42	VERTICAL	peak
4	7242.052	42.55	35.70	6.35	36.96	47.64	68.20	-20.56	VERTICAL	peak
5	10580.000	39.69	39.56	6.39	36.74	48.90	68.20	-19.30	VERTICAL	peak
6	15870.000	40.59	38.52	7.70	36.26	50.55	74.00	-23.45	VERTICAL	peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1252.885	50.44	25.03	2.62	38.10	39.99	68.20	-28.21	HORIZONTAL	peak
2	1672.779	48.07	25.67	3.21	37.48	39.47	74.00	-34.53	HORIZONTAL	peak
3	4456.315	46.06	30.75	5.35	36.62	45.54	68.20	-22.66	HORIZONTAL	peak
4	7015.420	42.92	35.04	6.41	36.74	47.63	68.20	-20.57	HORIZONTAL	peak
5	10580.000	41.77	39.56	6.39	36.74	50.98	68.20	-17.22	HORIZONTAL	peak
6	15870.000	40.59	38.52	7.70	36.26	50.55	74.00	-23.45	HORIZONTAL	peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1282.193	48.62	25.15	2.65	38.07	38.35	68.20	-29.85	VERTICAL	peak
2	1390.276	49.34	25.38	2.77	37.92	39.57	74.00	-34.43	VERTICAL	peak
3	3992.781	50.75	29.79	5.25	36.70	49.09	74.00	-24.91	VERTICAL	peak
4	7117.542	42.33	35.28	6.38	36.85	47.14	68.20	-21.06	VERTICAL	peak
5	11000.000	38.88	40.10	7.37	36.65	49.70	74.00	-24.30	VERTICAL	peak
6	16500.000	38.73	39.60	7.87	36.24	49.96	68.20	-18.24	VERTICAL	peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1224.247	49.26	24.85	2.60	38.12	38.59	74.00	-35.41	HORIZONTAL peak
2	1490.142	48.33	25.49	2.87	37.75	38.94	74.00	-35.06	HORIZONTAL peak
3	4456.315	45.45	30.75	5.35	36.62	44.93	68.20	-23.27	HORIZONTAL peak
4	7117.542	43.11	35.28	6.38	36.85	47.92	68.20	-20.28	HORIZONTAL peak
5	11000.000	39.00	40.10	7.37	36.65	49.82	74.00	-24.18	HORIZONTAL peak
6	16500.000	38.97	39.60	7.87	36.24	50.20	68.20	-18.00	HORIZONTAL peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1162.182	50.61	24.53	2.56	38.19	39.51	74.00	-34.49	VERTICAL peak
2	1398.336	49.09	25.39	2.77	37.92	39.33	74.00	-34.67	VERTICAL peak
3	3969.767	48.28	29.77	5.18	36.70	46.53	74.00	-27.47	VERTICAL peak
4	7158.806	42.63	35.40	6.37	36.88	47.52	68.20	-20.68	VERTICAL peak
5	11160.000	38.86	40.04	7.62	36.61	49.91	74.00	-24.09	VERTICAL peak
6	16740.000	38.43	40.49	7.63	36.19	50.36	68.20	-17.84	VERTICAL peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1252.885	49.62	25.03	2.62	38.10	39.17	68.20	-29.03	HORIZONTAL peak
2	1606.441	48.04	25.59	3.02	37.58	39.07	74.00	-34.93	HORIZONTAL peak
3	4495.125	45.23	30.80	5.33	36.60	44.76	68.20	-23.44	HORIZONTAL peak
4	8995.123	40.20	37.40	7.09	37.05	47.64	68.20	-20.56	HORIZONTAL peak
5	11160.000	39.58	40.04	7.62	36.61	50.63	74.00	-23.37	HORIZONTAL peak
6	16740.000	38.59	40.49	7.63	36.19	50.52	68.20	-17.68	HORIZONTAL peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1109.660	52.02	24.39	2.51	38.23	40.69	74.00	-33.31	VERTICAL peak
2	1625.121	48.42	25.61	3.06	37.55	39.54	74.00	-34.46	VERTICAL peak
3	4405.090	45.32	30.68	5.37	36.63	44.74	68.20	-23.46	VERTICAL peak
4	8995.123	39.84	37.40	7.09	37.05	47.28	68.20	-20.92	VERTICAL peak
5	11400.000	39.66	39.94	8.11	36.56	51.15	74.00	-22.85	VERTICAL peak
6	17100.000	38.60	42.32	7.53	36.06	52.39	68.20	-15.81	VERTICAL peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1162.182	49.50	24.53	2.56	38.19	38.40	74.00	-35.60	HORIZONTAL	peak
2	1692.231	48.16	25.70	3.30	37.46	39.70	74.00	-34.30	HORIZONTAL	peak
3	4230.396	46.14	30.26	5.23	36.66	44.97	74.00	-29.03	HORIZONTAL	peak
4	7158.806	42.48	35.40	6.37	36.88	47.37	68.20	-20.83	HORIZONTAL	peak
5	11400.000	39.76	39.94	8.11	36.56	51.25	74.00	-22.75	HORIZONTAL	peak
6	17100.000	39.19	42.32	7.53	36.06	52.98	68.20	-15.22	HORIZONTAL	peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1182.513	50.72	24.60	2.57	38.17	39.72	74.00	-34.28	VERTICAL peak
2	1560.673	48.22	25.54	2.98	37.66	39.08	74.00	-34.92	VERTICAL peak
3	3992.781	50.91	29.79	5.25	36.70	49.25	74.00	-24.75	VERTICAL peak
4	7179.527	42.29	35.47	6.37	36.90	47.23	68.20	-20.97	VERTICAL peak
5	11020.000	39.61	40.10	7.37	36.64	50.44	74.00	-23.56	VERTICAL peak
6	16530.000	38.52	39.76	7.83	36.23	49.88	68.20	-18.32	VERTICAL peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1252.885	51.34	25.03	2.62	38.10	40.89	68.20	-27.31	HORIZONTAL peak
2	1672.779	47.85	25.67	3.21	37.48	39.25	74.00	-34.75	HORIZONTAL peak
3	4456.315	46.62	30.75	5.35	36.62	46.10	68.20	-22.10	HORIZONTAL peak
4	7117.542	42.68	35.28	6.38	36.85	47.49	68.20	-20.71	HORIZONTAL peak
5	11020.000	39.56	40.10	7.37	36.64	50.39	74.00	-23.61	HORIZONTAL peak
6	16530.000	39.34	39.76	7.83	36.23	50.70	68.20	-17.50	HORIZONTAL peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1109.660	49.67	24.39	2.51	38.23	38.34	74.00	-35.66	VERTICAL peak
2	1525.000	49.85	25.52	2.94	37.70	40.61	74.00	-33.39	VERTICAL peak
3	3992.781	48.30	29.79	5.25	36.70	46.64	74.00	-27.36	VERTICAL peak
4	7200.309	42.53	35.54	6.36	36.92	47.51	68.20	-20.69	VERTICAL peak
5	11100.000	39.18	40.07	7.51	36.62	50.14	74.00	-23.86	VERTICAL peak
6	16650.000	38.58	40.10	7.74	36.21	50.21	68.20	-17.99	VERTICAL peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1274.802	48.84	25.12	2.64	38.07	38.53	68.20	-29.67	HORIZONTAL peak
2	1606.441	48.46	25.59	3.02	37.58	39.49	74.00	-34.51	HORIZONTAL peak
3	4279.589	45.62	30.42	5.27	36.65	44.66	74.00	-29.34	HORIZONTAL peak
4	7117.542	42.35	35.28	6.38	36.85	47.16	68.20	-21.04	HORIZONTAL peak
5	11100.000	39.76	40.07	7.51	36.62	50.72	74.00	-23.28	HORIZONTAL peak
6	16650.000	38.56	40.10	7.74	36.21	50.19	68.20	-18.01	HORIZONTAL peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1300.858	51.57	25.20	2.68	38.04	41.41	74.00	-32.59	VERTICAL peak
2	1615.754	48.10	25.60	3.04	37.55	39.19	74.00	-34.81	VERTICAL peak
3	4405.090	46.43	30.68	5.37	36.63	45.85	68.20	-22.35	VERTICAL peak
4	7158.806	42.80	35.40	6.37	36.88	47.69	68.20	-20.51	VERTICAL peak
5	11340.000	39.43	39.97	7.97	36.57	50.80	74.00	-23.20	VERTICAL peak
6	17010.000	40.34	41.75	7.39	36.10	53.38	68.20	-14.82	VERTICAL peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1252.885	49.18	25.03	2.62	38.10	38.73	68.20	-29.47	HORIZONTAL	peak
2	1682.477	49.23	25.68	3.25	37.48	40.68	74.00	-33.32	HORIZONTAL	peak
3	4430.628	46.09	30.72	5.36	36.62	45.55	68.20	-22.65	HORIZONTAL	peak
4	8995.123	40.23	37.40	7.09	37.05	47.67	68.20	-20.53	HORIZONTAL	peak
5	11340.000	38.82	39.97	7.97	36.57	50.19	74.00	-23.81	HORIZONTAL	peak
6	17010.000	39.20	41.75	7.39	36.10	52.24	68.20	-15.96	HORIZONTAL	peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1300.858	49.47	25.20	2.68	38.04	39.31	74.00	-34.69	VERTICAL peak
2	1702.042	47.53	25.72	3.36	37.46	39.15	74.00	-34.85	VERTICAL peak
3	4062.629	46.23	29.88	5.26	36.69	44.68	74.00	-29.32	VERTICAL peak
4	8995.123	39.50	37.40	7.09	37.05	46.94	68.20	-21.26	VERTICAL peak
5	11060.000	38.97	40.09	7.41	36.63	49.84	74.00	-24.16	VERTICAL peak
6	16590.000	37.99	39.93	7.79	36.22	49.49	68.20	-18.71	VERTICAL peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1252.885	50.05	25.03	2.62	38.10	39.60	68.20	-28.60	HORIZONTAL	peak
2	1634.543	50.33	25.62	3.09	37.55	41.49	68.20	-26.71	HORIZONTAL	peak
3	3969.767	47.52	29.77	5.18	36.70	45.77	74.00	-28.23	HORIZONTAL	peak
4	7158.806	42.10	35.40	6.37	36.88	46.99	68.20	-21.21	HORIZONTAL	peak
5	11060.000	39.82	40.09	7.41	36.63	50.69	74.00	-23.31	HORIZONTAL	peak
6	16590.000	38.98	39.93	7.79	36.22	50.48	68.20	-17.72	HORIZONTAL	peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1203.199	49.12	24.70	2.58	38.14	38.26	74.00	-35.74	VERTICAL peak
2	1525.000	50.15	25.52	2.94	37.70	40.91	74.00	-33.09	VERTICAL peak
3	4495.125	44.96	30.80	5.33	36.60	44.49	68.20	-23.71	VERTICAL peak
4	8995.123	39.90	37.40	7.09	37.05	47.34	68.20	-20.86	VERTICAL peak
5	11220.000	39.56	40.03	7.68	36.59	50.68	74.00	-23.32	VERTICAL peak
6	16830.000	40.19	40.94	7.52	36.17	52.48	68.20	-15.72	VERTICAL peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1289.627	49.37	25.17	2.66	38.04	39.16	68.20	-29.04	HORIZONTAL peak
2	1672.779	49.28	25.67	3.21	37.48	40.68	74.00	-33.32	HORIZONTAL peak
3	4379.699	45.93	30.64	5.35	36.63	45.29	74.00	-28.71	HORIZONTAL peak
4	7326.267	42.13	36.00	6.32	37.01	47.44	74.00	-26.56	HORIZONTAL peak
5	11220.000	39.42	40.03	7.68	36.59	50.54	74.00	-23.46	HORIZONTAL peak
6	16830.000	39.71	40.94	7.52	36.17	52.00	68.20	-16.20	HORIZONTAL peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1203.199	49.09	24.70	2.58	38.14	38.23	74.00	-35.77	VERTICAL peak
2	1663.137	48.89	25.65	3.18	37.48	40.24	74.00	-33.76	VERTICAL peak
3	3969.767	49.46	29.77	5.18	36.70	47.71	74.00	-26.29	VERTICAL peak
4	7117.542	43.10	35.28	6.38	36.85	47.91	68.20	-20.29	VERTICAL peak
5	11490.000	39.76	39.90	8.27	36.55	51.38	74.00	-22.62	VERTICAL peak
6	17235.000	37.88	43.01	7.80	36.02	52.67	68.20	-15.53	VERTICAL peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1274.802	49.49	25.12	2.64	38.07	39.18	68.20	-29.02	HORIZONTAL peak
2	1587.975	50.44	25.57	3.00	37.58	41.43	74.00	-32.57	HORIZONTAL peak
3	4430.628	46.31	30.72	5.36	36.62	45.77	68.20	-22.43	HORIZONTAL peak
4	7158.806	44.52	35.40	6.37	36.88	49.41	68.20	-18.79	HORIZONTAL peak
5	11490.000	39.98	39.90	8.27	36.55	51.60	74.00	-22.40	HORIZONTAL peak
6	17235.000	37.12	43.01	7.80	36.02	51.91	68.20	-16.29	HORIZONTAL peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1252.885	48.76	25.03	2.62	38.10	38.31	68.20	-29.89	VERTICAL	peak
2	1390.276	50.00	25.38	2.77	37.92	40.23	74.00	-33.77	VERTICAL	peak
3	3856.668	46.74	29.62	4.73	36.72	44.37	74.00	-29.63	VERTICAL	peak
4	7158.806	41.99	35.40	6.37	36.88	46.88	68.20	-21.32	VERTICAL	peak
5	11570.000	39.53	39.78	8.29	36.54	51.06	74.00	-22.94	VERTICAL	peak
6	17355.000	37.20	43.40	7.98	35.99	52.59	68.20	-15.61	VERTICAL	peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

		Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
		MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1		1162.182	49.37	24.53	2.56	38.19	38.27	74.00	-35.73	HORIZONTAL peak
2		1692.231	49.85	25.70	3.30	37.46	41.39	74.00	-32.61	HORIZONTAL peak
3		3969.767	47.41	29.77	5.18	36.70	45.66	74.00	-28.34	HORIZONTAL peak
4		7015.420	42.68	35.04	6.41	36.74	47.39	68.20	-20.81	HORIZONTAL peak
5		11570.000	39.11	39.78	8.29	36.54	50.64	74.00	-23.36	HORIZONTAL peak
6		17355.000	37.73	43.40	7.98	35.99	53.12	68.20	-15.08	HORIZONTAL peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1252.885	50.81	25.03	2.62	38.10	40.36	68.20	-27.84	VERTICAL peak
2	1663.137	48.34	25.65	3.18	37.48	39.69	74.00	-34.31	VERTICAL peak
3	3879.027	48.06	29.66	4.82	36.72	45.82	74.00	-28.18	VERTICAL peak
4	7015.420	42.84	35.04	6.41	36.74	47.55	68.20	-20.65	VERTICAL peak
5	11650.000	38.88	39.65	8.32	36.53	50.32	74.00	-23.68	VERTICAL peak
6	17475.000	36.81	43.90	8.20	35.97	52.94	68.20	-15.26	VERTICAL peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1148.823	49.26	24.49	2.55	38.19	38.11	74.00	-35.89	HORIZONTAL	peak
2	1672.779	48.46	25.67	3.21	37.48	39.86	74.00	-34.14	HORIZONTAL	peak
3	4405.090	45.88	30.68	5.37	36.63	45.30	68.20	-22.90	HORIZONTAL	peak
4	7200.309	42.40	35.54	6.36	36.92	47.38	68.20	-20.82	HORIZONTAL	peak
5	11650.000	39.09	39.65	8.32	36.53	50.53	74.00	-23.47	HORIZONTAL	peak
6	17475.000	36.86	43.90	8.20	35.97	52.99	68.20	-15.21	HORIZONTAL	peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1289.627	50.41	25.17	2.66	38.04	40.20	68.20	-28.00	VERTICAL peak
2	1682.477	47.71	25.68	3.25	37.48	39.16	74.00	-34.84	VERTICAL peak
3	3969.767	49.28	29.77	5.18	36.70	47.53	74.00	-26.47	VERTICAL peak
4	7200.309	41.61	35.54	6.36	36.92	46.59	68.20	-21.61	VERTICAL peak
5	11510.000	39.09	39.90	8.27	36.55	50.71	74.00	-23.29	VERTICAL peak
6	17265.000	37.04	43.21	7.89	36.01	52.13	68.20	-16.07	VERTICAL peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1274.802	48.55	25.12	2.64	38.07	38.24	68.20	-29.96	HORIZONTAL	peak
2	1578.822	49.16	25.56	2.99	37.62	40.09	74.00	-33.91	HORIZONTAL	peak
3	4482.150	45.02	30.78	5.34	36.61	44.53	68.20	-23.67	HORIZONTAL	peak
4	7117.542	43.69	35.28	6.38	36.85	48.50	68.20	-19.70	HORIZONTAL	peak
5	11510.000	39.64	39.90	8.27	36.55	51.26	74.00	-22.74	HORIZONTAL	peak
6	17265.000	37.47	43.21	7.89	36.01	52.56	68.20	-15.64	HORIZONTAL	peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1182.513	49.92	24.60	2.57	38.17	38.92	74.00	-35.08	VERTICAL	peak
2	1560.673	49.25	25.54	2.98	37.66	40.11	74.00	-33.89	VERTICAL	peak
3	4379.699	45.63	30.64	5.35	36.63	44.99	74.00	-29.01	VERTICAL	peak
4	7200.309	42.10	35.54	6.36	36.92	47.08	68.20	-21.12	VERTICAL	peak
5	11590.000	38.93	39.72	8.31	36.54	50.42	74.00	-23.58	VERTICAL	peak
6	17385.000	36.31	43.57	8.06	35.99	51.95	68.20	-16.25	VERTICAL	peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1203.199	48.63	24.70	2.58	38.14	37.77	74.00	-36.23	HORIZONTAL	peak
2	1672.779	48.34	25.67	3.21	37.48	39.74	74.00	-34.26	HORIZONTAL	peak
3	3856.668	47.10	29.62	4.73	36.72	44.73	74.00	-29.27	HORIZONTAL	peak
4	7200.309	42.28	35.54	6.36	36.92	47.26	68.20	-20.94	HORIZONTAL	peak
5	11590.000	38.74	39.72	8.31	36.54	50.23	74.00	-23.77	HORIZONTAL	peak
6	17385.000	37.33	43.57	8.06	35.99	52.97	68.20	-15.23	HORIZONTAL	peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1148.823	49.78	24.49	2.55	38.19	38.63	74.00	-35.37	VERTICAL
2	1525.000	54.14	25.52	2.94	37.70	44.90	74.00	-29.10	VERTICAL
3	3969.767	49.47	29.77	5.18	36.70	47.72	74.00	-26.28	VERTICAL
4	7242.052	41.68	35.70	6.35	36.96	46.77	68.20	-21.43	VERTICAL
5	11550.000	39.00	39.84	8.28	36.54	50.58	74.00	-23.42	VERTICAL
6	17325.000	37.10	43.40	7.98	36.00	52.48	68.20	-15.72	VERTICAL

Test Mode: 05; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1267.454	48.76	25.10	2.63	38.07	38.42	68.20	-29.78	HORIZONTAL peak
2	1672.779	48.49	25.67	3.21	37.48	39.89	74.00	-34.11	HORIZONTAL peak
3	4482.150	45.77	30.78	5.34	36.61	45.28	68.20	-22.92	HORIZONTAL peak
4	8995.123	39.48	37.40	7.09	37.05	46.92	68.20	-21.28	HORIZONTAL peak
5	11550.000	39.52	39.84	8.28	36.54	51.10	74.00	-22.90	HORIZONTAL peak
6	17325.000	37.81	43.40	7.98	36.00	53.19	68.20	-15.01	HORIZONTAL peak

7 Test Setup Photo

Refer to Appendix - Test Setup Photo for GZCR2209001150AT

8 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for GZCR2209001150AT

- End of the Report -