



TEST REPORT

Applicant Name : Cloudy Bay Lighting Supply Inc
Address : 1312 17th Street Suite 692 Denver Colorado United States 80202
Report Number : RA221228-64109E-RF-00
FCC ID: 2A4FVCBWL029SMORB

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Intelligent outdoor wall lamp
Model No.: CBWL029SMORB
Multiple Model(s) No.: N/A
Trade Mark: Cloudy Bay
Date Received: 2022/12/28
Report Date: 2023/02/02

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Andy Yu
EMC Engineer

Approved By:

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	8
EUT EXERCISE SOFTWARE	8
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- MPE-BASED EXEMPTION	13
FCC §15.203 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
TRANSD FACTOR & MARGIN CALCULATION.....	16
TEST DATA	16
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
FACTOR & MARGIN CALCULATION	22
TEST DATA	22
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST DATA	36

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST DATA	37
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	39
APPENDIX WI-FI.....	40
APPENDIX A: DTS BANDWIDTH	40
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	45
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	50
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	51
APPENDIX E: BAND EDGE MEASUREMENTS	56
APPENDIX F: DUTY CYCLE	59
APPENDIX BLE.....	62
APPENDIX A: DTS BANDWIDTH	62
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	64
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	66
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	68
APPENDIX E: BAND EDGE MEASUREMENTS	70
APPENDIX F: DUTY CYCLE	71

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA221228-64109E-RF-00	Original Report	2023/02/02

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2462MHz
Maximum Conducted Output Power	BLE 1M: 2.40dBm Wi-Fi: 15.45dBm(802.11b), 11.46dBm(802.11g), 10.68dBm(802.11n20), 8.94dBm(802.11n40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	1.5dBi (provided by the applicant)
Voltage Range	AC 120~277V
Sample serial number	1YJL-3 for Conducted and Radiated Emissions Test 1YJK-2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Line Conducted emission		2.72dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz- 18GHz	4.98dB
	18GHz- 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For Wi-Fi mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40, EUT was tested with Channel 3, 6 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“WiFi test tool v1.6.2”* exercise software was used and the power level as below*. The software and power level was provided by the manufacturer.

The device was tested with the worst case was performed as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	13	13	13
802.11g	6Mbps	20	20	20
802.11n-HT20	MCS0	20	20	20
802.11n-HT40	MCS0	13	13	13
BLE	1Mbps	3	3	3

The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the average power, peak power and PSD across all data rates, bandwidths and modulations.

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielded Detachable AC Cable	1.5	EUT	LISN/AC Mains

Block Diagram of Test Setup

For conducted emission



For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i), §1.1307 (b) (3) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2022/11/30	2025/11/29
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/11/25	2023/11/24
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
Agilent	USB wideband power sensor	U2021XA	MY54250003	2022/6/27	2023/6/26
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Cable	Unknown	1	Each time	Each time

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- MPE-Based Exemption

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BLE	2402-2480	2.5	1.5	-0.65	1.85	1.531	0.2	768
Wi-Fi	2412-2462	16.0	1.5	-0.65	15.35	34.28	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.
 2. The BLE and Wi-Fi cannot Simultaneous transmitting
 3. 0dBd=2.15dBi

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached, and the maximum antenna gain is 1.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$


Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Jason Liu on 2023-01-12.

EUT operation mode: Transmitting

BLE (Worst case is high channel)**AC 120V/60 Hz, Line**


Site : Shielding Room
Condition: Line
Job No. : RA221228-64109E-RF
Mode : BLE Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.151	9.90	33.61	43.51	55.93	-12.42	Average
2	0.151	9.90	50.46	60.36	65.93	-5.57	QP
3	0.182	9.90	26.93	36.83	54.42	-17.59	Average
4	0.182	9.90	43.56	53.46	64.42	-10.96	QP
5	0.222	9.89	24.11	34.00	52.73	-18.73	Average
6	0.222	9.89	41.51	51.40	62.73	-11.33	QP
7	0.329	9.85	10.71	20.56	49.47	-28.91	Average
8	0.329	9.85	22.48	32.33	59.47	-27.14	QP
9	0.559	9.84	11.18	21.02	46.00	-24.98	Average
10	0.559	9.84	20.50	30.34	56.00	-25.66	QP
11	2.858	9.93	23.67	33.60	46.00	-12.40	Average
12	2.858	9.93	28.82	38.75	56.00	-17.25	QP
13	10.099	10.00	19.20	29.20	50.00	-20.80	Average
14	10.099	10.00	25.24	35.24	60.00	-24.76	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Job No. : RA221228-64109E-RF
 Mode : BLE Transmitting


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	9.80	31.08	40.88	55.80	-14.92	Average
2	0.154	9.80	48.50	58.30	65.80	-7.50	QP
3	0.186	9.80	27.64	37.44	54.23	-16.79	Average
4	0.186	9.80	43.61	53.41	64.23	-10.82	QP
5	0.207	9.80	24.71	34.51	53.33	-18.82	Average
6	0.207	9.80	40.54	50.34	63.33	-12.99	QP
7	0.365	9.87	12.61	22.48	48.62	-26.14	Average
8	0.365	9.87	23.91	33.78	58.62	-24.84	QP
9	1.945	9.82	15.89	25.71	46.00	-20.29	Average
10	1.945	9.82	21.76	31.58	56.00	-24.42	QP
11	2.954	9.83	26.03	35.86	46.00	-10.14	Average
12	2.954	9.83	31.89	41.72	56.00	-14.28	QP
13	7.324	10.06	12.65	22.71	50.00	-27.29	Average
14	7.324	10.06	19.38	29.44	60.00	-30.56	QP

2.4G Wi-Fi (Worst case is 802.11b, high channel)**AC 120V/60 Hz, Line**

Site : Shielding Room
 Condition: Line
 Job No. : RA221228-64109E-RF
 Mode : 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.153	9.90	31.68	41.58	55.81	-14.23	Average
2	0.153	9.90	48.29	58.19	65.81	-7.62	QP
3	0.201	9.90	25.32	35.22	53.56	-18.34	Average
4	0.201	9.90	40.92	50.82	63.56	-12.74	QP
5	0.219	9.89	25.29	35.18	52.86	-17.68	Average
6	0.219	9.89	41.13	51.02	62.86	-11.84	QP
7	0.337	9.84	11.63	21.47	49.28	-27.81	Average
8	0.337	9.84	23.36	33.20	59.28	-26.08	QP
9	0.537	9.83	13.81	23.64	46.00	-22.36	Average
10	0.537	9.83	22.76	32.59	56.00	-23.41	QP
11	2.818	9.93	25.68	35.61	46.00	-10.39	Average
12	2.818	9.93	30.77	40.70	56.00	-15.30	QP
13	10.281	10.00	18.55	28.55	50.00	-21.45	Average
14	10.281	10.00	25.10	35.10	60.00	-24.90	QP

AC 120V/60 Hz, Neutral



Site : Shielding Room
Condition: Neutral
Job No. : RA221228-64109E-RF
Mode : 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.153	9.80	32.92	42.72	55.82	-13.10	Average
2	0.153	9.80	49.97	59.77	65.82	-6.05	QP
3	0.183	9.80	27.26	37.06	54.36	-17.30	Average
4	0.183	9.80	44.08	53.88	64.36	-10.48	QP
5	0.221	9.81	25.56	35.37	52.78	-17.41	Average
6	0.221	9.81	42.29	52.10	62.78	-10.68	QP
7	0.304	9.85	12.91	22.76	50.14	-27.38	Average
8	0.304	9.85	26.31	36.16	60.14	-23.98	QP
9	1.836	9.82	16.93	26.75	46.00	-19.25	Average
10	1.836	9.82	22.78	32.60	56.00	-23.40	QP
11	3.052	9.83	27.55	37.38	46.00	-8.62	Average
12	3.052	9.83	33.33	43.16	56.00	-12.84	QP
13	7.378	10.06	12.45	22.51	50.00	-27.49	Average
14	7.378	10.06	19.68	29.74	60.00	-30.26	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	24~25.5 °C
Relative Humidity:	50~58%
ATM Pressure:	101.0 kPa

The testing was performed by Jimi Zheng on 2023-01-16 for below 1GHz and on 2023-01-10 for above 1GHz.


EUT operation mode: Transmitting (Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

30MHz-1GHz:

Note: When the test result of Peak was less than the limit of QP more than 6dB, just the peak value was recorded.

BLE (Worst case is high channel)


Horizontal:



Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA221228-64109E-RF
Test Mode: BLE Transmitting


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	32.392	-12.11	41.24	29.13	40.00	-10.87	Peak
2	97.755	-12.26	40.70	28.44	43.50	-15.06	Peak
3	117.001	-12.97	43.31	30.34	43.50	-13.16	Peak
4	166.141	-13.97	51.10	37.13	43.50	-6.37	QP
5	193.518	-11.30	47.77	36.47	43.50	-7.03	Peak
6	274.074	-9.97	40.61	30.64	46.00	-15.36	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : RA221228-64109E-RF
 Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.472	-11.71	47.01	35.30	40.00	-4.70	QP
2	43.277	-9.94	46.40	36.46	40.00	-3.54	QP
3	115.980	-12.79	45.80	33.01	43.50	-10.49	Peak
4	166.725	-13.91	50.69	36.78	43.50	-6.72	QP
5	235.300	-10.96	42.29	31.33	46.00	-14.67	Peak
6	541.610	-3.94	31.81	27.87	46.00	-18.13	Peak

2.4G Wi-Fi (Worst case is 802.11b, high channel)**Horizontal:**

Site : chamber


Condition: 3m HORIZONTAL

Job No. : RA221228-64109E-RF

Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	43.659	-9.92	39.00	29.08	40.00	-10.92	Peak
2	55.027	-10.28	34.31	24.03	40.00	-15.97	Peak
3	99.093	-12.01	41.35	29.34	43.50	-14.16	Peak
4	111.934	-12.23	43.69	31.46	43.50	-12.04	Peak
5	169.525	-13.63	50.40	36.77	43.50	-6.73	QP
6	244.554	-10.61	44.02	33.41	46.00	-12.59	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : RA221228-64109E-RF
 Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.715	-11.64	47.21	35.57	40.00	-4.43	QP
2	44.043	-9.90	46.30	36.40	40.00	-3.60	QP
3	97.970	-12.25	47.48	35.23	43.50	-8.27	Peak
4	165.995	-13.98	51.30	37.32	43.50	-6.18	QP
5	277.215	-9.76	38.37	28.61	46.00	-17.39	Peak
6	793.744	-0.21	29.74	29.53	46.00	-16.47	Peak

1-25 GHz:**BLE 1M:**

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel 2402MHz									
2310	61.31	PK	330	1.4	H	-7.24	54.07	74	-19.93
2310	49.08	AV	330	1.4	H	-7.24	41.84	54	-12.16
2310	61.16	PK	231	2.1	V	-7.24	53.92	74	-20.08
2310	48.53	AV	231	2.1	V	-7.24	41.29	54	-12.71
2390	70.49	PK	332	1.5	H	-7.22	63.27	74	-10.73
2390	50.77	AV	332	1.5	H	-7.22	43.55	54	-10.45
2390	68.14	PK	352	2.5	V	-7.22	60.92	74	-13.08
2390	50.55	AV	352	2.5	V	-7.22	43.33	54	-10.67
4804	57.59	PK	19	2.3	H	-3.51	54.08	74	-19.92
4804	44.53	AV	19	2.3	H	-3.51	41.02	54	-12.98
4804	57.42	PK	100	1.1	V	-3.51	53.91	74	-20.09
4804	44.42	AV	100	1.1	V	-3.51	40.91	54	-13.09
Middle Channel 2440MHz									
4880	57.54	PK	37	1.2	H	-3.38	54.16	74	-19.84
4880	44.68	AV	37	1.2	H	-3.38	41.3	54	-12.70
4880	56.97	PK	149	1.6	V	-3.38	53.59	74	-20.41
4880	44.77	AV	149	1.6	V	-3.38	41.39	54	-12.61
High Channel 2480MHz									
2483.5	80.07	PK	143	1.8	H	-7.20	72.87	74	-1.13
2483.5	54.48	AV	143	1.8	H	-7.20	47.28	54	-6.72
2483.5	73.37	PK	119	1.1	V	-7.20	66.17	74	-7.83
2483.5	52.43	AV	119	1.1	V	-7.20	45.23	54	-8.77
2500	62.97	PK	153	1.9	H	-7.18	55.79	74	-18.21
2500	50.10	AV	153	1.9	H	-7.18	42.92	54	-11.08
2500	62.73	PK	322	1.8	V	-7.18	55.55	74	-18.45
2500	50.24	AV	322	1.8	V	-7.18	43.06	54	-10.94
4960	56.99	PK	163	1.9	H	-3.01	53.98	74	-20.02
4960	44.23	AV	163	1.9	H	-3.01	41.22	54	-12.78
4960	57.33	PK	192	2	V	-3.01	54.32	74	-19.68
4960	44.23	AV	192	2	V	-3.01	41.22	54	-12.78

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11b									
Low Channel 2412MHz									
2310	60.66	PK	196	1.5	H	-7.24	53.42	74	-20.58
2310	49.36	AV	196	1.5	H	-7.24	42.12	54	-11.88
2310	61.09	PK	288	1.8	V	-7.24	53.85	74	-20.15
2310	48.73	AV	288	1.8	V	-7.24	41.49	54	-12.51
2390	65.01	PK	279	1.8	H	-7.22	57.79	74	-16.21
2390	51.50	AV	279	1.8	H	-7.22	44.28	54	-9.72
2390	64.35	PK	116	1.7	V	-7.22	57.13	74	-16.87
2390	52.09	AV	116	1.7	V	-7.22	44.87	54	-9.13
4824	60.39	PK	246	1.9	H	-3.52	56.87	74	-17.13
4824	55.49	AV	246	1.9	H	-3.52	51.97	54	-2.03
4824	58.07	PK	267	1.4	V	-3.52	54.55	74	-19.45
4824	48.48	AV	267	1.4	V	-3.52	44.96	54	-9.04
Middle Channel 2437MHz									
4874	61.89	PK	222	1.1	H	-3.42	58.47	74	-15.53
4874	52.53	AV	222	1.1	H	-3.42	49.11	54	-4.89
4874	58.82	PK	138	2.3	V	-3.42	55.4	74	-18.60
4874	48.88	AV	138	2.3	V	-3.42	45.46	54	-8.54
High Channel 2462MHz									
2483.5	64.99	PK	243	1.3	H	-7.20	57.79	74	-16.21
2483.5	50.84	AV	243	1.3	H	-7.20	43.64	54	-10.36
2483.5	64.55	PK	345	1.4	V	-7.20	57.35	74	-16.65
2483.5	51.48	AV	345	1.4	V	-7.20	44.28	54	-9.72
2500	62.76	PK	214	1.5	H	-7.18	55.58	74	-18.42
2500	49.76	AV	214	1.5	H	-7.18	42.58	54	-11.42
2500	63.38	PK	306	1.9	V	-7.18	56.2	74	-17.80
2500	49.96	AV	306	1.9	V	-7.18	42.78	54	-11.22
4924	60.77	PK	228	1.5	H	-3.16	57.61	74	-16.39
4924	51.81	AV	228	1.5	H	-3.16	48.65	54	-5.35
4924	58.88	PK	256	1.1	V	-3.16	55.72	74	-18.28
4924	48.53	AV	256	1.1	V	-3.16	45.37	54	-8.63

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11g									
Low Channel 2412MHz									
2310	61.26	PK	136	2.2	H	-7.24	54.02	74	-19.98
2310	48.60	AV	136	2.2	H	-7.24	41.36	54	-12.64
2310	60.53	PK	90	2.3	V	-7.24	53.29	74	-20.71
2310	48.64	AV	90	2.3	V	-7.24	41.40	54	-12.60
2390	64.46	PK	307	2	H	-7.22	57.24	74	-16.76
2390	50.96	AV	307	2	H	-7.22	43.74	54	-10.26
2390	65.20	PK	313	1.4	V	-7.22	57.98	74	-16.02
2390	50.91	AV	313	1.4	V	-7.22	43.69	54	-10.31
4824	57.05	PK	171	1.5	H	-3.52	53.53	74	-20.47
4824	44.55	AV	171	1.5	H	-3.52	41.03	54	-12.97
4824	56.98	PK	352	2	V	-3.52	53.46	74	-20.54
4824	44.53	AV	352	2	V	-3.52	41.01	54	-12.99
Middle Channel 2437MHz									
4874	57.53	PK	112	2.4	H	-3.42	54.11	74	-19.89
4874	44.66	AV	112	2.4	H	-3.42	41.24	54	-12.76
4874	57.96	PK	135	1.6	V	-3.42	54.54	74	-19.46
4874	44.97	AV	135	1.6	V	-3.42	41.55	54	-12.45
High Channel 2462MHz									
2483.5	70.91	PK	198	1.7	H	-7.20	63.71	74	-10.29
2483.5	57.28	AV	198	1.7	H	-7.20	50.08	54	-3.92
2483.5	67.36	PK	34	1.8	V	-7.20	60.16	74	-13.84
2483.5	54.14	AV	34	1.8	V	-7.20	46.94	54	-7.06
2500	62.96	PK	287	1.9	H	-7.18	55.78	74	-18.22
2500	49.56	AV	287	1.9	H	-7.18	42.38	54	-11.62
2500	63.31	PK	300	1.3	V	-7.18	56.13	74	-17.87
2500	50.52	AV	300	1.3	V	-7.18	43.34	54	-10.66
4924	57.10	PK	65	1.9	H	-3.16	53.94	74	-20.06
4924	44.67	AV	65	1.9	H	-3.16	41.51	54	-12.49
4924	57.91	PK	77	1.9	V	-3.16	54.75	74	-19.25
4924	44.42	AV	77	1.9	V	-3.16	41.26	54	-12.74

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n20									
Low Channel 2412MHz									
2310	60.86	PK	337	1.4	H	-7.24	53.62	74	-20.38
2310	48.63	AV	337	1.4	H	-7.24	41.39	54	-12.61
2310	61.06	PK	135	1.7	V	-7.24	53.82	74	-20.18
2310	48.59	AV	135	1.7	V	-7.24	41.35	54	-12.65
2390	64.96	PK	209	1.1	H	-7.22	57.74	74	-16.26
2390	51.07	AV	209	1.1	H	-7.22	43.85	54	-10.15
2390	65.25	PK	7	2.4	V	-7.22	58.03	74	-15.97
2390	50.98	AV	7	2.4	V	-7.22	43.76	54	-10.24
4824	57.38	PK	118	1.6	H	-3.52	53.86	74	-20.14
4824	44.94	AV	118	1.6	H	-3.52	41.42	54	-12.58
4824	57.57	PK	330	2.3	V	-3.52	54.05	74	-19.95
4824	45.12	AV	330	2.3	V	-3.52	41.60	54	-12.40
Middle Channel 2437MHz									
4874	58.14	PK	104	1.1	H	-3.42	54.72	74	-19.28
4874	45.34	AV	104	1.1	H	-3.42	41.92	54	-12.08
4874	57.59	PK	220	1.8	V	-3.42	54.17	74	-19.83
4874	45.15	AV	220	1.8	V	-3.42	41.73	54	-12.27
High Channel 2462MHz									
2483.5	74.16	PK	158	2	H	-7.20	66.96	74	-7.04
2483.5	57.14	AV	158	2	H	-7.20	49.94	54	-4.06
2483.5	66.30	PK	52	1.1	V	-7.20	59.1	74	-14.90
2483.5	51.84	AV	52	1.1	V	-7.20	44.64	54	-9.36
2500	62.65	PK	84	1.9	H	-7.18	55.47	74	-18.53
2500	50.15	AV	84	1.9	H	-7.18	42.97	54	-11.03
2500	62.91	PK	332	1.4	V	-7.18	55.73	74	-18.27
2500	49.72	AV	332	1.4	V	-7.18	42.54	54	-11.46
4924	57.73	PK	95	2.2	H	-3.16	54.57	74	-19.43
4924	45.26	AV	95	2.2	H	-3.16	42.10	54	-11.90
4924	57.37	PK	269	1.1	V	-3.16	54.21	74	-19.79
4924	45.00	AV	269	1.1	V	-3.16	41.84	54	-12.16

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n40									
Low Channel 2422MHz									
2310	61.94	PK	126	2.4	H	-7.24	54.70	74	-19.30
2310	49.62	AV	126	2.4	H	-7.24	42.38	54	-11.62
2310	61.73	PK	143	2	V	-7.24	54.49	74	-19.51
2310	49.45	AV	143	2	V	-7.24	42.21	54	-11.79
2390	68.58	PK	141	2.4	H	-7.22	61.36	74	-12.64
2390	52.83	AV	141	2.4	H	-7.22	45.61	54	-8.39
2390	67.94	PK	77	1.3	V	-7.22	60.72	74	-13.28
2390	52.62	AV	77	1.3	V	-7.22	45.40	54	-8.60
4844	57.28	PK	287	1.7	H	-3.54	53.74	74	-20.26
4844	44.98	AV	287	1.7	H	-3.54	41.44	54	-12.56
4844	57.72	PK	297	2	V	-3.54	54.18	74	-19.82
4844	45.25	AV	297	2	V	-3.54	41.71	54	-12.29
Middle Channel 2437MHz									
4874	57.84	PK	13	2.2	H	-3.42	54.42	74	-19.58
4874	45.37	AV	13	2.2	H	-3.42	41.95	54	-12.05
4874	57.56	PK	97	1.1	V	-3.42	54.14	74	-19.86
4874	45.00	AV	97	1.1	V	-3.42	41.58	54	-12.42
High Channel 2452MHz									
2483.5	77.50	PK	34	2.4	H	-7.20	70.3	74	-3.70
2483.5	58.91	AV	34	2.4	H	-7.20	51.71	54	-2.29
2483.5	71.30	PK	212	1.4	V	-7.20	64.1	74	-9.90
2483.5	54.83	AV	212	1.4	V	-7.20	47.63	54	-6.37
2500	62.92	PK	342	2	H	-7.18	55.74	74	-18.26
2500	50.33	AV	342	2	H	-7.18	43.15	54	-10.85
2500	63.05	PK	293	1.2	V	-7.18	55.87	74	-18.13
2500	49.74	AV	293	1.2	V	-7.18	42.56	54	-11.44
4904	57.91	PK	268	2.2	H	-3.26	54.65	74	-19.35
4904	45.42	AV	268	2.2	H	-3.26	42.16	54	-11.84
4904	58.19	PK	206	2.3	V	-3.26	54.93	74	-19.07
4904	44.97	AV	206	2.3	V	-3.26	41.71	54	-12.29



Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit


The other spurious emission which is in the noise floor level was not recorded.

1-18 GHz:**Pre-scan for 802.11 b, Low Channel****Horizontal****Vertical**


18 -25GHz:

Pre-scan for 802.11 b, Low Channel

Horizontal



Vertical



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang on 2023-01-10 and 2023-02-01.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For wifi mode:

Test Method: ANSI C63.10-2013 Clause 11.9.1.1


1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



For BLE mode:

Test Method: ANSI C63.10-2013 Clause 11.9.2.3.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data**Environmental Conditions**

Temperature:	23℃
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang on 2023-01-10 and 2023-02-01.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	23℃
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang on 2023-01-10 and 2023-02-01.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

For BLE mode:

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



For wifi mode:


Test Method: ANSI C63.10-2013 Clause 11.10.3

Method AVGPSD-1 uses trace averaging with EUT transmitting at full power throughout each sweep.

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
- d) Set VBW $\geq [3 \cdot \text{RBW}]$.
- e) Detector = power averaging (rms) or sample detector (when rms not available).
- f) Ensure that the number of measurement points in the sweep $\geq [2 \cdot \text{span} / \text{RBW}]$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (rms) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.

j) If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).



Test Data

Environmental Conditions

Temperature:	23°C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang on 2023-01-10 and 2023-02-01.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

APPENDIX Wi-Fi


Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	8.32	0.5	PASS
		2437	8.56	0.5	PASS
		2462	9.56	0.5	PASS
11G	Ant1	2412	10.08	0.5	PASS
		2437	11.32	0.5	PASS
		2462	11.32	0.5	PASS
11N20SISO	Ant1	2412	11.32	0.5	PASS
		2437	15.08	0.5	PASS
		2462	11.32	0.5	PASS
11N40SISO	Ant1	2422	33.84	0.5	PASS
		2437	33.84	0.5	PASS
		2452	32.64	0.5	PASS

Test Graphs




11G_Ant1_2412




Date: 1.FEB.2023 21:17:28

11G_Ant1_2437




Date: 1.FEB.2023 21:18:46

11G_Ant1_2462




Date: 1.FEB.2023 21:19:41

11N20SISO_Ant1_2412




Date: 1.FEB.2023 21:22:07

11N20SISO_Ant1_2437




Date: 1.FEB.2023 21:23:19

11N20SISO_Ant1_2462




Date: 1.FEB.2023 21:25:14



**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel Frequency[MHz]	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	14.785	---	---
		2437	14.865	---	---
		2462	14.665	---	---
11G	Ant1	2412	16.184	---	---
		2437	16.224	---	---
		2462	16.184	---	---
11N20SISO	Ant1	2412	17.023	---	---
		2437	17.023	---	---
		2462	16.983	---	---
11N40SISO	Ant1	2422	35.724	---	---
		2437	35.644	---	---
		2452	35.644	---	---


Test Graphs




11G_Ant1_2412



11G_Ant1_2437



11G_Ant1_2462



11N20SISO_Ant1_2412



Date: 1.FEB.2023 21:22:17

11N20SISO_Ant1_2437



Date: 1.FEB.2023 21:23:10

11N20SISO_Ant1_2462



Date: 1.FEB.2023 21:25:24




**Appendix C: Maximum conducted output power
Test Result**

Test Mode	Antenna	Frequency [MHz]	Average Power [dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	15.45	≤30.00	PASS
		2437	15.39	≤30.00	PASS
		2462	15.00	≤30.00	PASS
11G	Ant1	2412	9.46	≤30.00	PASS
		2437	11.26	≤30.00	PASS
		2462	10.93	≤30.00	PASS
11N20SISO	Ant1	2412	9.31	≤30.00	PASS
		2437	10.11	≤30.00	PASS
		2462	10.68	≤30.00	PASS
11N40SISO	Ant1	2422	8.64	≤30.00	PASS
		2437	8.62	≤30.00	PASS
		2452	8.94	≤30.00	PASS


**Appendix D: Maximum power spectral density
Test Result**

Test Mode	Antenna	Frequency[MHz]	Result[dBm/10kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-10.69	≤8.00	PASS
		2437	-11.06	≤8.00	PASS
		2462	-11.41	≤8.00	PASS
11G	Ant1	2412	-18.93	≤8.00	PASS
		2437	-17.17	≤8.00	PASS
		2462	-17.35	≤8.00	PASS
11N20SISO	Ant1	2412	-19.32	≤8.00	PASS
		2437	-18.82	≤8.00	PASS
		2462	-17.81	≤8.00	PASS
11N40SISO	Ant1	2422	-21.38	≤8.00	PASS
		2437	-22.80	≤8.00	PASS
		2452	-21.18	≤8.00	PASS


Test Graphs




11G Ant1_2412




11G Ant1_2437




11G Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452




Appendix E: Band edge measurements


Test Graphs




11G Ant1 High 2462




11N20SISO Ant1 Low 2412




11N20SISO Ant1 High 2462



11N40SISO_Ant1_Low_2422





11N40SISO_Ant1_High_2452



**Appendix F: Duty Cycle
Test Result**

Test Mode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2437	100.00	100.00	100.00
11G	Ant1	2437	100.00	100.00	100.00
11N20SISO	Ant1	2437	100.00	100.00	100.00
11N40SISO	Ant1	2437	100.00	100.00	100.00

Test Graphs




APPENDIX BLE

Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.63	0.5	PASS
		2440	0.63	0.5	PASS
		2480	0.63	0.5	PASS


Test Graphs



**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.015	---	---
		2440	1.011	---	---
		2480	1.011	---	---


Test Graphs



**Appendix C: Maximum conducted output power
Test Result**

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
BLE_1M	Ant1	2402	0.76	≤30	PASS
		2440	1.65	≤30	PASS
		2480	2.40	≤30	PASS


Test Graphs



**Appendix D: Maximum power spectral density
Test Result**


Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-10.29	≤8.00	PASS
		2440	-9.36	≤8.00	PASS
		2480	-8.64	≤8.00	PASS

Test Graphs



Appendix E: Band edge measurements


Test Graphs



Appendix F: Duty Cycle Test Result

Test Mode	Antenna	Frequency[MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2440	0.44	0.63	69.84

Test Graphs



***** END OF REPORT *****